

MEASUREMENT REPORT
of
2.4GHz Wireless Trackball Laser
Mouse

Applicant : Ione Technology Inc.
FCC ID : F2QRFLYNXR5U
EUT : 2.4GHz Wireless Trackball Laser Mouse
Model : Lynx-R5

Test by :

Training Research Co., Ltd.

TEL : 886-2-26935155 FAX : 886-2-26934440
No. 255, Nan-yang Street, Shijr, Taipei Hsien 221, Taiwan

CERTIFICATION


We here by verify that:

The test data, data evaluation, test procedures and equipment configurations shown in this report were made mainly in accordance with the procedures given in ANSI C63.4 (2003) as a reference. All tests were conducted by **Training Research Co., Ltd.**, No. 255, Nan-yang Street, Shijr, Taipei Hsien 221, Taiwan. Also, we attest to the accuracy of each.


We further submit that the energy emitted by the sample EUT tested as described in the report is **in compliance with** the technical requirements set forth in the FCC Rules Part 15 Subpart C Section 15.249.

Applicant : Ione Technology Inc.
Applicant address : 9F, No. 75, Sec 1, Hsin Tai Wu Road, Hsichih, Taipei Hsien, Taiwan
Report No. : I2615080253
Test Date : December 08, 2008

Prepared by:


Jack Tsai

Approved by:


Frank Tsai

Conditions of issue :

- (1) **This test report shall not be reproduced except in full, without written approval of TRC. And the test result contained within this report only relate to the sample submitted for testing.**
- (2) **This report must not be used by the client to claim product endorsement by NVLAP or any agency of U.S. Government.**
- (3) **This test report, measurements made by TRC are traceable to the NIST only Conducted and Radiated Method.**



Tables of Contents

CHAPTER 1 GENERAL	4
1.1 INTRODUCTION	4
1.2 DESCRIPTION OF EUT	4
1.3 TEST METHOD	4
1.4 DESCRIPTION OF SUPPORT EQUIPMENT	4
1.5 CONFIGURATION OF SYSTEM UNDER TEST	5
1.6 TEST PROCEDURE	6
1.7 LOCATION OF THE TEST SITE	6
1.8 GENERAL TEST CONDITION	6
CHAPTER 2 CONDUCTED EMISSIONS MEASUREMENTS	7
2.1 TEST CONDITION & SETUP	7
2.2 LIST OF TEST INSTRUMENTS	7
2.3 TEST RESULT OF CONDUCTED EMISSIONS	7
CHAPTER 3 RADIATED EMISSIONS MEASUREMENTS	8
3.1 TEST CONDITION & SETUP	8
3.2 LIST OF TEST INSTRUMENTS	10
3.3 TEST RESULT OF RADIATED EMISSIONS	11
Fundamental Emissions	11
3.4 TEST RESULT OF SPURIOUS RADIATED EMISSIONS	12
3.5 TEST RESULT OF THE BANDEDGE	18
Bottom channel	19
Top Channel	20

Chapter 1 General

1.1 Introduction

The following measurement report is submitted on behalf of Applicant in support of a wireless mouse certification in accordance with Part 2 Subpart J and Part 15 Subpart C of the Commission's Rules and Regulations.

1.2 Description of EUT

FCC ID	: F2QRFLYNXR5U
Product Name	: 2.4GHz Wireless Trackball Laser Mouse
Model	: Lynx-R5
Frequency Range	: 2400MHz ~ 2483.5MHz
Operating Frequency	: 2402.8MHz ~ 2479.8MHz
Modulation Skill	: GFSK
Power Type	: Powered by DC 1.5V batteries (AA*2)

1.3 Test method

The fundamental frequency of transmitter emitted is due to a press on button of the EUT. There are security codes for avoiding the possibility of duplicating codes in adjacent systems. The coding must be matching with the companion receiver.

While testing the EUT was adjusted at a position, which transmits the maximum emission.

Test mode

Set different channel (bottom channel / near middle channel / near top channel) being tested

(a) Radiated test:


making EUT to the mode of continuous TX

1.4 Description of Support Equipment

None

1.5 Configuration of System Under Test

1.5.1 Radiated of Transmission



1.6 Test Procedure

All measurements contained in this report were performed mainly according to the techniques described in Measurement procedure ANSI C63.4 (2003).

1.7 Location of the Test Site

The radiated emissions measurements required by the rules were performed on the **three-meter, semi-anechoic Chamber (FCC Registration Number: 93906)** maintained by *Training Research Co., Ltd.* 1F, No. 255, Nan-yang Street, Shijr, Taipei Hsien 221, Taiwan, R.O.C. Complete description and measurement data have been placed on file with the commission. The conducted power line emissions tests and other test items were performed in an anechoic chamber also located at Training Research Co., Ltd. 1F, No. 255, Nan-yang Street, Shijr, Taipei Hsien 221, Taiwan, R.O.C. *Training Research Co., Ltd.* is listed by the FCC as a facility available to do measurement work for others on a contract basis.

1.8 General Test Condition

The conditions under which the EUT operates were varied to determine their effect on the equipment's emission characteristics. The final configuration of the test system and the mode of operation used during these tests was chosen as that which produced the highest emission levels. However, only those conditions which the EUT was considered likely to encounter in normal use were investigated.

In test, they were set in high power and continuously transmitting mode. The Highest, Middle and Lowest of EUT were all tested. The setting up procedure is recorded on 1.3 Test Method.

Chapter 2 Conducted Emissions Measurements

2.1 Test Condition & Setup

The EUT operates solely by the batteries (AA*2 DC 1.5V batteries).

According to the rule of section 15.207(c), the EUT exempt to the power line conducted test.

2.2 List of Test Instruments

N/A (Not applicable)

2.3 Test Result of Conducted Emissions

N/A (Not applicable)

Chapter 3 Radiated Emissions Measurements

3.1 Test Condition & Setup

We'd performed the test by the radiated emission skill: The EUT was placed in an semi-anechoic chamber, and set the EUT transmitting continuously and scanned at 3-meter distance to determine its emission characteristics. The physical arrangement of the EUT was varied (within the scope of arrangements likely to be encountered in actual use) to determine the effect on the unit's emanations in amplitude, directivity, and frequency. The exact system configuration, which produced the highest emissions was noted so it could be reproduced later during the final tests. For the measurement above 1GHz, according to the guidance we'd set the spectrum analyzer's 6dB bandwidth RBW to 1MHz.

This was done to ensure that the final measurements would demonstrate the worst-case interference potential of the EUT.

Final radiation measurements were made on a three-meter, semi-anechoic chamber. The EUT system was placed on a nonconductive turntable, which is 0.8 meters height, top surface 1.0 x 1.5 meter.

The spectrum was examined from 30 MHz to 1000 MHz using an Hewlett Packard 85460A EMI Receiver, SCHWARZECK whole range Small Biconical Antenna (model: UBAA9114 & BBVU9135) is used to measure frequency from 30 MHz to 1GHz. The final test is used the HP 85460A spectrum and 8564E spectrum was examined from 1GHz to 25GHz using an Hewlett Packard Spectrum Analyzer, EMCO/HP Horn Antenna (Model 3115 / 84125-80008) for 1G - 25GHz.

A nonconductive material surrounded the EUT to supporting the EUT for standing on three orthogonal planes. At each frequency, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. There are two spectrum analyzers use on this testing, HP 85460A for frequency 30MHz to 1000MHz, and 8564E for frequency 1GHz to 25GHz. No post-detector video filters were used in the test. The spectrum analyzer's 6dB bandwidth was set to 120KHz (spectrum was examined from 30 MHz to 1000 MHz), the spectrum analyzer's 6 dB bandwidth was set to 1 MHz (spectrum was examined from 1GHz to 25GHz) and the analyzer was operated in the maximum hold mode. There is a test condition applies in this test item, the test procedure description as the following:

Three channels were tested, one in the near top, one in the near middle and the other in bottom channel. The setting up procedure is recorded on <1.3>

With the transmitter operating from a AC source and using the internal of EUT, radiates spurious emissions falling within the restricted bands of 15.209 were measured at operating frequencies corresponding to upper, middle and bottom channels in the 2400 ~ 2483.5 MHz band.

The actual field intensity in decibels referenced to 1 microvolt per meter (dBμV/m) is determined by algebraically adding the measured reading in dBμV, the antenna factor (dB), and cable loss (dB) at the appropriate frequency. Since the EUT was set to transmit continuously, with *duty cycle* is present.

For frequency between 30MHz to 1000MHz

$F_{Ia} \text{ (dBμV/m)} = F_{Ir} \text{ (dBμV)} + \text{Correction Factors} + \text{Duty Cycle}$

F_{Ia} : Actual Field Intensity

F_{Ir} : Reading of the Field Intensity

Correction Factors = Antenna factor + (Cable loss – Amplitude gain) + Switching box loss

For frequency between 1GHz to 25GHz

$F_{Ia} \text{ (dBμV/m)} = F_{Ir} \text{ (dBμV)} + \text{Correction Factor} + \text{Duty Cycle}$

F_{Ia} : Actual Field Intensity

F_{Ir} : Reading of the Field Intensity

Correction Factors = Antenna factor + (Cable loss – Amplitude gain) + Switching box loss

3.2 List of Test Instruments

Instrument Name	Model No.	Brand	Serial No.	Calibration Date
				Next time
EMI Receiver	8546A	HP	3520A00242	04/15/09
RF Filter Section	85460A	HP	3448A00217	04/15/09
Small Biconical Antenna	UBAA9114 & BBVU9135	SCHWARZECK	127	01/10/09
Pre-amplifier	PA1F	TRC	1FAC	01/10/09
Coaxial Cable (Double shielded, 15 meter)	A30A30-0058-50FS-15M	JYEBAO	SMA-01	01/10/09
Coaxial Cable (1.1 meter)	A30A30-0058-50FS-1M	JYEBAO	SMA-02	01/10/09
Spectrum Analyzer	8564E	HP	3720A00840	03/17/09
Microwave Preamplifier	84125C	HP	US36433002	02/05/09
Horn Antenna	3115	EMCO	9104-3668	08/06/09
Standard Guide Horn Antenna	84125-80008	HP	18-26.5GHz	12/14/08
Standard Guide Horn Antenna	84125-80001	HP	26.5-40GHz	02/12/09
Horn Antenna	1196E (3115)	HP (EMCO)	9704-5178	08/13/09
Pre-amplifier	PA2F	TRC	2F1GZ	01/10/09
Coaxial Cable (3 miter)	A30A30-0058-50FST118	JYEBAO	MSA-05	01/10/09
Coaxial Cable (1 meter)	A30A30-0058-50FST118	JYEBAO	MSA-04	01/10/09

3.3 Test Result of Radiated Emissions

The peak values of fundamental emissions from the EUT at various antenna heights, antenna polarization, EUT orientation, etc. are recorded on the following.

Testing room : Temperature : 25 ° C Humidity : 73 % RH

Fundamental Emissions

Channel	Frequency (MHz)	A. P. (H/V)	A.H. (m)	Table (degree)	Peak (dBμV/m)	Limit (dBμV)	Margin (dBμV)
Bottom	2402.8	H	1.00	241	88.72	94.00	-5.28
		V	1.00	164	78.72	94.00	-15.28
Near middle	2438.8	H	1.00	360	88.15	94.00	-5.85
		V	1.00	239	76.15	94.00	-17.85
Top	2479.8	H	1.00	290	86.76	94.00	-7.24
		V	1.00	57	76.26	94.00	-17.74

Note:

1. A. P. means antenna polarization, horizontal and vertical.
2. A. H. means antenna height.
3. Table means turntable turning position.
4. Peak amplitude means the fundamental emission measured.
5. Margin = Peak – Limit

3.4 Test Result of Spurious Radiated Emissions

The highest peak values of radiated emissions from the EUT at various antenna heights, antenna polarizations, EUT orientation, etc. are recorded on the following.

Test Conditions: Temperature : 25 ° C Humidity : 73 % RH

Test mode: Bottom channel for 30MHz to 1GHz [Horizontal]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table ()			Limit (dBμV/m)	Margin (dB)
200.96	25.75	1.00	187	-3.34	22.41	43.50	-21.09
316.15	22.75	1.00	139	-2.70	20.05	46.00	-25.95
802.36	32.51	1.00	35	11.71	44.22	46.00	-1.78

Test mode: Bottom channel for 30MHz to 1GHz [Vertical]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table ()			Limit (dBμV/m)	Margin (dB)
200.96	22.23	1.00	114	-3.34	18.89	43.50	-24.61
316.15	23.71	1.00	330	-2.70	21.01	46.00	-24.99
802.36	22.52	1.00	300	11.71	34.23	46.00	-11.77

Note:

1. Margin = Amplitude – limit, if margin is minus means under limit.
2. Corrected Amplitude = Reading Amplitude + Correction Factors
3. Correction factor = Antenna factor + (Cable Loss – Amplitude gain) + Switching Box Loss

Test mode: Bottom channel for 1GHz to 26.5GHz [Horizontal]

Frequency	Ant. H.	Table	Amplitude		Correction Factor	Corrected Amplitude		Limit		Margin
			Peak / Ave.			Peak / Ave.		Peak / Ave.		
MHz	m	degree	dBμV		dB/m	dBμV/m		dBμV/m		dB
1601.31	1.00	280	37.99	31.50	14.31	52.30	45.81	73.96	53.96	-8.15
4805.41	1.00	113	58.44	48.27	3.69	62.13	51.96	73.96	53.96	-2.00
19221.87	1.00	27	46.50	---	1.60	48.10	---	73.96	53.96	-5.86
21626.67	1.00	128	44.83	---	2.80	47.63	---	73.96	53.96	-6.33
24027.92	1.00	303	45.00	---	3.19	48.19	---	73.96	53.96	-5.77

Test mode: Bottom channel for 1GHz to 26.5GHz [Vertical]

Frequency	Ant. H.	Table	Amplitude		Correction Factor	Corrected Amplitude		Limit		Margin
			Peak / Ave.			Peak / Ave.		Peak / Ave.		
MHz	m	degree	dBμV		dB/m	dBμV/m		dBμV/m		dB
1602.08	1.00	94	34.33	---	14.30	48.63	---	73.96	53.96	-5.33
4805.42	1.00	49	56.10	46.61	3.69	59.79	50.30	73.96	53.96	-3.66
19221.87	1.00	268	47.32	---	1.60	48.92	---	73.96	53.96	-5.04
21626.67	1.00	174	46.65	---	2.80	49.45	---	73.96	53.96	-4.51
24027.92	1.00	258	47.49	---	3.19	50.68	---	73.96	53.96	-3.28

Note:

1. Margin = Corrected - Limit.

Test mode: Near middle channel for 30MHz to 1GHz [Horizontal]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table ()			Limit (dBμV/m)	Margin (dB)
199.75	23.48	1.00	155	-3.31	20.17	43.50	-23.33
208.24	23.67	1.00	175	-3.64	20.03	43.50	-23.47
814.49	27.83	1.00	259	12.11	39.94	46.00	-6.06

Test mode: Near middle channel for 30MHz to 1GHz [Vertical]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table ()			Limit (dBμV/m)	Margin (dB)
250.67	24.22	1.00	295	-3.20	21.02	46.00	-24.98
287.05	24.70	1.00	207	-3.45	21.25	46.00	-24.75
813.27	25.07	1.00	49	12.07	37.14	46.00	-8.86

Test mode: Near middle channel for 1GHz to 26.5GHz [Horizontal]

Frequency	Ant. H.	Table	Amplitude		Correction Factor	Corrected Amplitude		Limit		Margin
			Peak / Ave.			Peak / Ave.		Peak / Ave.		
MHz	m	degree	dBμV		dB/m	dBμV/m		dBμV/m		dB
1625.32	1.00	229	39.67	33.50	13.94	53.61	47.44	73.96	53.96	-6.52
3250.00	1.00	69	37.00	---	11.63	48.63	---	73.96	53.96	-5.33
4877.42	1.00	177	57.11	47.44	3.97	61.08	51.41	73.96	53.96	-2.55
12193.96	1.00	276	40.44	---	9.76	50.20	---	73.96	53.96	-3.76
24389.17	1.00	97	45.50	---	3.24	48.74	---	73.96	53.96	-5.22

Test mode: Near middle channel for 1GHz to 26.5GHz [Vertical]

Frequency	Ant. H.	Table	Amplitude		Correction Factor	Corrected Amplitude		Limit		Margin
			Peak / Ave.			Peak / Ave.		Peak / Ave.		
MHz	m	degree	dBμV		dB/m	dBμV/m		dBμV/m		dB
1625.00	1.00	221	36.00	---	13.94	49.94	---	73.96	53.96	-4.02
4877.41	1.00	89	53.61	44.61	3.97	57.58	48.58	73.96	53.96	-5.38
12193.96	1.00	142	38.60	---	9.76	48.36	---	73.96	53.96	-5.60
21948.96	1.00	205	45.83	---	3.06	48.89	---	73.96	53.96	-5.07
24389.17	1.00	43	45.83	---	3.24	49.07	---	73.96	53.96	-4.89

Test mode: Top channel for 30MHz to 1GHz [Horizontal]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table ()			Limit (dBμV/m)	Margin (dB)
129.43	27.93	1.00	276	-2.99	24.94	43.50	-18.56
156.10	29.43	1.00	276	-4.18	25.25	43.50	-18.25
826.61	29.08	1.00	90	12.50	41.58	46.00	-4.42

Test mode: Top channel for 30MHz to 1GHz [Vertical]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table ()			Limit (dBμV/m)	Margin (dB)
128.21	21.57	1.00	64	-2.91	18.66	43.50	-24.84
337.97	23.46	1.00	47	-2.42	21.04	46.00	-24.96
878.75	21.42	1.00	128	14.36	35.78	46.00	-10.22

Test mode: Top channel for 1GHz to 26.5GHz [Horizontal]

Frequency	Ant. H.	Table	Amplitude		Correction Factor	Corrected Amplitude		Limit		Margin
			Peak / Ave.			Peak / Ave.		Peak / Ave.		
MHz	m	degree	dBμV		dB/m	dBμV/m		dBμV/m		dB
1652.64	1.00	336	42.34	36.83	13.51	55.85	50.34	73.96	53.96	-3.62
4959.44	1.00	208	53.79	46.27	4.24	58.03	50.51	73.96	53.96	-3.45
19838.12	1.00	315	46.17	---	1.90	48.07	---	73.96	53.96	-5.89
22317.29	1.00	210	44.83	---	3.32	48.15	---	73.96	53.96	-5.81
24796.46	1.00	256	46.34	---	2.22	48.56	---	73.96	53.96	-5.40

Test mode: Top channel for 1GHz to 26.5GHz [Vertical]

Frequency	Ant. H.	Table	Amplitude		Correction Factor	Corrected Amplitude		Limit		Margin
			Peak / Ave.			Peak / Ave.		Peak / Ave.		
MHz	m	degree	dBμV		dB/m	dBμV/m		dBμV/m		dB
1652.08	1.00	340	38.33	---	13.52	51.85	---	73.96	53.96	-2.11
4959.42	1.00	242	51.62	41.94	4.24	55.86	46.18	73.96	53.96	-7.78
19838.12	1.00	165	48.16	---	1.90	50.06	---	73.96	53.96	-3.90
22317.29	1.00	330	45.82	---	3.32	49.14	---	73.96	53.96	-4.82
24796.46	1.00	44	47.16	---	2.22	49.38	---	73.96	53.96	-4.58


3.5 Test Result of the Bandedge

§ 15.249 (c) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

We perform this section by the *radiated manner*, the RBW is set to 100kHz and VBW>RBW. We'd made the observation *up to 10th harmonics and the criterion is all the harmonic/spurious emissions must be 50dB below the highest emission level measured*. If the emissions fall in the restricted bands stated in the Part15.205(a) must also *comply with the radiated emission limits specified in Part15.209(a)*. (Peak mode: RBW=VBW=1MHz, Average mode: RBW=1MHz; VBW=10Hz)

The following pages show our observations referring to the bottom channel and near top: channel respectively. Test Condition & Setup: same as 4.1 to 4.2.

Bottom channel




This is the hard copy of our bandedge measurement generated by our bandedge testing program. The plot shown above is the bandedge of lowest channel.

1. The lobe left by the fundamental side is already 50dB below the highest emission level.
2. The emissions recorded in the restricted band is do comply with the Part 15.209(a) – as below.

<i>Radiated Emission</i>					<i>Corrected Amplitude</i>		<i>Class B (3m)</i>		
<i>Frequency (MHz)</i>	<i>Ant. P.</i>	<i>Ant. H. (m)</i>	<i>Table ()</i>	<i>Factors (dB)</i>	<i>(dBuV/m)</i>		<i>Limit (dBuV/m)</i>		<i>Margin (dB)</i>
					<i>Peak</i>	<i>Average</i>	<i>Peak</i>	<i>Ave.</i>	
2381.62	Hor	1.00	215	9.16	49.83	---	73.96	53.96	-4.13
2390.07	Hor	1.00	186	9.18	51.18	---	73.96	53.96	-2.78
2382.70	Ver	1.00	159	9.16	43.66	---	73.96	53.96	-10.30
2390.02	Ver	1.00	305	9.18	42.02	---	73.96	53.96	-11.94

Top Channel



This is the hard copy of our bandedge measurement generated by our bandedge testing program. The plot shown above is the bandedge of highest channel.

1. The lobe right by the fundamental side is already 50dB below the highest emission level.
2. The emissions recorded in the restricted band is do comply with the Part 15.209(a) – as below

Radiated Emission					Corrected Amplitude		Class B (3m)		
Frequency (MHz)	Ant. P.	Ant. H. (m)	Table ()	Factors (dB)	(dBμV/m)		Limit (dBμV/m)		Margin (dB)
					Peak	Average	Peak	Ave.	
2482.95	Hor	1.00	130	9.44	60.44	43.61	73.96	53.96	-10.35
2487.76	Hor	1.00	207	9.46	51.62	---	73.96	53.96	-2.34
2500.01	Hor	1.00	225	9.49	43.66	---	73.96	53.96	-10.30
2512.43	Hor	1.00	0	9.51	44.68	---	73.96	53.96	-9.28
2483.50	Ver	1.00	166	9.44	50.61	---	73.96	53.96	-3.35
2487.64	Ver	1.00	195	9.46	47.62	---	73.96	53.96	-6.34
2500.01	Ver	1.00	69	9.49	42.49	---	73.96	53.96	-11.47
2511.85	Ver	1.00	199	9.51	45.01	---	73.96	53.96	-8.95