

**Environmental evaluation and exposure limit according to FCC CFR 47part 1,  
§1.1307, §1.1310**

The Wireless Transceiver is classified as a mobile device. The Wireless Transceiver includes transmitter operating according to FCC part 15 subpart C section 15.247 (FHSS)

The FCC limit for power density for general population/uncontrolled exposure is  $1500 \text{ mW/cm}^2$  for 300 – 1500 MHz frequency range:

$$P = 912.75/1500 = 0.61 \text{ mW/cm}^2$$

The power density  $P (\text{mW/cm}^2) = P_T / 4\pi r^2$

$P_T$  is the transmitted power, which is equal to the peak transmitter output power 13.78 dBm plus maximum antenna gain 7 dBi, the maximum equivalent isotropically radiated power EIRP is

$$P_T = 13.78 \text{ dBm} + 7 \text{ dBi} = 20.78 \text{ dBm} = 119.67 \text{ mW.}$$

The power density at 20 cm (minimum safe distance, required for mobile devices), calculated as follows:

$$\text{Compliance with FCC limit: } 119.67 \text{ mW} / 4\pi (20 \text{ cm})^2 = 0.024 \text{ mW/cm}^2 \ll 0.61 \text{ mW/cm}^2$$

General public cannot be exposed to dangerous RF level.