

EMF TEST REPORT

Test Report No. : OT-23O-RWD-004

Reception No. : 2308002740

Applicant : InBody Co., Ltd.

Address : InBody Bldg., 625, Eonju-ro, Gangnam-gu, Seoul 06106 KOREA

Manufacturer : InBody Co., Ltd.

Address : 15, Heugam-gil, Ipjang-myeon, Seobuk-gu, Cheonan-si, Chungcheongnam-do 31025 KOREA

Type of Equipment : Portable Stadiometer

FCC ID. : F60PUSH

Model Name : PUSH

Multiple Model Name : N/A

Serial number : N/A

Total page of Report : 6 pages (including this page)

Date of Incoming : September 04, 2023

Date of issue : October 04, 2023

SUMMARY

The equipment complies with the regulation; **FCC CFR 47 PART 2.1093**

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

This report is not correlated with the "KS Q ISO/IEC 17025 and KOLAS accreditation" of Korean Laboratory Accreditation Scheme.



Tested by
Su-Min, You / Sr. Engineer
ONETECH Corp.

Reviewed by
Tae-Ho, Kim / Chief Engineer
ONETECH Corp.

Approved by
Jae-Ho, Lee / Chief Engineer
ONETECH Corp.

CONTENTS**PAGE**

1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION	5
2.1 PRODUCT DESCRIPTION.....	5
2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	5
3. EUT MODIFICATIONS.....	5
4. RF EXPOSURE EVALUATION	6
4.1 RF EXPOSURE CALCULATION	6
4.2 EUT DESCRIPTION.....	6
4.3 TEST RESULT	6
4.3.1 Test data for Bluetooth LE	6

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-23O-RWD-004	October 04, 2023	Initial Release	All

1. VERIFICATION OF COMPLIANCE

Applicant : InBody Co., Ltd.

Address : InBody Bldg., 625, Eonju-ro, Gangnam-gu, Seoul 06106 KOREA

Contact Person : Min seok, Lee / Manager

Telephone No. : +82-2-2182-8918

FCC ID : F6OPUSH

Model Name : PUSH

Brand Name : 

Serial Number : N/A

Date : October 04, 2023

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM
E.U.T. DESCRIPTION	Portable Stadiometer
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	KDB 447498 D01 General RF Exposure Guidance v06
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
Modifications on the Equipment to Achieve Compliance	None

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. GENERAL INFORMATION

2.1 Product Description

The InBody Co., Ltd., Model PUSH (referred to as the EUT in this report) is a Portable Stadiometer. The product specification described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	Portable Stadiometer
OPERATING FREQUENCY	2 402 MHz ~ 2 480 MHz
MODULATION TYPE	GFSK
RF OUTPUT POWER	-9.53 dBm
NUMBER OF CHANNEL	40 Channel
ANTENNA TYPE	Chip Antenna
ANTENNA GAIN	3.70 dBi
Electrical Rating	DC 3.0 V
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	38.4 MHz, 32.768 kHz

2.2 Alternative type(s)/model(s); also covered by this test report.

-. None

3. EUT MODIFICATIONS

-. None

4. RF EXPOSURE EVALUATION

4.1 RF Exposure Calculation

According to the FCC rule §4.3. General SAR test exclusion guidance, the limit for 1-g and 10-g SAR test exclusion thresholds are ≤ 3.0 for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR by the device operating 100 MHz to 6 GHz and test separation distances ≤ 50 mm

4.2 EUT Description

Kind of EUT	Portable Stadiometer
Device Category	☒ Portable (< 20 cm separation) ☐ Mobile (> 20 cm separation) ☐ Others
Exposure Evaluation Applied	☐ MPE ☐ SAR ☒ N/A

4.3 Test Result

According to the procedure, KDB 447498 D01, the standalone SAR test exclusion threshold is

$$[(\text{Max. Power of channel, including tune-up tolerance, mW})/(\text{Min. test separation distance, mm})] \times [\sqrt{f(\text{GHz})}] < 3.0$$

$$= [(0.14/5)] \times \sqrt{2.402} = 0.04$$

4.3.1 Test data for Bluetooth LE

Frequency (MHz)	Target Power W/tolerance (dBm)	Max tune up power (dBm)	Max tune up power (mW)	Separation distance (mm)	RF exposure
2 402.00	-9.53 ± 1.0	-8.53	0.14	5	0.04