



FCC PART 27

TEST AND MEASUREMENT REPORT

For

ADC Telecommunications Inc.

P.O. Box 1101, Minneapolis, Minnesota 55440, USA

FCC ID: F8I-SP0700LH
Model: FWU-L6000HUDART

Report Type: Original Report	Product Type: FlexWave™ URH Host Card
Test Engineer: Dennis Huang 	
Report Number: R1102156-27	
Report Date: 2011-03-03	
Victor Zhang 	
Reviewed By: RF Lead	
Prepared By: (84) Bay Area Compliance Laboratories Corp. 1274 Anvilwood Avenue, Sunnyvale, CA 94089, USA Tel: (408) 732-9162 Fax: (408) 732 9164	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, NIST, or any agency of the Federal Government.

* This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk “*” (Rev.2)

TABLE OF CONTENTS

1	GENERAL INFORMATION	5
1.1	PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	5
1.2	MECHANICAL DESCRIPTION	5
1.3	EUT PHOTO	5
1.4	OBJECTIVE	6
1.5	RELATED SUBMITTAL(S)/GRANT(S).....	6
1.6	TEST METHODOLOGY	6
1.7	MEASUREMENT UNCERTAINTY.....	6
1.8	TEST FACILITY.....	6
2	SYSTEM TEST CONFIGURATION	8
2.1	JUSTIFICATION	8
2.2	EUT EXERCISE SOFTWARE.....	8
2.3	EQUIPMENT MODIFICATIONS	8
2.4	SUPPORT EQUIPMENT LIST	8
2.5	LOCAL SUPPORT EQUIPMENT AND SOFTWARE LIST AND DETAILS	8
2.6	INTERNAL CONFIGURATIONS OF EUT.....	8
2.7	INTERFACE PORTS AND CABLES	9
3	SUMMARY OF TEST RESULTS.....	10
4	FCC §2.1046 & §27.50 – RF OUTPUT POWER.....	11
4.1	APPLICABLE STANDARD	11
4.2	TEST PROCEDURE	11
4.3	TEST RESULTS	11
5	FCC §2.1047 - MODULATION CHARACTERISTIC.....	12
5.1	APPLICABLE STANDARD	12
5.2	TEST RESULT	12
6	FCC §2.1049 & §27.53 – OCCUPIED BANDWIDTH.....	13
6.1	APPLICABLE STANDARD	13
6.2	TEST PROCEDURE	13
6.3	TEST RESULTS	13
7	FCC §2.1053 & §27.53 – SPURIOUS RADIATED EMISSIONS	14
7.1	APPLICABLE STANDARD	14
7.2	TEST PROCEDURE	14
7.3	TEST RESULTS	14
8	FCC §2.1051 & §27.53 - SPURIOUS EMISSIONS AT ANTENNA TERMINALS.....	15
8.1	APPLICABLE STANDARD	15
8.2	TEST RESULTS	15
9	FCC §27.53 – BAND EDGE	16
9.1	APPLICABLE STANDARD	16
9.2	TEST PROCEDURE	16
9.3	TEST RESULTS	16
10	FCC §2.1055 & §27.54 – FREQUENCY STABILITY.....	17
10.1	APPLICABLE STANDARD	17
10.2	TEST PROCEDURE	17

10.3 TEST RESULTS	17
11 FCC §1.1307(B), §27.52 & §2.1091 - RF EXPOSURE INFORMATION	18
11.1 APPLICABLE STANDARD	18
11.2 MPE PREDICTION	18
11.3 TEST RESULT	18
12 EXHIBIT A - FCC ID LABELING REQUIREMENTS	19
12.1 FCC ID LABEL REQUIREMENT	19
12.2 FCC ID LABEL CONTENTS	19
12.3 FCC ID LABEL LOCATION	19
13 EXHIBIT B - TEST SETUP PHOTOGRAPHS.....	20
13.1 RADIATED EMISSIONS 30 MHZ TO 1 GHZ - FRONT VIEW	20
13.2 RADIATED EMISSIONS 30 MHZ TO 1 GHZ- REAR VIEW.....	20
13.3 RADIATED EMISSIONS ABOVE 1 GHZ - FRONT VIEW	21
13.4 RADIATED EMISSIONS ABOVE 1 GHZ- REAR VIEW.....	21
14 EXHIBIT C - EUT PHOTOGRAPHS	22
14.1 EUT FRONT VIEW	22
14.2 EUT TOP VIEW.....	22
14.3 EUT BOTTOM VIEW	23
14.4 SUPPORTING EQUIPMENT FRONT VIEW – URH & DRU HOST.....	23
14.5 SUPPORTING EQUIPMENT REAR VIEW – URH HOST.....	24
14.6 SUPPORTING EQUIPMENT REAR VIEW – DRU Host.....	24
14.7 SUPPORT EQUIPMENT FRONT VIEW - MRAU	25
14.8 SUPPORT EQUIPMENT REAR VIEW - MRAU	25
14.9 SUPPORT EQUIPMENT FRONT VIEW – IFEU.....	26
14.10 SUPPORT EQUIPMENT REAR VIEW – IFEU.....	26
14.11 SUPPORT EQUIPMENT POWER SUPPLIES FRONT VIEW	27
14.12 SUPPORT EQUIPMENT FRONT VIEW - SRAU.....	27
14.13 EUT PCB BOTTOM VIEW 1	28
14.14 EUT PCB BOTTOM VIEW 2	28

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	R1102156-27	Original Report	2011-03-03

1 General Information

1.1 Product Description for Equipment under Test (EUT)

This test and measurement report was prepared on behalf of *ADC Telecommunications, Inc.* and their product FCC ID: *F8I-SP0700LH*, Model: *FWU-L6000HUDART;FlexWave Prism Host 700 Rx Lower ABC* which will henceforth be referred to as the “EUT”. The EUT is a wireless network card which operates in 700MHZ LTE band A+B Uplink only. It operates in a multi-operator/multi-protocol single platform system supporting up to 8 Radio Frequency (RF) bands. It consists of a Host Unit, an Expansion Unit (comprised of a DART Remote Module (DRU), IF Expansion Module (IFEU), and Power Supply), and Remote Amplifiers Units (RAUs). The Host, DRU and IFEU are intended for telecom closet indoor use. The RAU is intended to be installed above a false ceiling in an environmentally controlled office. Its operating frequency is from 698 MHz to 716 MHz.

1.2 Mechanical Description

EUT measures approximately 195 mm (**L**) x 93 mm (**W**) x 27 mm (**H**), and weighs approximately 322g.

The test data gathered are from production sample, serial number: BTW184120002 provided by the manufacturer.

1.3 EUT Photo



Please refer to Exhibit C for more EUT photographs.

1.4 Objective

This type approval report is prepared on behalf of ADC Telecommunications, Inc. in accordance with Part 2, Subpart J, Part 27, Subpart E, of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC rules for RF output power, modulation characteristic, occupied bandwidth, spurious emissions at antenna terminal, field strength of spurious radiation, frequency stability, band edge, and conducted and radiated margin.

1.5 Related Submittal(s)/Grant(s)

Refer to: FCC ID: F8I-SP851970H, BACL Report: R1001143

1.6 Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

Part 27 - Miscellaneous Wireless Communications Services

Applicable Standards: TIA/EIA-603-C, ANSI C63.4-2003.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratory, Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

1.7 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in the field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the values ranging from +2.0 dB for Conducted Emissions tests and +4.0 dB for Radiated Emissions tests are the most accurate estimates pertaining to uncertainty of EMC measurements at BACL Corp.

Detailed instrumentation measurement uncertainties can be found in BACL Corp. report QAP-018.

1.8 Test Facility

The test site used by BACL Corp. to collect radiated and conducted emissions measurement data is located at its facility in Sunnyvale, California, USA.

The test sites at BACL have been fully described in reports submitted to the Federal Communication Commission (FCC) and Voluntary Control Council for Interference (VCCI). The details of these reports has been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 11 and

December 10, 1997 and Article 8 of the VCCI regulations on December 25, 1997. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission, Industry Canada, and Voluntary Control Council for Interference has the reports on file and is listed under FCC registration number: 90464, IC registration number: 3062A, and VCCI Registration Number: R-2463 and C-2698. The test site has been approved by the FCC, IC, and VCCI for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, BACL is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200167-0). The current scope of accreditations can be found at <http://ts.nist.gov/ts/htdocs/210/214/scopes/2001670.htm>

2 System Test Configuration

2.1 Justification

The EUT was configured for testing according to EIA/TIA-603-C.

The final qualification test was performed with the EUT operating at normal mode.

2.2 EUT Exercise Software

Signal was sent through EUT using a signal generator; device was set to normal operating mode.

2.3 Equipment Modifications

No modifications were made to the EUT.

2.4 Support Equipment List

Manufacturer	Description	Model	Serial Number
ADC Telecommunication	Master RAU	742784-0 Rev:1	MR101Y8C / Unit #9
ADC Telecommunication	Master RAU	-	Unit 3
Unipower Corporation	AC/DC Power Supply	TPCR1V3C-Z	24090T0019
ADC Telecommunication	IF Expansion Module	-	S/N7

2.5 Local Support Equipment and Software List and Details

Manufacturer	Description	Model	Serial Number
Rhode & Schwarz	Signal Generator	SMIQ 03	849192/0085

2.6 Internal Configurations of EUT

Manufacturer	Description	Model	Serial Number
ADC Telecommunication	URH Host 700ABC1 RF Dart PCB Board	1472952G REV20	BTW184120002

2.7 Interface Ports and Cables

Cable Description	Length (m)	To	From
Shielded Cable (Duplex Fiber Optic)	3	Host Unit	DRU (Dart Remote Unit)
75 Ohm Coax Cable	3	IF Expansion Unit (IFEU)	SRAU
75 Ohm Coax Cable	50 x 2	IF Expansion Unit (IFEU)	MRAU
50 ohm CATV cable	< 1	DRU	IF Expansion Unit
RF Cable	< 1	Main Hub/RAU	Spectrum Analyzer
RF Cable	< 1	Main Hub/RAU	Signal Generator

3 Summary of Test Results

FCC Rules	Description of Tests	Results
§2.1046, §27.50 (i)	RF Output Power	Note ¹
§2.1047	Modulation Characteristics	N/A
§2.1049 (h), §27.53 (c)	Occupied Bandwidth	Note ¹
§2.1053, §27.53 (c)	Spurious Radiated Emissions	Note ¹
§2.1051, §27.53 (c)	Spurious Emissions at Antenna Terminals	Note ¹
§27.53 (c)	Band Edge	Note ¹
§27.54	Frequency Stability	Note ¹
§27.52, §2.1091	RF Exposure Info	Compliant

Note¹:

Please refer to FCC ID: F8I-SP851970H, BACL Report: R1001143.

4 FCC §2.1046 & §27.50 – RF Output Power

4.1 Applicable Standard

According to §27.50, the maximum effective radiated power (ERP) of fixed and base station must not exceed 1000 Watts.

4.2 Test Procedure

Conducted:

The RF output of the transmitter was connected to the signal generator and the spectrum analyzer through sufficient attenuation.

4.3 Test Results

Please refer to FCC ID: F8I-SP851970H, BACL Report: R1001143.

5 FCC §2.1047 - Modulation Characteristic

5.1 Applicable Standard

According to FCC §2.1047(d) and Part 27, there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

5.2 Test Result

N/A

6 FCC §2.1049 & §27.53 – Occupied Bandwidth

6.1 Applicable Standard

Requirements: FCC §2.1049 and §27.53.

6.2 Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 100 kHz and the 26 dB & 99% bandwidth was recorded.

6.3 Test Results

Please refer to FCC ID: F8I-SP851970H, BACL Report: R1001143.

7 FCC §2.1053 & §27.53 – Spurious Radiated Emissions

7.1 Applicable Standard

Requirements: FCC §2.1053, §27.53.

7.2 Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = 10 log (TX Power in Watts/0.001) – the absolute level

Spurious attenuation limit in dB = $43 + 10 \log_{10}$ (power out in Watts)

7.3 Test Results

Please refer to FCC ID: F8I-SP851970H, BACL Report: R1001143.

8 FCC §2.1051 & §27.53 - Spurious Emissions at Antenna Terminals

8.1 Applicable Standard

Requirements: CFR 47, § 2.1051. § 27.53.

The spectrum shall be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1057.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB

8.2 Test Results

Please refer to FCC ID: F8I-SP851970H, BACL Report: R1001143.

9 FCC §27.53 – Band Edge

9.1 Applicable Standard

According to FCC §27.53, the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

9.2 Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency.

9.3 Test Results

Please refer to FCC ID: F8I-SP851970H, BACL Report: R1001143.

10 FCC §2.1055 & §27.54 – Frequency Stability

10.1 Applicable Standard

According to FCC §27.54, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

10.2 Test Procedure

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from - 30 °C to + 50 °C using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from battery end point to 115 % of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification — the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.000\ 25\%$ ($\pm 2.5\ ppm$) of the center frequency.

10.3 Test Results

Please refer to FCC ID: F8I-SP851970H, BACL Report: R1001143.

11 FCC §1.1307(b), §27.52 & §2.1091 - RF Exposure Information

11.1 Applicable Standard

According to §1.1310 and §2.1091 (Mobile Devices) RF exposure is calculated.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

Note: f = frequency in MHz

* = Plane-wave equivalent power density

11.2 MPE Prediction

Predication of MPE limit at a given distance, equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

11.3 Test Result

Maximum peak output power at antenna input terminal (dBm): -10.81

Maximum peak output power at antenna input terminal (mW): 0.1

Prediction distance (cm): 20

Prediction frequency (MHz): 703

Antenna Gain, typical (dBi): 8.0

Maximum Antenna Gain (numeric): 6.310

Power density at predication frequency and distance (mW/cm²): 0.000013

MPE limit for uncontrolled exposure at predication frequency (mW/cm²): 0.4680