



TEST REPORT

Report No. : AE010456-1

Date : 2004 September 22

Client : IVL Technologies Ltd.
6710 Bertram Place,
Victoria, BC Canada,
V9A 7M6

Sample Description : One (1) submitted sample stated to be :
Model Name : Karaoke Microphone
Model No. : OKH08
Rating : AC 120V / DC 6V
No. of sample(s) : Two (2) set(s) ***

Date Received : 2004 June 24.
2004 September 10.

Test Period : 2004 June 24 – 2004 June 30.
2004 June 30 – 2004 July 06.
2004 September 10 – 2004 September 22.

Test Requested : FCC Part 15 Certification

Test Method : FCC Rules and Regulations Part 15 – April 2004
ANSI C63.4 – 2001

Test Result : See attached sheet(s) from page 2 to 14.

Conclusion : The submitted sample was found to comply with requirement of FCC
Part 15 Subpart B.

For and on behalf of
CMA Testing and Certification Laboratories

Authorized Signature : 

Page 1 of 14

Danny Chui
EMC Engineer - EL. Division

FCC ID : FEE-OKH08-001



TEST REPORT

Report No. : AE010456-1

Date : 2004 September 22

Table of Contents

1	General Information	3
1.1	General Description.....	3
1.2	Related Submittal Grants.....	3
1.3	Location of the test site.....	4
1.4	List of measuring equipment	5
1.5	List of support equipment.....	6
2	Description of the radiated emission test	7
2.1	Test Procedure	7
2.2	Test Result	7
2.3	Radiated Emission Measurement Data.....	8
2.3	Radiated Emission Measurement Data.....	9
3	Description of the Line-conducted Test	10
3.1	Test Procedure	10
3.2	Test Result	10
3.3	Graph and Table of Conducted Emission Measurement Data	10
4	Photograph	11
4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission.....	11
4.2	Photographs of the External and Internal Configurations of the EUT	11
5	Supplementary document	11
6	Appendices.....	12



TEST REPORT

Report No. : AE010456-1

Date : 2004 September 22

1 General Information

1.1 General Description

The equipment under test (EUT) is a karaoke microphone with internal memory and a Secure Digital (SD) card slot. The EUT is controlled by a crystal operating at 72 MHz. The EUT has A/V output for karaoke function and USB interface for transferring music from and to a PC.

A brief circuit description is saved with filename : OpDes.pdf

1.2 Related Submittal Grants

This is a single application for certification of a computer peripheral product.

FCC ID : FEE-OKH08-001

Page 3 of 14



TEST REPORT

Report No. : AE010456-1

Date : 2004 September 22

1.3 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2001. An Open Area Testing Site is set up for investigation and located at :

Top of the Roof, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2001. A double shielded room is located at :

Roof Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

FCC ID : FEE-OKH08-001

Page 4 of 14

This document shall not be reproduced either in full or in part except with written approval by the Authorized Representative of CMA Testing.
Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.
Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



TEST REPORT

Report No. : AE010456-1

Date : 2004 September 22

1.4 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Certification No.
EMI Test Receiver	R&S	ESCS30	100001	S21141
Broadband Antenna	Schaffner	CBL6113B	2718	AC1753
Signal Generator	IFR	2023B	202302/938	Nil
LISN	R&S	ESH3-Z5	100038	S21142
LISN	R&S	ESH3-Z5	100010	20-70405
Pulse Limiter	R&S	ESH3-Z2	100001	20-73194
Biconical Antenna	R&S	HK116	837414/004	4000.7752.02



TEST REPORT

Report No. : AE010456-1

Date : 2004 September 22

1.5 List of support equipment

1. Intel CPU PIII 800EB / 256 cache / 133MHz
Model: L103A455-0041 SL4MB
2. Intel Mother Board
Model: Intel Type: D815EEA
3. IBM Hard-disk
Model: DTLA-30720, 20.5GB
4. Proview LCD Monitor
Model: 568
S/N: FYUJ240040133
5. IBM Mouse
Model: 12J3618
S/N: 23-005077
6. Acer Keyboard
Model: 6511-VA
7. Hewlett Packard LaserJet 2100TN
Model: C4172A
S/N: SGGS038577
8. PenPower Handwriting System
Model: PP403N
S/N: PT9122239
9. USB cable
(Provided by Applicant)
10. Earphone

FCC ID : FEE-OKH08-001

Page 6 of 14



TEST REPORT

Report No. : AE010456-1

Date : 2004 September 22

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2001.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

2.2 Test Result

All modes had been test. The measurement data based on measurements employing the CISPR quasi-peak detector were indicated in next page.

All other measurement were 20 dB below the 15.109 limits. Thus, those highest emissions were presented in next page (section 2.3).

It was found that the EUT meet the FCC requirement.

FCC ID : FEE-OKH08-001

Page 7 of 14



TEST REPORT

Report No. : AE010456-1

Date : 2004 September 22

2.3 Radiated Emission Measurement Data

**Radiated emission
pursuant to
the requirement of FCC Part 15 subpart B**

Mode : USB with PC-connected

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V/m)	Antenna and Cable factor (dB)	Field Strength (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
72.001	H	26.6	6.3	32.9	40.0	-7.1
144.002	H	21.8	12.4	34.2	43.5	-9.3
180.001	H	22.0	10.5	32.5	43.5	-11.0
216.002	H	25.9	10.1	36.0	46.0	-10.0
240.002	H	20.9	10.1	31.0	46.0	-15.0
252.002	H	18.5	14.2	32.7	46.0	-13.3
288.002	H	28.1	14.2	42.3	46.0	-3.7
324.002	H	18.4	15.6	34.0	46.0	-12.0
360.002	H	25.5	15.6	41.1	46.0	-4.9
396.002	H	25.3	15.6	40.9	46.0	-5.1

FCC ID : FEE-OKH08-001

Page 8 of 14



TEST REPORT

Report No. : AE010456-1

Date : 2004 September 22

2.3 Radiated Emission Measurement Data

**Radiated emission
pursuant to
the requirement of FCC Part 15 subpart B**

Mode : Standalone

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V/m)	Antenna and Cable factor (dB)	Field Strength (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
72.000	H	26.1	6.3	32.4	40.0	-7.6
144.009	H	20.8	12.4	33.2	43.5	-10.3
180.001	H	23.2	10.5	33.7	43.5	-9.8
216.001	H	32.4	10.1	42.5	46.0	-3.5
240.002	H	26.9	10.1	37.0	46.0	-9.0
252.012	H	18.8	14.2	33.0	46.0	-13.0
288.002	H	28.1	14.2	42.3	46.0	-3.7
324.002	H	17.1	15.6	32.7	46.0	-13.3
360.003	H	26.3	15.6	41.9	46.0	-4.1
396.003	H	24.9	15.6	40.5	46.0	-5.5

FCC ID : FEE-OKH08-001

Page 9 of 14



TEST REPORT

Report No. : AE010456-1

Date : 2004 September 22

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2001. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

The PC connected mode had been tested. The EUT connecting with an USB cable and earphone produced the maximum emission. The measurement data was indicated in Appendix.

The result showed that the EUT met the FCC requirement.

3.3 Graph and Table of Conducted Emission Measurement Data

For electronic filing, the document are saved with filename TestRpt2.pdf

FCC ID : FEE-OKH08-001

Page 12 of 14



TEST REPORT

Report No. : AE010456-1

Date : 2004 September 22

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup5.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho8.jpg

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp1.jpg, LabelSmp2.pdf
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem1.pdf, Schem2.pdf, Schem3.pdf,
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf



TEST REPORT

Report No. : AE010456-1

Date : 2004 September 22

6 Appendices

A1.	Photos of the set-up of Radiated Emissions	1 page
A2.	Photos of the set-up of Conducted Emissions	2 pages
A3.	Photos of External Configurations	1 page
A4.	Photos of Internal Configurations	4 pages
A5.	ID Label/Location	2 pages
A6.	Conducted Emission Test Result	4 pages
A7.	Block Diagram	1 page
A8.	Schematics Diagram	6 pages
A9.	User Manual	21 pages
A10.	Operation Description	5 pages

***** End of Report *****