



# PCTEST Engineering Laboratory, Inc.

6660-B Dobbin Road • Columbia, MD 21045 • U.S.A.

TEL (410) 290-6652 • FAX (410) 290-6654

<http://www.pctestlab.com>



## CERTIFICATE OF COMPLIANCE FCC Part 24 Certification

LG Information & Communications, Ltd.  
Communication Terminal Research Lab  
459-9, Kasan-dong, Keumchun-ku  
Seoul 153-023, Korea  
Attn: Harris Ahn, Principal Engineer

Dates of Tests: December 16-17, 1999  
Test Report S/N: 24.991213674.FFM  
Test Site: PCTEST Lab, Columbia MD USA

FCC ID

**FFMLGI3000W**

APPLICANT

**LG Information & Communications, Ltd.**

|                       |                                                      |
|-----------------------|------------------------------------------------------|
| Classification:       | Licensed Portable Transmitter Held to Ear (PCE)      |
| FCC Rule Part(s):     | §24(E), §2                                           |
| EUT Type:             | Single-Band PCS CDMA Internet Phone                  |
| Trade Name/Model(s):  | LGIC LGI-3000W                                       |
| Frequency Range:      | Tx: 1851.25 – 1908.75MHz<br>Rx: 1931.25 – 1988.75MHz |
| Max. RF Output Power: | 0.32 Watts EIRP (25.0 dBm)                           |
| Frequency Tolerance:  | 0.00025% (2.5 ppm)                                   |
| Emission Designator:  | 1M25F9W                                              |

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947 with the following remarks (Note Codes):

*\*(BC) The output power is continuously variable from the value listed in this entry to 5%-10% of the value listed.*

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 853(a).

  
Randy Ortanez  
President & Chief Engineer




9 9 1 1 2 9 6 2 7 . C K L

**NVLAP**<sup>®</sup>  
LAB CODE 100431-0

## TABLE OF CONTENTS

---

|               |                                                 |       |
|---------------|-------------------------------------------------|-------|
| ATTACHMENT A: | COVER LETTER(S)                                 |       |
| ATTACHMENT B: | ATTESTATION STATEMENT(S)                        |       |
| ATTACHMENT C: | TEST REPORT                                     |       |
| 1.1           | SCOPE                                           | 1     |
| 2.1           | INTRODUCTION (SITE DESCRIPTION)                 | 2     |
| 3.1           | INSERTS PER §2.1033                             | 3     |
| 4.1           | DESCRIPTION OF TESTS                            | 4-5   |
| 5.1           | TEST DATA (Equivalent Isotropic Radiated Power) | 6     |
| 6.1           | TEST DATA (RADIATED)                            | 7-9   |
| 7.1           | TEST DATA (FREQUENCY STABILITY)                 | 10-11 |
| 8.1           | PLOTS OF EMISSIONS                              | 12    |
| 9.1           | LIST OF TEST EQUIPMENT                          | 13    |
| 10.1          | SAMPLE CALCULATIONS                             | 14    |
| 11.1          | RECOMMENDATION / CONCLUSION                     | 15    |
| ATTACHMENT D: | TEST PLOTS                                      |       |
| ATTACHMENT E: | FCC ID LABEL / LOCATION                         |       |
| ATTACHMENT F: | TEST SETUP PHOTOGRAPHS                          |       |
| ATTACHMENT G: | EXTERNAL PHOTOGRAPHS                            |       |
| ATTACHMENT H: | INTERNAL PHOTOGRAPHS                            |       |
| ATTACHMENT I: | BLOCK DIAGRAM(S)                                |       |
| ATTACHMENT J: | SCHEMATIC DIAGRAM(S) & DESCRIPTION              |       |
| ATTACHMENT K: | PARTS LIST/TUNE UP PROCEDURE                    |       |
| ATTACHMENT L: | OPERATIONAL DESCRIPTION                         |       |
| ATTACHMENT M: | USER'S MANUAL                                   |       |
| ATTACHMENT N: | SAR MEASUREMENT REPORT                          |       |
| ATTACHMENT O: | SAR TEST DATA                                   |       |
| ATTACHMENT P: | SAR TEST SETUP PHOTOGRAPHS                      |       |



# MEASUREMENT REPORT



## 1.1 Scope

*Product Evaluation and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.*

## §2.1033 General Information

|                        |                                                  |
|------------------------|--------------------------------------------------|
| <b>Applicant Name:</b> | <b>LG Information &amp; Communications, Ltd.</b> |
| <b>Address:</b>        | <b>Communication Terminal Research Lab</b>       |
|                        | <b>459-9, Kasan-dong, Keumchun-ku</b>            |
|                        | <b>Seoul 153-023, Korea</b>                      |
| <b>Attention:</b>      | <b>Harris Ahn, Principal Engineer</b>            |

- |                         |                                                |
|-------------------------|------------------------------------------------|
| • FCC ID:               | <b>FFMLGI3000W</b>                             |
| • Trade Name(s):        | <b>LGIC</b>                                    |
| • Model(s):             | <b>LGI-3000W</b>                               |
| • Quantity:             | Quantity production is planned                 |
| • Tx Frequency Range:   | 1851.25 – 1908.75 MHz                          |
| • Rx Frequency Range:   | 1931.25 – 1988.75 MHz                          |
| • Emission Designator:  | 1M25F9W                                        |
| • Max. RF Output Power: | 0.32 W EIRP (25.0 dBm)                         |
| • FCC Classification:   | Part 24 Licensed Portable Tx Held to Ear (PCE) |
| • Equipment (EUT) Type: | Single-Band PCS CDMA Internet Phone            |
| • FCC Rule Part(s):     | § 24(E), §2                                    |
| • Application Type:     | Certification                                  |
| • Modulation:           | CDMA                                           |
| • AC/DC Power Adapter:  | 4.2VDC 1000mA (Model: AC-TC RAINBOW)           |
| • Frequency Tolerance:  | ± 2.5 ppm                                      |
| • Dates of Tests:       | December 16-17, 1999                           |
| • Place of Tests:       | PCTEST Lab, Columbia, MD U.S.A.                |

9 9 1 1 2 9 6 2 7 . C K L



## 2.1 INTRODUCTION

These measurement tests were conducted at **PCTEST Engineering Laboratory, Inc.** facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on October 19, 1992.

PCTEST Lab is recognized under the National Voluntary Laboratory Accreditation Program for satisfactory compliance with criteria established in Title 15, Part 285 Code of Federal Regulations. These criteria encompass the requirements of ISO/IEC Guide 25 and the relevant requirements of ISO 9002 (ANSI/ASQC Q92-1987) as suppliers of calibration or test results. The Scope of PCTEST Accreditation are for Electromagnetic Compatibility and Telecommunications and FCC.

## 2.2 PCTEST Location

The map at right shows the location of the PCTEST Lab, its proximity to the FCC Lab, the Columbia vicinity area, the Baltimore-Washington International (BWI) airport, and the city of Baltimore, and the Washington, D.C. area. (see Figure1).




Figure 1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area.

### **3.1 INSERTS PER §2.1033(d)**

---

#### **§2.1033(d) Function of Active Devices (Confidential)**

The Function of active devices are shown in Attachment K.

#### **§2.1033(d) Circuit Diagrams & Description (Confidential)**

The circuit diagrams & description are shown in Attachment J.

#### **§2.1033(d) Block Diagrams (Confidential)**

The block diagrams are shown in Attachment I.

#### **§2.1033(d) Operating Instructions**

The instruction manual is shown in Attachment M.

#### **§2.1033(d) Tune-Up Procedure (Confidential)**

The tune-up procedure is shown in Attachment K.

#### **§2.1033(d) Parts List (Confidential)**

The parts list is shown in Attachment K.

#### **§2.1033(d) Description of Freq. Stabilization Circuit (Confidential)**

The description of frequency stabilization circuit is shown in Attachment J.

#### **§2.1033(d)( Description for Suppression of Spurious Radiation, for Limiting Modulation, and Harmonic Suppresion Circuits (Confidential)**

The description of suppression stabilization circuits are shown in Attachment J.

## 4.1 DESCRIPTION OF TESTS

---

### **4.2 §24.238 Occupied Bandwidth Emission Limits**

- (a) On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log (P)$  dB.
- (b) Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.
- (c) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.
- (d) The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

### **4.3 §2.1051 Spurious and Harmonic Emissions at Antenna Terminal**

The level of the carrier and the various conducted spurious and harmonic frequencies are measured by means of a calibrated spectrum analyzer and microwave pre-amplifier. The spectrum is scanned from 10 MHz or the lowest frequency generated in the equipment up to 20 GHz. The transmitter is set to its maximum rated output power and modulated according to the manufacturer's supplied modulation characteristics.

| BLOCK | Freq. Range (MHz)<br>Transmitter (Tx) | Freq. Range (MHz)<br>Receiver (Rx) |
|-------|---------------------------------------|------------------------------------|
| A     | 1850 - 1865                           | 1930 - 1945                        |
| B     | 1870 - 1885                           | 1950 - 1965                        |
| C     | 1895 - 1910                           | 1975 - 1990                        |
| D     | 1865 - 1870                           | 1945 - 1950                        |
| E     | 1885 - 1890                           | 1965 - 1970                        |
| F     | 1890 - 1895                           | 1970 - 1975                        |

Table 1. Broadband PCS Service Frequency Blocks.

## **4.1 DESCRIPTION OF TESTS (CONTINUED)**

---

### **4.4 §24.229 Frequencies**

At the input terminals of the spectrum analyzer, an isolator (RF pad), and a high-pass filter are connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests), and the analyzer. The high-pass filter (signals below 2 GHz) is to limit the fundamental frequency from interfering with the measurement of low level spurious and harmonic emissions and to ensure that the preamplifier is not saturated.

### **4.5 §2.1053 Radiation Spurious and Harmonic Emissions**

Radiation and harmonic emissions above 1 GHz is measured at out 3-meter indoor site. The EUT is placed on the turntable connected to a dummy load in normal operation using the intended power source. A receiving antenna located 3 meters from the turntable receives any signal radiated from the transmitter and its operating accessories. The antenna is varied from 1 to 4 meters and the polarization is varied (horizontal and vertical) to determine the worst-case emission level. To obtain actual radiated signal strength, a signal generator is adjusted in output until a reading identical to that obtained with the actual transmitter is obtained at the receiver. Signal strength is read directly from the generator and recorded on the attached table.

### **4.6 §24.135 Frequency Stability/Temperature Variation**

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

*Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.0001$  ( $\pm 1$  ppm) of the center frequency.*

**NOTE: The EUT is tested down to the battery endpoint.**

## 5.1 Test Data

### 5.2 § 24.232(b) Equivalent Isotropic Radiated Power (E.I.R.P.)

#### Radiated measurements at 3 meters

Supply Voltage: 4.0 VDC

Modulation: PCS CDMA

| FREQ.<br>(MHz) | LEVEL<br>(dBm) | AFCL<br>(dB) | POL<br>(H/V) | Height<br>(m) | Azimuth<br>(° angle) | F/S<br>( $\mu$ V/m) | EIRP<br>(dBm) | EIRP<br>(W) | Battery  |
|----------------|----------------|--------------|--------------|---------------|----------------------|---------------------|---------------|-------------|----------|
| 1851.25        | -22.20         | 35.31        | V            | 1.3           | 90.0                 | 1012744.7           | 24.88         | 0.308       | Standard |
| 1880.00        | -22.25         | 35.48        | V            | 1.3           | 90.0                 | 1026833.4           | 25.00         | 0.316       | Standard |
| 1908.75        | -22.50         | 35.65        | V            | 1.3           | 90.0                 | 1017419.4           | 24.92         | 0.311       | Standard |

#### NOTES:

1. The bandwidth is set per §24.238 (RBW = 3MHz, VBW = 3MHz).
2. The spectrum was checked from 25 MHz up to the 10th harmonic.
3. All emissions not listed were found to be more than 20dB below the limit.
4. < -130dBm is below the floor of the spectrum analyzer.
5. The EUT is manipulated through 3 orthogonal axis and the worst-case are reported.
6. The EUT is placed 3m. away from the receiving antenna and the EIRP is calculated using the formula:

$$\text{EIRP (dBm)} = 10 \log_{10} \left( \left( \frac{r(\text{mV/m})}{1 \times 10^6} \right)^2 / 30.0 / 1 \times 10^{-3} \right)$$

$$\text{EIRP (dBm)} = 10 \log_{10} \left[ \left( \frac{3 \times \text{FS}}{1 \times 10^6} \right)^2 / (30.0) \times 1000 \right]$$

$$\text{EIRP (Watts)} = \left\{ \frac{3 \times \text{FS}}{1 \times 10^6} \right\}^2 / 30.0$$

## 6.1 Test Data

### Radiated Measurements

#### 6.2 § 2.993 Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1851.25 MHz  
 CHANNEL: 0025 (Low)  
 MEASURED OUTPUT POWER: 25.00 dBm = 0.32 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  38.01 dBc

| FREQ.<br>(MHz) | LEVEL<br>(dBm) | AFCL<br>(dB) | POL<br>(H/V) | F/S<br>( $\mu$ V/m) | EIRP<br>(dBm) | (dBc) |
|----------------|----------------|--------------|--------------|---------------------|---------------|-------|
| 3702.50        | -87.0          | 44.4         | V            | 1659.6              | -30.83        | 55.8  |
| 5553.75        | -96.0          | 49.7         | V            | 1083.9              | -34.53        | 59.5  |
| 7405.00        | -120.0         | 53.7         | V            | 108.4               | -54.53        | 79.5  |
| 9256.25        | -126.5         | 57.2         | V            | 76.7                | -57.53        | 82.5  |
| 11107.50       | < -130         | 58.0         |              |                     |               |       |
|                |                |              |              |                     |               |       |

#### NOTES:

- The bandwidth is set per §24.238.
- The spectrum was checked from 25 MHz up to the 10th harmonic.
- All emissions not listed were found to be more than 20dB below the limit.
- < -130dBm is below the floor of the spectrum analyzer.
- The EUT is manipulated through 3 orthogonal axis and the worst-case are reported.
- The EUT is placed 3m. Away from the receiving antenna and the EIRP is calculated using the formula:  

$$\text{EIRP (dBm)} = 10\log_{10}(((r(\text{mV/m})/1 \times 10^6)^2/30.0/1 \times 10^{-3})$$

$$\text{EIRP (dBm)} = 10\log_{10}[(3 \times \text{FS}/1 \times 10^6)^2 / (30.0) \times 1000]$$

$$\text{EIRP (Watts)} = [3 \times \text{FS}]/1 \times 10^6]^2 / 30.0$$

## 6.1 Test Data (Continued)

### Radiated Measurements

#### 6.3 § 2.993 Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1880.00 MHz  
 CHANNEL: 0600 (Middle)  
 MEASURED OUTPUT POWER: 25.00 dBm = 0.32 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  38.01 dBc

| FREQ.<br>(MHz) | LEVEL<br>(dBm) | AFCL<br>(dB) | POL<br>(H/V) | F/S<br>( $\mu$ V/m) | EIRP<br>(dBm) | (dBc) |
|----------------|----------------|--------------|--------------|---------------------|---------------|-------|
| 3760.00        | -86.5          | 44.7         | V            | 1819.7              | -30.03        | 55.0  |
| 5640.00        | -96.2          | 49.9         | V            | 1083.9              | -34.53        | 59.5  |
| 7520.00        | -119.6         | 54.0         | V            | 117.5               | -53.83        | 78.8  |
| 9400.00        | -126.0         | 57.4         | V            | 83.2                | -56.83        | 81.8  |
| 11280.00       | < -130         | 58.2         |              |                     |               |       |
|                |                |              |              |                     |               |       |

#### NOTES:

- The bandwidth is set per §24.238.
- The spectrum was checked from 25 MHz up to the 10th harmonic.
- All emissions not listed were found to be more than 20dB below the limit.
- < -130dBm is below the floor of the spectrum analyzer.
- The EUT is manipulated through 3 orthogonal axis and the worst-case are reported.
- The EUT is placed 3m. Away from the receiving antenna and the EIRP is calculated using the formula:  

$$\text{EIRP (dBm)} = 10\log_{10}(((r(\text{mV/m})/1 \times 10^6)^2/30.0/1 \times 10^{-3})$$

$$\text{EIRP (dBm)} = 10\log_{10}[(3 \times \text{FS}/1 \times 10^6)^2 / (30.0) \times 1000]$$

$$\text{EIRP (Watts)} = [3 \times \text{FS}]/1 \times 10^6]^2 / 30.0$$

## 6.1 Test Data (Continued)

### Radiated Measurements

#### 6.4 § 2.993 Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1908.75 MHz  
 CHANNEL: 1175 (High)  
 MEASURED OUTPUT POWER: 25.00 dBm = 0.32 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  38.01 dBc

| FREQ.<br>(MHz) | LEVEL<br>(dBm) | AFCL<br>(dB) | POL<br>(H/V) | F/S<br>( $\mu$ V/m) | EIRP<br>(dBm) | (dBc) |
|----------------|----------------|--------------|--------------|---------------------|---------------|-------|
| 3817.50        | -86.0          | 45.0         | V            | 1995.3              | -29.23        | 54.2  |
| 5726.25        | -97.2          | 50.1         | V            | 988.6               | -35.33        | 60.3  |
| 7635.00        | -119.7         | 54.2         | V            | 118.9               | -53.73        | 78.7  |
| 9543.75        | -125.0         | 57.7         | V            | 96.6                | -55.53        | 80.5  |
| 11452.50       | < -130         | 58.4         |              |                     |               |       |
|                |                |              |              |                     |               |       |

#### NOTES:

- The bandwidth is set per §24.238.
- The spectrum was checked from 25 MHz up to the 10th harmonic.
- All emissions not listed were found to be more than 20dB below the limit.
- < -130dBm is below the floor of the spectrum analyzer.
- The EUT is manipulated through 3 orthogonal axis and the worst-case are reported.
- The EUT is placed 3m. Away from the receiving antenna and the EIRP is calculated using the formula:  

$$\text{EIRP (dBm)} = 10\log_{10}(((r(\text{mV/m})/1 \times 10^6)^2/30.0)/1 \times 10^{-3})$$

$$\text{EIRP (dBm)} = 10\log_{10}[(3 \times \text{FS}/1 \times 10^6)^2 / (30.0) \times 1000]$$

$$\text{EIRP (Watts)} = [3 \times \text{FS}]/1 \times 10^6]^2 / 30.0$$

## 7.1 Test Data


### 7.2 § 24.135 FREQUENCY STABILITY

OPERATING FREQUENCY: 1,880,000,017 Hz  
 CHANNEL: 600  
 REFERENCE VOLTAGE: 4.0 VDC  
 DEVIATION LIMIT: 0.00025 % or 2.5 ppm

| VOLTAGE<br>(%) | POWER<br>(VDC) | TEMP<br>(°C) | FREQ.<br>(Hz) | Deviation<br>(%) |
|----------------|----------------|--------------|---------------|------------------|
| 100 %          | 4.00           | + 20 (Ref)   | 1,880,000,017 | 0.000000         |
| 100 %          |                | - 30         | 1,879,999,940 | 0.000004         |
| 100 %          |                | - 20         | 1,879,999,959 | 0.000003         |
| 100 %          |                | - 10         | 1,879,999,983 | 0.000002         |
| 100 %          |                | 0            | 1,880,000,006 | 0.000001         |
| 100 %          |                | + 10         | 1,880,000,013 | 0.000000         |
| 100 %          |                | + 20         | 1,880,000,017 | 0.000000         |
| 100 %          |                | + 30         | 1,880,000,034 | -0.000001        |
| 100 %          |                | + 40         | 1,880,000,041 | -0.000001        |
| 100 %          |                | + 50         | 1,880,000,047 | -0.000002        |
| 100 %          |                | + 60         | 1,880,000,056 | -0.000002        |
| 85 %           | 3.40           | + 20         | 1,880,000,017 | 0.000000         |
| 115 %          | 4.60           | + 20         | 1,880,000,017 | 0.000000         |
| BATT. ENDPOINT | 2.48           | + 20         | 1,880,000,017 | 0.000000         |

# 7.1 Test Data (Continued)

## 7.2 § 24.135 FREQUENCY STABILITY



## **8.1 PLOT(S) OF EMISSIONS**

---

(SEE ATTACHMENT D)

## 9.1 TEST EQUIPMENT

| 9.2 Type                          | Model                                                                       | Cal. Due Date | S/N                    |
|-----------------------------------|-----------------------------------------------------------------------------|---------------|------------------------|
| Microwave Spectrum Analyzer       | HP 8566B (100Hz-22GHz)                                                      | 08/15/00      | 3638A08713             |
| Microwave Spectrum Analyzer       | HP 8566B (100Hz-22GHz)                                                      | 04/17/00      | 2542A11898             |
| Spectrum Analyzer/Tracking Gen.   | HP 8591A (100Hz-1.8GHz)                                                     | 08/10/00      | 3144A02458             |
| Signal Generator*                 | HP 8640B (500Hz-1GHz)                                                       | 06/03/00      | 2232A19558             |
| Signal Generator*                 | HP 8640B (500Hz-1GHz)                                                       | 06/03/00      | 1851A09816             |
| Signal Generator*                 | Rohde & Schwarz (0.1-1000MHz)                                               | 09/11/00      | 894215/012             |
| Ailtech/Eaton Receiver            | NM 37/57A-SL (30-1000MHz)                                                   | 04/12/00      | 0792-03271             |
| Ailtech/Eaton Receiver            | NM 37/57A (30-1000MHz)                                                      | 03/11/00      | 0805-03334             |
| Ailtech/Eaton Receiver            | NM 17/27A (0.1-32MHz)                                                       | 09/17/00      | 0608-03241             |
| Quasi-Peak Adapter                | HP 85650A                                                                   | 08/15/00      | 2043A00301             |
| Ailtech/Eaton Adapter             | CCA-7 CISPR/ANSI QP Adapter                                                 | 03/11/00      | 0194-04082             |
| Gigatronics Universal Power Meter | 8657A                                                                       |               | 1835256                |
| Gigatronics Power Sensor          | 80701A (0.05-18GHz)                                                         |               | 1833460                |
| Signal Generator                  | HP 8648D (9kHz-4GHz)                                                        |               | 3613A00315             |
| Amplifier Research                | 5S1G4 (5W, 800MHz-4.2GHz)                                                   |               | 22322                  |
| Network Analyzer                  | HP 8753E (30kHz-3GHz)                                                       |               | JP38020182             |
| Audio Analyzer                    | HP 8903B                                                                    |               | 3011A09025             |
| Modulation Analyzer               | HP 8901A                                                                    |               | 2432A03467             |
| Power Meter                       | HP 437B                                                                     |               | 3125U24437             |
| Power Sensor                      | HP 8482H (30µW-3W)                                                          |               | 2237A02084             |
| Harmonic/Flicker Test System      | HP 6841A (IEC 555-2/3)                                                      |               | 3531A00115             |
| Broadband Amplifier (2)           | HP 8447D                                                                    |               | 1145A00470, 1937A03348 |
| Broadband Amplifier               | HP 8447F                                                                    |               | 2443A03784             |
| Horn Antenna                      | EMCO Model 3115 (1-18GHz)                                                   |               | 9704-5182              |
| Horn Antenna                      | EMCO Model 3115 (1-18GHz)                                                   |               | 9205-3874              |
| Horn Antenna                      | EMCO Model 3116 (18-40GHz)                                                  |               | 9203-2178              |
| Biconical Antenna (4)             | Eaton 94455/Eaton 94455-1/Singer 94455-1/Compliance Design 1295, 1332, 0355 |               |                        |
| Log-Spiral Antenna (3)            | Ailtech/Eaton 93490-1                                                       |               | 0608, 1103, 1104       |
| Roberts Dipoles                   | Compliance Design (1 set)                                                   |               |                        |
| Ailtech Dipoles                   | DM-105A (1 set)                                                             |               | 33448-111              |
| EMCO LISN (6)                     | 3816/2                                                                      |               | 1079                   |
| Microwave Preamplifier 40dB Gain  | HP 83017A (0.5-26.5GHz)                                                     |               | 3123A00181             |
| Microwave Cables                  | MicroCoax (1.0-26.5GHz)                                                     |               |                        |
| Ailtech/Eaton Receiver            | NM37/57A-SL                                                                 |               | 0792-03271             |
| Spectrum Analyzer                 | HP 8594A                                                                    |               | 3051A00187             |
| Spectrum Analyzer (2)             | HP 8591A                                                                    |               | 3034A01395, 3108A02053 |
| Microwave Survey Meter            | Holaday Model 1501 (2.450GHz)                                               |               | 80931                  |
| Digital Thermometer               | Extech Instruments 421305                                                   |               | 426966                 |
| Attenuator                        | HP 8495A (0-70dB) DC-4GHz                                                   |               |                        |
| Bi-Directional Coax Coupler       | Narda 3020A (50-1000MHz)                                                    |               |                        |
| Shielded Screen Room              | RF Lindgren Model 26-2/2-0                                                  |               | 6710 (PCT270)          |
| Shielded Semi-Anechoic Chamber    | Ray Proof Model S81                                                         |               | R2437 (PCT278)         |
| Environmental Chamber             | Associated Systems Model 1025 (Temperature/Humidity)                        |               | PCT285                 |

\* Calibration traceable to the National Institute of Standards and Technology (NIST).

## 10.1 SAMPLE CALCULATIONS

---

### A. EIRP Calculation

$$\text{Level } \mu\text{V/m @ 3 meters} = \text{Log}_{10}^{-1} \left( \frac{\text{dBm} + 107 + \text{AFCL}}{20} \right)$$

$$\text{Log}_{10}^{-1} \left( \frac{-14 + 107 + 31.7}{20} \right)$$

$$1717908.4 \mu\text{V/m @ 3 meters}$$

Sample Calculation (relative to a dipole)

$$\text{EIRP (dBm)} = 10 \text{Log}_{10} \left( \frac{(r(\mu\text{V/m})1 \times 10^6)^2}{30.0/1 \times 10^{-3}} \right)$$

$$\text{EIRP (dBm)} = 10 \text{Log}_{10} \left( \frac{(3(1717908.4)1 \times 10^6)^2}{30.0/1 \times 10^{-3}} \right)$$

$$\text{EIRP (dBm)} = 29.46$$

### B. Emission Designator per §2.201

CDMA Sample

2M + 2DK

CDMA BW = 1.25 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

Emission Designator = 1M25F9W

## 11.1 RECOMMENDATION/CONCLUSION

---

The data collected shows that the **LG Information & Communications, Ltd. Single-Band PCS CDMA Internet Phone FCC ID: FFMLGI3000W** complies with all the requirements of Parts 2 and 24 of the FCC rules.