

Prüfbericht-Nr.: <i>Test Report No.:</i>	CN25SB3H 001	Auftrags-Nr.: <i>Order No.:</i>	326071829	Seite 1 von 23 <i>Page 1 of 23</i>
Kunden-Referenz-Nr.: <i>Client Reference No.:</i>	1288983	Auftragsdatum: <i>Order date.:</i>	2025-01-07	
Auftraggeber: <i>Client:</i>	IKEA of Sweden AB Box 702, SE-343 81 Älmhult, Sweden			
Prüfgegenstand: <i>Test item:</i>	Fixed Luminaire			
Bezeichnung / Typ-Nr.: <i>Identification / Type No.:</i>	B2412			
Auftrags-Inhalt: <i>Order content:</i>	TÜV Rheinland EMC service			
Prüfgrundlage: <i>Test specification:</i>	FCC 47 CFR Part 15, Subpart B:2023 Class B ICES-005:2018			
Wareneingangsdatum: <i>Date of receipt:</i>	2025-01-10	Refer to the EUT photos file		
Prüfmuster-Nr.: <i>Test sample No.:</i>	A003998857-001			
Prüfzeitraum: <i>Testing period:</i>	2025-05-08~2025-05-23			
Ort der Prüfung: <i>Place of testing:</i>	Refer to clause 1.1			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland (Shanghai) Co., Ltd.			
Prüfergebnis*: <i>Test result*:</i>	Pass			
geprüft von: <i>tested by:</i>	genehmigt von: <i>authorized by:</i>			
Datum: <i>Date:</i> 2025-07-24	<i>Rambo Liu</i> Rambo Liu	Ausstellungsdatum: <i>Issue date:</i> 2025-07-24	<i>Hexiong Liu</i> HeXiong g Liu	
Stellung: / Position	Project engineer	Stellung: / Position:	Authorizer	
Sonstiges / Other:	FCC ID: FHO- B2412 Test Firm Name: TUV Rheinland (Shanghai) Co., Ltd. Designation Number: CN1396 Test Firm Registration Number: 930979			
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>	Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>			
* Legende: P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet Legend: P(ass) = passed a.m. test specifications(s) F(ail) = failed a.m. test specifications(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Anmerkungen

Remarks

1	<p>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</p> <p><i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system.</i></p> <p><i>Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i></p>
2	<p>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature</p> <p><i>As contractually agreed, this document has been signed digitally only. TÜV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TÜV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i></p>
3	<p>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</p> <p><i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i></p> <p><i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i></p>
4	<p>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</p> <p><i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i></p>

Prüfbericht - Nr.: CN25SB3H 001
*Test Report No.:***Seite 3 von 23**
*Page 3 of 23***Revision history of test report:**

Report number	Issue date	Contents and reason for change if appropriate
CN25SB3H 001	2025-07-24	Initial release.

Contents

1	TEST SITES	5
1.1	TEST FACILITIES	5
2	GENERAL PRODUCT INFORMATION	6
2.1	PRODUCT FUNCTION AND INTENDED USE	6
2.2	RATINGS AND SYSTEM DETAILS	6
2.3	INDEPENDENT OPERATION MODES	6
2.4	DESCRIPTION OF INTERCONNECTING CABLES	6
2.5	NOISE GENERATING AND NOISE SUPPRESSING PARTS	6
2.6	HIGHEST FREQUENCY GENERATED OR USED IN THE DEVICE OR ON WHICH THE DEVICE OPERATES OR TUNES	6
2.7	SUBMITTED DOCUMENTS	6
3	TEST SET-UP AND OPERATION MODES	7
3.1	PRINCIPLE OF CONFIGURATION SELECTION	7
3.2	EQUIPMENT AND CABLE ARRANGEMENT	7
3.3	PHYSICAL CONFIGURATION FOR TESTING	8
3.4	TEST OPERATION AND TEST SOFTWARE	8
3.5	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	8
3.6	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE	8
4	CONFORMITY DECISION RULE	9
5	TEST RESULTS EMISSION	10
5.1	EMISSION IN THE FREQUENCY RANGE UP TO 30 MHz	10
5.1.1	Conducted Emission	10
5.2	EMISSION IN THE FREQUENCY RANGE ABOVE 30 MHz	16
5.2.1	Radiated Emission (30 - 1000 MHz)	16
6	PHOTOGRAPHS OF THE TEST SET-UP	22
7	LIST OF TEST AND MEASUREMENT INSTRUMENTS	23
8	LIST OF FIGURES	23

1 Test Sites

1.1 Test Facilities

Laboratory: TÜV Rheinland (Shanghai) Co., Ltd.

Address: Workshop 14, North Half of Workshop 10 and Workshop 16, Pingqian (Taicang) Modern Industrial Park, No.525, Yuewang Lingang South Road, Shaxi, Taicang, Jiangsu, China

The used test equipment is in accordance with CISPR 16-1 series standards for measurement of radio interference.

Refer to clause 7 for test and measurement instruments.

2 General Product Information

2.1 Product Function and Intended Use

The EUT (equipment under test) is an ordinary fixed luminaire for lighting and similar use. For further information, refer to the user's manual.

2.2 Ratings and System Details

Rated input : AC 120 V, 50-60 Hz
Rated power : Max 5.9 W

2.3 Independent Operation Modes

The basic operation modes are: "On" or "Off" with dimmer.

2.4 Description of interconnecting cables

None.

2.5 Noise Generating and Noise Suppressing Parts

Refer to the circuit diagram for further information.

2.6 Highest frequency generated or used in the device or on which the device operates or tunes

The highest frequency used in the EUT is less than 108 MHz.

2.7 Submitted Documents

Circuit diagram, label and user's manual.

3 Test Set-up and Operation Modes

3.1 Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible emission level. The test conditions were adapted accordingly in reference to the instructions for use.


Refer to the related paragraph of this report.

The sequence of testing:


1. Conducted emission tests were performed on 2025-05-23.
2. Radiated emission tests were performed on 2025-05-08.

3.2 Equipment and cable arrangement

Block diagram for radiated emission tests is as follows:



(Conducted emission)



(Radiated emission 30-1000 MHz)

Also refer to photographs on clause 6 for test setups for both conducted emission test and radiated emission test.

3.3 Physical Configuration for Testing

Refer to the related paragraph of this report.

3.4 Test Operation and Test Software

Refer to the related paragraph of this report. No software was used.

3.5 Special Accessories and Auxiliary Equipment

None.

3.6 Countermeasures to achieve EMC Compliance

No special measure is employed to achieve the requirement.

4 Conformity Decision Rule

For all EMI tests (when included in this report), as measurement uncertainties are less than the values U_{CISPR} given in CISPR 16-4-2, compliance with the limits is determined by comparing measurement results directly with corresponding limits without taking into consideration of measurement uncertainties.

5 Test Results EMISSION

5.1 Emission in the Frequency Range up to 30 MHz

5.1.1 Conducted Emission

Result:	Passed
Date of testing	: 2025-05-23
Test procedure	: FCC 47 CFR Part 15, Subpart B:2023, ICES-005:2018, ANSI C63.4-2014 and CISPR 16-2-1
Frequency range	: 0.15 – 30 MHz
Limits	: Quasi-peak limit: 0.15 – 0.5 MHz, 66 to 56 dB μ V (decrease with the logarithm of frequency); 0.5 – 5 MHz, 56 dB μ V; 5 – 30 MHz, 60 dB μ V Average limit: 0.15 – 0.5 MHz, 56 to 46 dB μ V (decrease with the logarithm of frequency); 0.5 – 5 MHz, 46 dB μ V; 5 – 30 MHz, 50 dB μ V
Bandwidth of EMI receiver for final measurement	: 9 kHz
Measurement time for final measurement	: 1 s
Kind of test site	: Shielded room
Input voltage	: AC 120 V, 60 Hz
Operational mode	: Lighting on
Ambient condition	: Temperature: 24.2 °C; Relative humidity: 33.1 %
Expanded measurement uncertainty ($k=2$)	: 2.33 dB The minimum margin to the limit is 27.21 dB at 0.152250 MHz. The margin is higher than the expanded measurement uncertainty.

The measurement setup was made according to ANSI C63.4-2014 in a shielded room. The measurement equipment like test receivers, quasi-peak detector and artificial mains network (AMN) are in compliance with CISPR 16-1 series standards.

The tested object was set-up on a wooden support. The EUT was set 0.8 m away from the AMN. The cord longer than necessary to be connected to the AMN was folded forth and back parallel so as to form a bundle with a length between 0.3 m and 0.4 m. The disturbance voltage test was performed on the neutral line and phase line of the power supply of the EUT respectively.

Prüfbericht - Nr.: CN25SB3H 001
Test Report No.:Seite 11 von 23
Page 11 of 23


The following figures and tables were measured by an automatic measuring system. Both quasi-peak and average measurements were performed. In the following spectral diagram, “*” means Quasi-Peak Value and “*” means Average Value results.

Notes on following tables of conducted emission results and conversions:

Level (dB μ V): final measurement results by using quasi-peak detector and average detector


Transd (dB): transducer factors including cable loss, insertion loss of artificial mains network and gain of pre-amplifier (if used)

Margin: Limit (dB μ V) - Level (dB μ V)


Figure 1: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, Line L, maximum lighting mode


Final measurement result:

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.152250	27.99	---	65.88	37.89	L1	10.6
0.350250	---	7.75	48.96	41.21	L1	10.5
0.467250	15.86	---	56.56	40.70	L1	10.5
0.467250	---	8.18	46.56	38.38	L1	10.5
0.584250	15.16	---	56.00	40.84	L1	10.5
0.584250	---	6.70	46.00	39.30	L1	10.5
0.701250	---	6.71	46.00	39.29	L1	10.5
0.701250	14.31	---	56.00	41.69	L1	10.5
0.820500	13.63	---	56.00	42.37	L1	10.5
0.935250	---	4.52	46.00	41.48	L1	10.5
0.937500	13.03	---	56.00	42.97	L1	10.5
15.481500	---	8.03	50.00	41.97	L1	11.0


Figure 2: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, Line N, maximum lighting mode

Final measurement result:

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.159000	21.79	---	65.52	43.73	N	10.3
0.345750	---	7.05	49.06	42.02	N	10.3
0.462750	15.37	---	56.64	41.27	N	10.3
0.462750	---	7.88	46.64	38.76	N	10.3
0.577500	14.83	---	56.00	41.17	N	10.3
0.577500	---	6.35	46.00	39.65	N	10.3
0.694500	---	6.13	46.00	39.87	N	10.3
0.694500	14.12	---	56.00	41.88	N	10.3
0.809250	13.15	---	56.00	42.85	N	10.3
0.924000	---	4.14	46.00	41.86	N	10.3
0.926250	12.32	---	56.00	43.68	N	10.3
15.481500	---	7.90	50.00	42.10	N	10.9

Figure 3: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, Line L, minimum lighting mode


Final measurement result:

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.150000	---	11.06	56.00	44.94	L1	10.6
0.152250	38.67	---	65.88	27.21	L1	10.6
0.440250	---	5.29	47.06	41.76	L1	10.5
0.514500	---	5.08	46.00	40.92	L1	10.5
0.514500	10.89	---	56.00	45.11	L1	10.5
0.881250	---	0.71	46.00	45.29	L1	10.5
0.953250	8.02	---	56.00	47.98	L1	10.5
4.614000	7.00	---	56.00	49.00	L1	10.6
4.976250	---	1.33	46.00	44.67	L1	10.6
11.105250	7.49	---	60.00	52.51	L1	10.9
15.481500	13.97	---	60.00	46.03	L1	11.0
15.481500	---	7.87	50.00	42.13	L1	11.0

Figure 4: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, Line N, minimum lighting mode

Final measurement result:

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.174750	34.95	---	64.73	29.78	N	10.3
0.294000	---	4.54	50.41	45.87	N	10.3
0.442500	---	5.19	47.02	41.83	N	10.3
0.514500	---	4.91	46.00	41.09	N	10.3
0.516750	10.82	---	56.00	45.18	N	10.3
0.883500	---	0.85	46.00	45.15	N	10.3
0.883500	8.14	---	56.00	47.86	N	10.3
4.251750	7.02	---	56.00	48.98	N	10.4
4.908750	---	1.17	46.00	44.83	N	10.4
7.476000	7.43	---	60.00	52.57	N	10.6
15.481500	13.89	---	60.00	46.11	N	10.9
15.481500	---	7.87	50.00	42.13	N	10.9

5.2 Emission in the Frequency Range above 30 MHz

5.2.1 Radiated Emission (30 – 1000 MHz)

Result:	Passed
----------------	---------------

Date of testing	: 2025-05-08
Test procedure	: FCC 47 CFR Part 15, Subpart B:2023, ICES-005:2018, ANSI C63.4-2014 and CISPR 16-2-3
Product classification	: Class B
Frequency range	: 30 – 1000 MHz (see Note 1)
Limits	: Quasi-peak limits (3 m distance): (see Note 2) 30 – 88 MHz, 40 dB μ V/m; 88 – 216 MHz, 43.5 dB μ V/m; 216 – 1000 MHz, 46 dB μ V/m
Bandwidth of EMI receiver for final measurement	: 120 kHz
Measurement time for final measurement	: 1 s
Kind of test site	: Semi-anechoic chamber
Supply voltage	: AC 120 V, 60 Hz
Operational mode	: Lighting on
Ambient condition	: Temperature: 25.6 °C; Relative humidity: 36.3 %
Expanded measurement uncertainty ($k=2$)	: 5.40 dB The minimum margin to the limit is 10.1 dB at 30.485000 MHz. The margin is higher than the expanded measurement uncertainty.

The radiated disturbance test was carried out in a semi-anechoic chamber. The test distance from the receiving antenna to the EUT is 3 m. The normalized site attenuation of the semi-anechoic chamber is regularly calibrated to ensure the radiated disturbance test results are valid. During the test, the EUT was placed on a 0.8 m high wooden table above the reference ground plane. The wooden table was rotated 360° around and the height of the antenna varied from 1 m to 4 m to find the maximum disturbance. The test was performed with the antenna both in its horizontal and vertical polarizations.

The following figures and tables were measured by an automatic measurement system. Before final measurement, a survey was conducted with EUT's speed control adjusted to determine in which state the maximum disturbance was obtained. The final measurement was made in the state the maximum disturbance was obtained. In the following spectral diagram, "x" means quasi-peak test results.

Notes on the following tables of radiated emission results and conversions:

QuasiPeak (dB μ V/m): final measurement results by using quasi-peak detector.


Corr. (dB): correction factor including antenna factor, cable loss, and gain of pre-amplifier (if used).

Margin: Limit (dB μ V/m) - QuasiPeak (dB μ V/m).

Prüfbericht - Nr.: CN25SB3H 001
Test Report No.:Seite 17 von 23
Page 17 of 23


Note 1: The highest frequency in the EUT is less than 108 MHz. According to FCC Part 15 subpart B §15.33 (b) (1), the upper frequency for radiated emission measurement is 1000 MHz.

Note 2: The class B limits of ICES-005:2018 is stricter than those FCC 47 CFR Part 15, Subpart B:2023 for 3 m test distance. Therefore, the former limits are used in following figures and tables.


Figure 5: Spectral diagrams and measurement results, 30-1000 MHz, Horizontal polarization, maximum lighting mode


Final quasi-peak measurement results:


Frequency (MHz)	QuasiPeak (dBuV/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
31.212500	29.6	120.000	235.0	H	91.0	25.0	10.5	40.0
127.242500	22.1	120.000	295.0	H	-180.0	18.8	21.4	43.5
264.618750	24.2	120.000	260.0	H	3.0	20.9	21.9	46.0
619.638750	30.6	120.000	160.0	H	84.0	26.8	15.4	46.0
866.382500	33.6	120.000	310.0	H	99.0	28.8	12.4	46.0
974.780000	34.3	120.000	220.0	H	-118.0	29.7	11.8	46.0

Figure 6: Spectral diagrams and measurement results, 30-1000 MHz, Vertical polarization, maximum lighting mode

Final quasi-peak measurement results:

Frequency (MHz)	QuasiPeak (dBµV/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
30.727500	29.8	120.000	100.0	V	-180.0	25.3	10.2	40.0
55.341250	21.2	120.000	105.0	V	-163.0	13.4	18.8	40.0
118.876250	22.7	120.000	220.0	V	-116.0	19.0	20.9	43.5
562.287500	30.8	120.000	135.0	V	34.0	26.7	15.2	46.0
846.497500	33.7	120.000	100.0	V	11.0	28.9	12.3	46.0
864.563750	34.0	120.000	180.0	V	94.0	28.9	12.0	46.0

Figure 7: Spectral diagrams and measurement results, 30-1000 MHz, Horizontal polarization, minimum lighting mode

Final quasi-peak measurement results:

Frequency (MHz)	QuasiPeak (dBuV/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
30.485000	29.9	120.000	215.0	H	74.0	25.4	10.1	40.0
115.845000	22.1	120.000	350.0	H	32.0	18.9	21.4	43.5
598.177500	30.7	120.000	175.0	H	12.0	26.6	15.3	46.0
790.965000	31.9	120.000	100.0	H	-162.0	28.0	14.1	46.0
860.562500	33.9	120.000	200.0	H	39.0	29.0	12.2	46.0
992.240000	34.3	120.000	290.0	H	77.0	29.8	11.7	46.0

Figure 8: Spectral diagrams and measurement results, 30-1000 MHz, Vertical polarization, minimum lighting mode

Final quasi-peak measurement results:

Frequency (MHz)	QuasiPeak (dBµV/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
31.091250	29.6	120.000	110.0	V	-162.0	25.1	10.4	40.0
54.977500	20.9	120.000	190.0	V	-114.0	13.5	19.1	40.0
559.256250	30.4	120.000	210.0	V	74.0	26.7	15.6	46.0
862.502500	33.8	120.000	125.0	V	31.0	28.9	12.2	46.0
958.653750	33.8	120.000	165.0	V	19.0	29.2	12.2	46.0
997.817500	34.3	120.000	105.0	V	94.0	29.8	11.7	46.0

Prüfbericht - Nr.: CN25SB3H 001
Test Report No.:

Seite 22 von 23
Page 22 of 23

6 Photographs of the Test Set-Up

Refer to the test setup file.

7 List of Test and Measurement Instruments

Equipment no	Name	Model	Serial no	Manufacturer	Calibration date	Due date
EMC-S-028	EMI measurement software	EMC32-E+ (10.60.20)	100150	Rohde & Schwarz	N/A	N/A
EMC-C-366	Thermohygrometer	608-H1	2485149174	testo	2024-07-26	2025-07-26
EMC-C-195	EMI test receiver	ESR3	102794	Rohde & Schwarz	2024-08-03	2025-08-03
EMC-C-190	Artificial mains network	ENV432	101514	Rohde & Schwarz	2024-10-11	2025-10-11
EMC-S-032	EMI measurement software	EMC32-MEB (10.60.20)	100697	Rohde & Schwarz	N/A	N/A
EMC-C-155	BiLog antenna	CBL 6112D	40530	Teseq	2025-03-24	2026-09-24
EMC-C-121	Thermohygrometer	608-H1	1241320265	testo	2024-06-25	2025-06-25
EMC-C-066	EMI test receiver	ESCI	100280	Rohde & Schwarz	2024-10-17	2025-10-17
EMC-C-001	3 m semi-anechoic chamber	SAC3	FJ129002	Frankonia	2023-12-03	2026-12-03

8 List of Figures

Figure 1: Spectral Diagrams, Conducted Emission, 150 kHz - 30 MHz, Line L, maximum lighting mode	12
Figure 2: Spectral Diagrams, Conducted Emission, 150 kHz - 30 MHz, Line N, maximum lighting mode.....	13
Figure 3: Spectral Diagrams, Conducted Emission, 150 kHz - 30 MHz, Line L, minimum lighting mode.....	14
Figure 4: Spectral Diagrams, Conducted Emission, 150 kHz - 30 MHz, Line N, minimum lighting mode	15
Figure 5: Spectral diagrams and measurement results, 30-1000 MHz, Horizontal polarization, maximum lighting mode	18
Figure 6: Spectral diagrams and measurement results, 30-1000 MHz, Vertical polarization, maximum lighting mode	19
Figure 7: Spectral diagrams and measurement results, 30-1000 MHz, Horizontal polarization, minimum lighting mode	20
Figure 8: Spectral diagrams and measurement results, 30-1000 MHz, Vertical polarization, minimum lighting mode	21

End of test report