

## EMC TEST REPORT

**No. SH12010478-002**

Applicant : IKEA of Sweden AB  
P.O. Box 702, S-343 81 Älmhult, SWEDEN

Manufacturer : IKEA of Sweden AB  
P.O. Box 702, S-343 81 Älmhult, SWEDEN

Equipment : Remote controller

Type/Model : E1201C ANSLUTA

### SUMMARY

The equipment complies with the requirements according to the following standard(s):

**47CFR Part 15 (2011):** Radio Frequency Devices

**ANSI C63.4 (2003):** American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

**RSS-210 Issue 8 (December 2010):** Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment

**RSS-Gen Issue 3 (December 2010):** General Requirements and Information for the Certification of Radiocommunication Equipment

Date of issue: March 18, 2013

Prepared by:

Reviewed by:



Star Guo (*Project Engineer*)



Daniel Zhao (*Reviewer*)



**FCC ID: FHO-E1201C**  
**IC: 10912A-E1201C**

## **Description of Test Facility**

Name: Intertek Testing Services Limited Shanghai  
Address: Building No.86, 1198 Qinzhou Road(North), Shanghai 200233, P.R. China

FCC Registration Number: 236597  
IC Assigned Code: 2042B-1

Name of contact: Steve Li  
Tel: +86 21 64956565 ext. 214  
Fax: +86 21 54262335 ext. 214

## Content

<b>SUMMARY</b> .....	<b>1</b>
<b>DESCRIPTION OF TEST FACILITY</b> .....	<b>2</b>
<b>1. GENERAL INFORMATION</b> .....	<b>4</b>
1.1 Applicant Information.....	4
1.2 Identification of the EUT .....	4
1.3 Technical specification .....	5
1.4 Mode of operation during the test / Test peripherals used.....	5
<b>2. TEST SPECIFICATION</b> .....	<b>6</b>
2.1 Instrument list .....	6
2.2 Test Standard .....	6
<b>3. FUNDAMENTAL &amp; SPURIOUS EMISSION &amp; RESTRICT BAND RADIATED EMISSION</b> .....	<b>8</b>
3.1 Test limit .....	8
3.2 Test Configuration .....	9
3.3 Test procedure and test setup.....	9
3.4 Test protocol .....	10
<b>4. DEACTIVATING TIME</b> .....	<b>12</b>
4.1 Test limit .....	12
4.2 Test Configuration .....	13
4.3 Test procedure and test setup.....	13
4.4 Test protocol .....	13
<b>5. POWER LINE CONDUCTED EMISSION</b> .....	<b>14</b>
5.1 Limit.....	14
5.2 Test configuration .....	14
5.3 Test procedure and test set up.....	15
5.4 Test protocol .....	16
<b>6. EMISSION BANDWIDTH</b> .....	<b>17</b>
6.1 Test limit .....	17
6.2 Test Configuration .....	17
6.3 Test procedure and test setup.....	17
6.4 Test protocol .....	18
<b>7. OCCUPIED BANDWIDTH</b> .....	<b>19</b>
7.1 Test limit .....	19
7.2 Test Configuration .....	19
7.3 Test procedure and test setup.....	19
7.4 Test protocol .....	20



## **1. General Information**

### **1.1 Applicant Information**

Applicant: IKEA of Sweden AB  
P.O. Box 702, S-343 81 Älmhult, SWEDEN

Manufacturer: IKEA of Sweden AB  
P.O. Box 702, S-343 81 Älmhult, SWEDEN

Sample received date: January 11,2012  
Sample Identification No : \*0120111-12-001\*  
Date of test : January 11-March 24,2012

### **1.2 Identification of the EUT**

Equipment: Remote controller  
Type/model: E1201C ANSLUTA  
FCC ID: FHO-E1201C  
IC: 10912A-E1201C



### 1.3 Technical specification

Operation Frequency Band:	433.92MHz
Modulation:	ASK
Antenna Designation:	Integral antenna, non-user removable.
Gain of Antenna:	1.2dBi
Rating:	Battery: DC 3V Working frequency: 433.92MHz
Description of EUT:	There is one model only. The EUT transmits RF signal to control the working condition of the corresponding receiver.
Channel Description:	There is one channel only, namely 433.92MHz.

### 1.4 Mode of operation during the test / Test peripherals used

Within this test report, EUT was tested with modulation and tested under its rating voltage and frequency.

For the EUT is handheld device, it was set up and tested in three axes (X, Y and Z). The three axes were tested one by one while the test receiver worked as “max hold” continuously and the highest reading among the whole test procedure was recorded.

## 2. Test Specification

### 2.1 Instrument list

Equipment	Type	Manu.	Internal no.	Cal. Date	Due date
Test Receiver	ESIB 26	R&S	EC 3045	2012-10-21	2013-10-20
Semi-anechoic chamber	-	Albatross project	EC 3048	2012-5-21	2013-5-20
Bilog Antenna	CBL 6112D	TESEQ	EC 4206	2011-5-16	2013-5-15
Horn antenna	HF 906	R&S	EC 3049	2011-5-13	2013-5-12
Pre-amplifier	Pre-amp 18	R&S	EC 3222	2012-4-12	2013-4-11
Test Receiver	ESCS 30	R&S	EC 2107	2012-10-21	2013-10-20
A.M.N.	ESH2-Z5	R&S	EC 3119	2013-1-9	2014-1-8
A.M.N.	ESH3-Z5	R&S	EC 2109	2013-1-10	2014-1-9
High Pass Filter	WHKX 1.0/15G-10SS	Wainwright	EC4297-1	2013-2-8	2014-2-7
High Pass Filter	WHKX 2.8/18G-12SS	Wainwright	EC4297-2	2013-2-8	2014-2-7
High Pass Filter	WHKX 7.0/1.8G-8SS	Wainwright	EC4297-3	2013-2-8	2014-2-7
Band Reject Filter	WRCGV 2400/2483- 2390/2493- 35/10SS	Wainwright	EC4297-4	2013-2-8	2014-2-7
Test Receiver	FSV40	R&S	/	2012-10-21	2013-10-20
Power Splitter/Combiner	ZN2PD2-63	Mini-Circuits	815	2012-12-3	2013-12-2

### 2.2 Test Standard

47CFR Part 15 (2011): Radio Frequency Devices

ANSI C63.4 (2003): American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

RSS-210 Issue 8 (December 2010): Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment

RSS-Gen Issue 3 (December 2010): General Requirements and Information for the Certification of Radiocommunication Equipment




### 2.3 Test Summary

**This report applies to tested sample only. This report shall not be reproduced in part without written approval of Intertek Testing Service Shanghai Limited.**

TEST ITEM	FCC REFERANCE	IC REFERANCE	RESULT
Fundamental & spurious emission	15.231(b)	RSS-210 Issue 8 Annex A1.1.2	Pass
Restrict band radiated emission	15.205	RSS-210 Issue 8 Clause 2.2	Pass
Power line conducted emission	15.207	RSS-Gen Issue 3 Clause 7.2.4	NA
Emission bandwidth	15.231(c)	RSS-210 Issue 8 Annex A1.1.3	Pass
Deactivating time	15.231(a)(1)	RSS-210 Issue 8 Annex A1.1.1	Pass
Occupied bandwidth	-	RSS-Gen Issue 3 Clause 4.6.1	Tested



### 3.2 Test Configuration



### 3.3 Test procedure and test setup

The measurement was applied in a semi-anechoic chamber. While testing for spurious emission higher than 1GHz, the pre-amplifier and high pass filter is equipped just at the output terminal of the antenna.

The EUT and simulators were placed on a 0.8m high wooden turntable above the horizontal metal ground plane. The turn table rotated 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna which was mounted on an antenna mast. The antenna moved up and down between from 1meter to 4 meters to find out the maximum emission level.

Both horizontal and vertical polarities of the receiving antenna were assessed and the higher reading was listed in this report.

The radiated emission was measured using the test receiver with the resolutions bandwidth set as:

- RBW = 100kHz, VBW = 300kHz (30MHz~1GHz)
- RBW = 1MHz, VBW = 3MHz (>1GHz for PK)

### 3.4 Test protocol

Antenna	Frequency (MHz)	Correct Factor (dB/m)	Corrected Reading (dBuV/m)	Emission Type	Limit (dBuV/m)	Margin	Detector
H	136.91	14.70	18.60	Restrict	43.50	24.90	PK
H	325.47	15.90	45.90	Spurious	60.80	14.90	PK
H	434.32	18.80	79.30	Fundamental	80.80	1.50	PK
H	409.39	18.40	28.70	Restrict	46.00	17.30	PK
H	867.81	23.60	52.60	Spurious	60.80	8.20	PK
H	1112.22	-13.10	29.80	Restrict	54.00	24.20	PK
H	2606.21	-7.50	48.30	Spurious	60.80	12.50	PK
H	3475.95	-5.20	42.90	Spurious	60.80	17.90	PK
H	4177.35	-3.40	37.80	Restrict	54.00	16.20	PK
V	113.58	14.90	17.70	Restrict	43.50	25.80	PK
V	325.47	15.90	31.80	Spurious	60.80	29.00	PK
V	434.33	18.80	76.80	Fundamental	80.80	4.00	PK
V	406.33	18.30	22.90	Restrict	46.00	23.10	PK
V	652.04	21.50	36.20	Spurious	60.80	24.60	PK
V	867.81	23.60	39.50	Spurious	60.80	21.30	PK
V	1301.60	-12.50	36.60	Restrict	54.00	17.40	PK
V	2171.34	-8.40	49.40	Spurious	60.80	11.40	PK
V	2606.21	-7.50	49.50	Spurious	60.80	11.30	PK
V	2802.60	-7.20	35.90	Restrict	54.00	18.10	PK
V	4198.39	-3.3	38.40	Restrict	54.00	15.60	PK

- Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz)
2. Corrected Reading = Original Receiver Reading + Correct Factor
  3. Margin = limit - Corrected Reading
  4. If PK reading is less than AV limit, the AV test can be elided.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB, Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV, limit = 40.00dBuV/m.

Then Correct Factor =  $30.20 + 2.00 - 32.00 = 0.20\text{dB/m}$ ; Corrected Reading =  $10\text{dBuV} + 0.20\text{dB/m} = 10.20\text{dBuV/m}$ ; Margin =  $40.00\text{dBuV/m} - 10.20\text{dBuV/m} = 29.80\text{dB}$ .


## 4. Deactivating time

Test result: PASS

### 4.1 Test limit

- (1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.
- (2) A transmitter activated automatically shall cease transmission within 5 seconds after activation.
- (3) Periodic transmissions at regular predetermined intervals are not permitted. However, polling or supervision transmissions, including data, to determine system integrity of transmitters used in security or safety applications are allowed if the total duration of transmissions does not exceed more than two seconds per hour for each transmitter. There is no limit on the number of individual transmissions, provided the total transmission time does not exceed two seconds per hour.
- (4) Intentional radiators which are employed for radio control purposes during emergencies involving fire, security, and safety of life, when activated to signal an alarm, may operate during the pendency of the alarm condition.
- (5) Transmission of set-up information for security systems may exceed the transmission duration limits in (1) and (2) above, provided such transmission are under the control of a professional installer and do not exceed ten seconds after a manually operated switch is released or a transmitter is activated automatically. Such set-up information may include data.

### 4.2 Test Configuration



### 4.3 Test procedure and test setup

The measurement was applied in a semi-anechoic chamber.  
The central frequency of test receiver was set as the operating frequency of EUT and the Span was set as 0.  
The EUT was switched once. The test receiver recorded the whole time from the triggered moment to the time of stopping radiating. For manual switching, to avoid uncertainty, the operating above would be repeated five times and the worst data is recorded.

### 4.4 Test protocol

Whole time from the triggered moment to the time of stopping radiating: 50ms.  
As a result, the EUT complies with the limit of 5s' deactivating time.

## 5. Power line conducted emission


Test result: NA

### 5.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	QP	AV
0.15-0.5	66 to 56*	56 to 46 *
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

### 5.2 Test configuration



For table top equipment, wooden support is 0.8m height table

For floor standing equipment, wooden support is 0.1m height rack.

### **5.3 Test procedure and test set up**

The EUT are connected to the main power through a line impedance stabilization network (LISN). This provides a  $50\Omega/50\mu\text{H}$  coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a  $50\Omega/50\mu\text{H}$  coupling impedance with  $50\Omega$  termination.

Both sides (Line and Neutral) of AC line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4 on conducted measurement. The bandwidth of the test receiver is set at 9 kHz.

### 5.4 Test protocol

Power line: L

Frequency	Correct Factor (dB)	Corrected Reading (dBuV)		Limit (dBuV)		Margin (dB)	
		QP	AV	QP	AV	QP	AV
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-

Remark: 1. Correction Factor (dB) = LISN Factor (dB) + Cable Loss (dB).  
2. Margin (dB) = Limit - Corrected Reading.  
3. If the margin higher than 20dB, it would be marked as \*.

Power line: N

Frequency	Correct Factor (dB)	Corrected Reading (dBuV)		Limit (dBuV)		Margin (dB)	
		QP	AV	QP	AV	QP	AV
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-

Remark: 1. Correction Factor (dB) = LISN Factor (dB) + Cable Loss (dB).  
2. Margin (dB) = Limit - Corrected Reading.  
3. If the margin higher than 20dB, it would be marked as \*.

## 6. Emission Bandwidth


**Test Status: Pass**

### 6.1 Test limit

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20dB down from the modulated carrier.

The limit for the EUT =  $0.25\% * 433.95\text{MHz} = 1085\text{kHz}$

### 6.2 Test Configuration



### 6.3 Test procedure and test setup

The EUT and simulators were placed on a 0.8m high wooden turntable above the horizontal metal ground plane. The turn table rotated 360 degrees to determine the position of the



maximum emission level. The EUT was set 3 meters away from the receiving antenna which was mounted on an antenna mast. The antenna moved up and down between from 1 meter to 4 meters to find out the maximum emission level.

The central frequency of test receiver was set near the operating frequency of EUT.

The test was conducted using the Spectrum Analyzer with the resolutions bandwidth set at 10kHz, the video bandwidth set at 30kHz.

#### **6.4 Test protocol**

Temperature : 25 °C  
Relative Humidity : 55 %

Channel	Emission Bandwidth (kHz)	Limit (kHz)
1	51	1085


## 7. Occupied Bandwidth

Test Status: Tested

### 7.1 Test limit

None

### 7.2 Test Configuration



### 7.3 Test procedure and test setup

The occupied bandwidth per RSS-Gen Issue 3 Clause 4.6.1 was measured using the Spectrum Analyzer with the resolutions bandwidth set at 10kHz, the video bandwidth set at 30kHz.

**7.4 Test protocol**

Temperature : 25 °C  
Relative Humidity : 55 %

Channel	Occupied Bandwidth (kHz)
1	197