

# IKEA OF SWEDEN AB

# TEST REPORT

**SCOPE OF WORK**

EMC TESTING–E2311-S

**REPORT NUMBER**

220329070GZU-004

**ISSUE DATE**

25-April-2024

**[REVISED DATE]**

[-----]

**PAGES**

8

**DOCUMENT CONTROL NUMBER**

© 2017 INTERTEK



## TEST REPORT

Applicant Name & : IKEA OF SWEDEN AB  
Address : Box 702 343 81 ÄLMHULT, SWEDEN  
Manufacturing Site : NanChang Innotech Homesmart Co., Ltd.  
1st to 5th floor, 2-1#, Nanchang Small and Medium-sized Enterprises  
Entrepr Guowei Industrial Park, No. 669 Huangtang E Rd, Linkong  
Economic Zone, NANCHANG Jiangxi, China  
Intertek Report No: 231122098GZU-004  
FCC ID: FHO-E2311-S

## Test standards

**47 CFR PART 1, Subpart I, Section 1.1310**  
**KDB 680106 D01 Wireless Power Transfer v04**

## Sample Description

Product : Wireless Charger  
Model No. : E2311-S  
Electrical Rating : Input: 5Vdc, 2A  
Output: 5W Max  
Serial No. : Not Labeled  
Date Received : 22 November 2023  
Date Test : 06 January 2024-16 January 2024  
Conducted

Prepared and Checked By

  
\_\_\_\_\_

Ace Yao

Engineer

Approved By:

  
\_\_\_\_\_

Dean Liu

Sr. Project Engineer

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**TEST REPORT**

**CONTENT**

**TEST REPORT ..... 1**

**CONTENT ..... 3**

**1.0 TEST RESULT SUMMARY ..... 4**

**2.0 GENERAL DESCRIPTION..... 5**

    2.1 PRODUCT DESCRIPTION .....5

    2.2 TEST FACILITY.....5

    2.3 EUT EXERCISING SOFTWARE.....5

    2.4 SPECIAL ACCESSORIES.....5

    2.5 EQUIPMENT MODIFICATION .....5

    2.6 SUPPORT EQUIPMENT LIST AND DESCRIPTION .....5

**3.0 EMF TEST..... 7**

    3.1 STANDARD REQUIREMENT..... 7

    3.2 TEST DATA..... 8

**4.0 TEST EQUIPMENT LIST ..... 8**

**TEST REPORT****1.0 TEST RESULT SUMMARY**

Classification of EUT: Class B

Test Item	Standard	Result
EMF	47 CFR PART 1, Subpart I, Section 1.1310	PASS

Remark:

When determining the test results, measurement uncertainty of tests has been considered.

## TEST REPORT

### 2.0 General Description

#### 2.1 Product Description

Operating Frequency	110.1-146.2KHz
Type of Modulation:	Load modulation
Antenna Type	Inductive loop coil antenna
Power Supply:	Input: 5Vdc, 2A Output: 5W Max
Power cord:	--

#### 2.2 Test Facility

Room102/104, No 203, KeZhu Road, Science City, GETDD Guangzhou, China

A2LA Certificate Number 0078.10

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch is accredited by A2LA and Listed in FCC website. FCC accredited test labs may perform both Certification testing under Parts 15 and 18 and Declaration of Conformity testing.

#### 2.3 EUT Exercising Software

N/A

#### 2.4 Special Accessories

N/A

#### 2.5 Equipment Modification

Any modifications installed previous to testing by IKEA OF SWEDEN AB will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Guangzhou Branch.

#### 2.6 Support Equipment List and Description

This product was tested with corresponding support equipment as below:  
Support Equipment:

**TEST REPORT**

Equipment	Model No.	Rating	Supplier
Mobile phone	IPhone 8	--	Intertek
Power adapter	MDY-11-EX	Output: 33W.max	Intertek

**Remark:** WPT client was one of typical client devices, it's selected such that the EUT was fully exercised at maximum power from its transmitter. It will not be sold together.

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above evaluated respectively

Pretest mode	Description	
Standby Mode	kept transmitting continuously	
Charging Mode	CH: Low	WPT client is charging at 1% battery power, 50% and 99% battery power respectively, keep transmitting continuously
	CH: Middle	
	CH: High	

## TEST REPORT

### 3.0 EMF TEST

#### 3.1 Standard Requirement

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.1m normally can be maintained between the user and the device.

##### (a) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm <sup>2</sup> )	Averaging Times  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	F/300	6
1500-100000	--	--	5	6

##### (b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm <sup>2</sup> )	Averaging Times  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	F/1500	30
1500-100000	--	--	1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density

**TEST REPORT**

**3.2 Test Data**

Input Voltage: 120V/60Hz  
Ambient Condition: 24°C, 50%RH

Test distance: 20 cm surrounding the device.

H-Filed Strength:

Test Position	Probe Measure Result (A/m)			50% Limit (A/m)	Limit (A/m)
	WPT client in 1% battery power	WPT client in 50% battery power	WPT client in 99% battery power		
Side 1	0.053	0.044	0.040	0.815	1.63
Side 2	0.066	0.060	0.051	0.815	1.63
Side 3	0.055	0.048	0.041	0.815	1.63
Side 4	0.071	0.064	0.060	0.815	1.63
Top	0.079	0.069	0.058	0.815	1.63

**4.0 Test Equipment List**

Equip. No.	Equipment	Model	Manufacturer	Cal. date	Due date
EM007-03	Exposure Level Tester	ELT-400	NARDA	2023/3/08	2024/3/07

\*\*\*\*\*End of the test report\*\*\*\*\*