

Prüfbericht-Nr.: Test report no.:	CN24UHSG 001	Auftrags-Nr.: Order no.:	326050127	Seite 1 von 19 Page 1 of 19
Kunden-Referenz-Nr.: Client reference no.:	1288983	Auftragsdatum: Order date:	2024-09-03	
Auftraggeber: Client:	IKEA of Sweden AB Box 702, SE-343 81, Älmhult, Sweden			
Prüfgegenstand: Test item:	Remote control (Dual button)			
Bezeichnung / Typ-Nr.: Identification / Type no.:	E2489			
Auftrags-Inhalt: Order content:	TÜV Rheinland EMC service			
Prüfgrundlage: Test specification:	FCC 47 CFR Part 15, Subpart B:2022 Class B ICES-003:2020			
Wareneingangsdatum: Date of sample receipt:	2024-09-26	Refer to the EUT photos file		
Prüfmuster-Nr.: Test sample no.:	A003813660-005			
Prüfzeitraum: Testing period:	Refer to test report			
Ort der Prüfung: Place of testing:	Refer to clause 1.1			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shanghai) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:	<i>Xuelan Zhang</i> XueLan Zhang	genehmigt von: authorized by:	<i>Jacky Chen</i> Jacky C.L. Chen	
Datum: Date:	2024-12-23	Ausstellungsdatum: Issue date:	2024-12-23	
Stellung / Position:	Project engineer	Stellung / Position:	Authorizer	
Sonstiges / <i>Other:</i>	FCC ID: FHO-E2489 IC: 10912A-E2489 Test Firm Name: TUV Rheinland (Shanghai) Co., Ltd. Designation Number: CN1396 Test Firm Registration Number: 930979			
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n)	F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
* Legend:	P(ass) = passed a.m. test specification(s)	F(ail) = failed a.m. test specification(s)	N/A = not applicable	N/T = not tested
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.: CN24UHSG 001
Test report no.:

Seite 2 von 19
Page 2 of 19

Anmerkungen
Remarks

1	<p>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</p> <p><i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system.</i></p> <p><i>Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i></p>
2	<p>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature</p> <p><i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i></p>
3	<p>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</p> <p><i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i></p> <p><i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i></p>
4	<p>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</p> <p><i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i></p>

Prüfbericht - Nr.: CN24UHSG 001

Test Report No.:

Seite 3 von 19

Page 3 of 19

Revision history of test report:

Report number	Issue date	Contents and reason for change if appropriate
CN24UHSG 001	2024-12-23	Initial release.

Prüfbericht - Nr.: CN24UHSG 001
Test Report No.:

Seite 4 von 19
Page 4 of 19

TEST SUMMARY

5.1.1 RADIATED EMISSION (30 MHz - 1 GHz)

Result:

Passed

5.1.2 RADIATED EMISSION (ABOVE 1 GHz)

Result:

Passed

Contents

1	TEST SITES	6
1.1	TEST FACILITIES	6
2	GENERAL PRODUCT INFORMATION	7
2.1	PRODUCT FUNCTION AND INTENDED USE	7
2.2	RATINGS AND SYSTEM DETAILS	7
2.3	INDEPENDENT OPERATION MODESS	7
2.4	DESCRIPTION OF INTERCONNECTING CABLES.....	7
2.5	NOISE GENERATING AND NOISE SUPPRESSING PARTS	7
2.6	HIGHEST FREQUENCY GENERATED OR USED IN THE DEVICE OR ON WHICH THE DEVICE OPERATES OR TUNES	7
2.7	SUBMITTED DOCUMENTS.....	7
3	TEST SET-UP AND OPERATION MODES	8
3.1	PRINCIPLE OF CONFIGURATION SELECTION	8
3.2	EQUIPMENT AND CABLE ARRANGEMENT.....	8
3.3	TEST SOFTWARE	8
3.4	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	8
3.5	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE	8
4	CONFORMITY DECISION RULE	9
5	TEST RESULTS EMISSION	10
5.1	EMISSION IN THE FREQUENCY RANGE ABOVE 30 MHz.....	10
5.1.1	<i>Radiated emission (30 MHz - 1 GHz)</i>	10
5.1.2	<i>Radiated emission (Above 1 GHz)</i>	14
6	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	18
7	LIST OF FIGURES.....	19

Prüfbericht - Nr.: CN24UHSG 001
Test Report No.:

Seite 6 von 19
Page 6 of 19

1 Test Sites

1.1 Test Facilities

Laboratory: TÜV Rheinland (Shanghai) Co., Ltd.

Address: Workshop14, North Half of Workshop 10 and Workshop 16, Pingqian (Taicang) Modern Industrial Park, No.525, Yuewang Lingang South Road, Shaxi, Taicang, Jiangsu, China

The used test equipment is in accordance with CISPR 16-1 series standards for measurement of radio interference.

Refer to Clause 6 for test and measurement instruments.

2 General Product Information

2.1 Product Function and Intended Use

The EUT (equipment under test) is Remote control (Dual button). For the further information, refer to the user's manual.

2.2 Ratings and System Details

Rated input : 3 Vdc, 2xAAA
Protection class : III

2.3 Independent Operation Modess

The basic operation mode is on by 2.4 GHz by thread, Zigbee, BLE connection and the indicator light works normally.

2.4 Description of interconnecting cables

None.

2.5 Noise Generating and Noise Suppressing Parts

Refer to the circuit diagram for further information.

2.6 Highest frequency generated or used in the device or on which the device operates or tunes

The highest frequency used in the EUT is 2.4 GHz.

2.7 Submitted Documents

Circuit diagram, PCB layout and rating label.

3 Test Set-up and Operation Modes

3.1 Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible emission level. The test conditions were adapted accordingly in reference to the instructions for use.


Refer to the related paragraph of this report.

The sequence of testing:

1. Radiated emission tests were performed on 2024-10-28.

3.2 Equipment and cable arrangement

Block diagram for radiated emission tests is as follows:



(Radiated emission)

Also refer to photographs on attachment 1 for test setups for radiated emission test.

3.3 Test Software

No special test software was used during the tests.

3.4 Special Accessories and Auxiliary Equipment

During the tests, the below equipment were used.

No.	Equipment	Model	Manufacturer
1	Cell phone	Iphone 15 Plus	Apple

3.5 Countermeasures to achieve EMC Compliance

No other special measure is employed to achieve the requirement.

4 Conformity Decision Rule

For all EMI tests included in this report, as measurement uncertainties are less than the values U_{CISPR} given in CISPR 16-4-2, compliance with the limits is determined by comparing measurement results directly with corresponding limits without taking into consideration of measurement uncertainties.

5 Test Results EMISSION

5.1 Emission in the Frequency Range above 30 MHz

5.1.1 Radiated emission (30 MHz - 1 GHz)

Result:	Passed
----------------	---------------

Date of testing	: 2024-10-28
Test procedure	: FCC 47 CFR Part 15, Subpart B:2022, ICES-003:2020, ANSI C63.4-2014 and CISPR 16-2-3
Frequency range	: 30 – 1000 MHz
Limits	: Quasi-peak limits (3 m distance): 30 – 88 MHz, 40 dB μ V/m; 88 – 216 MHz, 43.5 dB μ V/m; 216 – 1000 MHz, 46 dB μ V/m (see Note 1)
Bandwidth of EMI receiver for final measurement	: 120 kHz
Measurement time for final measurement	: 1 s
Kind of test site	: Semi-anechoic chamber
Operational mode	: Mode as defined in clause 2.3
Input voltage	: 3 Vdc, 2xAAA
Ambient condition	: Temperature: 20.5 °C; Relative humidity: 45 %
Expanded measurement uncertainty ($k=2$)	: 5.4 dB The minimum margin to the limit is 12.09 dB at 30.242500 MHz. The margin is higher than expanded measurement uncertainty.

The radiated disturbance test was carried out in a semi-anechoic chamber. The test distance from the receiving antenna to the EUT is 3 m. The normalized site attenuation of the semi-anechoic chamber is regularly calibrated to ensure the radiated disturbance test results are valid. During the test, the EUT was placed on a 0.8 m high wooden table above the reference ground plane. The wooden table was rotated 360° around and the height of the antenna was varied from 1 m to 4 m to find the maximum disturbance. The test was performed with the antenna both in its horizontal and vertical polarizations.

The following figures and tables were those measured by an automatic measurement system. A preview test was firstly performed with peak detector. The final test was performed with quasi-peak at those critical frequencies during the preview test. In the following spectral diagram, “◆” means quasi-peak test results.

Prüfbericht - Nr.: CN24UHSG 001

Test Report No.:

Seite 11 von 19

Page 11 of 19


Notes on following tables of radiated emission results and conversions:

QuasiPeak (dB μ V/m): final measurement results by using quasi-peak detector

Corr. (dB): correction factor including: antenna factor, cable loss, and gain of pre-amplifier (if used)

Margin: Limit (dB μ V/m) - QuasiPeak (dB μ V/m)


Figure 1: Spectral Diagrams and measurement results, horizontal polarization (30 MHz to 1 GHz)



Final Quasi-peak measurement result:

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
30.848750	27.64	40.00	12.36	1000.0	120.000	100.0	H	61.0
42.731250	21.47	40.00	18.53	1000.0	120.000	100.0	H	-124.0
134.638750	21.38	43.50	22.12	1000.0	120.000	200.0	H	-140.0
471.350000	28.05	46.00	17.95	1000.0	120.000	100.0	H	-131.0
693.480000	30.29	46.00	15.71	1000.0	120.000	100.0	H	-158.0
924.340000	33.04	46.00	12.96	1000.0	120.000	100.0	H	15.0

Figure 2: Spectral Diagrams and measurement results, vertical polarization (30 MHz to 1 GHz)



Final Quasi-peak measurement result:

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
30.242500	27.91	40.00	12.09	1000.0	120.000	100.0	V	44.0
43.580000	21.07	40.00	18.93	1000.0	120.000	100.0	V	136.0
346.341250	24.56	46.00	21.44	1000.0	120.000	200.0	V	-119.0
495.236250	28.32	46.00	17.68	1000.0	120.000	200.0	V	-54.0
575.867500	30.00	46.00	16.00	1000.0	120.000	200.0	V	-45.0
913.791250	33.10	46.00	12.90	1000.0	120.000	200.0	V	127.0

5.1.2 Radiated emission (Above 1 GHz)

Result:	Passed
----------------	---------------

Date of testing	: 2024-10-28
Port	: Enclosure
Test procedure	: FCC 47 CFR Part 15, Subpart B:2022, ANSI C63.4-2014 and CISPR 16-2-3 ICES-003:2020
Limit	: Above 1 GHz, Peak limit: 74 dB μ V/m; Average limit: 54 dB μ V/m
Frequency range	: 1-18 GHz Note: The highest frequency in the EUT is 2.4 GHz. According to FCC Part 15 subpart B §15.33 (b) (1), the upper frequency for radiated emission measurement is 12 GHz. The actual test frequency is up to 18 GHz.
Bandwidth of EMI receiver for final measurement	: 1000 kHz
Measurement time for final measurement	: 1 s
Test distance	: 3 m
Kind of test site	: Semi-anechoic chamber
Operational mode	: Mode as defined in clause 2.3
Input voltage	: 3 Vdc, 2xAAA
Earthing	: No earthing
Ambient condition	: Temperature: 20.5 °C; Relative humidity: 45 %
Expanded measurement uncertainty ($k=2$)	: 5.08 dB (1-6 GHz) 5.21 dB (6-18 GHz) The minimum margin to the limit is 7.0 dB at 17975.562500 MHz. The margin is higher than expanded measurement uncertainty.

The radiated disturbance test was carried out in a semi-anechoic chamber. The test distance from the receiving antenna to the EUT is 3 m. The normalized site attenuation of the semi-anechoic chamber is regularly calibrated to ensure the radiated disturbance test results are valid. During the test, the EUT was placed on a poly table, which is 0.8 m high. The wooden table was rotated 360° around and the antenna was varied from 1 m to 4 m to find the maximum disturbance. The test was performed with the antenna both in its horizontal and vertical polarizations.

The following figures and tables were those measured by an automatic measurement system. The final test was performed with peak detector and average detector at those critical frequencies during the preview test. In the following figure, “x(red)” means measurement results with peak detector and “+ (blue)” means measurement results with average detector.

Notes on following tables of radiated emission results and conversions:

Prüfbericht - Nr.: CN24UHSG 001

Test Report No.:

Seite 15 von 19

Page 15 of 19

Peak (dB μ V/m): final measurement results by using peak detector


Average (dB μ V/m): final measurement results by using average detector

Corr. (dB): correction factor including: antenna factor, cable loss, and gain of pre-amplifier (if used)

Margin: Limit PK (dB μ V/m) - Peak (dB μ V/m)

Limit CAV (dB μ V/m) – Average (dB μ V/m)

Figure 3: Spectral Diagrams and measurement results, 1-18 GHz, horizontal polarization



Final Peak measurement results:


Frequency (MHz)	Average (dBµV/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµV/m)
1471.218750	20.2	1000.000	100.0	V	0.0	-18.5	41.0	74.0
2241.000000	23.6	1000.000	100.0	V	0.0	-15.2	37.6	74.0
7190.125000	33.6	1000.000	100.0	V	0.0	-5.3	27.9	74.0
8081.562500	34.9	1000.000	100.0	V	0.0	-3.2	26.2	74.0
14408.218750	39.5	1000.000	100.0	V	0.0	3.4	22.0	74.0
17976.625000	46.9	1000.000	100.0	V	0.0	13.0	14.3	74.0

Final Average measurement results:

Frequency (MHz)	Average (dBµV/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµV/m)
1471.218750	20.2	1000.000	100.0	V	0.0	-18.5	33.8	54.0
2241.000000	23.6	1000.000	100.0	V	0.0	-15.2	30.5	54.0
7190.125000	33.6	1000.000	100.0	V	0.0	-5.3	20.4	54.0
8081.562500	34.9	1000.000	100.0	V	0.0	-3.2	19.1	54.0
14408.218750	39.5	1000.000	100.0	V	0.0	3.4	14.5	54.0
17976.625000	46.9	1000.000	100.0	V	0.0	13.0	7.1	54.0

Figure 4: Spectral Diagrams and measurement results, 1-18 GHz, vertical polarization

Level [dBμV/m]



Final Peak measurement results:

Frequency (MHz)	MaxPeak (dBμV/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBμV/m)
1310.250000	33.6	1000.000	100.0	V	0.0	-18.7	40.4	74.0
2309.531250	36.2	1000.000	100.0	V	0.0	-15.5	37.8	74.0
4919.562500	39.9	1000.000	100.0	V	0.0	-10.7	34.1	74.0
7974.781250	48.7	1000.000	100.0	V	0.0	-2.9	25.3	74.0
14390.687500	51.4	1000.000	100.0	V	0.0	3.3	22.7	74.0
17975.562500	59.4	1000.000	100.0	V	0.0	12.9	14.6	74.0

Final Average measurement results:

Frequency (MHz)	Average (dBμV/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBμV/m)
1310.250000	20.7	1000.000	100.0	V	0.0	-18.7	33.3	54.0
2309.531250	23.6	1000.000	100.0	V	0.0	-15.5	30.5	54.0
4919.562500	27.1	1000.000	100.0	V	0.0	-10.7	26.9	54.0
7974.781250	35.7	1000.000	100.0	V	0.0	-2.9	18.3	54.0
14390.687500	38.9	1000.000	100.0	V	0.0	3.3	15.2	54.0
17975.562500	47.0	1000.000	100.0	V	0.0	12.9	7.0	54.0

6 List of Test and Measurement Instruments

Equip.	Description	Model	Manufacturer	Last Date	Due Date
				DD.MM.YYYY	DD.MM.YYYY
G1811378	3m semi-anechoic chamber	SAC3	Frankonia	03.12.2023	03.12.2026
G1811391	EMI test receiver	ESCI	Rohde&Schwarz	17.10.2024	17.10.2025
G1811425	Bilog antenna	CBL 6112D	Teseq	20.04.2023	20.04.2026
9062745	EMI measurement software	EMC32-MEB (10.60.20)	Rohde&Schwarz	N/A	N/A
G1822702	Spectrum analyser	FSV40	Rohde&Schwarz	15.07.2024	15.07.2025
G1825372	Preamplifier	EMC184045SE	Taiwan EMCI	24.07.2024	24.07.2025
G1831065	Broadband horn antenna	BBHA 9170	Schwarzbeck	18.06.2023	18.06.2028

7 List of Figures

Figure 1: Spectral Diagrams and measurement results, horizontal polarization (30 MHz to 1 GHz)	12
Figure 2: Spectral Diagrams and measurement results, vertical polarization (30 MHz to 1 GHz)	13
Figure 3: Spectral Diagrams and measurement results, 1-18 GHz, horizontal polarization.....	16
Figure 4: Spectral Diagrams and measurement results, 1-18 GHz, vertical polarization.....	17

End of test report