

Prüfbericht-Nr.: Test report no.:	CN24EKHE 001	Auftrags-Nr.: Order no.:	326050137	Seite 1 von 39 Page 1 of 39
Kunden-Referenz-Nr.: Client reference no.:	1288983	Auftragsdatum: Order date:	2024-09-03	
Auftraggeber: Client:	IKEA of Sweden AB Box 702, SE-343 81 Älmhult, Sweden			
Prüfgegenstand: Test item:	Remote Control (Scroll Wheel)			
Bezeichnung / Typ-Nr.: Identification / Type no.:	E2490			
Auftrags-Inhalt: Order content:	Test Report			
Prüfgrundlage: Test specification:	FCC CFR47 Part 15, Subpart C Section 15.247 RSS-Gen Issue 5, Amendment 2, February 2021 RSS-247 Issue 3, August 2023 ANSI C63.10: 2013			
Wareneingangsdatum: Date of sample receipt:	2024-09-09	Refer to photo document.		
Prüfmuster-Nr.: Test sample no.:	A003813660-006~007			
Prüfzeitraum: Testing period:	2024-11-02 ~ 2024-11-14			
Ort der Prüfung: Place of testing:	TÜV Rheinland (Shanghai) Co., Ltd.			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shanghai) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:	<input checked="" type="checkbox"/> <u>Hongfei Wu</u>	genehmigt von: authorized by:	<input checked="" type="checkbox"/> <u>Elliot Zhang</u>	
Datum: Date:	2025-07-17 <small>Signed by: Hongfei Wu</small>	Datum: Date:	2025-07-17 <small>Signed by: Elliot Zhang</small>	
Stellung / Position:	Sachverständige(r)/Expert	Stellung / Position:	Sachverständige(r)/Expert	
Sonstiges / Other:	FCC ID: FHO-E2490 IC: 10912A-E2490 HVIN: E2490 PMN: BILRESA			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n)	F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
* Legend:	P(ass) = passed a.m. test specification(s)	F(ail) = failed a.m. test specification(s)	N/A = not applicable	N/T = not tested
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.: CN24EKHE 001
Test report no.:

Seite 2 von 39
Page 2 of 39

Anmerkungen
Remarks

1	<p>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</p> <p><i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i></p>
2	<p>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature</p> <p><i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i></p>
3	<p>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</p> <p><i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report. Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i></p>
4	<p>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</p> <p><i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i></p>

TEST SUMMARY

5.1.1 ANTENNA REQUIREMENT*RESULT: Pass***5.1.2 6dB & 99% BANDWIDTH***RESULT: Pass***5.1.3 OUTPUT POWER***RESULT: Pass***5.1.4 POWER SPECTRAL DENSITY***RESULT: Pass***5.1.5 CONDUCTED BAND EDGE AND OUT-OF BAND EMISSIONS***RESULT: Pass***5.2.1 CONDUCTED EMISSION***RESULT: N/A***5.3.1 RADIATED BAND-EDGE***RESULT: Pass***5.3.2 RADIATED SPURIOUS EMISSION***RESULT: Pass*

Contents

1.	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS.....	5
2.	TEST SITES	6
2.1	TEST FACILITIES.....	6
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	7
2.3	TRACEABILITY	7
2.4	CALIBRATION	7
2.5	MEASUREMENT UNCERTAINTY	8
3.	GENERAL PRODUCT INFORMATION.....	9
3.1	PRODUCT FUNCTION AND INTENDED USE	9
3.2	RATINGS AND SYSTEM DETAILS.....	9
3.3	INDEPENDENT OPERATION MODES.....	10
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS	10
4.	TEST SET-UP AND OPERATION MODES.....	11
4.1	PRINCIPLE OF CONFIGURATION SELECTION	11
4.2	TEST OPERATION AND TEST SOFTWARE.....	11
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	11
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	11
5.	TEST RESULTS	12
5.1	CONDUCTED TESTING AT ANTENNA PORT	12
5.1.1	<i>Antenna Requirement.....</i>	<i>12</i>
5.1.2	<i>6dB & 99% Bandwidth.....</i>	<i>14</i>
5.1.3	<i>Output Power</i>	<i>21</i>
5.1.4	<i>Power Spectral Density</i>	<i>22</i>
5.1.5	<i>Conducted Band Edge and out-of Band Emissions.....</i>	<i>26</i>
5.2	EMISSION IN THE FREQUENCY RANGE UP TO 30MHZ.....	28
5.2.1	<i>Conducted Emission.....</i>	<i>28</i>
5.3	EMISSION IN THE FREQUENCY RANGE ABOVE 30MHZ	29
5.3.1	<i>Radiated Band-Edge</i>	<i>29</i>
5.3.2	<i>Radiated Spurious Emission.....</i>	<i>32</i>
6.	LIST OF TABLES	39
7.	LIST OF FIGURES	39

1. General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Photographs of the Test Set-up

2. Test Sites

2.1 Test Facilities

TÜV Rheinland (Shanghai) Co., Ltd.
No.14 building and north half of No.10 workshop building, No.525, Yuewang Lingang South Road, Pingqian (Taicang) Modern Industrial Park, Shaxi Town, Taicang City, Jiangsu Province, P.R. China

The used test equipment is in accordance with CISPR 16 for measurement of radio interference.

The Federal Communications Commission has reviewed the technical characteristics of the radiated and conducted emission facility, and has found these test facilities to be in compliance with the requirements of section 2.948 of the FCC rules. The description of the test facility is listed under FCC registration number 930979.

The Innovation, Science and Economic Development Canada has reviewed the technical characteristics of the radiated and conducted emission facility, and has found these test facilities to be in compliance. The description of the test facility is listed under chambers filing number 33038.

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Equip.	Description	Model	Manufacturer	Due Date DD.MM.YYYY
G1811378	3m semi-anechoic chamber	SAC3	Frankonia	03.12.2026
G1811391	EMI test receiver	ESCI	Rohde&Schwarz	16.10.2024
G1811425	Bilog antenna	CBL 6112D	Teseq	20.04.2026
G1825371	Preamplifier	EMC051845SE	Taiwan EMCI	24.07.2025
G1822694	Double ridged broadband horn antenna	BBHA 9120 D	Schwarzbeck	24.03.2026
G1825372	Preamplifier	EMC184045SE	Taiwan EMCI	24.07.2025
G1831065	Broadband horn antenna	BBHA 9170	Schwarzbeck	18.06.2028
G1822702	Spectrum analyser	FSV40	Rohde&Schwarz	15.07.2025
9053477	OSP	OSP-B157W8	Rohde & Schwarz	15.12.2024
9053474	Signal generator	SMB100B (6 GHz)	Rohde & Schwarz	15.12.2024
9053476	Vector Signal generator	SMW200A	Rohde & Schwarz	15.12.2024
9047770	Wireless connectivity tester	CMW270	Rohde & Schwarz	23.08.2025
software				
EMC-S-036	RF measurement software	WMS32-WB (11.40.00)	Rohde & Schwarz	NA
9062745	EMI measurement software	EMC32-MEB (10.60.20)	Rohde&Schwarz	NA

2.3 Traceability

All measurement equipment calibrations are traceable to NIST or where calibration is performed outside the United States, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

Table 2: Measurement Uncertainty

Measurement Type	Frequency	Uncertainty
Antenna Port Conducted Emission	< 1GHz	±0.39dB
	> 1GHz	±0.68dB
Conducted Emission	150kHz - 30MHz	±3.39dB
Radiated Emission	9kHz - 30MHz	±2.93dB
	30MHz - 1GHz	±5.34dB
	> 1GHz	±5.40dB

3. General Product Information

3.1 Product Function and Intended Use

The EUT (Equipment Under Test) is a remote control and which support Bluetooth, Zigbee and Thread function.

The aim of this report is to evaluate RF character of BLE of the EUT.

3.2 Ratings and System Details

Table 3: Technical Specification of EUT

General Description of EUT	
Product Name:	Remote Control (Scroll Wheel)
Model No.:	E2490
Operation Voltage:	DC 3V (2*AAA battery)
RF Technical:	1) BLE 2) Zigbee 3) Thread
Technical Specification of BLE	
Frequency Range:	2402~2480MHz
Modulation Type:	GFSK
Data Rate:	1Mbps
Antenna Type:	Stamping Antenna
Antenna Gain:	2.45 dBi (declared by client)

Table 4: Operation Channel List

RF Channel	Frequency [MHz]						
00	2402	10	2422	20	2442	30	2462
01	2404	11	2424	21	2444	31	2464
02	2406	12	2426	22	2446	32	2466
03	2408	13	2428	23	2448	33	2468
04	2410	14	2430	24	2450	34	2470
05	2412	15	2432	25	2452	35	2472
06	2414	16	2434	26	2454	36	2474
07	2416	17	2436	27	2456	37	2476
08	2418	18	2438	28	2458	38	2478
09	2420	19	2440	29	2460	39	2480

3.3 Independent Operation Modes

Test frequencies are lowest channel: 2402 MHz, middle channel: 2440 MHz and highest channel: 2480 MHz

The basic operation modes are:

- A. On, BLE transmitting mode
- B. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured to measure its maximum power level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All testing were performed according to the procedures in ANSI C63.10: 2013.

Test Software: sscm 5.13.1

Table 5: Power parameter value

Mode	Power Parameter Setting Value
BLE	3 dBm

4.3 Special Accessories and Auxiliary Equipment

Table 6: Auxiliary Equipment

Equipment	Manufacturer	Model
Laptop	Lenovo	21AJ-S57N0J

4.4 Countermeasures to achieve EMC Compliance

Null.

Prüfbericht - Nr.: CN24EKHE 001
Test Report No.**Seite 13 von 39**
Page 13 of 39**RSS-Gen 6.8 – Antenna Requirement**

Requirement: When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

Results:

a) Antenna Type:	Stamping Antenna
b) Manufacture:	N/A
c) Model No.:	N/A
d) Gain with reference to an isotropic radiator:	2.45 dBi

Verdict: **PASS**

5.1.2 6dB & 99% Bandwidth

RESULT:**Pass**

Date of testing : 2024-11-05
Ambient temperature : 22.4°C
Relative humidity : 50.2%
Atmospheric pressure : 101kPa
Test requirement : FCC Part 15.247(a)(2)
RSS-247 Issue 3, August 2023, Clause 5.2(a)
Test procedure : ANSI C63.10: 2013
Test voltage : DC 3V
Test modes applied : A


6dB Bandwidth, 2402MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	0.693070	0.500000	---	2401.623762	2402.316832

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2402.000000	2.7	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40300 GHz	2.40300 GHz
Span	2.000 MHz	2.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 40
Sweeptime	18.938 1/4 s	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	9 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.01 dB	0.50 dB


6dB Bandwidth, 2440MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2440.000000	0.673268	0.500000	---	2439.643564	2440.316832

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2440.000000	2.5	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43900 GHz	2.43900 GHz
Stop Frequency	2.44100 GHz	2.44100 GHz
Span	2.000 MHz	2.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 40
SweepTime	18.938 1/4 s	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	10 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.21 dB	0.50 dB


6dB Bandwidth, 2480MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	0.693070	0.500000	---	2479.643564	2480.336634

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2480.000000	2.2	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47900 GHz	2.47900 GHz
Stop Frequency	2.48100 GHz	2.48100 GHz
Span	2.000 MHz	2.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 40
Sweeptime	18.938 1/4 s	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	10 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.00 dB	0.50 dB


99% Occupied Channel Bandwidth, 2402MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	1.035000	---	---	2401.482500	2402.517500

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2402.000000	PASS

99 % Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.39900 GHz	2.39900 GHz
Stop Frequency	2.40500 GHz	2.40500 GHz
Span	6.000 MHz	6.000 MHz
RBW	30.000 kHz	>= 30.000 kHz
VBW	100.000 kHz	>= 90.000 kHz
SweepPoints	400	~ 400
Sweeptime	63.216 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	8 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.22 dB	0.30 dB


99% Occupied Channel Bandwidth, 2440MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2440.000000	1.020000	---	---	2439.482500	2440.502500

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2440.000000	PASS

99 % Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43700 GHz	2.43700 GHz
Stop Frequency	2.44300 GHz	2.44300 GHz
Span	6.000 MHz	6.000 MHz
RBW	30.000 kHz	>= 30.000 kHz
VBW	100.000 kHz	>= 90.000 kHz
SweepPoints	400	~ 400
Sweeptime	63.216 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	9 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.12 dB	0.30 dB


99% Occupied Channel Bandwidth, 2480MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	1.020000	---	---	2479.482500	2480.502500

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2480.000000	PASS

99 % Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47700 GHz	2.47700 GHz
Stop Frequency	2.48300 GHz	2.48300 GHz
Span	6.000 MHz	6.000 MHz
RBW	30.000 kHz	>= 30.000 kHz
VBW	100.000 kHz	>= 90.000 kHz
SweepPoints	400	~ 400
Sweptime	63.216 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	12 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.25 dB	0.30 dB

5.1.3 Output Power

RESULT:**Pass**

Date of testing : 2024-11-05
Ambient temperature : 22.4°C
Relative humidity : 50.2%
Atmospheric pressure : 101kPa
Test requirement : FCC Part 15.247(b)(3)
RSS-247 Issue 3, August 2023, Clause 5.4(d)
Test procedure : ANSI C63.10: 2013
Test voltage : DC 3V
Test modes applied : A

Table 8: Peak Output Power

Frequency [MHz]	Peak Conducted Output Power [dBm]	Limit [dBm]
2402	3.1	30
2440	2.9	30
2480	2.8	30

Note:

1. The cable loss is taken into account in results.
2. EIRP=Conducted Output Power + Antenna Gain (2.45dBi), which is far below the 4 W (36dBm).

5.1.4 Power Spectral Density


RESULT:**Pass**

Date of testing : 2024-11-05
Ambient temperature : 22.4°C
Relative humidity : 50.2%
Atmospheric pressure : 101kPa
Test requirement : FCC Part 15.247(e)
RSS-247 Issue 3, August 2023, Clause 5.2(b)
Test procedure : ANSI C63.10: 2013
Test voltage : DC 3V
Test modes applied : A

Power Spectral Density, 2402MHz

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2402.000000	2401.977509	-6.435	8.0	PASS

Peak Power Spectral Density



— Limit — Sum Level ◆ PSD


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40148 GHz	2.40148 GHz
Stop Frequency	2.40252 GHz	2.40252 GHz
Span	1.040 MHz	1.040 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	208	~ 208
SweepTime	1.040 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	7 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.10 dB	0.50 dB

Power Spectral Density, 2440MHz

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2440.000000	2439.967503	-5.952	8.0	PASS

Peak Power Spectral Density



— Limit — Sum Level ◆ PSD


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43950 GHz	2.43950 GHz
Stop Frequency	2.44050 GHz	2.44050 GHz
Span	1.010 MHz	1.010 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	202	~ 202
SweepTime	1.010 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	6 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.29 dB	0.50 dB

Power Spectral Density, 2480MHz

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2480.000000	2479.967512	-6.434	8.0	PASS



Peak Power Spectral Density



— Limit — Sum Level ◆ PSD

Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47948 GHz	2.47948 GHz
Stop Frequency	2.48052 GHz	2.48052 GHz
Span	1.040 MHz	1.040 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	208	~ 208
SweepTime	1.040 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	6 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.29 dB	0.50 dB

Figure 2: Conducted Spurious Emission

Figure 3: Conducted Band Edge


5.2 Emission in the Frequency Range up to 30MHz

5.2.1 Conducted Emission

RESULT:**N/A**

Date of testing : /
Ambient temperature : /
Relative humidity : /
Atmospheric pressure : /
Test requirement : FCC Part 15.207 (a)
RSS-Gen Issue 5, Amendment 2, February 2021, Clause
8.8
Test procedure : KDB 558074 D01v05r02
ANSI C63.10: 2013
Test voltage : /
Test modes applied : /

Note: This product is power by battery, so it is not applicable for this test.

5.3 Emission in the Frequency Range above 30MHz


5.3.1 Radiated Band-Edge

RESULT:**Pass**

Date of testing	:	2024-11-05
Ambient temperature	:	22.4°C
Relative humidity	:	50.2%
Atmospheric pressure	:	101kPa
Test requirement	:	FCC Part 15.247(d) FCC Part 15.205(a) FCC Part 15.209(a) RSS-Gen Issue 5, Amendment 2, February 2021, Clause 8.9 RSS-Gen Issue 5, Amendment 2, February 2021, Clause 8.10 RSS-247 Issue 3, August 2023, Clause 5.5
Test procedure	:	ANSI C63.10: 2013
Test voltage	:	DC 3V
Test modes applied	:	A

Figure 4: Radiated Band-Edge, 2402MHz, H

Copy of 2310~ 2410 BE 1-18GHz_HL050_FSV40_Pre


PK


Frequency (MHz)	MaxPeak (dBµV/m)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµV/m)
2327.375000	63.5	32.8	10.5	74.0

AV

Frequency (MHz)	Average (dBµV/m)	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµV/m)
2327.375000	50.1	32.8	3.9	54.0

Figure 5: Radiated Band-Edge, 2402MHz, V

Copy of 2310~ 2410 BE 1-18GHz_HL050_FSV40_Pre


PK


Frequency (MHz)	MaxPeak (dBµV/m)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµV/m)
2386.350000	63.1	32.6	10.9	74.0

AV

Frequency (MHz)	Average (dBµV/m)	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµV/m)
2386.350000	49.9	32.6	4.1	54.0

Figure 6: Radiated Band-Edge, 2480MHz, H

Copy of 2470~ 2500 BE_1-18GHz_HL050_FSV40_Pre


PK


Frequency (MHz)	MaxPeak (dBµV/m)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµV/m)
2488.742500	63.3	32.5	10.7	74.0

AV

Frequency (MHz)	Average (dBµV/m)	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµV/m)
2488.742500	49.9	32.5	4.1	54.0

Figure 7: Radiated Band-Edge, 2480MHz, V

Copy of 2470~ 2500 BE_1-18GHz_HL050_FSV40_Pre


PK

Frequency (MHz)	MaxPeak (dBµV/m)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµV/m)
2497.022500	63.8	32.5	10.2	74.0

AV

Frequency (MHz)	Average (dBµV/m)	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµV/m)
2497.022500	50.0	32.5	4.0	54.0


5.3.2 Radiated Spurious Emission

RESULT:**Pass**

Date of testing : 2024-11-02
Ambient temperature : 21.3°C
Relative humidity : 59.2%
Atmospheric pressure : 101kPa
Test requirement : FCC Part 15.247(d)
FCC Part 15.209(a)
RSS-Gen Issue 5, Amendment 2, February 2021, Clause 8.9
RSS-247 Issue 3, August 2023, Clause 5.5
Test procedure : ANSI C63.10: 2013
Test voltage : DC 3V
Test modes applied : A

Note:

For the frequency range from 18GHz to 25GHz, no emission was found.

Figure 8: Radiated Spurious Emission, 2402MHz


Limit and Margin
QP


Frequency (MHz)	QuasiPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
31.212500	27.6	H	24.3	12.4	40.0
192.717500	36.5	H	15.9	7.0	43.5
240.853750	35.7	H	18.5	10.3	46.0
845.042500	33.1	H	28.9	12.9	46.0
31.091250	27.7	V	24.3	12.3	40.0
254.797500	23.1	V	20.1	22.9	46.0
546.646250	30.1	V	26.6	15.9	46.0
978.902500	34.0	V	29.8	20.0	54.0

PK

Frequency (MHz)	MaxPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµV/m)
1330.000000	38.5	H	-18.6	35.5	74.0
2124.100000	39.2	H	-16.3	34.8	74.0
4803.700000	42.2	H	-10.8	31.8	74.0
6580.600000	43.5	H	-7.0	30.5	74.0
7866.800000	48.1	H	-3.7	25.9	74.0
9932.600000	48.0	H	-3.2	26.0	74.0
12699.100000	48.6	H	-1.0	25.4	74.0
16424.250000	49.7	H	1.9	24.3	74.0
1463.500000	40.1	V	-18.4	33.9	74.0
2131.000000	42.8	V	-16.2	31.2	74.0
3055.600000	39.7	V	-14.6	34.3	74.0
4804.600000	44.3	V	-10.8	29.7	74.0
7944.900000	47.4	V	-3.0	26.6	74.0
9938.650000	47.2	V	-3.2	26.8	74.0
12279.450000	48.5	V	-1.6	25.5	74.0
17983.500000	59.9	V	13.1	14.1	74.0

AV

Frequency (MHz)	Average (dBµV/m)	Pol	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµV/m)
1330.000000	23.9	H	-18.6	30.1	54.0
2124.100000	25.7	H	-16.3	28.3	54.0
4803.700000	35.1	H	-10.8	18.9	54.0
6580.600000	33.7	H	-7.0	20.3	54.0
7866.800000	35.1	H	-3.7	18.9	54.0
9932.600000	35.0	H	-3.2	19.0	54.0
12699.100000	35.7	H	-1.0	18.3	54.0
16424.250000	37.1	H	1.9	16.9	54.0
1463.500000	26.6	V	-18.4	27.4	54.0
2131.000000	30.7	V	-16.2	23.3	54.0
3055.600000	28.6	V	-14.6	25.4	54.0
4804.600000	41.5	V	-10.8	12.5	54.0
7944.900000	35.1	V	-3.0	18.9	54.0
9938.650000	34.6	V	-3.2	19.4	54.0
12279.450000	35.5	V	-1.6	18.5	54.0
17983.500000	46.8	V	13.1	7.2	54.0

Figure 9: Radiated Spurious Emission, 2440MHz


Limit and Margin
QP


Frequency (MHz)	QuasiPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
32.546250	26.9	H	23.6	13.1	40.0
192.596250	35.6	H	15.9	7.9	43.5
240.853750	35.6	H	18.5	10.4	46.0
857.773750	33.3	H	28.9	12.7	46.0
30.242500	28.0	V	24.7	12.0	40.0
260.738750	23.8	V	20.8	22.2	46.0
598.662500	30.9	V	26.9	15.1	46.0
897.180000	33.3	V	28.8	12.7	46.0

PK

Frequency (MHz)	MaxPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµV/m)
1463.800000	36.9	H	-18.4	37.1	74.0
2125.300000	39.7	H	-16.3	34.3	74.0
3100.600000	36.6	H	-14.3	37.4	74.0
4880.800000	42.5	H	-10.7	31.5	74.0
7085.800000	46.2	H	-4.8	27.8	74.0
9341.350000	48.1	H	-3.6	25.9	74.0
12159.550000	48.7	H	-1.4	25.3	74.0
17966.450000	60.6	H	12.8	13.4	74.0
1063.000000	39.2	V	-19.9	34.8	74.0
2123.800000	41.4	V	-16.3	32.6	74.0
3916.000000	37.7	V	-13.1	36.3	74.0
4880.500000	47.9	V	-10.7	26.2	74.0
7796.950000	47.0	V	-4.3	27.0	74.0
10421.000000	48.2	V	-1.8	25.8	74.0
13604.950000	51.1	V	1.4	22.9	74.0
17973.600000	59.2	V	12.9	14.8	74.0

AV

Frequency (MHz)	Average (dBµV/m)	Pol	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµV/m)
1463.800000	23.8	H	-18.4	30.2	54.0
2125.300000	27.6	H	-16.3	26.4	54.0
3100.600000	25.6	H	-14.3	28.4	54.0
4880.800000	36.4	H	-10.7	17.6	54.0
7085.800000	33.5	H	-4.8	20.6	54.0
9341.350000	35.0	H	-3.6	19.0	54.0
12159.550000	35.7	H	-1.4	18.3	54.0
17966.450000	46.6	H	12.8	7.4	54.0
1063.000000	26.8	V	-19.9	27.2	54.0
2123.800000	26.1	V	-16.3	27.9	54.0
3916.000000	27.4	V	-13.1	26.6	54.0
4880.500000	42.6	V	-10.7	11.4	54.0
7796.950000	34.1	V	-4.3	19.9	54.0
10421.000000	35.4	V	-1.8	18.6	54.0
13604.950000	38.3	V	1.4	15.7	54.0
17973.600000	46.6	V	12.9	7.4	54.0

Figure 10: Radiated Spurious Emission, 2480MHz


Limit and Margin
QP

Frequency (MHz)	QuasiPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
31.212500	27.6	H	24.3	12.4	40.0
192.717500	36.4	H	15.9	7.1	43.5
240.853750	34.4	H	18.5	11.6	46.0
853.287500	33.3	H	29.0	12.7	46.0
30.242500	27.9	V	24.7	12.1	40.0
267.771250	23.4	V	20.4	22.6	46.0
629.945000	30.2	V	26.5	15.8	46.0
977.568750	34.0	V	29.8	20.0	54.0

PK

Frequency (MHz)	MaxPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµV/m)
1463.200000	37.3	H	-18.4	36.7	74.0
2257.300000	42.8	H	-15.3	31.2	74.0
4960.600000	40.5	H	-10.6	33.5	74.0
6625.900000	43.0	H	-7.1	31.0	74.0
7116.050000	46.5	H	-4.6	27.5	74.0
9937.550000	47.8	H	-3.2	26.2	74.0
13408.050000	49.9	H	0.5	24.1	74.0
17966.450000	59.4	H	12.8	14.6	74.0
1464.100000	42.3	V	-18.4	31.7	74.0
2260.300000	42.5	V	-15.3	31.5	74.0
4959.700000	45.6	V	-10.6	28.4	74.0
6508.900000	43.9	V	-7.0	30.1	74.0
7959.750000	48.3	V	-2.9	25.7	74.0
11095.850000	47.6	V	-1.9	26.4	74.0
13397.600000	50.5	V	0.5	23.5	74.0
17976.900000	59.8	V	13.0	14.2	74.0

AV

Frequency (MHz)	Average (dBµV/m)	Pol	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµV/m)
1463.200000	23.6	H	-18.4	30.4	54.0
2257.300000	26.3	H	-15.3	27.7	54.0
4960.600000	34.8	H	-10.6	19.2	54.0
6625.900000	33.6	H	-7.1	20.4	54.0
7116.050000	33.8	H	-4.6	20.2	54.0
9937.550000	34.7	H	-3.2	19.3	54.0
13408.050000	37.1	H	0.5	16.9	54.0
17966.450000	46.5	H	12.8	7.5	54.0
1464.100000	27.9	V	-18.4	26.1	54.0
2260.300000	29.7	V	-15.3	24.3	54.0
4959.700000	41.7	V	-10.6	12.3	54.0
6508.900000	33.7	V	-7.0	20.3	54.0
7959.750000	35.3	V	-2.9	18.7	54.0
11095.850000	34.6	V	-1.9	19.4	54.0
13397.600000	36.8	V	0.5	17.2	54.0
17976.900000	46.7	V	13.0	7.3	54.0

6. List of Tables

Table 1: List of Test and Measurement Equipment	7
Table 2: Measurement Uncertainty	8
Table 3: Technical Specification of EUT	9
Table 4: Operation Channel List	10
Table 5: Power parameter value.....	11
Table 6: Auxiliary Equipment.....	11
Table 7: Antenna Requirement.....	12
Table 8: Peak Output Power	21

7. List of Figures

Figure 1: Reference level	26
Figure 2: Conducted Spurious Emission.....	27
Figure 3: Conducted Band Edge	27
Figure 4: Radiated Band-Edge, 2402MHz, H.....	30
Figure 5: Radiated Band-Edge, 2402MHz, V	30
Figure 6: Radiated Band-Edge, 2480MHz, H.....	31
Figure 7: Radiated Band-Edge, 2480MHz, V	31
Figure 8: Radiated Spurious Emission, 2402MHz	33
Figure 9: Radiated Spurious Emission, 2440MHz	35
Figure 10: Radiated Spurious Emission, 2480MHz	37