

Prüfbericht-Nr.: Test Report No.:	CN24P27P 001	Auftrags-Nr.: Order No.:	326058866	Seite 1 von 31 Page 1 of 31
Kunden-Referenz-Nr.: Client Reference No.:	1288983	Auftragsdatum: Order date.:	2024-10-22	
Auftraggeber: Client:	IKEA of Sweden AB Box 702, SE-343 81, Älmhult Sweden			
Prüfgegenstand: Test item:	GREJSIMOJS Mouse Speaker			
Bezeichnung / Typ-Nr.: Identification / Type No.:	E2498			
Auftrags-Inhalt: Order content:	TÜV Rheinland EMC service			
Prüfgrundlage: Test specification:	FCC 47 CFR Part 15, Subpart B:2023 Class B ICES-003:2020			
Wareneingangsdatum: Date of receipt:	2024-12-09	Refer to the EUT photos file		
Prüfmuster-Nr.: Test sample No.:	A003881280-009/-010			
Prüfzeitraum: Testing period:	Refer to test report			
Ort der Prüfung: Place of testing:	Refer to clause 1.1			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shanghai) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: / tested by:	genehmigt von: / authorized by:			
Datum: / Date: 2025-02-17	<i>Xuelan Zhang</i>	Datum: / Date: 2025-02-17	<i>See Zhang</i>	
Stellung: / Position: Project engineer		Stellung: / Position: Authorizer		
Sonstiges / Other:	FCC ID: FHO-E2498 IC: 10912A-E2498 Test Firm Name: TUV Rheinland (Shanghai) Co., Ltd. Designation Number: CN1396 Test Firm Registration Number: 930979			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende: P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet Legend: P(ass) = passed a.m. test specifications(s) F(ail) = failed a.m. test specifications(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.				

Prüfbericht - Nr.: CN24P27P 001

Seite 2 von 31

Test Report No.:

Page 2 of 31

Anmerkungen
Remarks

- | | |
|---|--|
| 1 | <p>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben.
Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</p> <p><i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system.</i></p> <p><i>Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i></p> |
| 2 | <p>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature</p> <p><i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i></p> |
| 3 | <p>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben.
Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</p> <p><i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i></p> <p><i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i></p> |
| 4 | <p>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</p> <p><i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i></p> |

Prüfbericht - Nr.: CN24P27P 001

Test Report No.:

Seite 3 von 31

Page 3 of 31

Revision history of test report:

Report number	Issue date	Contents and reason for change if appropriate
CN24P27P 001	2025-02-17	Initial release.

Contents

1	TEST SITES	5
1.1	TEST FACILITIES	5
2	GENERAL PRODUCT INFORMATION	6
2.1	PRODUCT FUNCTION AND INTENDED USE.....	6
2.2	RATINGS AND SYSTEM DETAILS	6
2.3	INDEPENDENT OPERATION MODESS	6
2.4	DESCRIPTION OF INTERCONNECTING CABLES.....	6
2.5	NOISE GENERATING AND NOISE SUPPRESSING PARTS	6
2.6	HIGHEST FREQUENCY GENERATED OR USED IN THE DEVICE OR ON WHICH THE DEVICE OPERATES OR TUNES	6
2.7	SUBMITTED DOCUMENTS.....	6
3	TEST SET-UP AND OPERATION MODES	7
3.1	PRINCIPLE OF CONFIGURATION SELECTION	7
3.2	EQUIPMENT AND CABLE ARRANGEMENT.....	7
3.3	TEST SOFTWARE	8
3.4	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	8
3.5	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE	8
4	CONFORMITY DECISION RULE	9
5	TEST RESULTS E M I S S I O N	10
5.1	EMISSION IN THE FREQUENCY RANGE UP TO 30 MHZ.....	10
5.1.1	<i>Mains Terminal Continuous Disturbance Voltage</i>	10
5.2	EMISSION IN THE FREQUENCY RANGE ABOVE 30 MHZ.....	14
5.2.1	<i>Radiated emission (30 MHz - 1 GHz)</i>	14
5.2.2	<i>Radiated emission (Above 1 GHz)</i>	22
6	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	30
7	LIST OF FIGURES.....	31

1 Test Sites

1.1 Test Facilities

Laboratory: TÜV Rheinland (Shanghai) Co., Ltd.
Address: Workshop14, North Half of Workshop 10 and Workshop 16, Pingqian (Taicang) Modern Industrial Park, No.525, Yuewang Lingang South Road, Shaxi, Taicang, Jiangsu, China

The used test equipment is in accordance with CISPR 16-1 series standards for measurement of radio interference.

Refer to Clause 6 for test and measurement instruments.

2 General Product Information

2.1 Product Function and Intended Use

The EUT (equipment under test) is a GREJSIMOJS Mouse Speaker. For the further information, refer to the user's manual.

2.2 Ratings and System Details

Rated input	: DC 5 V, 1 A; Rechargeable li-ion battery, Capacity: 2500 mAh
Audio output	: 2 W
Protection class	: III

2.3 Independent Operation Modess

The basic operation mode is the below,

1. Continuous playing 1 kHz audio signal by Bluetooth.
2. Charging mode by USB charger
3. Charging mode by computer

2.4 Description of interconnecting cables

None.

2.5 Noise Generating and Noise Suppressing Parts

Refer to the circuit diagram for further information.

2.6 Highest frequency generated or used in the device or on which the device operates or tunes

The highest frequency used in the EUT is 2.4 GHz.

2.7 Submitted Documents

Circuit diagram, user's manual and rating label.

3 Test Set-up and Operation Modes

3.1 Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible emission level. The test conditions were adapted accordingly in reference to the instructions for use.


Refer to the related paragraph of this report.

The sequence of testing:


1. Radiated emission tests were performed on 2024-12-17.
2. Conducted emission tests were performed on 2024-12-17~2024-12-19.

3.2 Equipment and cable arrangement

Block diagram for both conducted emission and radiated emission tests is as follows:



(Conducted emission)



(Radiated emission)

3.3 Test Software

No special test software was used during the tests.

3.4 Special Accessories and Auxiliary Equipment

During the tests, the below equipment were used.

No.	Equipment	Model	Manufacturer
1	Cell phone	STF-AL10	Huawei
2	USB charger	E2301-EU	IKEA
3	Computer	ThinkPad T450	lenovo

3.5 Countermeasures to achieve EMC Compliance

No other special measure is employed to achieve the requirement.

4 Conformity Decision Rule

For all EMI tests included in this report, as measurement uncertainties are less than the values U_{CISPR} given in CISPR 16-4-2, compliance with the limits is determined by comparing measurement results directly with corresponding limits without taking into consideration of measurement uncertainties.

5 Test Results EMISSION

5.1 Emission in the Frequency Range up to 30 MHz

5.1.1 Mains Terminal Continuous Disturbance Voltage

Result:	Passed
----------------	---------------

Date of testing	: 2024-12-17
Test procedure	: FCC 47 CFR Part 15, Subpart B:2023, ICES-003:2020, ANSI C63.4-2014 and CISPR 16-2-1
Frequency range	: 0.15 – 30 MHz
Limits	: Quasi-peak limit: 0.15 - 0.5 MHz, 66 to 56 dB μ V (decrease with the logarithm of frequency); 0.5 - 5 MHz, 56 dB μ V; 5 - 30 MHz, 60 dB μ V Average limit: 0.15 - 0.5 MHz, 56 to 46 dB μ V (decrease with the logarithm of frequency); 0.5 – 5 MHz, 46 dB μ V; 5 – 30 MHz, 50 dB μ V
Bandwidth of EMI receiver for final measurement	: 9 kHz
Measurement time for final measurement	: 1 s
Kind of test site	: Shielded room
Input voltage	: AC 120 V, 60 Hz (powered with USB charger)
Operational mode	: Mode 2 as defined in clause 2.3
Ambient condition	: Temperature: 20.5 °C; Relative humidity: 48.2 %
Expanded measurement uncertainty ($k=2$)	: 2.33 dB The minimum margin to the limit is 8.87 dB at 0.487500 MHz. The margin is higher than expanded measurement uncertainty.

The measurement setup was made according to ANSI C63.4-2014 in a shielded room.

The measurement equipment like test receivers, quasi-peak detector and artificial mains network (AMN) are in compliance with CISPR 16-1 series standards.

The tested object was set-up on a wooden support. The EUT was set 0.8 m away from the AMN. The cord longer than necessary to be connected to the AMN was folded forth and back parallel so as to form a bundle with a length between 0.3 m and 0.4 m.

The disturbance voltage test was performed on the neutral line and phase line of the power supply of the EUT respectively.

The following figures and tables were those measured by an automatic measuring system. Both quasi-peak and average measurements were performed. In the following spectral diagram, “◆” mean Quasi-Peak Value and “◆” mean Average Value results.

Prüfbericht - Nr.: CN24P27P 001

Test Report No.:

Seite 11 von 31

Page 11 of 31


Notes on following tables of conducted emission results and conversions:

Level (dB μ V): final measurement results by using quasi-peak detector and average detector

Transd (dB): transducer factor including cable loss, insertion loss of artificial mains network and gain of pre-amplifier (if used)

Margin: Limit (dB μ V) - Level (dB μ V)

Figure 1: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, L




Final Quasi-peak measurement result:

Frequency (MHz)	QuasiPeak (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.172500	48.91	64.84	15.93	1000.0	9.000	L1	10.3
0.444750	37.31	56.97	19.66	1000.0	9.000	L1	10.3
0.487500	45.37	56.21	10.84	1000.0	9.000	L1	10.3
0.528000	34.33	56.00	21.67	1000.0	9.000	L1	10.3
1.009500	34.82	56.00	21.18	1000.0	9.000	L1	10.7
1.061250	34.23	56.00	21.77	1000.0	9.000	L1	10.7

Final Average measurement result:

Frequency (MHz)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.442500	26.07	47.02	20.95	1000.0	9.000	L1	10.3
0.487500	37.34	46.21	8.87	1000.0	9.000	L1	10.3
0.530250	24.61	46.00	21.39	1000.0	9.000	L1	10.3
0.615750	23.79	46.00	22.21	1000.0	9.000	L1	10.3
1.016250	24.38	46.00	21.62	1000.0	9.000	L1	10.7
1.059000	23.71	46.00	22.29	1000.0	9.000	L1	10.7

Figure 2: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, N



Final Quasi-peak measurement result:

Frequency (MHz)	QuasiPeak (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.174750	49.51	64.73	15.22	1000.0	9.000	N	10.5
0.399750	36.11	57.86	21.75	1000.0	9.000	N	10.3
0.444750	38.73	56.97	18.24	1000.0	9.000	N	10.3
0.487500	42.56	56.21	13.65	1000.0	9.000	N	10.2
0.528000	34.93	56.00	21.07	1000.0	9.000	N	10.2
0.573000	32.67	56.00	23.33	1000.0	9.000	N	10.3

Final Average measurement result:

Frequency (MHz)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.172500	30.36	54.84	24.48	1000.0	9.000	N	10.5
0.444750	23.06	46.97	23.91	1000.0	9.000	N	10.3
0.487500	33.29	46.21	12.92	1000.0	9.000	N	10.2
0.530250	20.63	46.00	25.37	1000.0	9.000	N	10.2
0.615750	20.41	46.00	25.59	1000.0	9.000	N	10.3
1.018500	20.88	46.00	25.12	1000.0	9.000	N	10.4

5.2 Emission in the Frequency Range above 30 MHz

5.2.1 Radiated emission (30 MHz - 1 GHz)

Result:	Passed
----------------	---------------

Date of testing	: 2024-12-17~2024-12-19
Test procedure	: FCC 47 CFR Part 15, Subpart B:2023, ICES-003:2020, ANSI C63.4-2014 and CISPR 16-2-3
Frequency range	: 30 – 1000 MHz
Limits	: Quasi-peak limits (3 m distance): 30 – 88 MHz, 40 dB μ V/m; 88 – 216 MHz, 43.5 dB μ V/m; 216 – 1000 MHz, 46 dB μ V/m
Bandwidth of EMI receiver for final measurement	: 120 kHz
Measurement time for final measurement	: 1 s
Kind of test site	: Semi-anechoic chamber
Operational mode	: Modes 1, 2, 3 as defined in clause 2.3
Input voltage	: AC 120 V; 60 Hz (powered by USB charger) DV 5 V (powered by computer) Powered by rechargeable li-ion battery
Ambient condition	: Temperature: 20.5 °C; Relative humidity: 45 %
Expanded measurement uncertainty ($k=2$)	: 5.40 dB The minimum margin to the limit is 12.1 dB at 30.242500 MHz, 30.363750 MHz. The margin is higher than expanded measurement uncertainty.

The radiated disturbance test was carried out in a semi-anechoic chamber. The test distance from the receiving antenna to the EUT is 3 m. The normalized site attenuation of the semi-anechoic chamber is regularly calibrated to ensure the radiated disturbance test results are valid. During the test, the EUT was placed on a 0.8 m high wooden table above the reference ground plane. The wooden table was rotated 360° around and the height of the antenna was varied from 1 m to 4 m to find the maximum disturbance. The test was performed with the antenna both in its horizontal and vertical polarizations.

The following figures and tables were those measured by an automatic measurement system. A preview test was firstly performed with peak detector. The final test was performed with quasi-peak at those critical frequencies during the preview test. In the following spectral diagram, “×” means quasi-peak test results.

Prüfbericht - Nr.: CN24P27P 001

Test Report No.:

Seite 15 von 31

Page 15 of 31


Notes on following tables of radiated emission results and conversions:

QuasiPeak (dB μ V/m): final measurement results by using quasi-peak detector

Corr. (dB): correction factor including: antenna factor, cable loss, and gain of pre-amplifier (if used)

Margin: Limit (dB μ V/m) - QuasiPeak (dB μ V/m)


Figure 3: Spectral Diagrams and measurement results, horizontal polarization (30 MHz to 1 GHz), mode 1



Final Quasi-peak measurement result:

Frequency (MHz)	QuasiPeak (dBµ/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµ/m)
30.363750	27.9	120.000	150.0	H	111.0	24.6	12.1	40.0
111.358750	21.6	120.000	130.0	H	144.0	18.7	21.9	43.5
265.103750	23.7	120.000	110.0	H	-146.0	20.7	22.3	46.0
462.862500	27.8	120.000	110.0	H	96.0	24.6	18.2	46.0
694.692500	30.3	120.000	110.0	H	-48.0	26.8	15.7	46.0
845.770000	33.2	120.000	150.0	H	155.0	28.9	12.8	46.0


Figure 4: Spectral Diagrams and measurement results, vertical polarization (30 MHz to 1 GHz), mode 1



Final Quasi-peak measurement result:


Frequency (MHz)	QuasiPeak (dBµ/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµ/m)
30.242500	27.9	120.000	100.0	V	-62.0	24.7	12.1	40.0
108.448750	21.5	120.000	130.0	V	116.0	18.5	22.1	43.5
264.133750	23.7	120.000	100.0	V	-129.0	20.8	22.3	46.0
554.648750	30.2	120.000	110.0	V	84.0	26.7	15.8	46.0
843.708750	33.1	120.000	150.0	V	22.0	28.9	12.9	46.0
906.880000	33.3	120.000	130.0	V	-132.0	28.9	12.7	46.0

Figure 5: Spectral Diagrams and measurement results, horizontal polarization (30 MHz to 1 GHz), mode 2



Final Quasi-peak measurement result:


Frequency (MHz)	QuasiPeak (dBµ/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµ/m)
31.818750	27.3	120.000	150.0	H	113.0	23.9	12.7	40.0
116.087500	21.8	120.000	130.0	H	-59.0	18.8	21.7	43.5
258.556250	23.7	120.000	120.0	H	-107.0	20.6	22.3	46.0
605.816250	30.5	120.000	120.0	H	-88.0	27.0	15.5	46.0
732.401250	31.0	120.000	110.0	H	-33.0	27.5	15.0	46.0
862.745000	33.3	120.000	130.0	H	-2.0	28.8	12.8	46.0

Figure 6: Spectral Diagrams and measurement results, vertical polarization (30 MHz to 1 GHz), mode 2


Final Quasi-peak measurement result:

Frequency (MHz)	QuasiPeak (dBµ/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµ/m)
34.971250	27.3	120.000	110.0	V	24.0	22.5	12.7	40.0
130.758750	21.7	120.000	110.0	V	140.0	18.7	21.8	43.5
261.587500	23.9	120.000	140.0	V	130.0	20.9	22.1	46.0
544.463750	29.9	120.000	140.0	V	39.0	26.5	16.1	46.0
727.066250	30.9	120.000	150.0	V	-156.0	27.3	15.1	46.0
875.112500	33.3	120.000	110.0	V	101.0	28.6	12.8	46.0


Figure 7: Spectral Diagrams and measurement results, horizontal polarization (30 MHz to 1 GHz), mode 3



Final Quasi-peak measurement result:

Frequency (MHz)	QuasiPeak (dBµ/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµ/m)
30.606250	27.8	120.000	120.0	H	135.0	24.5	12.2	40.0
106.751250	21.4	120.000	140.0	H	107.0	18.4	22.1	43.5
264.861250	23.6	120.000	150.0	H	-136.0	20.7	22.4	46.0
552.223750	30.2	120.000	140.0	H	-47.0	26.7	15.8	46.0
856.682500	33.3	120.000	130.0	H	-10.0	28.9	12.7	46.0
973.325000	33.9	120.000	140.0	H	-78.0	29.7	20.1	54.0

Figure 8: Spectral Diagrams and measurement results, vertical polarization (30 MHz to 1 GHz), mode 3



Final Quasi-peak measurement result:

Frequency (MHz)	QuasiPeak (dBµ/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµ/m)
30.970000	27.7	120.000	100.0	V	-43.0	24.4	12.3	40.0
119.482500	21.9	120.000	150.0	V	97.0	18.9	21.6	43.5
262.557500	23.9	120.000	110.0	V	-152.0	20.9	22.1	46.0
518.152500	29.0	120.000	110.0	V	-5.0	25.6	17.0	46.0
896.452500	33.3	120.000	110.0	V	147.0	28.8	12.7	46.0
996.605000	33.9	120.000	130.0	V	179.0	29.8	20.1	54.0

5.2.2 Radiated emission (Above 1 GHz)

Result:	Passed
----------------	---------------

Date of testing	: 2024-12-17~2024-12-19
Port	: Enclosure
Test procedure	: FCC 47 CFR Part 15, Subpart B:2023, ANSI C63.4-2014 and CISPR 16-2-3 ICES-003:2020
Limit	: Above 1 GHz, Peak limit: 74 dB μ V/m; Average limit: 54 dB μ V/m
Frequency range	: 1-18 GHz Note: The highest frequency in the EUT is 2.4 GHz. According to FCC Part 15 subpart B §15.33 (b) (1), the upper frequency for radiated emission measurement is 12 GHz. The actual test frequency is up to 18 GHz.
Bandwidth of EMI receiver for final measurement	: 1000 kHz
Measurement time for final measurement	: 1 s
Test distance	: 3 m
Kind of test site	: Semi-anechoic chamber
Operational mode	: Modes 1, 2, 3 as defined in clause 2.3
Input voltage	: AC 120 V; 60 Hz (powered by USB charger) DV 5 V (powered by computer) Powered by rechargeable li-ion battery
Earthing	: No earthing
Ambient condition	: Temperature: 20.5 °C; Relative humidity: 45 %
Expanded measurement uncertainty ($k=2$)	: 5.08 dB (1-6 GHz) 5.21 dB (6-18 GHz) The minimum margin to the limit is 7.5 dB at 17973.968750 MHz and 17970.781250 MHz. The margin is higher than expanded measurement uncertainty.

The radiated disturbance test was carried out in a semi-anechoic chamber. The test distance from the receiving antenna to the EUT is 3 m. The normalized site attenuation of the semi-anechoic chamber is regularly calibrated to ensure the radiated disturbance test results are valid. During the test, the EUT was placed on a poly table, which is 0.8 m high. The wooden table was rotated 360° around and the antenna was varied from 1 m to 4 m to find the maximum disturbance. The test was performed with the antenna both in its horizontal and vertical polarizations.

The following figures and tables were those measured by an automatic measurement system. The final test was performed with peak detector and average detector at those critical frequencies during the preview test. In the following figure, “x(red)” means measurement results with peak detector and “+ (blue)” means measurement results with average detector.

Prüfbericht - Nr.: CN24P27P 001

Test Report No.:

Seite 23 von 31

Page 23 of 31

Notes on following tables of radiated emission results and conversions:


Peak (dB μ V/m): final measurement results by using peak detector

Average (dB μ V/m): final measurement results by using average detector

Corr. (dB): correction factor including: antenna factor, cable loss, and gain of pre-amplifier (if used)

Margin: Limit PK (dB μ V/m) - Peak (dB μ V/m)

Limit CAV (dB μ V/m) – Average (dB μ V/m)

Figure 9: Spectral Diagrams and measurement results, 1-18 GHz, horizontal polarization, mode 1

Final Peak measurement results:


Frequency (MHz)	MaxPeak (dBµ/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµ/m)
2261.718750	38.6	1000.000	100.0	H	180.0	-15.6	35.4	74.0
2399.843750	43.2	1000.000	100.0	H	180.0	-16.0	30.8	74.0
7238.468750	51.1	1000.000	100.0	H	180.0	-6.3	22.9	74.0
7383.500000	48.9	1000.000	100.0	H	180.0	-6.3	25.1	74.0
14367.843750	51.9	1000.000	100.0	H	180.0	2.3	22.1	74.0
17982.468750	58.7	1000.000	100.0	H	180.0	12.1	15.3	74.0

Final Average measurement results:

Frequency (MHz)	Average (dBµ/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµ/m)
2261.718750	23.6	1000.000	100.0	H	180.0	-15.6	30.4	54.0
2399.843750	22.0	1000.000	100.0	H	180.0	-16.0	32.0	54.0
7238.468750	32.9	1000.000	100.0	H	180.0	-6.3	21.1	54.0
7383.500000	32.5	1000.000	100.0	H	180.0	-6.3	21.5	54.0
14367.843750	39.3	1000.000	100.0	H	180.0	2.3	14.7	54.0
17982.468750	46.1	1000.000	100.0	H	180.0	12.1	8.0	54.0

Figure 10: Spectral Diagrams and measurement results, 1-18 GHz, vertical polarization, mode 1

Level [dBμV/m]




Final Peak measurement results:

Frequency (MHz)	MaxPeak (dBμV/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBμV/m)
1548.781250	33.6	1000.000	100.0	V	-180.0	-18.9	40.4	74.0
4885.562500	41.6	1000.000	100.0	V	-180.0	-11.3	32.4	74.0
8115.562500	47.4	1000.000	100.0	V	-180.0	-4.2	26.6	74.0
10532.750000	47.3	1000.000	100.0	V	-180.0	-2.3	26.7	74.0
14363.062500	51.4	1000.000	100.0	V	-180.0	2.3	22.6	74.0
17972.375000	59.5	1000.000	100.0	V	-180.0	11.9	14.5	74.0

Final Average measurement results:

Frequency (MHz)	Average (dBμV/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBμV/m)
1548.781250	20.8	1000.000	100.0	V	-180.0	-18.9	33.2	54.0
4885.562500	28.0	1000.000	100.0	V	-180.0	-11.3	26.0	54.0
8115.562500	34.5	1000.000	100.0	V	-180.0	-4.2	19.5	54.0
10532.750000	35.0	1000.000	100.0	V	-180.0	-2.3	19.0	54.0
14363.062500	39.2	1000.000	100.0	V	-180.0	2.3	14.8	54.0
17972.375000	46.5	1000.000	100.0	V	-180.0	11.9	7.6	54.0

Figure 11: Spectral Diagrams and measurement results, 1-18 GHz, horizontal polarization, mode 2



Final Peak measurement results:


Frequency (MHz)	MaxPeak (dBµ/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµ/m)
1426.593750	34.5	1000.000	100.0	H	-180.0	-18.6	39.5	74.0
5044.406250	40.2	1000.000	100.0	H	-180.0	-11.0	33.8	74.0
7147.625000	46.1	1000.000	100.0	H	-180.0	-5.5	27.9	74.0
8134.687500	47.4	1000.000	100.0	H	-180.0	-4.3	26.7	74.0
14388.031250	52.3	1000.000	100.0	H	-180.0	2.3	21.7	74.0
17973.968750	59.1	1000.000	100.0	H	-180.0	11.9	14.9	74.0

Final Average measurement results:

Frequency (MHz)	Average (dBµ/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµ/m)
1426.593750	21.5	1000.000	100.0	H	-180.0	-18.6	32.5	54.0
5044.406250	27.6	1000.000	100.0	H	-180.0	-11.0	26.4	54.0
7147.625000	33.2	1000.000	100.0	H	-180.0	-5.5	20.8	54.0
8134.687500	34.7	1000.000	100.0	H	-180.0	-4.3	19.3	54.0
14388.031250	39.1	1000.000	100.0	H	-180.0	2.3	14.9	54.0
17973.968750	46.5	1000.000	100.0	H	-180.0	11.9	7.5	54.0

Figure 12: Spectral Diagrams and measurement results, 1-18 GHz, vertical polarization, mode 2

Level [dB μ V/m]




Final Peak measurement results:

Frequency (MHz)	MaxPeak (dB μ V/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dB μ V/m)
1380.906250	35.0	1000.000	100.0	V	-180.0	-18.7	39.0	74.0
4749.031250	40.3	1000.000	100.0	V	-180.0	-11.5	33.7	74.0
7924.843750	48.0	1000.000	100.0	V	-180.0	-3.8	26.0	74.0
10346.812500	47.7	1000.000	100.0	V	-180.0	-2.7	26.3	74.0
14374.750000	51.6	1000.000	100.0	V	-180.0	2.3	22.4	74.0
17967.593750	58.1	1000.000	100.0	V	-180.0	11.8	15.9	74.0

Final Average measurement results:

Frequency (MHz)	Average (dB μ V/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dB μ V/m)
1380.906250	21.3	1000.000	100.0	V	-180.0	-18.7	32.7	54.0
4749.031250	27.1	1000.000	100.0	V	-180.0	-11.5	26.9	54.0
7924.843750	34.5	1000.000	100.0	V	-180.0	-3.8	19.5	54.0
10346.812500	35.2	1000.000	100.0	V	-180.0	-2.7	18.8	54.0
14374.750000	39.3	1000.000	100.0	V	-180.0	2.3	14.7	54.0
17967.593750	46.5	1000.000	100.0	V	-180.0	11.8	7.6	54.0

Figure 13: Spectral Diagrams and measurement results, 1-18 GHz, horizontal polarization, mode 3




Final Peak measurement results:

Frequency (MHz)	MaxPeak (dBµ/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµ/m)
1824.500000	34.1	1000.000	100.0	H	-180.0	-18.6	39.9	74.0
2465.718750	40.6	1000.000	100.0	H	-180.0	-16.2	33.4	74.0
7964.156250	47.8	1000.000	100.0	H	-180.0	-3.6	26.3	74.0
11389.125000	48.8	1000.000	100.0	H	-180.0	-2.4	25.2	74.0
14369.437500	51.7	1000.000	100.0	H	-180.0	2.3	22.3	74.0
17967.593750	59.0	1000.000	100.0	H	-180.0	11.8	15.0	74.0

Final Average measurement results:

Frequency (MHz)	Average (dBµ/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµ/m)
1824.500000	21.5	1000.000	100.0	H	-180.0	-18.6	32.5	54.0
2465.718750	25.5	1000.000	100.0	H	-180.0	-16.2	28.5	54.0
7964.156250	35.3	1000.000	100.0	H	-180.0	-3.6	18.7	54.0
11389.125000	35.9	1000.000	100.0	H	-180.0	-2.4	18.1	54.0
14369.437500	39.1	1000.000	100.0	H	-180.0	2.3	14.9	54.0
17967.593750	46.4	1000.000	100.0	H	-180.0	11.8	7.6	54.0

Figure 14: Spectral Diagrams and measurement results, 1-18 GHz, vertical polarization, mode 3

 Level [dB μ V/m]


Final Peak measurement results:

Frequency (MHz)	MaxPeak (dB μ V/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dB μ V/m)
1407.468750	38.9	1000.000	100.0	V	180.0	-18.7	35.1	74.0
2994.312500	41.9	1000.000	100.0	V	180.0	-15.1	32.2	74.0
5358.906250	42.5	1000.000	100.0	V	180.0	-11.6	31.5	74.0
7935.468750	47.7	1000.000	100.0	V	180.0	-3.7	26.3	74.0
14368.906250	52.3	1000.000	100.0	V	180.0	2.3	21.7	74.0
17970.781250	57.6	1000.000	100.0	V	180.0	11.9	16.5	74.0

Final Average measurement results:

Frequency (MHz)	Average (dB μ V/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dB μ V/m)
1407.468750	21.2	1000.000	100.0	V	180.0	-18.7	32.8	54.0
2994.312500	26.0	1000.000	100.0	V	180.0	-15.1	28.0	54.0
5358.906250	26.9	1000.000	100.0	V	180.0	-11.6	27.1	54.0
7935.468750	35.0	1000.000	100.0	V	180.0	-3.7	19.0	54.0
14368.906250	39.2	1000.000	100.0	V	180.0	2.3	14.8	54.0
17970.781250	46.5	1000.000	100.0	V	180.0	11.9	7.5	54.0

6 List of Test and Measurement Instruments

Equip.	Description	Model	Manufacturer	Last Date DD.MM.YYYY	Due Date DD.MM.YYYY
9061503	Shielded enclosure	10.055x3.605x3.000	Frankonia	08.11.2023	08.11.2028
9023229	EMI test receiver	ESR3	Rohde&Schwarz	03.08.2024	03.08.2025
G1830003	Artificial mains network	ENV432	Rohde&Schwarz	11.10.2024	11.10.2025
G1824248	Dual display multimeter	F45	Fluke	28.06.2024	28.06.2025
9062744	EMI measurement software	EMC32-E+(10.60.20)	Rohde&Schwarz	N/A	N/A
G1811378	3m semi-anechoic chamber	SAC3	Frankonia	03.12.2023	03.12.2026
G1811391	EMI test receiver	ESCI	Rohde&Schwarz	17.10.2024	17.10.2025
G1811425	Bilog antenna	CBL 6112D	Teseq	20.04.2023	20.04.2026
9062745	EMI measurement software	EMC32-MEB (10.60.20)	Rohde&Schwarz	N/A	N/A
9042162	EMI test receiver	ESR7	Rohde&Schwarz	05.02.2024	05.02.2025
9053499	Signal conditioning unit	SCU18F	Rohde & Schwarz	11.10.2024	11.10.2025
G1822702	Spectrum analyser	FSV40	Rohde&Schwarz	15.07.2024	15.07.2025
G1825371	Preamplifier	EMC051845SE	Taiwan EMCI	24.07.2024	24.07.2025
G1822694	Double ridged broadband horn antenna	BBHA 9120 D	Schwarzbeck	24.03.2021	24.03.2026

7 List of Figures

Figure 1: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, L.....	12
Figure 2: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, N	13
Figure 3: Spectral Diagrams and measurement results, horizontal polarization (30 MHz to 1 GHz), mode 1	16
Figure 4: Spectral Diagrams and measurement results, vertical polarization (30 MHz to 1 GHz), mode 1	17
Figure 5: Spectral Diagrams and measurement results, horizontal polarization (30 MHz to 1 GHz), mode 2	18
Figure 6: Spectral Diagrams and measurement results, vertical polarization (30 MHz to 1 GHz), mode 2	19
Figure 7: Spectral Diagrams and measurement results, horizontal polarization (30 MHz to 1 GHz), mode 3	20
Figure 8: Spectral Diagrams and measurement results, vertical polarization (30 MHz to 1 GHz), mode 3	21
Figure 9: Spectral Diagrams and measurement results, 1-18 GHz, horizontal polarization, mode 1.....	24
Figure 10: Spectral Diagrams and measurement results, 1-18 GHz, vertical polarization, mode 1	25
Figure 11: Spectral Diagrams and measurement results, 1-18 GHz, horizontal polarization, mode 2.....	26
Figure 12: Spectral Diagrams and measurement results, 1-18 GHz, vertical polarization, mode 2.....	27
Figure 13: Spectral Diagrams and measurement results, 1-18 GHz, horizontal polarization, mode 3.....	28
Figure 14: Spectral Diagrams and measurement results, 1-18 GHz, vertical polarization, mode 3.....	29

End of test report