

Prüfbericht-Nr.: Test report no.:	CN252QXJ 001	Auftrags-Nr.: Order no.:	326071880	Seite 1 von 53 Page 1 of 53
Kunden-Referenz-Nr.: Client reference no.:	1288983	Auftragsdatum: Order date:	2025-01-07	
Auftraggeber: Client:	IKEA of Sweden AB Box 702, SE-343 81 Älmhult, Sweden			
Prüfgegenstand: Test item:	SOLSKYDD Bluetooth speaker 45			
Bezeichnung / Typ-Nr.: Identification / Type no.:	E2506			
Auftrags-Inhalt: Order content:	Test Report			
Prüfgrundlage: Test specification:	FCC CFR47 Part 15, Subpart C Section 15.247 RSS-Gen Issue 5, Amendment 2, February 2021 RSS-247 Issue 3, August 2023 ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024+Errata to C63.10a-2024			
Wareneingangsdatum: Date of sample receipt:	2025-01-08	Refer to photo document.		
Prüfmuster-Nr.: Test sample no.:	A003905685-005~007			
Prüfzeitraum: Testing period:	2025-02-26 ~ 2025-05-21			
Ort der Prüfung: Place of testing:	TÜV Rheinland (Shanghai) Co., Ltd.			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shanghai) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:	<input checked="" type="checkbox"/> <u>Hongfei Wu</u>	genehmigt von: authorized by:	<input checked="" type="checkbox"/> <u>Yanli Fan</u>	
Datum: Date:	2025-09-01 <small>Signed by: Hongfei Wu</small>	Datum: Date:	2025-09-01 <small>Signed by: Yanli Fan</small>	
Stellung / Position:	Sachverständige(r)/Expert	Stellung / Position:	Sachverständige(r)/Expert	
Sonstiges / Other:	FCC ID: FHO-E2506 IC: 10912A-E2506 HVIN: E2506 PMN: SOLSKYDD Bluetooth speaker 45			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n)	F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
* Legend:	P(ass) = passed a.m. test specification(s)	F(ail) = failed a.m. test specification(s)	N/A = not applicable	N/T = not tested
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.: CN252QXJ 001
Test report no.:

Seite 2 von 53
Page 2 of 53

Anmerkungen
Remarks

<p>1</p>	<p>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfbedingungen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</p> <p><i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i></p>
<p>2</p>	<p>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature</p> <p><i>As contractually agreed, this document has been signed digitally only. TÜV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TÜV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i></p>
<p>3</p>	<p>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</p> <p><i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i></p>
<p>4</p>	<p>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezueglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</p> <p><i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i></p>

TEST SUMMARY

5.1.1 ANTENNA REQUIREMENT*RESULT: Pass***5.1.2 6dB & 99% BANDWIDTH***RESULT: Pass***5.1.3 OUTPUT POWER***RESULT: Pass***5.1.4 POWER SPECTRAL DENSITY***RESULT: Pass***5.1.5 CONDUCTED BAND EDGE AND OUT-OF BAND EMISSIONS***RESULT: Pass***5.2.1 CONDUCTED EMISSION***RESULT: Pass***5.3.1 RADIATED BAND-EDGE***RESULT: Pass***5.3.2 RADIATED SPURIOUS EMISSION***RESULT: Pass*

Contents

1.	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS	5
2.	TEST SITES	6
2.1	TEST FACILITIES	6
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS	7
2.3	TRACEABILITY	7
2.4	CALIBRATION	8
2.5	MEASUREMENT UNCERTAINTY	8
3.	GENERAL PRODUCT INFORMATION	9
3.1	PRODUCT FUNCTION AND INTENDED USE	9
3.2	RATINGS AND SYSTEM DETAILS	9
3.3	INDEPENDENT OPERATION MODES	10
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS	10
4.	TEST SET-UP AND OPERATION MODES	11
4.1	PRINCIPLE OF CONFIGURATION SELECTION	11
4.2	TEST OPERATION AND TEST SOFTWARE	11
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	11
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE	12
5.	TEST RESULTS	13
5.1	CONDUCTED TESTING AT ANTENNA PORT	13
5.1.1	<i>Antenna Requirement</i>	13
5.1.2	<i>6dB & 99% Bandwidth</i>	15
5.1.3	<i>Output Power</i>	23
5.1.4	<i>Power Spectral Density</i>	24
5.1.5	<i>Conducted Band Edge and out-of Band Emissions</i>	31
5.2	EMISSION IN THE FREQUENCY RANGE UP TO 30MHZ	36
5.2.1	<i>Conducted Emission</i>	36
5.3	EMISSION IN THE FREQUENCY RANGE ABOVE 30MHZ	39
5.3.1	<i>Radiated Band-Edge</i>	39
5.3.2	<i>Radiated Spurious Emission</i>	46
6.	LIST OF TABLES	53
7.	LIST OF FIGURES	53

1. General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Photographs of the Test Set-up

2. Test Sites

2.1 Test Facilities

TÜV Rheinland (Shanghai) Co., Ltd.

Workshop14, North Half of Workshop 10 and Workshop 16, Pingqian (Taicang) Modern Industrial Park, No.525, Yuewang Lingang South Road, Shaxi, Taicang, Jiangsu, China

The used test equipment is in accordance with CISPR 16 for measurement of radio interference.

The Federal Communications Commission has reviewed the technical characteristics of the radiated and conducted emission facility, and has found these test facilities to be in compliance with the requirements of section 2.948 of the FCC rules. The description of the test facility is listed under FCC registration number 930979.

The Innovation, Science and Economic Development Canada has reviewed the technical characteristics of the radiated and conducted emission facility, and has found these test facilities to be in compliance. The description of the test facility is listed under chambers filing number 33038.

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Equip.	Description	Model	Manufacturer	Due Date DD.MM.YYYY
EMC-C-196	Wireless connectivity tester	CMW270	Rohde & Schwarz	23.08.2025
EMC-C-302	Signal generator	SMB100B (6 GHz)	Rohde & Schwarz	10.12.2025
EMC-C-303	Vector Signal generator	SMW200A	Rohde & Schwarz	10.12.2025
EMC-C-304	OSP	OSP-B157W8	Rohde & Schwarz	10.12.2025
EMC-C-161	Spectrum analyser	FSV40	Rohde&Schwarz	15.07.2025
EMC-C-018	Double ridged horn antenna	BBHA 9120 D	Schwarzbeck	24.03.2026
EMC-C-066	EMI test receiver	ESCI	Rohde&Schwarz	27.10.2025
EMC-C-068	Broadband horn antenna	BBHA 9170	Schwarzbeck	18.06.2028
EMC-C-155	BiLog antenna	CBL 6112D	Teseq	24.03.2026
EMC-C-175	Preamplifier	EMC051845SE	EMCI Taiwan	24.07.2025
EMC-C-001	3 m semi-anechoic chamber	SAC3	Frankonia	03.12.2026
EMC-C-141	Shielded enclosure	10.055x3.605x3.000	Frankonia	08.11.2028
EMC-C-195	EMI test receiver	ESR3	Rohde&Schwarz	03.08.2025
EMC-C-190	Artificial mains network	ENV432	Rohde&Schwarz	11.10.2025
EMC-C-045	Dual display multimeter	F45	Fluke	28.06.2025
software				
EMC-S-036	RF measurement software	WMS32-WB (11.40.00)	Rohde&Schwarz	NA
EMC-S-032	EMI measurement software	EMC32-E+ (10.60.20)	Rohde&Schwarz	NA
EMC-S-028	EMI measurement software	EMC32-MEB (10.60.20)	Rohde&Schwarz	NA

2.3 Traceability

All measurement equipment calibrations are traceable to NIST or where calibration is performed outside the United States, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

Table 2: Measurement Uncertainty

Measurement Type	Frequency	Uncertainty
Antenna Port Conducted Emission	< 1GHz	±0.39dB
	> 1GHz	±0.68dB
Conducted Emission	150kHz - 30MHz	±2.33dB
Radiated Emission	9kHz - 30MHz	±2.93dB
	30MHz - 1GHz	±5.34dB
	> 1GHz	±5.40dB

3. General Product Information

3.1 Product Function and Intended Use

The EUT (Equipment Under Test) is a speaker and which support Bluetooth and 2.4GHz proprietary function.

The aim of this report is to evaluate RF character of 2.4 GHz proprietary of the EUT.

3.2 Ratings and System Details

Table 3: Technical Specification of EUT

General Description of EUT	
Product Name:	SOLSKYDD Bluetooth speaker 45
Model No.:	E2506
Operation Voltage:	AC 100~240V, 50-60Hz
Test Voltage:	DC 3.3V for RF conducted and radiated test AC 120V, 60Hz for conducted emission
RF Technical:	1) Bluetooth Classic 2) 2.4 GHz proprietary
Technical Specification of 2.4 GHz proprietary	
Frequency Range:	2402~2480MHz
Modulation Type:	GFSK
Data Rate:	1Mbps ,2Mbps
Equipment Type:	Non-FHSS
Antenna Type:	PCB Antenna
Antenna Gain:	1.5 dBi (declared by client)

Table 4: Operation Channel List

RF Channel	Frequency [MHz]						
00	2402	10	2422	20	2442	30	2462
01	2404	11	2424	21	2444	31	2464
02	2406	12	2426	22	2446	32	2466
03	2408	13	2428	23	2448	33	2468
04	2410	14	2430	24	2450	34	2470
05	2412	15	2432	25	2452	35	2472
06	2414	16	2434	26	2454	36	2474
07	2416	17	2436	27	2456	37	2476
08	2418	18	2438	28	2458	38	2478
09	2420	19	2440	29	2460	39	2480

3.3 Independent Operation Modes

Test frequencies are lowest channel: 2402 MHz, channel: 2404MHz, middle channel: 2440 MHz and highest channel: 2480 MHz

The basic operation modes are:

- A. 2.4 GHz proprietary transmitting mode
- B. Radio operating mode

3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured to measure its maximum power level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All testing were performed according to the procedures in ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024+Errata to C63.10a-2024.

Test Software: Telink BDT, V5.7.4

Table 5: Power parameter value

Mode	Frequency [MHz]	Power Parameter Setting Value
2.4 GHz proprietary	2402	2.0
	2404	8.2
	2440	8.2
	2480	8.2

4.3 Special Accessories and Auxiliary Equipment

Table 6: Special Accessories

Accessories	Parameter
RF Cable between the antenna port and test system	Cable loss: 0.5dB

Note: The RF cable used in the test was provided by

- Client
 Test Lab

And the cable loss has been factored in the related test.

Table 7: Auxiliary Equipment

Equipment	Manufacturer	Model
Laptop	Lenovo	21AJ-S57N0J

4.4 Countermeasures to achieve EMC Compliance

Null.

Prüfbericht - Nr.: CN252QXJ 001
Test Report No.**Seite 14 von 53**
Page 14 of 53**RSS-Gen 6.8 – Antenna Requirement**

Requirement: When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

Results:

a) Antenna Type:	PCB Antenna
b) Manufacture:	N/A
c) Model No.:	N/A
d) Gain with reference to an isotropic radiator:	1.5 dBi

Verdict: PASS

5.1.2 6dB & 99% Bandwidth

RESULT:**Pass**

Date of testing : 2025-04-16
Ambient temperature : 20.2°C
Relative humidity : 52.2%
Atmospheric pressure : 101kPa
Test requirement : FCC Part 15.247(a)(2)
RSS-247 Issue 3, August 2023, Clause 5.2(a)
RSS-Gen Issue 5, Amendment 2, February 2021, Clause
6.7
Test procedure : ANSI C63.10-2020+Cor. 1-2023+C63.10a-
2024+Errata to C63.10a-2024
Test voltage : DC 3.3V
Test modes applied : A


6dB Bandwidth (1Mbps,2402MHz)

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	0.534654	0.500000	---	2401.663366	2402.198020

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2402.000000	1.3	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40300 GHz	2.40300 GHz
Span	2.000 MHz	2.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 40
Sweeptime	18.938 μ s	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	12 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.01 dB	0.50 dB


6dB Bandwidth(1Mbps,2440MHz)

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2440.000000	0.534654	0.500000	---	2439.663366	2440.198020

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2440.000000	7.5	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43900 GHz	2.43900 GHz
Stop Frequency	2.44100 GHz	2.44100 GHz
Span	2.000 MHz	2.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 40
Sweeptime	18.938 μ s	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	12 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.05 dB	0.50 dB


6dB Bandwidth(1Mbps,2480MHz)

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	0.534654	0.500000	---	2479.663366	2480.198020

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2480.000000	7.7	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47900 GHz	2.47900 GHz
Stop Frequency	2.48100 GHz	2.48100 GHz
Span	2.000 MHz	2.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 40
Sweeptime	18.938 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	10 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.02 dB	0.50 dB


6dB Bandwidth (2Mbps,2402MHz)

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	0.910891	0.500000	---	2401.405941	2402.316832

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2402.000000	1.4	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40000 GHz	2.40000 GHz
Stop Frequency	2.40400 GHz	2.40400 GHz
Span	4.000 MHz	4.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 80
Sweeptime	18.938 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	10 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.00 dB	0.50 dB


6dB Bandwidth (2Mbps,2440MHz)

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2440.000000	0.910891	0.500000	---	2439.405941	2440.316832

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2440.000000	7.5	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43800 GHz	2.43800 GHz
Stop Frequency	2.44200 GHz	2.44200 GHz
Span	4.000 MHz	4.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 80
Sweeptime	18.938 μ s	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	21 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.04 dB	0.50 dB


6dB Bandwidth (2Mbps,2480MHz)

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	0.910891	0.500000	---	2479.405941	2480.316832







(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2480.000000	7.7	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47800 GHz	2.47800 GHz
Stop Frequency	2.48200 GHz	2.48200 GHz
Span	4.000 MHz	4.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 80
Sweeptime	18.938 μ s	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	14 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.13 dB	0.50 dB

99% Occupied Channel Bandwidth


5.1.4 Power Spectral Density


RESULT:**Pass**

Date of testing	:	2025-04-16
Ambient temperature	:	20.2°C
Relative humidity	:	52.2%
Atmospheric pressure	:	101kPa
Test requirement	:	FCC Part 15.247(e) RSS-247 Issue 3, August 2023, Clause 5.2(b)
Test procedure	:	ANSI C63.10-2020+Cor. 1-2023+C63.10a- 2024+Errata to C63.10a-2024
Test voltage	:	DC 3.3V
Test modes applied	:	A

Power Spectral Density (1Mbps, 2402MHz)

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2402.000000	2401.756900	0.115	8.0	PASS

Peak Power Spectral Density



— Limit — Sum Level ◆ PSD


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40160 GHz	2.40160 GHz
Stop Frequency	2.40240 GHz	2.40240 GHz
Span	801.981 kHz	801.981 kHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	160	~ 160
Sweeptime	1.070 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	3 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.14 dB	0.50 dB

Power Spectral Density(1Mbps, 2440MHz)

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2440.000000	2439.756900	6.278	8.0	PASS

Peak Power Spectral Density



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43960 GHz	2.43960 GHz
Stop Frequency	2.44040 GHz	2.44040 GHz
Span	801.981 kHz	801.981 kHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	160	~ 160
Sweeptime	1.070 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	3 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.25 dB	0.50 dB

Power Spectral Density(1Mbps, 2480MHz)

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2480.000000	2479.756900	6.468	8.0	PASS

Peak Power Spectral Density



— Limit
 — Sum Level
 ◆ PSD


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47960 GHz	2.47960 GHz
Stop Frequency	2.48040 GHz	2.48040 GHz
Span	801.981 kHz	801.981 kHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	160	~ 160
SweepTime	1.070 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	3 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.00 dB	0.50 dB

Power Spectral Density(2Mbps, 2402MHz)

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2402.000000	2401.509520	-4.247	8.0	PASS

Peak Power Spectral Density



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40132 GHz	2.40132 GHz
Stop Frequency	2.40268 GHz	2.40268 GHz
Span	1.366 MHz	1.366 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	273	~ 273
Sweeptime	1.370 ms	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	3 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.00 dB	0.50 dB

Power Spectral Density(2Mbps, 2440MHz)

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2440.000000	2439.509520	1.974	8.0	PASS

Peak Power Spectral Density



— Limit — Sum Level ◆ PSD


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43932 GHz	2.43932 GHz
Stop Frequency	2.44068 GHz	2.44068 GHz
Span	1.366 MHz	1.366 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	273	~ 273
SweepTime	1.370 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	4 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.10 dB	0.50 dB

Power Spectral Density(2Mbps, 2440MHz)

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2480.000000	2479.509520	2.146	8.0	PASS

Peak Power Spectral Density(2)



— Limit — Sum Level ◆ PSD


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47932 GHz	2.47932 GHz
Stop Frequency	2.48068 GHz	2.48068 GHz
Span	1.366 MHz	1.366 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	273	~ 273
Sweeptime	1.370 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	4 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.02 dB	0.50 dB

5.1.5 Conducted Band Edge and out-of Band Emissions

RESULT:**Pass**

Date of testing	:	2025-02-28~2025-05-21
Ambient temperature	:	20.2°C~20.4°C
Relative humidity	:	50.5%~52.2%
Atmospheric pressure	:	101kPa
Test requirement	:	FCC Part 15.247(d) RSS-247 Issue 3, August 2023, Clause 5.5
Test procedure	:	ANSI C63.10-2020+Cor. 1-2023+C63.10a- 2024+Errata to C63.10a-2024
Test voltage	:	DC 3.3V
Test modes applied	:	A

Figure 1: Reference level







Figure 2: Conducted Spurious Emission



Figure 3: Conducted Band Edge


5.2 Emission in the Frequency Range up to 30MHz


5.2.1 Conducted Emission

RESULT:**Pass**

Date of testing	:	2025-02-26
Ambient temperature	:	22.4°C
Relative humidity	:	50.0%
Atmospheric pressure	:	101kPa
Test requirement	:	FCC Part 15.207 (a) RSS-Gen Issue 5, Amendment 2, February 2021, Clause 8.8
Test procedure	:	KDB 558074 D01v05r02 ANSI C63.10-2020+Cor. 1-2023+C63.10a- 2024+Errata to C63.10a-2024
Test voltage	:	AC 120V, 60Hz
Test modes applied	:	B

Figure 4: Conducted Emission, L

Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.350250	46.78	---	58.96	12.18	1000.0	9.000	L1	10.3
0.352500	---	39.15	48.90	9.76	1000.0	9.000	L1	10.3
0.363750	---	35.35	48.64	13.29	1000.0	9.000	L1	10.3
0.363750	43.85	---	58.64	14.79	1000.0	9.000	L1	10.3
0.766500	35.13	---	56.00	20.87	1000.0	9.000	L1	10.4
1.020750	35.72	---	56.00	20.28	1000.0	9.000	L1	10.7
1.047750	---	28.73	46.00	17.27	1000.0	9.000	L1	10.7
1.351500	35.94	---	56.00	20.06	1000.0	9.000	L1	10.4
1.378500	---	28.96	46.00	17.04	1000.0	9.000	L1	10.4
1.684500	---	28.77	46.00	17.23	1000.0	9.000	L1	10.2
3.102000	38.73	---	56.00	17.27	1000.0	9.000	L1	10.2
3.210000	---	31.60	46.00	14.40	1000.0	9.000	L1	10.2

Figure 5: Conducted Emission, N

Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.352500	---	38.11	48.90	10.79	1000.0	9.000	N	10.4
0.352500	45.85	---	58.90	13.06	1000.0	9.000	N	10.4
0.363750	---	34.03	48.64	14.61	1000.0	9.000	N	10.4
0.363750	42.57	---	58.64	16.07	1000.0	9.000	N	10.4
0.764250	34.12	---	56.00	21.88	1000.0	9.000	N	10.4
1.018500	34.42	---	56.00	21.58	1000.0	9.000	N	10.4
1.376250	---	28.01	46.00	17.99	1000.0	9.000	N	10.4
1.707000	34.68	---	56.00	21.32	1000.0	9.000	N	10.5
1.986000	---	28.09	46.00	17.91	1000.0	9.000	N	10.5
2.904000	---	30.01	46.00	15.99	1000.0	9.000	N	10.6
3.102000	38.06	---	56.00	17.94	1000.0	9.000	N	10.6
3.210000	---	31.00	46.00	15.00	1000.0	9.000	N	10.6

5.3 Emission in the Frequency Range above 30MHz


5.3.1 Radiated Band-Edge

RESULT:**Pass**

Date of testing	:	2025-04-17
Ambient temperature	:	20.5°C
Relative humidity	:	52.7%
Atmospheric pressure	:	101kPa
Test requirement	:	FCC Part 15.247(d) FCC Part 15.205(a) FCC Part 15.209(a) RSS-Gen Issue 5, Amendment 2, February 2021, Clause 8.9 RSS-Gen Issue 5, Amendment 2, February 2021, Clause 8.10 RSS-247 Issue 3, August 2023, Clause 5.5
Test procedure	:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024+Errata to C63.10a-2024
Test voltage	:	DC 3.3V
Test modes applied	:	A

Figure 6: Radiated Band-Edge, 1Mbps, 2402MHz, H

XXY-2310~2410 BE 1-18GHz_HL050_FSV40_Pre-10-YUNFANG


Figure 7: Radiated Band-Edge, 1Mbps, 2402MHz, V

XXY-2310~2410 BE 1-18GHz_HL050_FSV40_Pre-10-YUNFANG





Figure 8: Radiated Band-Edge, 1Mbps, 2404MHz, H

 XXY-2310⁺ 2410 BE 1-18GHz_HL050_FSV40_Pre-10-YUNFANG

Figure 9: Radiated Band-Edge, 1Mbps, 2404MHz, V



 XXY-2310⁺ 2410 BE 1-18GHz_HL050_FSV40_Pre-10-YUNFANG


Figure 10: Radiated Band-Edge, 1Mbps, 2480MHz, H

XXY-2470 2500 BE_1-18GHz_HL050_FSV40_Pre-10-YUNFANG


Figure 11: Radiated Band-Edge, 1Mbps, 2480MHz, V

XXY-2470 2500 BE_1-18GHz_HL050_FSV40_Pre-10-YUNFANG





Figure 12: Radiated Band-Edge, 2Mbps, 2402MHz, H

XXY-2310~2410 BE 1-18GHz_HL050_FSV40_Pre-10-YUNFANG


Figure 13: Radiated Band-Edge, 2Mbps, 2402MHz, V

XXY-2310~2410 BE 1-18GHz_HL050_FSV40_Pre-10-YUNFANG





Figure 14: Radiated Band-Edge, 2Mbps, 2404MHz, H

XXY-2310~2410 BE 1-18GHz_HL050_FSV40_Pre-10-YUNFANG


Figure 15: Radiated Band-Edge, 2Mbps, 2404MHz, V

XXY-2310~2410 BE 1-18GHz_HL050_FSV40_Pre-10-YUNFANG






Figure 16: Radiated Band-Edge, 2Mbps, 2480MHz, H

XXY-2470 2500 BE_1-18GHz_HL050_FSV40_Pre-10-YUNFANG


Figure 17: Radiated Band-Edge, 2Mbps, 2480MHz, V

XXY-2470 2500 BE_1-18GHz_HL050_FSV40_Pre-10-YUNFANG




5.3.2 Radiated Spurious Emission

RESULT:**Pass**

Date of testing	:	2025-04-17
Ambient temperature	:	20.5°C
Relative humidity	:	52.7%
Atmospheric pressure	:	101kPa
Test requirement	:	FCC Part 15.247(d) FCC Part 15.209(a) RSS-Gen Issue 5, Amendment 2, February 2021, Clause 8.9 RSS-247 Issue 3, August 2023, Clause 5.5
Test procedure	:	ANSI C63.10-2020+Cor. 1-2023+C63.10a- 2024+Errata to C63.10a-2024
Test voltage	:	DC 3.3V
Test modes applied	:	A

Note:

For the frequency range from 18GHz to 25GHz, no emission was found.

Figure 18: Radiated Spurious Emission, 1Mbps, 2402MHz


Limit and Margin
QP


Frequency (MHz)	QuasiPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
30.606250	27.8	H	24.5	12.2	40.0
36.183750	25.1	H	21.9	14.9	40.0
47.945000	19.7	H	15.8	20.3	40.0
115.966250	21.8	H	18.8	21.7	43.5
315.786250	25.1	H	20.7	20.9	46.0
566.773750	30.1	H	26.5	15.9	46.0
33.273750	26.6	V	23.3	13.4	40.0
39.215000	23.5	V	20.2	16.5	40.0
43.943750	21.0	V	17.7	19.0	40.0
113.905000	21.8	V	18.8	21.7	43.5
548.343750	30.3	V	26.7	15.8	46.0
844.436250	33.2	V	28.9	12.8	46.0

PK

Frequency (MHz)	MaxPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµV/m)
1395.454546	36.3	H	-18.7	37.7	74.0
1864.545455	39.0	H	-18.4	35.0	74.0
4804.818182	42.3	H	-11.4	31.7	74.0
6921.727273	45.4	H	-7.4	28.6	74.0
11554.000000	49.1	H	-1.8	24.9	74.0
17976.281250	56.4	H	12.0	17.7	74.0
1054.818182	38.7	V	-20.1	35.3	74.0
2128.818182	43.9	V	-16.6	30.1	74.0
4804.818182	44.2	V	-11.4	29.8	74.0
6994.818182	45.3	V	-6.6	28.7	74.0
10350.531250	50.3	V	-2.7	23.7	74.0
17973.187500	56.8	V	11.9	17.2	74.0

AV

Frequency (MHz)	Average (dBµV/m)	Pol	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµV/m)
1395.454546	22.0	H	-18.7	32.0	54.0
1864.545455	21.5	H	-18.4	32.5	54.0
4804.818182	32.8	H	-11.4	21.2	54.0
6921.727273	31.4	H	-7.4	22.6	54.0
11554.000000	36.3	H	-1.8	17.7	54.0
17976.281250	46.8	H	12.0	7.2	54.0
1054.818182	24.2	V	-20.1	29.8	54.0
2128.818182	23.8	V	-16.6	30.2	54.0
4804.818182	30.8	V	-11.4	23.2	54.0
6994.818182	32.2	V	-6.6	21.8	54.0
10350.531250	35.7	V	-2.7	18.3	54.0
17973.187500	46.9	V	11.9	7.1	54.0

Figure 19: Radiated Spurious Emission, 1Mbps, 2440MHz


Limit and Margin
QP


Frequency (MHz)	QuasiPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
30.727500	27.8	H	24.5	12.2	40.0
45.035000	21.4	H	17.1	18.6	40.0
159.980000	25.4	H	16.9	18.1	43.5
300.387500	25.9	H	20.2	20.1	46.0
566.410000	30.2	H	26.5	15.8	46.0
896.937500	33.3	H	28.8	12.7	46.0
32.910000	26.7	V	23.5	13.3	40.0
38.608750	23.8	V	20.5	16.2	40.0
45.035000	20.3	V	17.1	19.7	40.0
118.633750	22.0	V	18.9	21.5	43.5
531.732500	29.3	V	25.8	16.7	46.0
860.926250	33.4	V	28.9	12.7	46.0

PK

Frequency (MHz)	MaxPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµV/m)
1464.454546	42.2	H	-18.7	31.8	74.0
2125.545455	41.1	H	-16.6	33.0	74.0
4880.909091	42.0	H	-11.3	32.0	74.0
6541.272727	44.2	H	-7.6	29.8	74.0
10357.406250	49.1	H	-2.7	24.9	74.0
17966.656250	57.9	H	11.8	16.1	74.0
1332.727273	45.8	V	-18.8	28.2	74.0
1994.636364	43.4	V	-17.8	30.6	74.0
4881.181818	44.7	V	-11.3	29.3	74.0
6367.272727	43.9	V	-8.5	30.1	74.0
7318.312500	48.2	V	-6.6	25.9	74.0
17982.125000	57.8	V	12.1	16.2	74.0

AV

Frequency (MHz)	Average (dBµV/m)	Pol	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµV/m)
1464.454546	21.3	H	-18.7	32.8	54.0
2125.545455	23.9	H	-16.6	30.1	54.0
4880.909091	32.6	H	-11.3	21.4	54.0
6541.272727	31.6	H	-7.6	22.4	54.0
10357.406250	35.7	H	-2.7	18.3	54.0
17966.656250	46.8	H	11.8	7.2	54.0
1332.727273	21.2	V	-18.8	32.8	54.0
1994.636364	23.0	V	-17.8	31.0	54.0
4881.181818	28.5	V	-11.3	25.5	54.0
6367.272727	30.3	V	-8.5	23.7	54.0
7318.312500	33.1	V	-6.6	20.9	54.0
17982.125000	46.6	V	12.1	7.4	54.0

Figure 20: Radiated Spurious Emission, 1Mbps, 2480MHz


Limit and Margin
QP

Frequency (MHz)	QuasiPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
30.848750	27.8	H	24.4	12.2	40.0
62.737500	17.4	H	12.7	22.6	40.0
123.362500	21.8	H	18.8	21.7	43.5
215.876250	19.0	H	16.0	24.5	43.5
591.993750	30.6	H	26.8	15.4	46.0
880.205000	33.3	H	28.7	12.7	46.0
39.457500	23.3	V	20.1	16.7	40.0
47.945000	19.1	V	15.8	20.9	40.0
257.222500	23.5	V	20.4	22.5	46.0
589.326250	30.5	V	26.7	15.5	46.0
934.161250	33.1	V	28.9	12.9	46.0

PK

Frequency (MHz)	MaxPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµV/m)
1465.000000	40.8	H	-18.7	33.2	74.0
2699.909091	39.2	H	-15.4	34.8	74.0
4959.181818	40.6	H	-11.2	33.5	74.0
6986.090909	45.3	H	-6.7	28.7	74.0
7949.781250	48.5	H	-3.7	25.5	74.0
17957.375000	56.4	H	11.6	17.6	74.0
1332.181818	43.2	V	-18.8	30.8	74.0
2228.363636	44.5	V	-15.7	29.5	74.0
2926.818182	45.4	V	-15.1	28.6	74.0
4959.181818	43.9	V	-11.2	30.1	74.0
7438.281250	49.0	V	-6.1	25.0	74.0
17966.312500	56.3	V	11.8	17.7	74.0

AV

Frequency (MHz)	Average (dBµV/m)	Pol	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµV/m)
1465.000000	21.2	H	-18.7	32.8	54.0
2699.909091	24.7	H	-15.4	29.3	54.0
4959.181818	28.2	H	-11.2	25.8	54.0
6986.090909	32.1	H	-6.7	21.9	54.0
7949.781250	35.5	H	-3.7	18.5	54.0
17957.375000	46.7	H	11.6	7.3	54.0
1332.181818	21.3	V	-18.8	32.7	54.0
2228.363636	24.1	V	-15.7	29.9	54.0
2926.818182	24.6	V	-15.1	29.4	54.0
4959.181818	27.6	V	-11.2	26.4	54.0
7438.281250	33.9	V	-6.1	20.1	54.0
17966.312500	46.8	V	11.8	7.2	54.0

6. List of Tables

Table 1: List of Test and Measurement Equipment.....	7
Table 2: Measurement Uncertainty.....	8
Table 3: Technical Specification of EUT.....	9
Table 4: Operation Channel List.....	10
Table 5: Power parameter value.....	11
Table 6: Special Accessories.....	11
Table 7: Auxiliary Equipment.....	11
Table 8: Antenna Requirement.....	13
Table 9: Peak Output Power.....	23

7. List of Figures

Figure 1: Reference level.....	32
Figure 2: Conducted Spurious Emission.....	34
Figure 3: Conducted Band Edge.....	35
Figure 4: Conducted Emission, L.....	37
Figure 5: Conducted Emission, N.....	38
Figure 6: Radiated Band-Edge, 1Mbps, 2402MHz, H.....	40
Figure 7: Radiated Band-Edge, 1Mbps, 2402MHz, V.....	40
Figure 8: Radiated Band-Edge, 1Mbps, 2404MHz, H.....	41
Figure 9: Radiated Band-Edge, 1Mbps, 2404MHz, V.....	41
Figure 10: Radiated Band-Edge, 1Mbps, 2480MHz, H.....	42
Figure 11: Radiated Band-Edge, 1Mbps, 2480MHz, V.....	42
Figure 12: Radiated Band-Edge, 2Mbps, 2402MHz, H.....	43
Figure 13: Radiated Band-Edge, 2Mbps, 2402MHz, V.....	43
Figure 14: Radiated Band-Edge, 2Mbps, 2404MHz, H.....	44
Figure 15: Radiated Band-Edge, 2Mbps, 2404MHz, V.....	44
Figure 16: Radiated Band-Edge, 2Mbps, 2480MHz, H.....	45
Figure 17: Radiated Band-Edge, 2Mbps, 2480MHz, V.....	45
Figure 18: Radiated Spurious Emission, 1Mbps, 2402MHz.....	47
Figure 19: Radiated Spurious Emission, 1Mbps, 2440MHz.....	49
Figure 20: Radiated Spurious Emission, 1Mbps, 2480MHz.....	51