

# IKEA of Sweden AB

## TEST REPORT

**SCOPE OF WORK**

EMC TESTING— LED1928G3

**REPORT NUMBER**

190920047GZU-001

**ISSUE DATE**

19 December 2019

**[REVISED DATE]**

[-----]

**PAGES**

16

**DOCUMENT CONTROL NUMBER**

FCC Part 15:2018-d

© 2017 INTERTEK



## TEST REPORT

Telephone: 86-20-8213 9688  
Facsimile: 86-20-3205 7538  
[www.intertek.com](http://www.intertek.com)

Applicant Name & : IKEA of Sweden AB  
Address : Box 702, 343 81 Älmhult, SWEDEN  
Manufacturing Site : Dongguan Kee Tat Lighting Limited  
Kai Shek Cheng, Dongguan City, 523000 Guangdong Province  
Intertek Report No: 190920047GZU-001

## Test standards

**CFR 47, FCC Part 15, Subpart B:2018**

## Sample Description

Product : Self-ballasted LED Lamp (Non-dimmable E12 LED lamp)  
Model No. : LED1928G3  
Electrical Rating : 120 V ~; 60 Hz; E12; 2.4 W; 35 mA  
Serial No. : Not Labeled  
Date Received : 20 September 2019  
Date Test : 20 September 2019 to 04 November 2019  
Conducted

Prepared and Checked By

Approved By:



Jed Guo

Engineer

Intertek Guangzhou



Helen Ma

Team Leader

Intertek Guangzhou

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**TEST REPORT**

**CONTENT**

**TEST REPORT ..... 1**

**CONTENT ..... 3**

**1. TEST RESULTS SUMMARY ..... 4**

**2. EMC RESULTS CONCLUSION..... 5**

**3. LABORATORY MEASUREMENTS..... 6**

**4. EQUIPMENT USED DURING TEST ..... 7**

**5. EMI TEST..... 8**

5.1 CONDUCTED DISTURBANCE VOLTAGE AT MAINS PORTS ..... 8

5.1.1 *Block Diagram of Test Setup*..... 8

5.1.2 *Test Setup and Procedure*..... 8

5.1.3 *Limit*..... 9

5.1.4 *Test Data and curve*..... 10

5.2 RADIATED EMISSION 30 MHz -1000 MHz..... 12

5.2.1 *Block Diagram of Test Setup*..... 12

5.2.2 *Test Setup and Procedure*..... 12

5.2.3 *Limit*..... 13

5.2.4 *Test Data and Curve* ..... 14

5.3 RADIATED EMISSION ABOVE 1 GHZ..... 15

**6. APPENDIX I - PHOTOS OF TEST SETUP ..... 16**

## TEST REPORT

### 1. TEST RESULTS SUMMARY

Classification of EUT: Class B

Test Item	Standard	Result
Conducted disturbance voltage at mains ports	CFR 47, FCC Part 15, Subpart B	Pass
Radiated emission (30 MHz–1 GHz)	CFR 47, FCC Part 15, Subpart B	Pass
Radiated emission (Above 1 GHz)	CFR 47, FCC Part 15, Subpart B	N/A
Remark: Reference publication is used for methods of measurement: ANSI C63.4:2014		

Remark:

1. The symbol "N/A" in above table means Not Applicable.
2. When determining the test results, measurement uncertainty of tests has been considered.

## TEST REPORT

### 2. EMC RESULTS CONCLUSION

RE: EMC Testing Pursuant to FCC part 15 performed on the Self-ballasted LED Lamp (Non-dimmable E12 LED lamp), Model: LED1928G3

We tested the Self-ballasted LED Lamp (Non-dimmable E12 LED lamp), Model: LED1928G3 to determine if it was in compliance with the relevant standards as marked on the Test Results Summary. We found that the unit met the requirement of FCC part 15 standard when tested as received. The worst case's test data was presented in this test report.

The production units are required to conform to the initial sample as received when the units are placed on the market.

## TEST REPORT

### 3. LABORATORY MEASUREMENTS

#### Configuration Information

Support Equipment: N/A

Rated Voltage and frequency under test: 120Vac, 60Hz  
 Condition of Environment: Temperature: 22~28°C  
 Relative Humidity:35~60%  
 Atmosphere Pressure:86~106kPa

#### Notes:

1. The EMI measurements had been made in the operating mode produced the largest emission in the frequency band being investigated consistent with normal applications. An attempt had been made to maximize the emission by varying the configuration of the EUT.

#### 2. Test Facility accreditation:

A2LA Certificate Number 0078.10

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch is accredited by A2LA and Listed in FCC website. FCC accredited test labs may perform both Certification testing under Parts 15 and 18 and Declaration of Conformity testing.

#### 3. Test Location:

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

All tests were performed at:

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD Guangzhou, China

Except Radiated Emissions was performed at:

Room102/104, No 203, KeZhu Road, Science City, GETDD Guangzhou, China

#### 4. Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Conduction Emission (9 kHz-150 kHz)	2.66 dB
2	Conduction Emission (150 kHz-30 MHz)	2.44 dB
3	Disturbance Power (30 MHz-300 MHz)	3.02 dB
4	Radiated Emission (30 MHz-1 GHz)	4.85 dB
5	Radiated Emission (1 GHz-6 GHz)	4.73 dB
6	Radiated Emission (6 GHz-18 GHz)	4.75 dB

The measurement uncertainty describes the overall uncertainty of the given measured value during the operation of the EUT.

Measurement uncertainty is calculated in accordance with CISPR16-4-2:2011

The measurement uncertainty is given with a confidence of 95%, k=2.

Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.

**TEST REPORT**

**4. EQUIPMENT USED DURING TEST**

**Conducted Disturbance-Mains Terminal (1)**

Equipment No.	Equipment	Model	Manufacturer	Calibration Interval
EM080-05	EMI receiver	ESCI	R&S	1Y
EM006-05	LISN	ENV216	R&S	1Y
SA047-112	Digital Temperature-Humidity Recorder	RS210	YIJIE	1Y
EM004-04	EMC shield Room	8m×3m×3m	Zhongyu	1Y

**Radiated Disturbance (30 MHz-1 GHz)**

Equipment No.	Equipment	Model	Manufacturer	Calibration Interval
EM030-04	3m Semi-Anechoic Chamber	9×6×6 m3	ETS-LINDGREN	1Y
EM031-02	EMI Test Receiver (9 kHz~7 GHz)	R&S ESR7	R&S	1Y
EM033-01	TRILOG Super Broadband test Antenna (30 MHz-3 GHz)	VULB 9163	SCHWARZBECK	1Y
EM031-02-01	Coaxial cable	/	R&S	1Y
EM036-01	Common-mode absorbing clamp	CMAD 20B	TESEQ	1Y
SA047-118	Digital Temperature-Humidity Recorder	RS210	YIJIE	1Y
EM045-01-01	EMC32 software (RE/RS)	V10.01.00	R&S	N/A

Detail of the equipment calibration due date:

Equipment No.	Cal. Due date (DD-MM-YYYY)
<b>Conducted Disturbance-Mains Terminal (1)</b>	
EM080-05	17/07/2020
EM006-05	16/06/2020
SA047-112	08/11/2020
EM004-04	13/01/2020

Equipment No.	Cal. Due date (DD-MM-YYYY)
<b>Radiated Disturbance (30 MHz-1 GHz)</b>	
EM030-04	9/04/2020
EM031-02	22/10/2020
EM033-01	19/09/2020
EM031-02-01	9/04/2020
EM036-01	21/07/2020
SA047-118	16/07/2020
EM045-01-01	N/A


## TEST REPORT

### 5. EMI TEST

#### 5.1 Conducted Disturbance Voltage at mains ports

Test Result: Pass

##### 5.1.1 Block Diagram of Test Setup



##### 5.1.2 Test Setup and Procedure

The EUT was set to achieve the maximum emission level. The mains terminal disturbance voltage was measured with the EUT in a shielded room. The EUT was connected to AC power source through an Artificial Mains Network which provides a 50Ω linear impedance Artificial hand is used if appropriate (for handheld apparatus). The load/control terminal disturbance voltage was measured with passive voltage probe if appropriate.

The table-top EUT was placed on a 0.8m high non-metallic table above earthed ground plane (Ground Reference Plane). And for floor standing EUT, was placed on a 0.1m high non-metallic supported on GRP. The EUT keeps a distance of at least 0.8m from any other of the metallic surface. The Artificial Mains Network is situated at a distance of 0.8m from the EUT. During the test, mains lead of EUT excess 0.8m was folded back and forth parallel to the lead so as to form a horizontal bundle with a length between 0.3m and 0.4m.

The bandwidth of test receiver was set at 9 kHz. The frequency range from 150 kHz to 30MHz was checked.

**TEST REPORT****5.1.3 Limit**

Frequency range MHz	AC mains terminals dB (uV)	
	Quasi-peak	Average
0.15 to 0.5	66 to 56*	56 to 46*
0.5 to 5	56	46
5 to 30	60	50

Note 1: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Note 2: The lower limit is applicable at the transition frequency.


**TEST REPORT**

**5.1.4 Test Data and curve**

**At mains terminal:**

**Tested Wire: Live**

**Operation Mode: lighting**



EDIT PEAK LIST (Final Measurement Results)					
TRACE		FREQUENCY	LEVEL dBµV		DELTA LIMIT dB
Trace1:	FCC15QP				
Trace2:	FCC15AV				
Trace3:	---				
1	Quasi Peak	186 kHz	58.48	L1	-5.72
2	Average	186 kHz	39.08	L1	-15.12
1	Quasi Peak	282 kHz	47.79	L1	-12.95
2	Average	374 kHz	28.29	L1	-20.11
1	Quasi Peak	470 kHz	40.59	L1	-15.91
2	Average	470 kHz	22.22	L1	-24.28
1	Quasi Peak	746 kHz	39.85	L1	-16.14
2	Average	1.026 MHz	22.08	L1	-23.91
1	Quasi Peak	1.314 MHz	34.04	L1	-21.95


Remark:

1. Corr. (dB) = LISN Factor (dB) + Cable Loss (dB)
2. Level (dBµV) = Corr. (dB) + Read Level (dBµV)
3. Delta Limit (dB) = Level (dBµV)-Limit (dBµV)

**TEST REPORT**

**Tested Wire: Neutral**

**Operation Mode: lighting**



EDIT PEAK LIST (Final Measurement Results)				
Trace1:	FCC15QP			
Trace2:	FCC15AV			
Trace3:	---			
TRACE	FREQUENCY	LEVEL dBµV	DELTA LIMIT dB	
1 Quasi Peak	182 kHz	59.70 L1	-4.68	
2 Average	182 kHz	42.53 L1	-11.86	
1 Quasi Peak	342 kHz	48.71 L1	-10.44	
2 Average	366 kHz	32.62 L1	-15.96	
1 Quasi Peak	462 kHz	47.33 L1	-9.32	
2 Average	462 kHz	28.42 L1	-18.22	
1 Quasi Peak	738 kHz	41.73 L1	-14.26	
2 Average	738 kHz	23.52 L1	-22.47	
1 Quasi Peak	1.29 MHz	37.65 L1	-18.34	
1 Quasi Peak	2.214 MHz	29.64 L1	-26.35	
1 Quasi Peak	4.062 MHz	29.08 L1	-26.91	

Remark:


1. Corr. (dB) = LISN Factor (dB) + Cable Loss (dB)
2. Level (dBµV) = Corr. (dB) + Read Level (dBµV)
3. Delta Limit (dB) = Level (dBµV)-Limit (dBµV)

## TEST REPORT

### 5.2 Radiated Emission 30 MHz -1000 MHz

Test Result: Pass

#### 5.2.1 Block Diagram of Test Setup



#### 5.2.2 Test Setup and Procedure

The measurement was applied in a semi-anechoic chamber. The EUT and simulators were placed on a 0.8 m high wooden turntable above the horizontal metal ground plane. The turn table rotated 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna which was mounted on an antenna mask. The antenna moved up and down between from 1 meter to 4 meters to find out the maximum emission level.

Broadband antenna was used as receiving antenna. Both horizontal and vertical polarization of the antenna was set on measurement. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4 requirement during radiated test.

The bandwidth setting on R&S Test Receiver was 120 kHz.

## TEST REPORT

For an unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a radiated emission limit is specified, up to the frequency shown in the following table:

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper Frequency of Radiated Measurement
Below 1.705 MHz	30MHz
1.705 MHz – 108 MHz	1 GHz
108 MHz – 500 MHz	2 GHz
500 MHz – 1 GHz	5 GHz
Above 1 GHz	5th harmonic of the highest frequency or 40 GHz, whichever is lower.
At transitional frequencies the lower limit applies.	

Remark: Radiated Emission was performed from 30 MHz to 1 GHz.

### 5.2.3 Limit


Class B limit at 3m test distance:

Frequency range MHz	Quasi-peak limits dB ( $\mu$ V/m)
30 to 88	40
88 to 216	43.5
216 to 960	46
960 to 1000	54
At transitional frequencies the lower limit applies.	

## TEST REPORT


### 5.2.4 Test Data and Curve

Operation Mode: EUT on lighting  
Horizontal



All emission levels are more than 6 dB below the limit.

Vertical



All emission levels are more than 6 dB below the limit.

## TEST REPORT

### 5.3 Radiated Emission above 1 GHz

**Test Result: Not Applicable**

**Remark:**

The highest internal source of the EUT is not more than 108 MHz, so the measurement above 1000 MHz is not applicable.

**TEST REPORT**

**6. APPENDIX I - PHOTOS OF TEST SETUP**

Test set up and EUT photos are put in 190920047GZU-001 Annex 1 separately as part of this test report.

\*\*\*\*\*End of Report\*\*\*\*\*