

# Label artwork

FCC ID: FHO-V2401

 Input: 5V DC, Max 3W  
Battery input: 3.6V DC (3x AA HR6), 1.8W  
Conforms to: UL Std 2108 and UL Std 962 Certified to: CSA  
Std C22.2 No.9.0-96 CAN ICES-005 (B) / NMB-005 (B)  
This device complies with Part 15 of the FCC Rules.  
Operation is subject to the following two conditions: (1) this  
device may not cause harmful interference, and (2) this  
device must accept any interference received, including  
interference that may cause undesired operation.  
Caution - Replace battery with IKEA LADDA type HR6 AA  
1.2V 2450mAh only. For use with Class 2 IKEA listed power  
supply with output 5V DC, min 1A  
ATTENTION - Uniquement remplacer les piles par des piles  
IKEA LADDA HR6 AA 1,2V 2450mAh.  
Utilisé avec un boîtier d'alimentation IKEA Classe 2 avec  
sortie de 5V DC, min. 1A.

c  u s

TYPE: V2401  
EKFÄNN  
Made in China

17796  


## Warning text:

SUITABLE FOR DAMP LOCATIONS  
CONVIENT AUX EMPLACEMENTS SECS HUMIDES  
ADECUADO PARA LUGARES HÚMEDOS

WALL MOUNT ONLY  
INSTALLATION MURALE SEULEMENT  
SÓLO MONTAJE EN PARED

## Label location for V2401

