

Michelin eTire™ Hand-Held-Reader Model # HHR1.0

Users Manual

(The user manual is in preparation. The following information will be contained in the final manual)

Compliance

Michelin *eTire*[™]

Model: HHR1.0

FCC ID: FI5-HHR10

IC: 5056A-HHR10

This device complies with part 15 of the FCC Rules and with RSS-210 of Industry Canada. Operation is subject to the following 2 conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operations.

NOTE: This equipment has been tested and found to be compliant with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

IMPORTANT

NOTE: This apparatus must not be modified in any way that causes its radio frequency performance to change from that established by the product in its original manufactured form. The antennas are a fixed part of the equipment and should not be tampered with. Failure to comply with these requirements may void the Product Warranty, as well as expose the end user to legal and/or financial liabilities. The device and its antenna must not be co-located or operating in conjunction with any other antenna or transmitter.

Any changes or modifications of equipment not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

WARNING

In order to comply with FCC RF exposure requirements, this device must be operated such that a minimum separation distance of 20 cm is maintained between the antenna and all persons during normal operation.