

FCC Test Report

FCC Part 15 Subpart C §15.247

Product Name : GSM MOBILE PHONE

Model No. : L700

FCC ID : FOCGC661838

Prepared By : Inventec Appliances(Pudong) Corporation

Address: : No.789 Pu Xing Road,Shanghai,PRC

Date of Receipt : 2012.03.28

Date of Test : 2012.03.28-2012.04.04

Report No. : 20120328FCC-B



Test Report Certification


Date of Issue : Mar.28.2012

Report No. : 20120328FCC-B

Product Name : GSM MOBILE PHONE
Model No. : L700
Trade Name : JZH-Mobile
Applicant : JZH-Mobile Communication technology Co., LTD
Address : 1302,A block, Haisong Building, Chegongmiao, Futian District, Shenzhen City, China.
Standard : FCC Part 15 Subpart C §15.247
Classification : Bluetooth: Digital Transmission System (DTS)
TX/RX Frequency Range : Bluetooth (2400 MHz ~ 2483.5 MHz)
Test Result : Complied

The Test Results relate only to the samples tested.
The test report shall not be reproduced except in full without the written approval of
IAC regulatory Laboratory

Documented By :  APR. 05.2012
Kelly Lin/Engineer

Tested By :  APR. 05.2012
Byran Hung/Senior Engineer

Approved By :  APR. 05.2012
Jeff Huang/Director of Operations

TABLE OF CONTENTS

| Description | Page |
|--|------|
| 1. GENERAL INFORMATION | 5 |
| 1.1 Applicant | 5 |
| 1.2 Manufacturer | 5 |
| 1.3 Feature of Equipment Under Test..... | 6 |
| 1.4 Applied Standards | 7 |
| 2. Test Configuration of Equipment Under Test..... | 8 |
| 2.1 RF Power | 8 |
| 2.2 Test Modes..... | 9 |
| 2.3 Connection Diagram of Test System | 10 |
| 3. Test Result | 12 |
| 3.1 Number of Channel Measurement..... | 12 |
| 3.2 20dB and 99% Bandwidth Measurement | 16 |
| 3.3 Hopping Channel Separation Measurement..... | 29 |
| 3.4 Dwell Time Measurement..... | 36 |
| 3.5 Peak Output Power Measurement..... | 49 |
| 3.6 Band Edges Measurement | 52 |
| 3.7 Spurious Emission Measurement..... | 58 |
| 3.8 AC Conducted Emission Measurement..... | 62 |
| 3.9 Radiated Emission Measurement | 66 |
| 3.10 Antenna Requirements | 77 |
| 4 List of Measuring Equipment..... | 78 |
| 5 Uncertainty Evaluation..... | 78 |

SUMMARY OF TEST RESULT

| Report Section | FCC Rule | IC Rule | Description | Limit | Result | Remark |
|----------------|----------------------|-----------|-----------------------|---|--------|--------|
| 4.1 | 15.247(a)(1) | A8.4(2) | Number of Channels | $\geq 15\text{Chs}$ | Pass | - |
| 4.2 | 15.247(a)(1) | A8.1(a) | 20dB Bandwidth | NA | Pass | - |
| 4.2 | - | Gen 4.4.1 | 99% Bandwidth | - | Pass | - |
| 4.3 | 15.247(a)(1) | A8.1(b) | Channel Separation | $\geq 2/3$ of 20dB BW | Pass | - |
| 4.4 | 15.247(a)(1) | A8.1(d) | Dwell Time of Each | $\leq 0.4\text{sec}$ in | Pass | - |
| | | | Channel | 31.6sec period | | |
| 4.5 | 15.247(b)(1) | A8.1(b) | Peak Output Power | $\leq 1\text{W}$ | Pass | - |
| 4.6 | 15.247(d) | A8.5 | Frequency Band Edges | $\leq 20\text{dBc}$ | Pass | - |
| 4.7 | 15.247(d) | A8.5 | Spurious Emission | $< 20\text{ dBc}$ | Pass | - |
| 4.8 | 15.207 | Gen 7.2.2 | AC Conducted Emission | Section 15.207(a) | Pass | - |
| 4.9 | 15.247(d) | A8.5 | Radiated Emission | FCC 47 CFR Part 15 Subpart C/ Section 15.209(a) &15.247(d) | Pass | - |
| 4.10 | 15.203 &15.247(b) | A8.4 | Antenna Requirement | N/A | Pass | - |

1. GENERAL INFORMATION**1.1 Applicant**

Company Name: JZH-Mobile Communication technology Co., LTD

Address: 1302,A block, Haisong Building, Chegongmiao, Futian District, Shenzhen City, China.

1.2 Manufacturer

Company Name: JZH-Mobile Communication technology Co., LTD

Address: 1302,A block, Haisong Building, Chegongmiao, Futian District, Shenzhen City, China.

1.3 Feature of Equipment Under Test

| Product Feature & Specification | |
|--|--|
| Equipment | GSM MOBILE PHONE |
| Brand Name | L700 |
| Model Name | JZH-Mobile |
| FCC ID | FOCGC661838 |
| Tx/Rx Frequency Range | Bluetooth (2400 MHz ~ 2483.5 MHz) |
| Number of Channels | BT : CH00 CH39 CH78 |
| Carrier Frequency of Each Channel | BT : 2402MHz 2441MHz 2480MHz |
| Channel Spacing | BT : 1MHz |
| Maximum Output Power to Antenna | BT : 11.13 (dBm) |
| Antenna Type | Monopole Antenna |
| HW Version | B085-MB-V0.1 |
| SW Version | B085-1D-ENTEL _L97 _V114 |
| Type of Modulation | BT(1Mbps):GFSK BT EDR(2Mbps):π /4-DQPSK BT EDR(3Mbps):8-DPSK |

Remark:

1. For other wireless features of this EUT, test report will be issued separately.
2. This test report recorded only product characteristics and test results of Digital Transmission System (DTS)
3. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description

1.4 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC Public Notice DA 00-705
- ANSI C63.4-2003

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2. Test Configuration of Equipment Under Test

2.1 RF Power

Preliminary tests were performed in different data rate and recorded the RF Output Power in the following table:

| Channel | Frequency | Bluetooth RF Output Power (dBm) | | |
|---------|-----------|---------------------------------|----------------|--------|
| | | Data Rate / Modulation | | |
| | | GFSK | $\pi/4$ -DQPSK | 8-DPSK |
| | | 1Mbps | 2Mbps | 3Mbps |
| Ch00 | 2402MHz | 11.13 | 11.11 | 11.10 |
| Ch39 | 2441MHz | 10.63 | 10.64 | 10.66 |
| Ch78 | 2480MHz | 9.56 | 9.56 | 9.57 |

Remark:

The EUT is programmed to transmit signal continuously for all testing.

2.2 Test Modes

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz), radiated emission (30MHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).


Pre-scanned tests were conducted to determine the final configuration from all possible combinations.

The following tables are showing the test modes as the worst cases and recorded in this report.


| Test Cases | | | |
|-----------------------|---|---|--|
| Test Item | Data Rate / Modulation | | |
| | Bluetooth 1Mbps GFSK | Bluetooth EDR 2Mbps $\pi/4$ -DQPSK | Bluetooth EDR 3Mbps 8-DPSK |
| Conducted TCs | Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz | Mode 4: CH00_2402 MHz Mode 5: CH39_2441 MHz Mode 6: CH78_2480 MHz | Mode 7: CH00_2402 MHz Mode 8: CH39_2441 MHz Mode 9: CH78_2480 MHz |
| Radiated TCs | N/A | N/A | Mode 1: CH00_2402 MHz + Battery Mode 2: CH39_2441 MHz + Battery Mode 3: CH78_2480 MHz + Battery |
| AC Conducted Emission | Mode 1 : GSM 850 Idle + Bluetooth Link + Adapter + Battery + Earphone Mode 2 : GSM 1900 Idle + Bluetooth Link + Adapter + Battery + Earphone | | |


2.3 Connection Diagram of Test System

30MHz~1GHz



Above 1GHz



<Conduction Test>

3. Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The modulation types of EUT are irrelevant to number of hopping channels deviation.
4. The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
Span = the frequency band of operation; RBW \geq 1% of the span; VBW \geq RBW; Sweep = auto;
Detector function = peak; Trace = max hold.
5. The number of hopping frequency used is defined as the device has the numbers of total channel.

3.1.4 Test Setup




3.1.5 Test Result of Number of Hopping Frequency

| | | | |
|------------------------|----------|----------------------------|-----------|
| Test Mode : | Mode 1~3 | Temperature : | 23°C~26°C |
| Test Engineer : | Hogan He | Relative Humidity : | 40%~60% |

| Number of Hopping Channels (Channel) | Limits (Channel) | Pass/Fail |
|---|---------------------|-----------|
| 79 | > 15 | Pass |


Number of Hopping Channel Plot on Channel 00 - 78



Date: 29.MAR.2012 02:26:32

| | | | |
|-----------------|----------|---------------------|-----------|
| Test Mode : | Mode 4~6 | Temperature : | 23°C~26°C |
| Test Engineer : | Hogan He | Relative Humidity : | 40%~60% |

| Number of Hopping Channels (Channel) | Limits (Channel) | Pass/Fail |
|---|---------------------|-----------|
| 79 | > 15 | Pass |


Number of Hopping Channel Plot on Channel 00 - 78

Date: 29.MAR.2012 02:39:21

| | | | |
|-----------------|----------|---------------------|-----------|
| Test Mode : | Mode 7~9 | Temperature : | 23°C~26°C |
| Test Engineer : | Hogan He | Relative Humidity : | 40%~60% |

| Number of Hopping Channels (Channel) | Limits (Channel) | Pass/Fail |
|---|---------------------|-----------|
| 79 | > 15 | Pass |

Number of Hopping Channel Plot on Channel 00 - 78



Date: 29.MAR.2012 03:06:53

3.2 20dB and 99% Bandwidth Measurement

3.2.1 Limit of 20dB Bandwidth

N/A


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. Use the following spectrum analyzer settings:
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel;
RBW \geq 1% of the 20 dB bandwidth; VBW \geq RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

3.2.4 Test Setup




3.2.5 Test Result of 20dB Bandwidth

| | | | |
|------------------------|------------|----------------------------|-----------|
| Test Mode : | Mode 1,2,3 | Temperature : | 23°C~26°C |
| Test Engineer : | Hogan He | Relative Humidity : | 40%~60% |


| Channel | Frequency (MHz) | 20dB Bandwidth (MHz) |
|---------|-----------------|----------------------|
| 00 | 2402 | 0.756 |
| 39 | 2441 | 0.756 |
| 78 | 2480 | 0.756 |

20 dB Bandwidth Plot on Channel 00




Date: 29.MAR.2012 03:34:15

20 dB Bandwidth Plot on Channel 39



Date: 29.MAR.2012 03:35:18

20 dB Bandwidth Plot on Channel 78




Date: 29.MAR.2012 03:36:05

| | | | |
|------------------------|------------|----------------------------|-----------|
| Test Mode : | Mode 4,5,6 | Temperature : | 23°C~26°C |
| Test Engineer : | Hogan He | Relative Humidity : | 40%~60% |


| Channel | Frequency (MHz) | 20dB Bandwidth (MHz) |
|---------|-----------------|----------------------|
| 00 | 2402 | 0.969 |
| 39 | 2441 | 0.972 |
| 78 | 2480 | 1.125 |

20 dB Bandwidth Plot on Channel 00




Date: 29.MAR.2012 03:42:39

20 dB Bandwidth Plot on Channel 39



Date: 12.MAR.2012 03:41:56

20 dB Bandwidth Plot on Channel 78




Date: 29.MAR.2012 03:40:45


| | | | |
|------------------------|------------|----------------------------|-----------|
| Test Mode : | Mode 7,8,9 | Temperature : | 23°C~26°C |
| Test Engineer : | Hogan He | Relative Humidity : | 40%~60% |

| Channel | Frequency (MHz) | 20dB Bandwidth (MHz) |
|---------|-----------------|----------------------|
| 00 | 2402 | 1.170 |
| 39 | 2441 | 1.173 |
| 78 | 2480 | 1.173 |


20 dB Bandwidth Plot on Channel 00



Date: 29.MAR.2012 03:43:25

20 dB Bandwidth Plot on Channel 39

Date: 29.MAR.2012 03:50:47

20 dB Bandwidth Plot on Channel 78


Date: 29.MAR.2012 03:51:41

3.2.6 Test Result of 99% Occupied Bandwidth


| | | | |
|------------------------|------------|----------------------------|-----------|
| Test Mode : | Mode 1,2,3 | Temperature : | 23°C~26°C |
| Test Engineer : | Hogan He | Relative Humidity : | 40%~60% |

| Channel | Frequency (MHz) | 99% Occupied Bandwidth (MHz) |
|---------|-----------------|------------------------------|
| 00 | 2402 | 0.825 |
| 39 | 2441 | 0.825 |
| 78 | 2480 | 0.825 |


99% Bandwidth Plot on Channel 00



Date: 29.MAR.2012 03:59:48

99% Occupied Bandwidth Plot on Channel 39


Date: 29.MAR.2012 03:58:56

99% Occupied Bandwidth Plot on Channel 78


Date: 29.MAR.2012 03:58:21

| | | | |
|-----------------|------------|---------------------|-----------|
| Test Mode : | Mode 4,5,6 | Temperature : | 23°C~26°C |
| Test Engineer : | Hogan He | Relative Humidity : | 40%~60% |


| Channel | Frequency (MHz) | 99% Occupied Bandwidth (MHz) |
|---------|-----------------|------------------------------|
| 00 | 2402 | 1.062 |
| 39 | 2441 | 1.062 |
| 78 | 2480 | 1.062 |

99% Bandwidth Plot on Channel 00

Date: 29.MAR.2012 03:55:21

99% Occupied Bandwidth Plot on Channel 39

Date: 29.MAR.2012 03:55:57

99% Occupied Bandwidth Plot on Channel 78


Date: 29.MAR.2012 03:56:46

| | | | |
|------------------------|------------|----------------------------|-----------|
| Test Mode : | Mode 7,8,9 | Temperature : | 23°C~26°C |
| Test Engineer : | Hogan He | Relative Humidity : | 40%~60% |


| Channel | Frequency (MHz) | 99% Occupied Bandwidth (MHz) |
|---------|-----------------|------------------------------|
| 00 | 2402 | 1.107 |
| 39 | 2441 | 1.107 |
| 78 | 2480 | 1.107 |

99% Bandwidth Plot on Channel 00

Date: 29.MAR.2012 03:54:35

99% Occupied Bandwidth Plot on Channel 39

Date: 29.MAR.2012 03:53:59

99% Occupied Bandwidth Plot on Channel 78

Date: 29.MAR.2012 03:53:23

3.3 Hopping Channel Separation Measurement

3.3.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. Please refer FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels; RBW \geq 1% of the span;
VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold.
5. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

3.3.4 Test Setup




3.3.5 Test Result of Hopping Channel Separation

| | | | |
|-----------------|------------|---------------------|-----------|
| Test Mode : | Mode 1,2,3 | Temperature : | 23°C~26°C |
| Test Engineer : | Hogan He | Relative Humidity : | 40%~60% |


| Channel | Frequency (MHz) | Frequency Separation (MHz) | (2/3 of 20dB BW) Limits (MHz) | Pass/Fail |
|---------|-----------------|----------------------------|-------------------------------|-----------|
| 00 | 2402 | 1.012 | 0.504 | Pass |
| 39 | 2441 | 1.000 | 0.504 | Pass |
| 78 | 2480 | 1.000 | 0.504 | Pass |

Channel Separation Plot on Channel 00 - 01




Date: 29.MAR.2012 04:19:25

Channel Separation Plot on Channel 39 - 40



Date: 29.MAR.2012 04:26:48

Channel Separation Plot on Channel 77 - 78




Date: 29.MAR.2012 05:38:58


| | | | |
|------------------------|------------|----------------------------|---------|
| Test Mode : | Mode 4,5,6 | Temperature : | 23℃~26℃ |
| Test Engineer : | Hogan He | Relative Humidity : | 40%~60% |

| Channel | Frequency (MHz) | Frequency Separation (MHz) | (2/3 of 20dB BW) Limits (MHz) | Pass/Fail |
|---------|-----------------|----------------------------|-------------------------------|-----------|
| 00 | 2402 | 1.004 | 0.646 | Pass |
| 39 | 2441 | 1.004 | 0.648 | Pass |
| 78 | 2480 | 1.004 | 0.750 | Pass |


Channel Separation Plot on Channel 00 - 01



Date: 29.MAR.2012 06:05:00

Channel Separation Plot on Channel 39 - 40

Date: 29.MAR.2012 05:56:40


Channel Separation Plot on Channel 77 - 78

Date: 29.MAR.2012 05:48:13


| | | | |
|------------------------|------------|----------------------------|-----------|
| Test Mode : | Mode 7,8,9 | Temperature : | 23°C~26°C |
| Test Engineer : | Hogan He | Relative Humidity : | 40%~60% |

| Channel | Frequency (MHz) | Frequency Separation (MHz) | (2/3 of 20dB BW) Limits (MHz) | Pass/Fail |
|---------|-----------------|----------------------------|-------------------------------|-----------|
| 00 | 2402 | 1.004 | 0.780 | Pass |
| 39 | 2441 | 1.004 | 0.782 | Pass |
| 78 | 2480 | 1.000 | 0.782 | Pass |

Channel Separation Plot on Channel 00 - 01




Channel Separation Plot on Channel 39 - 40



Date: 29.MAR.2012 07:23:14

Channel Separation Plot on Channel 77 - 78



Date: 29.MAR.2012 07:32:10

3.4 Dwell Time Measurement

3.4.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedure

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW \geq RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
5. Use the marker-delta function to calculate the dwell time.

3.4.4 Test Setup



3.4.5 Test Result of Dwell Time



| | | | |
|------------------------|----------|----------------------------|-----------|
| Test Mode : | Mode 2 | Temperature : | 23°C~26°C |
| Test Engineer : | Hogan He | Relative Humidity : | 40%~60% |



| Package Mode | Average Hopping Channel | Package Transfer Time (usec) | Dwell Time (sec) | Limits (sec) | Pass/Fail |
|---------------------|--------------------------------|-------------------------------------|-------------------------|---------------------|------------------|
| DH1 | 10.1 | 404 | 0.129 | 0.4 | Pass |
| DH3 | 5.1 | 1684 | 0.269 | 0.4 | Pass |
| DH5 | 3.4 | 2954 | 0.315 | 0.4 | Pass |



Remark:

1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
2. 79 channels come from the Hopping Channel number.
3. Average Hopping Channel = hops/sweep time
4. t: Package Transfer Time(us)

GFSK:

DH1 Dwell Time (One Pulse) Plot on Channel 39**DH1 Dwell Time (Count Pulses) Plot on Channel 39**

DH3 Dwell Time (One Pulse) Plot on Channel 39**DH3 Dwell Time (Count Pulses) Plot on Channel 39**



DH5 Dwell Time (One Pulse) Plot on Channel 39**DH5 Dwell Time (Count Pulses) Plot on Channel 39**



| | | | |
|------------------------|----------|----------------------------|-----------|
| Test Mode : | Mode 5 | Temperature : | 23°C~26°C |
| Test Engineer : | Hogan He | Relative Humidity : | 40%~60% |



| Package Mode | Average Hopping Channel | Package Transfer Time (usec) | Dwell Time (sec) | Limits (sec) | Pass/Fail |
|---------------------|--------------------------------|-------------------------------------|-------------------------|---------------------|------------------|
| 2DH1 | 10.1 | 420 | 0.134 | 0.4 | Pass |
| 2DH3 | 5.1 | 1704 | 0.273 | 0.4 | Pass |
| 2DH5 | 3.4 | 2974 | 0.317 | 0.4 | Pass |

Remark:

5. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
6. 79 channels come from the Hopping Channel number.
7. Average Hopping Channel = hops/sweep time
8. t: Package Transfer Time(us)

$\pi/4$ -DQPSK**2DH1 Dwell Time (One Pulse) Plot on Channel 39****2DH1 Dwell Time (Count Pulses) Plot on Channel 39**

2DH3 Dwell Time (One Pulse) Plot on Channel 39**2DH3 Dwell Time (Count Pulses) Plot on Channel 39**

2DH5 Dwell Time (One Pulse) Plot on Channel 39**2DH5 Dwell Time (Count Pulses) Plot on Channel 39**

| | | | |
|------------------------|----------|----------------------------|-----------|
| Test Mode : | Mode 8 | Temperature : | 23°C~26°C |
| Test Engineer : | Hogan He | Relative Humidity : | 40%~60% |


| Package Mode | Average Hopping Channel | Package Transfer Time (usec) | Dwell Time (sec) | Limits (sec) | Pass/Fail |
|---------------------|--------------------------------|-------------------------------------|-------------------------|---------------------|------------------|
| 3DH1 | 10.1 | 420 | 0.134 | 0.4 | Pass |
| 3DH3 | 5.1 | 1704 | 0.273 | 0.4 | Pass |
| 3DH5 | 3.4 | 2964 | 0.316 | 0.4 | Pass |

Remark:


9. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
10. 79 channels come from the Hopping Channel number.
11. Average Hopping Channel = hops/sweep time
12. t: Package Transfer Time(us)



8-DPSK



3DH1 Dwell Time (One Pulse) Plot on Channel 39



3DH1 Dwell Time (Count Pulses) Plot on Channel 39



3DH3 Dwell Time (One Pulse) Plot on Channel 39**3DH3 Dwell Time (Count Pulses) Plot on Channel 39**

3DH5 Dwell Time (One Pulse) Plot on Channel 39**3DH5 Dwell Time (Count Pulses) Plot on Channel 39**

3.5 Peak Output Power Measurement

3.5.1 Limit of Peak Output Power

Frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels: 1W (30 dBm).


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.

3.5.4 Test Setup




3.5.5 Test Result of Peak Output Power

| | | | |
|-----------------|--------------|---------------------|-------------|
| Test Mode : | Mode 7, 8, 9 | Temperature : | 23°C ~ 26°C |
| Test Engineer : | Hogan He | Relative Humidity : | 40%~60% |


| Channel | Frequency (MHz) | RF Power (dBm) | | |
|---------|--------------------|----------------|----------------------|-----------|
| | | 8-DPSK | Max. Limits (dBm) | Pass/Fail |
| | | 1 Mbps | | |
| 00 | 2402 | 11.13 | 30 | Pass |
| 39 | 2441 | 10.63 | 30 | Pass |
| 78 | 2480 | 9.56 | 30 | Pass |

Peak Output Power Plot on Channel 00




Date: 29.MAR.2012 13:02:55

Peak Output Power Plot on Channel 39



Date: 29.MAR.2012 13:00:24

Peak Output Power Plot on Channel 78



Date: 29.MAR.2012 12:59:09

3.6 Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

3.6.2 Measuring Instruments


See list of measuring instruments of this test report.

3.6.3 Test Procedures


1. The testing follows the guidelines in ANSI C63.4-2003 and FCC Public Notice DA 00-705 Measurement Guidelines.
2. RF antenna conducted test: Set RBW = 300kHz, Video bandwidth (VBW) \geq RBW. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 300k Hz RBW. Note: If the device complies with the use of power option 2 the attenuation under this paragraph shall be 30 dB instead of 20 dB.
3. Radiated emission test: Applies to band edge emissions that fall in the restricted bands listed in FCC Section 15.205. The maximum permitted average field strength is listed in FCC Section 15.209. A pre-amp is necessary for this measurement. For measurements above 1 GHz, set RBW = 1MHz, VBW = 1MHz, Sweep: Auto for Peak; set RBW = 1MHz, VBW = 10 Hz, Sweep: Auto for Average. If the emission is pulsed, modify the unit for continuous operation; use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation. See FCC Section 15.35(b) and (c).
4. In case the emission is fail due to the used RBW / VBW is too wide, marker-delta method of FCC Public Notice DA 00-705 will be followed.

3.6.4 Test Setup

<Radiated Band Edges>



<Conducted Band Edges>



3.6.5 Test Result of Radiated Band Edges

| | | | | | | | | | |
|--------------|--------|--|--|--|--|--|--|--|--|
| Test Band : | Mode 1 | | | | | | | | |
| Test Channel | 00 | | | | | | | | |

| Frequency GHz | Level dBuv/m | Over Limit dB | Limit Line dBuv/m | Read Level dBuv | Antenna Factor dB | Cable Loss dB | Preamp Factor dB | Remark | Polarity |
|------------------|-----------------|---------------------|-------------------------|-----------------------|-------------------------|---------------------|------------------------|---------|------------|
| 2.4 | 56.77 | -17.23 | 74 | 46.28 | 27.5 | 6.99 | 24 | Peak | Vertical |
| 2.4 | 51.4 | -2.6 | 54 | 40.91 | 27.5 | 6.99 | 24 | Average | Vertical |
| 2.4 | 71.3 | -2.7 | 74 | 60.81 | 27.5 | 6.99 | 24 | Peak | Horizontal |
| 2.4 | 66.98 | 12.98 | 54 | 56.49 | 27.5 | 6.99 | 24 | Average | Horizontal |


| | | | | | | | | | |
|--------------|--------|--|--|--|--|--|--|--|--|
| Test Band : | Mode 2 | | | | | | | | |
| Test Channel | 78 | | | | | | | | |

| Frequency GHz | Level dBuv/m | Over Limit dB | Limit Line dBuv/m | Read Level dBuv | Antenna Factor dB | Cable Loss dB | Preamp Factor dB | Remark | Polarity |
|------------------|-----------------|---------------------|-------------------------|-----------------------|-------------------------|---------------------|------------------------|---------|------------|
| 2.4835 | 58.61 | -15.39 | 74 | 47.33 | 27.5 | 6.99 | 24 | Peak | Vertical |
| 2.4835 | 48.48 | -5.52 | 54 | 37.2 | 27.5 | 6.99 | 24 | Average | Vertical |
| 2.4835 | 57.9 | -16.1 | 74 | 46.62 | 27.5 | 6.99 | 24 | Peak | Horizontal |
| 2.4835 | 46.86 | -7.14 | 54 | 35.58 | 27.5 | 6.99 | 24 | Average | Horizontal |

3.6.6 Test Result of Conducted Band Edges


| | | | |
|-----------------------|--------------|----------------------------|---------------------------------|
| Test Mode : | Mode 1 and 3 | Temperature : | 23°C~26°C |
| Test Channel : | 00 and 78 | Relative Humidity : | 40%~60% |
| | | | Test Engineer : Hogan He |

Low Band Edge Plot on Channel 00



Date: 31.MAR.2012 09:43:52


High Band Edge Plot on Channel 78



Date: 31.MAR.2012 09:55:23


| | | | |
|-----------------------|--------------|----------------------------|-----------|
| Test Mode : | Mode 4 and 6 | Temperature : | 23°C~26°C |
| Test Channel : | 00 and 78 | Relative Humidity : | 40%~60% |
| | | Test Engineer : | Hogan He |

Low Band Edge Plot on Channel 00



Date: 31.MAR.2012 09:44:59


High Band Edge Plot on Channel 78



Date: 31.MAR.2012 09:54:05


| | | | |
|-----------------------|--------------|----------------------------|-----------|
| Test Mode : | Mode 7 and 9 | Temperature : | 23°C~26°C |
| Test Channel : | 00 and 78 | Relative Humidity : | 40%~60% |
| | | Test Engineer : | Hogan He |

Low Band Edge Plot on Channel 00



Date: 31.MAR.2012 09:46:04

High Band Edge Plot on Channel 78



Date: 31.MAR.2012 09:53:05

3.7 Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

All harmonics/spurs must be at least 20 dB down from the highest emission level within the authorized band.


3.7.2 Measuring Instruments

See list of measuring instruments of this test report.

3.7.3 Test Procedures

1. The transmitter output was connected to the spectrum analyzer via a low loss cable.
2. Set RBW = 100 kHz, Video bandwidth (VBW) \geq RBW, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.


3.7.4 Test Setup



3.7.5 Test Result of Output Power


| | | | |
|-----------------------|--------|----------------------------|-----------|
| Test Mode : | Mode 7 | Temperature : | 23°C~26°C |
| Test Channel : | 00 | Relative Humidity : | 40%~60% |
| | | Test Engineer : | Hogan He |

Conducted Spurious Emission Plot between 9 kHz ~ 3 GHz



Date: 01.APR.2012 07:28:50


Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz



Date: 01.APR.2012 07:41:27


| | | | |
|-----------------------|--------|----------------------------|-----------|
| Test Mode : | Mode 8 | Temperature : | 23°C~26°C |
| Test Channel : | 39 | Relative Humidity : | 40%~60% |
| | | Test Engineer : | Hogan He |

Conducted Spurious Emission Plot between 9 kHz ~ 3 GHz



Date: 01.APR.2012 07:29:52


Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz



Date: 01.APR.2012 07:38:18


| | | | |
|-----------------------|--------|----------------------------|-----------|
| Test Mode : | Mode 9 | Temperature : | 23°C~26°C |
| Test Channel : | 78 | Relative Humidity : | 40%~60% |
| | | Test Engineer : | Hogan He |

Conducted Spurious Emission Plot between 9 kHz ~ 3 GHz



Date: 01.APR.2012 07:32:09

Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz



Date: 01.APR.2012 07:44:18

3.8 AC Conducted Emission Measurement

3.8.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

| Frequency of emission (MHz) | Conducted limit (dBuV) | |
|-----------------------------|------------------------|-----------|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56* | 56 to 46* |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

*Decreases with the logarithm of the frequency.


3.8.2 Measuring Instruments

See list of measuring instruments of this test report.

3.8.3 Test Procedures

1. Please follow the guidelines in ANSI C63.4-2003.
2. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connecting to the other LISN.
5. The LISN provides 50 ohm coupling impedance for the measuring instrument.
6. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
7. Both sides of AC line were checked for maximum conducted interference.
8. The frequency range from 150 kHz to 30 MHz was searched.
9. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.


3.8.4 Test Setup




3.8.5 Test Result of AC Conducted Emission



Test Voltage:120V/60Hz

Test mode:GSM850+Bluetooth Link+Earphone+Neutral



Test mode:GSM850+Bluetooth Link+Earphone+Line



Test mode:GSM1900+Bluetooth Link+Earphone+Neutral**Test mode:GSM1900+Bluetooth Link+Earphone+Line**

3.9 Radiated Emission Measurement

3.9.1 Limit of Radiated Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

| Frequency (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|--------------------|--------------------------------------|----------------------------------|
| 0.009 – 0.490 | 2400/F(kHz) | 300 |
| 0.490 – 1.705 | 24000/F(kHz) | 30 |
| 1.705 – 30.0 | 30 | 30 |
| 30 – 88 | 100 | 3 |
| 88 – 216 | 150 | 3 |
| 216 - 960 | 200 | 3 |
| Above 960 | 500 | 3 |

3.9.2 Measuring Instruments


See list of measuring instruments of this test report.

3.9.3 Test Procedures


1. The testing follows the guidelines in FCC KDB Publication No. 558074 (Measurement Guidelines of DTS).
2. Use the following spectrum analyzer settings:
 - (1) Span = wide enough to fully capture the emission being measured; RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold.
 - (2) Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.
Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB)
3. Follow the guidelines in ANSI C63.4-2003 with respect to maximizing the emission by rotating the EUT, measuring the emission for three EUT orthogonal planes, and adjusting the measurement antenna height and polarization. A pre-amp and a high pass filter are used for this test in order to get the good signal level.

3.9.4 Test Setup


9kHz~30MHz



30MHz~1GHz



Above 1GHz



3.9.5 Radiated Emission Measurement Results (9kHz ~ 30MHz)

| | | | |
|-----------------|-----------|---------------------|-----------|
| Test Engineer : | Hogan. He | Temperature : | 23°C~26°C |
| | | Relative Humidity : | 45%~60% |

| Frequency (MHz) | Reading (dBu V/m) | Factor(dB) Corr. | Result (dBu V/m) | Limit (dBu V/m) | Margin (dB) | Polarization |
|-----------------|-------------------|------------------|------------------|-----------------|-------------|--------------|
| 1.075 | 26.65 | 14.89 | 41.54 | 62.97 | -21.43 | Horizontal |
| 1.075 | 26.08 | 14.89 | 40.97 | 62.97 | -22.00 | Vertical |

Notes:

1 , No emission found between lowest internal or generated frequency to 30MHz.

2 , Laboratory's Information:


Prepared By : Accurate Technology Co., Ltd

Address: F1, Bldg. A, Changyuan New Material Port, Keyuan Rd., Science & Industry Park
Nanshan District, Shenzhen 518057, P.R. China


Company Registration Number : 752051

Date of Receipt: 2012.04.16

Radiated Emission Plot between 9 kHz ~ 30MHz




EUT: GSM MOBILE PHONE M/N: L700 Polarization: X

Radiated Emission Plot between 9 kHz ~ 30MHz


3.9.6 Radiated Emission Measurement Results (30MHz-18GHz)



| | |
|----------------|--|
| Test Channel : | 00 |
| Remark: | 2412MHz is Fundamental signal which can be ignored |

Radiated Emission 30MHz-1GHz Vertical







Radiated Emission 1GHz-18GHz Vertical





Radiated Emission 30MHz-1GHz Horizontal**Radiated Emission 1GHz-18GHz Horizontal**



| | |
|----------------|--|
| Test Channel : | 39 |
| Remark: | 2412MHz is Fundamental signal which can be ignored |

Radiated Emission 30MHz-1GHz Vertical**Radiated Emission 1GHz-18GHz Vertical**

Radiated Emission 30MHz-1GHz Horizontal**Radiated Emission 1GHz-18GHz Horizontal**

| | |
|----------------|--|
| Test Channel : | 78 |
| Remark: | 2412MHz is Fundamental signal which can be ignored |

Radiated Emission 30MHz-1GHz Vertical**Radiated Emission 1GHz-18GHz Vertical**

Radiated Emission 30MHz-1GHz Horizontal**Radiated Emission 1GHz-18GHz Horizontal**

3.9.7 Radiated Emission Measurement Results (18GHz-25GHz)

| | | | |
|-----------------|-----------|---------------------|-----------|
| Test Engineer : | Hogan. He | Temperature : | 23°C~26°C |
| | | Relative Humidity : | 40%~60% |

| Frequency (MHz) | Level (dBuV) | Over Limit (dB) | Limit Line (dBuV) | Remark |
|-----------------|--------------|-----------------|-------------------|----------|
| - | - | - | - | See Note |

Notes:

The amplitude of radiated emissions that are attenuated by more than 20dB below the permissible value has no need to be reported. The measurement performed at 1meter distance from turn table to antenna.

3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.10.2 Antenna Connected Construction

The antennas type used in this product is PIFA Antenna without connector and it is considered to meet antenna requirement.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

| No | Instrument/Ancillary | Provider | Type/Model | Cal. Date |
|----|----------------------|-------------|-----------------------|------------|
| 01 | Base Station | Agilent | E5515C | 2011.12.14 |
| 02 | Spectrum Analyzer | R&S | FSP30(9kHz~30GHz) | 2011.07.19 |
| 03 | Loop Antenna | Schwarzbeck | FMZB1516 | 2012.01.07 |
| 04 | Antenna | Schwarzbeck | VULB9165(30M-1G) | 2011.11.09 |
| 05 | Antenna | R&S | HF906(1G-18G) | 2011.08.10 |
| 06 | Antenna | Schwarzbeck | BBHA 9170 (15G-26.5G) | 2011.11.09 |
| 07 | High Pass Filter | R&S | System Integrated | 2011.11.14 |
| 08 | Thermal chamber | Hitachi | EC- 85MHP | 2011.12.25 |
| 09 | Pre-Amplifier | R&S | Pre-Amp | 2012.1.18 |
| 10 | Helical Antenna | ETS | 3102 (1G-10G) | NCR |
| 11 | Power Meter | R&S | NRP(10MHz~8GHz) | 2011.12.05 |
| 12 | Relay Switch | R&S | TS-REMI | NCR |

5 Uncertainty Evaluation



5.1 Uncertainty of Radiated Spurious Emission evaluation (30MHz~1GHz)



| Radiated Spurious Emission Measurement Uncertainty Evaluation | | | | | |
|---|--------------------------|-----------------------|-----------------------|---------------------|------|
| Contribution | Probability Distribution | Partition Coefficient | u(xi) | | |
| | | | Horizontal 30-1000MHz | Vertical 30-1000MHz | |
| Cable Loss Calibration | U01 | U-Shape | 1.41 | 0.17 | 0.17 |
| Sine wave voltage accuracy of Spectrum analyzer | U02 | Triangle | 2.45 | 0.82 | 0.82 |
| Impulse response of spectrum analyzer | U03 | Triangle | 2.45 | 0.61 | 0.61 |
| Pulse repetition rate of spectrum analyzer | U04 | Triangle | 2.45 | 0.61 | 0.61 |
| Spectrum analyzer noise level | U05 | Normal | 2.00 | 0.25 | 0.25 |
| Measurement of the signal path mismatch | U06 | U-Shape | 1.41 | 0.13 | 0.13 |
| Free-space antenna factor | U07 | Normal | 2.00 | 1.00 | 1.00 |
| Antenna Factor Interpolation for Frequency | U08 | Rectangular | 1.73 | 0.17 | 0.17 |
| Antenna factor with height in the correlation | U09 | Rectangular | 1.73 | 0.17 | 0.17 |
| Measurement antenna and the absorbing material in the image of the mutual coupling effect | U10 | Rectangular | 1.73 | 0.50 | 0.50 |
| Antenna phase center variation | U11 | Rectangular | 1.73 | 0.58 | 0.58 |
| Antenna cross polarization response | U12 | Rectangular | 1.73 | 0.52 | 0.52 |
| Antenna imbalance | U13 | Rectangular | 1.73 | 0.52 | 0.52 |
| Test distance error | U14 | Rectangular | 1.73 | 0.17 | 0.17 |
| Desktop terrain clearance variation | U15 | Normal | 2.00 | 0.05 | 0.05 |
| Random uncertainty | U16 | Standard deviation | 1.00 | 0.20 | 0.19 |
| Pre-Amplifier gain Calibration | U17 | U-Shape | 1.41 | 0.13 | 0.13 |
| Combined Standard Uncertainty $U_c(y)$ | U_c | Normal | 1.00 | 1.95 | 1.95 |
| Measuring Uncertainty for a level of Confidence of 95% ($U=2U_c(y)$) | $U=2U_c$ | Normal | 2 | 3.90 | 3.89 |


5.2 Uncertainty of Radiated Spurious Emission evaluation (1GHz~26.5GHz)

| Radiated Spurious Emission Measurement Uncertainty Evaluation | | | | | |
|---|--------------------------|-----------------------|--------------------|------------------|------|
| Contribution | Probability Distribution | Partition Coefficient | u(xi) | | |
| | | | Horizontal 1-25GHz | Vertical 1-25GHz | |
| Cable Loss Calibration | U01 | U-Shape | 1.41 | 0.17 | 0.17 |
| Sine wave voltage accuracy of Spectrum analyzer | U02 | Triangle | 2.45 | 0.82 | 0.82 |
| Impulse response of spectrum analyzer | U03 | Triangle | 2.45 | 0.61 | 0.61 |
| Pulse repetition rate of spectrum analyzer | U04 | Triangle | 2.45 | 0.61 | 0.61 |
| Spectrum analyzer noise level | U05 | Normal | 2.00 | 0.25 | 0.25 |
| Measurement of the signal path mismatch | U06 | U-Shape | 1.41 | 0.13 | 0.13 |
| Free-space antenna factor | U07 | Normal | 2.00 | 1.00 | 1.00 |
| Antenna Factor Interpolation for Frequency | U08 | Rectangular | 1.73 | 0.17 | 0.17 |
| Antenna factor with height in the correlation | U09 | Rectangular | 1.73 | NA | NA |
| Measurement antenna and the absorbing material in the image of the mutual coupling effect | U10 | Rectangular | 1.73 | 0.50 | 0.50 |
| Antenna phase center variation | U11 | Rectangular | 1.73 | 0.58 | 0.58 |
| Antenna cross polarization response | U12 | Rectangular | 1.73 | 0.52 | 0.52 |
| Antenna imbalance | U13 | Rectangular | 1.73 | 0.52 | 0.52 |
| Test distance error | U14 | Rectangular | 1.73 | 0.17 | 0.17 |
| Desktop terrain clearance variation | U15 | Normal | 2.00 | 0.05 | 0.05 |
| Random uncertainty | U16 | Standard deviation | 1.00 | 0.22 | 0.23 |
| Pre-Amplifier gain Calibration | U17 | U-Shape | 1.41 | 0.13 | 0.13 |
| Combined Standard Uncertainty $U_c(y)$ | U_c | Normal | 1.00 | 1.94 | 1.94 |
| Measuring Uncertainty for a level of Confidence of 95% ($U = 2U_c(y)$) | $U = kU_c$ | Normal | 2 | 3.89 | 3.89 |

APPENDIX B. SETUP PHOTOGRAPHS**FCC Part15C Radiated Emission Plot between 9 kHz ~ 30MHz****- Front****-Rear**

FCC Part15C Radiated Emission below 1GHz**- Front****-Rear**

FCC Part15C Radiated Emission above 1GHz**-Front****-Rear**

AC Conducted Emission Test Setup

END.