

# FCC Test Report

## FCC 47 CFR FCC Part 15 Subpart B

Product Name : GSM MOBILE PHONE

Model No. : L700

FCC ID : FOCGC661838

Prepared By : Inventec Appliances(Pudong) Corporation

Address: : No.789 Pu Xing Road,Shanghai,PRC

Date of Receipt : 2012.03.28

Date of Test : 2012.03.28-2012.04.04

Report No. : 20120328FCC-A



## Test Report Certification


Date of Issue : Mar.28.2012

Report No. : 20120328FCC-A


Product Name : GSM MOBILE PHONE  
Model No. : L700  
Trade Name : JZH-Mobile  
Applicant : JZH-Mobile Communication technology Co., LTD  
Address : 1302,A block, Haisong Building, Chegongmiao, Futian District, Shenzhen City, China.  
Standard : FCC 47 CFR FCC Part 15 Subpart B  
Classification : JBP  
Test Result : Complied

The Test Results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of IAC regulatory Laboratory

Documented By :  APR. 05.2012  
Kelly Lin/Engineer

Tested By :  APR. 05.2012  
Byran Hung/Senior Engineer

Approved By :  APR. 05.2012  
Jeff Huang/Director of Operations

## TABLE OF CONTENTS

Description	Page
1. <b>GENERAL INFORMATION</b> .....	5
1.1 <b>Applicant</b> .....	5
1.2 <b>Manufacturer</b> .....	5
1.3 <b>Applied Standards</b> .....	7
2. <b>Test Configuration of Equipment Under Test</b> .....	7
2.1 <b>Test Modes</b> .....	7
3. <b>Test Result</b> .....	8
3.1 <b>Test of AC Conducted Emission Measurement</b> .....	8
4. <b>List of Measuring Equipment</b> .....	18
5. <b>Ancillary Equipment List</b> .....	18
6. <b>Uncertainty Evaluation</b> .....	18

## SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.107	7.2.2	AC Conducted Emission	< 15.107 limits < RSS-Gen table 2 limits	PASS	Under limit 6 dB
3.2	15.109	7.2.3.2	Radiated Emission	< 15.109 limits or < RSS-Gen table 1 limits (Section 6)	PASS	Under limit 6dB

**1. GENERAL INFORMATION****1.1 Applicant**

Company Name: JZH-Mobile Communication technology Co., LTD

Address: 1302,A block, Haisong Building, Chegongmiao, Futian District, Shenzhen City, China.

**1.2 Manufacturer**

Company Name: JZH-Mobile Communication technology Co., LTD

Address: 1302,A block, Haisong Building, Chegongmiao, Futian District, Shenzhen City, China.

### 1.3 Feature of Equipment Under Test

Product Feature & Specification	
Equipment	GSM MOBILE PHONE
Brand Name	L700
Model Name	JZH-Mobile
FCC ID	FOCGC661838
HW Version	B085-MB-V0.1
SW Version	B085-1D-ENTEL _L97 _V114

**Remark:**

1. For other wireless features of this EUT, test report will be issued separately.
2. This test report recorded only product characteristics and test results of JBP.
3. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR FCC Part 15 Subpart B
- ANSI C63.4-2003

### Remark:

All test items were verified and recorded according to the standards and without any deviation during the test.

## 2. Test Configuration of Equipment Under Test

### 2.1 Test Modes

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

#### Abbreviations:

- EMI AC: AC conducted emissions
- EMI RE  $\geq$  1G: EUT radiated emissions  $\geq$  1GHz
- EMI RE < 1G: EUT radiated emissions < 1GHz

Test Item	Function Type
AC Conducted Emission	Mode1:GSM 850 Idle + Bluetooth Idle + Adapter + Battery + Earphone

Test Item	Function Type
Radiated Emissions < 1GHz	Mode1:GSM 850 Idle + Bluetooth Idle + Battery + Earphone+ LCD monitor+ Notebook+ Adapter + Mouse

Test Item	Function Type
Radiated Emissions > 1GHz	Mode1: GSM 850 Idle + Bluetooth Idle + Battery + Earphone+ LCD monitor+ Notebook+ Adapter + Mouse

### 3. Test Result

#### 3.1 Test of AC Conducted Emission Measurement

##### 3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


##### 3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

##### 3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.


### 3.1.4 Test Setup



### 3.1.5 Test Result of AC Conducted Emission


Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Byran Hung	Relative Humidity :	25~58%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM 850 Idle + Bluetooth Idle + Adapter + Battery + Earphone		

EMI Auto Test CISPR22



<b>Test Mode :</b>	Mode 1	<b>Temperature :</b>	22~24°C
<b>Test Engineer :</b>	Byran Hung	<b>Relative Humidity :</b>	25~58%
<b>Test Voltage :</b>	120Vac / 60Hz	<b>Phase :</b>	Neutral
<b>Function Type :</b>	GSM 850 Idle + Bluetooth Idle + Adapter + Battery + Earphone		

EMI Auto Test CISPR22



### 3.1.6 Limit of Radiated Emission

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

### 3.1.7 Measuring Instruments


See list of measuring instruments of this test report.

### 3.1.8 Test Procedure


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the quasi-peak method and reported
8. Emission level (dBuV/m) =  $20 \log \text{Emission level (uV/m)}$
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

### 3.1.9 Test Setup

30MHz~1GHz




Above 1GHz




### 3.1.10 Test Result of Radiated Emission

<b>Test Mode :</b>	Mode 1	<b>Temperature :</b>	22~24°C
<b>Test Engineer :</b>	Guo-Zheng Li	<b>Relative Humidity :</b>	25~58%
<b>Test Distance :</b>	3m	<b>Polarization :</b>	Vertical
<b>Function Type :</b>	GSM 850 Idle + Bluetooth Idle + Adapter + Battery + Earphone + LCD monitor+ Notebook + Adapter + Mouse		



Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
37.627160	28.8	2000.0	120.000	104.0	V	0.0	18.1	11.2	40.0
41.442720	27.1	2000.0	120.000	171.0	V	302.0	16.8	12.9	40.0
81.489200	30.8	2000.0	120.000	154.0	V	171.0	13.4	9.2	40.0
200.779040	38.7	2000.0	120.000	104.0	V	212.0	17.5	4.8	43.5
232.256520	34.4	2000.0	120.000	154.0	V	128.0	18.3	11.6	46.0


<b>Test Mode :</b>	Mode 1	<b>Temperature :</b>	22~24°C
<b>Test Engineer :</b>	Guo-Zheng Li	<b>Relative Humidity :</b>	25~58%
<b>Test Distance :</b>	3m	<b>Polarization :</b>	Horizontal
<b>Function Type :</b>	GSM 850 Idle + Bluetooth Idle + Adapter + Battery + Earphone + LCD monitor+ Notebook + Adapter + Mouse		




Frequency (MHz)	QuasiPeak (dB $\mu$ V/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V/m)
41.531640	30.0	2000.0	120.000	254.0	H	14.0	16.8	10.0	40.0
144.005960	38.9	2000.0	120.000	240.0	H	22.0	10.7	4.6	43.5
209.727200	38.8	2000.0	120.000	154.0	H	235.0	13.7	4.7	43.5

**Radiated Emission above 1GHz**

<b>Test Mode :</b>	Mode 1	<b>Temperature :</b>	22~24°C
<b>Test Engineer :</b>	Guo-Zheng Li	<b>Relative Humidity :</b>	25~58%
<b>Test Distance :</b>	3m	<b>Polarization :</b>	Vertical
<b>Function Type :</b>	GSM 850 Idle + Bluetooth Idle + Adapter + Battery + Earphone+ LCD monitor+ Notebook+Adapter+ Mouse		



<b>Test Mode :</b>	Mode 1	<b>Temperature :</b>	22~24°C
<b>Test Engineer :</b>	Guo-Zheng Li	<b>Relative Humidity :</b>	25~58%
<b>Test Distance :</b>	3m	<b>Polarization :</b>	Horizontal
<b>Function Type :</b>	GSM 850 Idle + Bluetooth Idle + Adapter + Battery + Earphone+ LCD monitor+ Notebook+ Adapter+ Mouse		



#### 4. List of Measuring Equipment

No	Instrument/Ancillary	Provider	Type/Model	Cal. Date
01	Base Station	Agilent	E5515C	2011.12.14
02	Spectrum Analyzer	R&S	FSP30(9kHz~30GHz)	2011.07.19
03	Antenna	Schaffner	HLA6120(9KHz~30MHz)	2011.11.09
04	Antenna	Schwarzbeck	VULB9165(30M-1G)	2011.11.09
05	Antenna	R&S	HF906(1G-18G)	2011.08.10
06	Antenna	Schwarzbeck	BBHA 9170 (15G-26.5G)	2011.11.09
07	High Pass Filter	R&S	System Integrated	2011.11.14
08	Thermal chamber	Hitachi	EC- 85MHP	2011.12.25
09	Pre-Amplifier	R&S	Pre-Amp	2012.1.18
10	Helical Antenna	ETS	3102 (1G-10G )	NCR
11	Power Meter	R&S	NRP(10MHz~8GHz)	2011.12.05
12	Relay Switch	R&S	TS-REMI	NCR

#### 5 Ancillary Equipment List

Product	Manufacturer	Model No.	Serial No.	Power Cord
Notebook PC	Toshiba	PSAGCT-0K501P	59162409Q	N/A
Adapter (NB)	Toshiba	PA-1750-09	PA3468E1AC3	M/N A-1750-09 PA -1750-09
LCD Monitor	HP	GTM002	3CQ84343SG	
Wlan AP	D-Link	DIR-815	PVK21B1000236	AC: I/P: Unshielded 1.8m DC:O/P: Unshielded 1.8m
Bluetooth headset	Jabra	OTE4		Unshielded 1.8m
Mouse	Lenovo	M20	OL08226936	Unshielded 1.0m


#### 6 Uncertainty Evaluation


##### 6.1 Ucertainty of Radiated Spurious Emission evaluation (30MHz~1GHz)

Radiated Spurious Emission Measurement Uncertainty Evaluation					
Contribution	Probability Distribution	Partition Coefficient	u(xi)		
			Horizontal 30-1000MHz	Vertical 30-1000MHz	
Cable Loss Calibration	U01	U-Shape	1.41	0.17	0.17
Sine wave voltage accuracy of Spectrum analyzer	U02	Triangle	2.45	0.82	0.82
Impulse response of spectrum analyzer	U03	Triangle	2.45	0.61	0.61
Pulse repetition rate of spectrum analyzer	U04	Triangle	2.45	0.61	0.61
Spectrum analyzer noise level	U05	Normal	2.00	0.25	0.25
Measurement of the signal path mismatch	U06	U-Shape	1.41	0.13	0.13
Free-space antenna factor	U07	Normal	2.00	1.00	1.00
Antenna Factor Interpolation for Frequency	U08	Rectangular	1.73	0.17	0.17
Antenna factor with height in the correlation	U09	Rectangular	1.73	0.17	0.17
Measurement antenna and the absorbing material in the image of the mutual coupling effect	U10	Rectangular	1.73	0.50	0.50
Antenna phase center variation	U11	Rectangular	1.73	0.58	0.58
Antenna cross polarization response	U12	Rectangular	1.73	0.52	0.52
Antenna imbalance	U13	Rectangular	1.73	0.52	0.52
Test distance error	U14	Rectangular	1.73	0.17	0.17
Desktop terrain clearance variation	U15	Normal	2.00	0.05	0.05
Random uncertainty	U16	Standard deviation	1.00	0.20	0.19
Pre-Amplifier gain Calibration	U17	U-Shape	1.41	0.13	0.13
Combined Standard Uncertainty $U_c(y)$	Uc	Normal	1.00	1.95	1.95
Measuring Uncertainty for a level of Confidence of 95% ( $U = 2U_c(y)$ )	$U = kU_c$	Normal	2	3.90	3.89

## 6.2 Uncertainty of Radiated Spurious Emission evaluation (1GHz~25GHz)

Radiated Spurious Emission Measurement Uncertainty Evaluation					
Contribution	Probability Distribution	Partition Coefficient	u(xi)		
			Horizontal 1-25GHz	Vertical 1-25GHz	
Cable Loss Calibration	U01	U-Shape	1.41	0.17	0.17
Sine wave voltage accuracy of Spectrum analyzer	U02	Triangle	2.45	0.82	0.82
Impulse response of spectrum analyzer	U03	Triangle	2.45	0.61	0.61
Pulse repetition rate of spectrum analyzer	U04	Triangle	2.45	0.61	0.61
Spectrum analyzer noise level	U05	Normal	2.00	0.25	0.25
Measurement of the signal path mismatch	U06	U-Shape	1.41	0.13	0.13
Free-space antenna factor	U07	Normal	2.00	1.00	1.00
Antenna Factor Interpolation for Frequency	U08	Rectangular	1.73	0.17	0.17
Antenna factor with height in the correlation	U09	Rectangular	1.73	NA	NA
Measurement antenna and the absorbing material in the image of the mutual coupling effect	U10	Rectangular	1.73	0.50	0.50
Antenna phase center variation	U11	Rectangular	1.73	0.58	0.58
Antenna cross polarization response	U12	Rectangular	1.73	0.52	0.52
Antenna imbalance	U13	Rectangular	1.73	0.52	0.52
Test distance error	U14	Rectangular	1.73	0.17	0.17
Desktop terrain clearance variation	U15	Normal	2.00	0.05	0.05
Random uncertainty	U16	Standard deviation	1.00	0.22	0.23
Pre-Amplifier gain Calibration	U17	U-Shape	1.41	0.13	0.13
Combined Standard Uncertainty $U_c(y)$	Uc	Normal	1.00	1.94	1.94
Measuring Uncertainty for a level of Confidence of 95% ( $U=2U_c(y)$ )	$U=kU_c$	Normal	2	3.89	3.89

**APPENDIX A. SETUP PHOTOGRAPHS****FCC Part15B Radiated Emission below 1GHz****Setup 1- EUT + Battery + Earphone + LCD monitor + Notebook + Adapter+ Mouse****-Front****-Rear**

**FCC Part15B Radiated Emission above 1GHz****Setup 1- EUT + Battery + Earphone + LCD monitor + Notebook + Adapter+ Mouse****-Front****-Rear**

**AC Conducted Emission Test Setup**

