

# **FCC TEST REPORT**

for

**CISPR PUB. 22 Class B**

Equipment : VGA CARD

Model No. : A4-VANTASD-A3-L

FCC ID : FQI-VANTASD

Filing Type : Certification

Applicant : **JOYTECH COMPUTER CO., LTD.**  
3F, No. 1, ALLEY 2, SZU-WEI LANE,  
CHUNG CHENG RD., HSIN TIEN CITY,  
TAIPEI HSIEN, TAIWAN, R.O.C.

- The test result refers exclusively to the test presented test model / sample.
- Without the written authorization of the test lab., the Test Report may not be copied.
- **Certificate or Test Report must not be used by the applicant to claim the product in this test report endorsement by NVLAP or any agency of U.S. government.**

***SPORTON International Inc.***

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

## Table of Contents

<b>CERTIFICATE OF COMPLIANCE .....</b>	<b>3</b>
<b>1. General Description of Equipment under Test .....</b>	<b>4</b>
1.1. Applicant .....	4
1.2. Manufacturer .....	4
1.3. Basic Description of Equipment under Test .....	4
1.4. Feature of Equipment under Test .....	4
<b>2. Test Configuration of Equipment under Test .....</b>	<b>5</b>
2.1. Test Manner .....	5
2.2. Description of Test System .....	5
2.3. Connection Diagram of Test System .....	7
<b>3. Test Software .....</b>	<b>8</b>
<b>4. General Information of Test .....</b>	<b>9</b>
4.1. Test Facility .....	9
4.2. Standard for Methods of Measurement .....	9
4.3. Test in Compliance with .....	9
4.4. Frequency Range Investigated .....	9
4.5. Test Distance .....	9
<b>5. Test of Conducted Powerline .....</b>	<b>10</b>
5.1. Major Measuring Instruments .....	10
5.2. Test Procedures .....	11
5.3. Typical Test Setup Layout of Conducted Powerline .....	12
5.4. Test Result of AC Powerline Conducted Emission .....	13
5.5. Photographs of Counducted Powerline Test Configuration .....	15
<b>6. Test of Radiated Emission .....</b>	<b>19</b>
6.1. Major Measuring Instruments .....	19
6.2. Test Procedures .....	20
6.3. Typical Test Setup Layout of Radiated Emission .....	21
6.4. Test Result of Radiated Emission .....	22
6.5. Photographs of Radiated Emission Test Configuration .....	24
<b>7. Antenna Factor &amp; Cable Loss .....</b>	<b>26</b>
<b>8. List of Measuring Equipments Used .....</b>	<b>27</b>

**CERTIFICATE OF COMPLIANCE**

for

**CISPR PUB. 22 Class B**


Equipment : VGA CARD

Model No. : A4-VANTASD-A3-L

FCC ID : FQI-VANTASD

Applicant : **JOYTECH COMPUTER CO., LTD.**  
3F, No. 1, ALLEY 2, SZU-WEI LANE,  
CHUNG CHENG RD., HSIN TIEN CITY,  
TAIPEI HSIEN, TAIWAN, R.O.C.**I HEREBY CERTIFY THAT:**

The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4 - 1992** and the energy emitted by this equipment was **passed CISPR PUB. 22** both radiated and conducted emission class B limits. Testing was carried out on Jun. 15, 1999 at **SPORTON International Inc.** LAB. in Lin Kou.

  
W. L. Huang  
General Manager**SPORTON International Inc.**

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

**1. General Description of Equipment under Test****1.1. Applicant**

JOYTECH COMPUTER CO., LTD.  
3F, No. 1, ALLEY 2, SZU-WEI LANE,  
CHUNG CHENG RD., HSIN TIEN CITY,  
TAIPEI HSIEN, TAIWAN, R.O.C.

**1.2. Manufacturer**

Same as 1.1.

**1.3. Basic Description of Equipment under Test**

Equipment : VGA CARD  
Model No. : A4-VANTASD-A3-L  
FCC ID : FQI-VANTASD  
Trade Name : JOYTECH  
DATA CABLE : Shielded  
Power Supply Type: N/A  
Power Cord : N/A

**1.4. Feature of Equipment under Test**

- Fast 32-bit VGA/SVGA
- High performance 128-bit 2D/GUI-DirectDraw Acceleration
- 206MHz Palette-DAC supporting up to 1600x1200@75Hz
- CCIR-656 Video Port and I<sup>2</sup>C

## **2. Test Configuration of Equipment under Test**

### **2.1. Test Manner**

- a. The EUT has been associated with personal computer and peripherals pursuant to ANSI C63.4-1992 and configuration operated in a manner which tended to maximize its emission characteristics in a typical application.
- b. The HITACHI Monitor, DELL PS/2 Keyboard, WINIC USB Mouse, HP Printer, ACEEX Modem, COMPAQ LCD Monitor and EUT were connected to the FIC PC for EMI test.
- c. The Following VGA display resolution were investigated during the compliance test:
  1. Horizontal frequency (640x480 to 1,600x1,200, 31.5 KHz to 109 KHz)
  2. Vertical frequency (60 Hz to 100 Hz)
- d. The Following LCD display resolution were investigated during the compliance test:
  1. Horizontal frequency (640x480 to 1,024x768, 31.5 KHz to 48 KHz)
  2. Vertical frequency (60 Hz )
- e. According to the above tests, we listed the following display modes as the worst cases:
  1. 1,600x1200 (non-interlanced 106 KHz), refresh rate 85 Hz, CRT Mode.
  2. 1,024x768 (non-interlanced 48 KHz), refresh rate 60 Hz, LCD Mode.
- f. Frequency range investigated: conduction 150 KHz to 30 MHz, radiation 30 MHz to 2000MHz.

### **2.2. Description of Test System**

**Support Unit 1. -- Monitor (HITACHI)**

FCC ID	: M9U9705C97BMD
Model No.	: CM803ET
Power Supply Type	: Switching
Power Cord	: Non-Shielded
Serial No.	: SP0181
Data Cable	: Shielded, 1.15m

**Support Unit 2. -- PS/2 Keyboard (DELL)**

FCC ID	: GYUM92SK
Model No.	: AT101(DE8M)
Serial No.	: SP0054
Data Cable	: Shielded, 360 degree via metal backshells, 1.9m

**Support Unit 3. -- USB Mouse (WINIC)**

FCC ID	: F4ZFDL-A50
Model No.	: FDM-A50
Serial No.	: SP0092
Data Cable	: Shielded, 1.5m

**Support Unit 4. -- Printer (HP)**

FCC ID	: B94C2642X
Model No.	: DeskJet 400
Power Supply Type	: Linear
Power Cord	: Non-Shielded
Serial No.	: SP0048
Data Cable	: Shielded, 360 degree via metal backshells, 1.35m

**Support Unit 5. -- Modem (ACEEX)**


FCC ID	: IFAXDM1414
Model No.	: DM1414
Power Supply Type	: Linear
Power Cord	: Non-Shielded
Serial No.	: SP0016
Data Cable	: Shielded, 360 degree via metal backshells, 1.15m

**Support Unit 6. -- LCD Monitor (COMPAQ)**

FCC ID	: N/A
Model No.	: FP500
Serial No.	: SP00190
Data Cable	: Shielded, 1.7m
Power Supply Type	: Switching
Power Cord	: Non-Shielded
Remark	: This support device was tested to comply with FCC standards and authorized under a declaration of conformity.

**Support Unit 7. -- Personal Computer (FIC)**

FCC ID	: N/A
Model No.	: P2L97
Power Supply Type	: Switching
Power Cord	: Non-Shielded
Serial No.	: SP0006
Data Cable	: Shielded
Remark	: This support device was tested to comply with FCC standards and authorized under a declaration of conformity.

**2.3. Connection Diagram of Test System**

1. The I/O cable is connected from EUT to the support unit 1.
2. The I/O cable is connected from PC to the support unit 2.
3. The I/O cable is connected from PC to the support unit 3.
4. The I/O cable is connected from PC to the support unit 4.
5. The I/O cable is connected from PC to the support unit 5.
6. The I/O cable is connected from EUT to the support unit 6.

### **3. Test Software**

An executive program, WINFCC.EXE under WIN 98, which generates a complete line of continuously repeating " H " pattern was used as the test software.

The program was executed as follows :

- a. Turn on the power of all equipment.
- b. The PC reads the test program from the floppy disk drive and runs it.
- c. The PC sends " H " messages to the monitor, and the monitor displays " H " patterns on the screen.
- d. The PC sends " H " messages to the printer, then the printer prints them on the paper.
- e. The PC sends " H " messages to the modem.
- f. The PC sends " H " messages to the internal Hard Disk, and the Hard Disk reads and writes the message.
- g. Repeat the steps from b to f.

## **4. General Information of Test**

### **4.1. Test Facility**

This test was carried out by SPORTON International Inc. in an openarea test site.

Openarea Test Site Location : No. 30-2, Lin 6, Diing-Fwu Tsuen, Lin-Kou-Hsiang,

Taipei Hsien, Taiwan, R.O.C.

TEL : 886-2-2601-1640

FAX : 886-2-2601-1695

### **4.2. Standard for Methods of Measurement**

ANSI C63.4-1992

### **4.3. Test in Compliance with**

CISPR PUB. 22 Class B

### **4.4. Frequency Range Investigated**

- a. Conduction: from 150 kHz to 30 MHz
- b. Radiation : from 30 MHz to 2,000 MHz

### **4.5. Test Distance**

The test distance of radiated emission from antenna to EUT is 10 M.

## **5. Test of Conducted Powerline**


Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 115 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-1992 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 5.3. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

### **5.1. Major Measuring Instruments**

Test Receiver	HP 8591EM
Attenuation	0 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
Step MHz	0.007 MHz
IF Bandwidth	9 kHz

**5.2. Test Procedures**

- a. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- b. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- c. All the support units are connect to the other LISN.
- d. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- e. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- f. Both sides of AC line were checked for maximum conducted interference.
- g. The frequency range from 150 kHz to 30 MHz was searched.
- h. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- i. If the emission level of the EUT in peak mode was 6 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 6 dB margin will be retested one by one using the quasi-peak method and reported.

**5.3. Typical Test Setup Layout of Conducted Powerline**

**5.4. Test Result of AC Powerline Conducted Emission****5.4.1. Test mode : 1600x1200 85Hz/106K (CRT Mode)**


- Temperature : 26°C
- Relative Humidity : 47 %
- Test Date : Jun. 15, 1999

**The Conducted Emission test was passed at minimum margin**

**NEUTRAL 0.242 MHz / 45.40 dBuV.**

Freq. (MHz)	Line or Neutral	Meter Reading				Limits				Margin	
		Q.P. (dBuV)	A.V. (dBuV)	Q.P. (uV)	A.V. (uV)	Q.P. (dBuV)	A.V. (dBuV)	Q.P. (uV)	A.V. (uV)	Q.P. (dB)	A.V. (dB)
0.218	L	45.40	44.90	186.21	175.79	62.89	52.89	1395.53	441.31	-17.49	-7.99
0.242	L	44.60	43.30	169.82	146.22	62.03	52.03	1262.89	399.36	-17.43	-8.73
0.278	L	41.30	40.20	116.14	102.33	60.88	50.88	1106.04	349.76	-19.58	-10.68
0.218	N	45.40	44.90	186.21	162.18	62.89	52.89	1395.53	441.31	-17.49	-7.99
0.242	N	45.40	44.20	186.21	162.18	62.03	52.03	1262.89	399.36	-16.63	-7.83
0.278	N	41.00	39.90	112.20	98.86	60.88	50.88	1106.04	349.76	-19.88	-10.98

Test Engineer :

  
PETER WANG

## 5.4.2. Test mode : 1024x768 60Hz/48K (LCD Mode)

- Temperature : 26°C
- Relative Humidity : 47 %
- Test Date : Jun. 15, 1999

**The Conducted Emission test was passed at minimum margin**

**NEUTRAL 0.243 MHz / 45.10 dBuV.**

Freq. (MHz)	Line or Neutral	Meter Reading				Limits				Margin	
		Q.P. (dBuV)	A.V. (dBuV)	Q.P. (uV)	A.V. (uV)	Q.P. (dBuV)	A.V. (dBuV)	Q.P. (uV)	A.V. (uV)	Q.P. (dB)	A.V. (dB)
0.218	L	45.90	45.40	197.24	186.21	62.89	52.89	1395.53	441.31	-16.99	-7.49
0.243	L	44.20	43.30	162.18	146.22	61.99	51.99	1257.92	397.79	-17.79	-8.69
0.343	L	38.60	36.00	85.11	63.10	59.13	49.13	904.72	286.10	-20.53	-13.13
0.218	N	45.90	45.40	197.24	186.21	62.89	52.89	1395.53	441.31	-16.99	-7.49
0.243	N	45.10	44.20	179.89	162.18	61.99	51.99	1257.92	397.79	-16.89	-7.79
0.344	N	38.30	35.50	82.22	59.57	59.11	49.11	902.20	285.30	-20.81	-13.61

Test Engineer :

Peter Wang  
PETER WANG

## **6. Test of Radiated Emission**


Radiated emissions from 30 MHz to 2,000 MHz were measured with a bandwidth of 120 kHz according to the methods defines in ANSI C63.4-1992. The EUT was placed on a nonmetallic stand in the open-field site, 0.8 meter above the ground plane, as shown in section 6.3. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions.

### **6.1. Major Measuring Instruments**

- Amplifier (HP 87405A)  
Attenuation 0 dB  
RF Gain 20 dB  
Signal Input 10 MHz to 3 GHz
  
- Spectrum Analyzer ( HP 8594A )  
Attenuation 0 dB  
Start Frequency 30 MHz  
Stop Frequency 2000 MHz  
Resolution Bandwidth 1 MHz  
Video Bandwidth 1 MHz  
Signal Input 9 KHz to 2.9 GHz
  
- Quasi-Peak Adapte ( HP 8594A )  
Resolution Bandwidth 120 KHz  
Frequency Band 30 MHz to 1 GHz  
Quasi-Peak Detector ON for Quasi-Peak Mode  
OFF for Peak Mode

**6.2. Test Procedures**

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 10 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a half wave dipole and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 6 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 6 dB margin will be repeated one by one using the quasi-peak method and reported.

**6.3. Typical Test Setup Layout of Radiated Emission**

## 6.4. Test Result of Radiated Emission

### 6.4.1. Test mode : 1600x1200 85Hz/106K (CRT Mode)

- Test Distance : 10 M
- Temperature : 31°C
- Relative Humidity : 65 %
- Test Date : Jun. 11, 1999
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Corrected Reading : Antenna Factor + Cable Loss + Reading = Emission

**The Radiated Emission test was passed at minimum margin**

**57.299 MHz / 26.88 dBuV (VERTICAL) Antenna Height 1 Meter, Turntable Degree 341 °.**

Frequency (MHz)	Polarity	Antenna Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Limits		Emission (dBuV/m)	Level (uV/m)	Margin (dB)
					(dBuV/m)	(uV/m)			
57.299	V	6.12	0.90	19.86	30.00	31.62	26.88	22.08	-3.12
171.826	V	10.06	1.59	14.96	30.00	31.62	26.61	21.40	-3.39
229.154	V	10.46	1.61	14.27	30.00	31.62	26.34	20.75	-3.66
57.000	H	6.12	0.90	19.27	30.00	31.62	26.29	20.63	-3.71
86.100	H	8.42	1.07	16.88	30.00	31.62	26.37	20.82	-3.63
114.600	H	11.98	1.06	13.44	30.00	31.62	26.48	21.09	-3.52

Test Engineer : William Lee  
WILLIAM LEE

**6.4.2. Test mode : 1024x768 60Hz/48K (LCD Mode)**

- Test Distance : 10 M
- Temperature : 31°C
- Relative Humidity : 65 %
- Test Date : Jun. 11, 1999
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Corrected Reading : Antenna Factor + Cable Loss + Reading = Emission

**The Radiated Emission test was passed at minimum margin**

**179.600 MHz / 26.97 dBuV (HORIZONTAL) Antenna Height 4 Meter, Turntable Degree 27 °.**

Frequency (MHz)	Polarity	Antenna Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Limits		Emission (dBuV/m)	Level (uV/m)	Margin (dB)
					(dBuV/m)	(uV/m)			
64.900	V	5.61	1.00	20.20	30.00	31.62	26.81	21.90	-3.19
113.600	V	11.90	1.04	14.00	30.00	31.62	26.94	22.23	-3.06
122.200	V	12.39	1.19	13.03	30.00	31.62	26.61	21.40	-3.39
147.000	V	10.79	1.34	14.62	30.00	31.62	26.75	21.75	-3.25
179.600	H	9.77	1.50	15.70	30.00	31.62	26.97	22.31	-3.03
212.800	H	9.63	1.62	15.46	30.00	31.62	26.71	21.65	-3.29

Test Engineer : William Lee  
WILLIAM LEE

## 7. Antenna Factor &amp; Cable Loss

Frequency (Mhz)	Antenna Factor (dB)	Cable Loss (dB)
30	16.7	0.6
35	15.5	0.7
40	14.2	0.7
45	11.3	0.8
50	8.4	0.8
55	6.8	0.9
60	5.1	0.9
65	5.6	1.0
70	6.1	0.8
75	6.6	0.8
80	7.2	0.8
85	8.2	1.1
90	9.2	0.9
95	10.0	1.3
100	10.8	1.1
110	11.7	1.1
120	12.4	1.1
130	11.8	1.4
140	10.8	1.2
150	10.8	1.2
160	10.5	1.3
170	10.1	1.5
180	9.7	1.5
190	9.4	1.3
200	9.0	1.4
220	10.0	1.6
240	11.0	1.5
260	11.8	1.6
280	12.3	1.7
300	12.9	1.8
320	13.8	1.8
340	14.8	1.9
360	15.6	2.0
380	16.1	2.1
400	16.6	2.2
450	16.7	2.7
500	17.7	2.0
550	19.0	2.5
600	19.0	2.8
650	18.7	2.8
700	18.7	2.8
750	19.9	2.6
800	21.3	3.1
850	21.4	3.3
900	21.2	3.6
950	22.4	3.7
1000	23.0	3.3
2000	26.4	6.4

## 8. List of Measuring Equipments Used

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver (site 2)	HP	8591EM	3710A01187	9 KHz – 1.8 GHz	Sep. 18, 1998	Conduction
LISN (EUT) (site 2)	Telemeter	NNB-2/16Z	98009	50 ohm / 50 uH	Jan. 22, 1999	Conduction
LISN (Support Unit) (site 2)	EMCO	3810/2NM	9703-1839	50 ohm / 50 uH	Jul. 06, 1998	Conduction
Amplifier (Site 3)	HP	87405A	3207A01437	10MHz –3 0GHz	Jun. 26, 1998	Radiation
Spectrum Analyzer (site 3)	HP	8594A	3051A00172	9KHz --2.9GHz	Apr. 16, 1999	Radiation
Bilog Antenna (Site 3)	CHASE	CBL6112A	2320	30MHz -2GHz	Sep. 10, 1998	Radiation
Half-wave dipole antenna (Site 3)	EMCO	3121C	9705-1285	28M - 1GHz	May 19, 1999	Radiation
Turn Table (site 3)	EMCO	2080	9711-2022	0 ~ 360 degree	N/A	Radiation
Antenna Mast (site 3)	EMCO	2075	9710-2101	1 m - 4 m	N/A	Radiation



SPORTON LAB.

D7O0701

Certificate No:

# CERTIFICATE OF COMPLIANCE

Authorized under Declaration of Conformity  
according to

47 CFR, Part 2 and Part 15 of the FCC Rules


Equipment Under Test : PERSONAL COMPUTER

Model No. : P2L97

Applicant : FIRST INTERNATIONAL COMPUTER INC.

6F, Formosa Plastics Rear Building 201,

Tung Hwa N. Rd., Taipei, Taiwan, R.O.C.



CERTIFY THAT:

THE MEASUREMENTS SHOWN IN THIS TEST REPORT WERE MADE IN ACCORDANCE WITH THE PROCEDURES GIVEN IN ANSI C63.4 - 1992 AND THE ENERGY EMITTED BY THIS EQUIPMENT WAS PASSED BOTH RADIATED AND CONDUCTED EMISSIONS CLASS B LIMITS. THE TESTING WAS COMPLETED ON SEP. 02, 1997 AT SPORTON INTERNATIONAL INC. LAB. IN NEI HWU.

W. L. Huang OCT 02, 97

W. L Huang  
GENERAL MANAGER