



M. Flom Associates, Inc.

International Compliance Testing Laboratory

3356 N. San Marcos Place, Suite 107
Chandler, AZ 85225

toll-free: (866) 311-3268
fax: (480) 926-3598

<http://www.mflom.com>
info@mflom.com

Environmental Assessment

for

Mobiles/Fixed Base Station

FCC ID: FRW2000-UHF1A

Model: P2000-UHF1A UHF/FM (Lo Split) Radio

to

Federal Communications Commission

47 CFR 1.1310 (MPE)

Radiofrequency Radiation Exposure Limits

Date Of Report: June 13, 2005

On the Behalf of the Applicant:

Wulfsberg Electronics Division

At the Request of:

P.O. 19404

Wulfsberg Electronics Division
6400 Wilkinson Drive
Prescott, AZ 86301-6164

Attention of:

Main: (928) 708-1550; Fax: (928) 541-7627
Mary Beaumont, Principal RF Engineer
Direct (928) 708-1543
Email: mary.beaumont@wulfsberg.com

Supervised By:

Michael Findley, Laboratory Manager

Table of Contents

Rule	Description	Page
	Test Report	1
	Identification of the Equipment Under Test	2
	Standard Test Conditions and Engineering Practices	4
1.1310	Environmental Assessment	5

Required information per ISO/IEC Guide 25-1990, paragraph 13.2:

a) **Test Report (Supplemental)**

b) Laboratory: M. Flom Associates, Inc.
(FCC: 31040/SIT) 3356 N. San Marcos Place, Suite 107
(Canada: IC 2044) Chandler, AZ 85225

c) Report Number: d0560023

d) Client: Wulfsberg Electronics Division
6400 Wilkinson Drive
Prescott, AZ 86301-6164

e) Identification: P2000-UHF1A UHF/FM (Lo Split) Radio
Description: FCC ID: FRW2000-UHF1A
Mobile FM

f) EUT Condition: Not required unless specified in individual tests.

g) Report Date: June 13, 2005
EUT Received: June 6, 2005

h, j, k): As indicated in individual tests.

i) Sampling method: No sampling procedure used.

l) Uncertainty: In accordance with MFA internal quality manual.

m) Supervised by:



Michael Findley, Laboratory Manager

n) Results: The results presented in this report relate only to the item tested.

o) Reproduction: This report must not be reproduced, except in full, without written permission from this laboratory.

Identification of the Equipment Under Test (EUT)

Name and Address of Applicant:

Wulfsberg Electronics Division
6400 Wilkinson Drive
Prescott, AZ 86301-6164

Manufacturer:

Wulfsberg Electronics Division
6400 Wilkinson Drive
Prescott, AZ 86301-6164

FCC ID: FRW2000-UHF1A

Model Number: P2000-UHF1A UHF/FM (Lo Split) Radio

Description: Mobile FM Transceiver

Type of Emission: 16K0F3E, 11K0F3E, 8K10F1E, 8K10F1D,
20K0F1E

Frequency Range, MHz: 380.000 to 470.000

Power Rating, Watts: 10.0
☒ Switchable ☐ Variable ☐ N/A

Modulation:

☐	AMPS
☐	TDMA
☐	CDMA
☒	OTHER

Antenna:

☐	Helical
☐	Monopole
☐	Whip
☒	Other

Note: For RF Safety test antenna gain taken at the upper range of expected gain (i.e. 0 dBd) and RF Power set to highest nominal power across all channels.



A2LA

"A2LA has accredited M. Flom Associates, Inc. Chandler, AZ for technical competence in the field of Electrical Testing. The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO/IEC 17025 – 1999 'General Requirements for the Competence of Testing and Calibration Laboratories' and any additional program requirements in the identified field of testing."

Certificate Number: **2152-01**



NIST

I am pleased to inform you that your laboratory has been validated by the Chinese Taipei Bureau of Standards, Metrology and Inspection (BSMI) under the Asia Pacific Economic Cooperation Mutual Recognition Agreement (APEC MRA). Your laboratory is now formally designated to act as a Conformity Assessment Body (CAB) under Appendix B, Phase I Procedures, of the APEC MRA between the American Institute in Taiwan (AIT) and the Taipei Economic and Cultural Representative Office (TECRO) in the United States, covering equipment subject to Electro-Magnetic Compatibility (EMC) requirements. The names of all validated and nominated laboratories will be posted on the NIST website at <http://ts.nist.gov/mra> under the 'Asia' category."

BSMI Number: **SL2-IN-E-041R**

Standard Test Conditions and Engineering Practices

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992/2000, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst-case measurements.

Name of Test:	Environmental Assessment
Specification:	FCC: 47 CFR 1.1310
Measurement Guide:	ANSI/IEEE C95.1 1992
Test Equipment:	Maximum Permissible Exposure (MPE) measurement system, consisting of: AR FP6001 Field Monitor Kit AR FP4000 Software Suite Laptop Computer
Measurement Procedure:	1. The following measurements were performed with a FP6001 probe using ANSI/IEEE C95.1 as a guide. 2. Prior to making any measurements, the measurements system was calibrated in accordance with the manufacturer's procedures. 3. The EUT's radiating element (antenna) was placed on a 1 m tall table for ease of testing. For equipment normally operated on a metal surface, a ground plane was used. 4. The remaining equipment necessary to operate the EUT was maintained at a distance from the measurement arrangement suitable to minimize interference with the measurements. 5. The minimum safe distance was calculated from the formula Power Density = $EIRP / 4\pi R^2$ (Peak Watts/m²). The calculation is shown with the measurement data. 6. With the EUT operating at maximum power, a search was initiated for worst case emissions with the probe raised and lowered over a range of 0.2 to 2 meters in height and over a horizontal plane of 0° to 360°. 7. Average values were calculated for the whole body (0.2-2.0m), lower body (0.2-0.8m) and upper body (1.0-2.0m).
Results:	Attached.

Test Setup: Maximum Permissible Exposure (MPE)



Name of Test: R.F. Radiation Exposure

FCC Rules: 1.1307, 1.1310, 1.1311, 2.1091
Description, EUT: See page 2 of Test Report

Limits: Uncontrolled Exposure 0.3-1.234 MHz: Limit [mW/cm²] = 100
47 CFR 1.1310 1.34-30 MHz: Limit [mW/cm²] = (180/f²)
Table 1, (B) 30-300 MHz: Limit [mW/cm²] = 0.2
300-1500 MHz: Limit [mW/cm²] = f/1500
1500-100,000 MHz: Limit [mW/cm²] = 1.0

Test Frequencies, MHz 380.025 425.025 469.975
Power, Conducted, W = 10.0
Antenna Gain = 3 dBi nominal (0.85 dBd)
Antenna Model AT-462 (Manufactured by Comant)

Pre-test Calculations
 $Power_{[W \text{ EIRP}]} = P_{[conducted]} \times G_{[antenna]} = 10.0 \times 2 \text{ (x50\% Duty Cycle)}$
 $Limit_{[mW/cm^2]} = 0.253, 0.284, 0.313$
 $Limit_{[W/m^2]} = 10 \times Limit_{[mW/cm^2]} = 2.53, 2.84, 3.13$
 $R_{[m]} = [P_{[W \text{ EIRP}]} / (4\pi \times Limit_{[W/m^2]})]^{1/2} = 0.56, 0.53, 0.50$

Results at tested distances	Probe Height, m	Power Density, mW/cm ²		
		Freq. 380 MHz Distance 50 cm	Freq. 425 MHz Distance 50 cm	Freq. 470 MHz Distance 50 cm
	2.0	0.135	0.122	0.120
	1.8	0.175	0.146	0.155
	1.6	0.201	0.182	0.175
	1.4	0.212	0.210	0.201
	1.2	0.235	0.220	0.215
	1.0	0.244	0.231	0.225
	0.8	0.192	0.187	0.190
	0.6	0.170	0.162	0.165
	0.4	0.137	0.125	0.132
	0.2	0.104	0.100	0.099

Power Density Calculations: The measured power density readings were summed and the results divided by the number of readings to calculate the average.

	MHz	MHz	MHz
Whole body average (0.2 - 0.8 m, mW/cm ²) =	0.181	0.169	0.168
Lower body average (0.2 - 0.8 m, mW/cm ²) =	0.151	0.144	0.147
Upper body average (1.0 - 2.0 m, mW/cm ²) =	0.200	0.185	0.182

(The following will be placed in the Instruction Manual)

Mandatory Safety Instructions to Installers & Users

Use only manufacturer or dealer supplied antenna.

Antenna Minimum Safe Distance: 50cm.

Antenna Gain: zero dBd referenced to a dipole.

The Federal Communications Commission has adopted a safety standard for human exposure to RF (Radio Frequency) energy which is below the OSHA (Occupational Safety and Health Act) limits.

Antenna Mounting: The antenna supplied by the manufacturer or radio dealer must not be mounted at a location such that during radio transmission, any person or persons can come closer than the above indicated minimum safe distance to the antenna i.e. **50cm**

To comply with current FCC RF Exposure limits, the antenna must be installed at or exceeding the minimum safe distance shown above, and in accordance with the requirements of the antenna manufacturer or supplier.

Warning: Maintain a separation distance from the antenna to a person(s) of at least **50cm**.

You, as the qualified end-user of this radio device must control the exposure conditions of bystanders to ensure the minimum separation distance (above) is maintained between the antenna and nearby persons for satisfying RF Exposure compliance. The operation of this transmitter must satisfy the requirements of Occupational/Controlled Exposure Environment, for work-related use. Transmit only when person(s) are at least the minimum distance from the properly installed, externally mounted antenna.

**Testimonial
and
Statement of Certification**

This is to certify that:

1. **That** the application was prepared either by, or under the direct supervision of, the undersigned.
2. **That** the technical data supplied with the application was taken under my direction and supervision.
3. **That** the data was obtained on representative units, randomly selected.
4. **That**, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.



Certifying Engineer:

David E. Lee, Quality Assurance Manager