



Stalmart Technology Limited

Addr: Rm1106-1107E, Building F, Xihaimingzhu, No.1, Taoyuan Road, Nanshan, Shenzhen GD 518052 China

04,01,2012

Request for Modular Approval Attestation for the Module (FCC ID: FTOSTTBTM C2BC3)

(i) The radio elements of the modular transmitter must have their own shielding. The physical crystal and tuning capacitors may be located external to the shielded radio elements.

The modular transmitter has its own shielding as shown on the external photo exhibits.

(ii) The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with part 15 requirements under conditions of excessive data rates or over-modulation.

All input/output data are buffered and processed by the onboard miccontroller.

(iii) The modular transmitter must have its own power supply regulation.

There is a 1.8V regulator on the module which provides stable supply voltage to the modular transsitter.

(iv) The modular transmitter must comply with the antenna and transmission system requirements of §§15.203, 15.204(b) and 15.204(c). The antenna must either be permanently attached or employ a “unique” antenna coupler (at all connections between the module and the antenna, including the cable). The “professional installation” provision of §15.203 is not applicable to modules but can apply to limited modular approvals under paragraph (b) of this section.

The modular transmitter has an integral PCB antenna.

(v) The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside an-other device during testing for compliance with part 15 requirements. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in §15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, un-less they will be marketed with the module (see §15.27(a)). The length of these lines shall be the length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified and commercially available

The modular transmitter has been performed the testing as a stand alone and then confirmed the compliance.

(vi) The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number. (A) If using a



Stalmart Technology Limited

Addr: Rm1106-1107E, Building F, Xihaimingzhu, No.1, Taoyuan Road, Nanshan, Shenzhen GD 518052 China

permanently affixed label, the modular transmitter must be labeled with its own FCC identification number, and, if the FCC identification number is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Trans-mitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning may be used. The Grant-ee may either provide such a label, an example of which must be included in the application for equipment author-ization, or, must provide adequate in-structions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization. (B) If the modular transmitter uses an electronic display of the FCC identi-fication number, the information must be readily accessible and visible on the modular transmitter or on the device in which it is installed. If the module is installed inside another device, then the outside of the device into which the module is installed must display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains FCC certified transmitter module(s)." Any similar wording that expresses the same meaning may be used. The user manual must include instructions on how to access the electronic display. A copy of these instructions must be in-cluded in the application for equipment authorization.

The modular transmitter FCC ID will be labeled onto it.

(vii) The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization.

The modular transmitter is compliant with part 15.247. Installation and other requirements are presented in the manual .

(viii) The modular transmitter must comply with any applicable RF exposure requirements in its final configuration.

The modular transmitter had been tested to comply with applicable RF exposure requirements.

Sincerely,

Signature: Nina Sun

Name/Title: Nina SUN / Sales Manager

Company Name: Stalmart Technology Limited.

Address: Rm1106-1107E, Building F, Xihaimingzhu, No.1, Taoyuan Road, Nanshan, Shenzhen Gunagdong 518052 China

TEL: +86-189-2606-3673

FAX: +86 75526667388

Email: stalmart@stalmart.com