



## Compliance Certification Services (Shenzhen) Inc.

Report No: C160317Z04-RP1\_MPE

FCC ID: G3OBWA16AA003

Date of Issue: April 12, 2016

## RADIO FREQUENCY EXPOSURE

### LIMIT

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See §15.247(b)(4) and §1.1307(b)(1) of this chapter.

### Conducted Power Results

Mode	Channel	Frequency(MHz)	Average Conducted Output Power (dBm)
GFSK	00	2402	-9.02
	39	2441	-8.69
	78	2480	-8.33
$\pi/4$ -DQPSK	00	2402	-9.42
	39	2441	-8.86
	78	2480	-8.54
8DPSK	00	2402	-13.04
	39	2441	-12.96
	78	2480	-12.59

### Manufacturing tolerance

GFSK (Average)			
Channel	Channel 00	Channel 39	Channel 78
Target (dBm)	-9.0	-8.0	-8.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
$\pi/4$ -DQPSK (Average)			
Channel	Channel 00	Channel 39	Channel 78
Target (dBm)	-9.0	-8.0	-8.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
8DPSK (Average)			
Channel	Channel 00	Channel 39	Channel 78
Target (dBm)	-13.0	-12.0	-12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0



## Compliance Certification Services (Shenzhen) Inc.

Report No: C160317Z04-RP1\_MPE

FCC ID: G3OBWA16AA003

Date of Issue: April 12, 2016

### EUT Specification

<b>EUT</b>	Mini Stereo System
<b>Frequency band (Operating)</b>	<input type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input checked="" type="checkbox"/> Bluetooth: 2.402GHz~ 2.480GHz <input type="checkbox"/> Others _____
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others _____
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure ( $S = 5mW/cm^2$ ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure ( $S=1mW/cm^2$ )
<b>Antenna diversity</b>	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	-7.0dBm (0.20mW)
<b>Antenna gain (Max)</b>	0dBi (Numeric gain:1.00)
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation
<b>Note:</b>	
1. The maximum output power(including turn tolerance) is <u>-7.0dBm (0.20mW)</u> and maximum antenna gain is <u>1dBi</u>	
2. For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20 cm, even if the calculations indicate that the MPE distance would be lesser.	



## Compliance Certification Services (Shenzhen) Inc.

Report No: C160317Z04-RP1\_MPE    FCC ID: G3OBWA16AA003

Date of Issue: April 12, 2016

## TEST RESULT

*No non-compliance noted.*

### Calculation

$$\text{Given } S = \frac{P \times G}{4\pi d^2} \quad \text{Equation 1}$$

Where  $d$  = distance in cm

$P$  = Power in mW

$G$  = Numeric antenna gain

$S$  = Power Density in mW/cm<sup>2</sup>

### Maximum Permissible Exposure

EUT Output Power=0.20mW

Numeric antenna gain=1.00

Substituting the MPE safe distance using  $d=20$  cm into **Equation 1** :

Fields

The power density  $S = 0.20 \times 1.00 / (4\pi \times 400) \text{ cm}^2 = 3.980891 \text{ e}^{-5} \text{ mW/cm}^2$

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm<sup>2</sup> even if the calculation indicates that the power density would be larger.)