



RF exposure report

For

SKYTEX TECHNOLOGY INC.

1900 Proforma Ave., #F-1, Ontario, CA91761

FCC ID: G4O-SP728

Model Number: SP728

This Report Concerns:	Equipment Type:
Original Report	MID
Test Engineer:	Simon
Report No.:	TMC14030602
Receive EUT	March 01, 2014/
Date/Test Date:	March 01 - March 06, 2014
Reviewed By:	 Michal ling
Prepared By:	Shenzhen WST Testing Technology Co., Ltd. 1F, No.9 Building, TGK Science & Technology Park, Shenzhen Tel: 86-755-33916437 Fax: 86-755-27822175

RF Exposure evaluation

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Worse case is as below: [2412MHz 7.53dBm(5.66mW) output power]

$(5.66\text{mW} / 5\text{mm}) \cdot [\sqrt{2.412(\text{GHz})}] = 1.758 < 3.0$ for 1-g SAR

Then SAR evaluation is not required