

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan  
District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053  
Fax: +86 (0) 755 2671 0594  
Email: ee.shenzhen@sgs.com

Report No.: SZEM120800494601  
Page: 1 of 100

## FCC REPORT

**Application No:** SZEM1208004946RF  
**Applicant:** SKYTEX Technology Inc.  
**Manufacturer:** NEXGEN GLOBAL LIMITED  
**Product Name:** MID PLAYER  
**Model No.(EUT):** SP-438BLK  
**Add Model No.:** SP-438W, SP-438R, SP-438B  
**FCC ID:** G4OSP438  
**Standards:** 47 CFR Part 15, Subpart C (2011)  
**Date of Receipt:** 2012-08-31  
**Date of Test:** 2012-09-25 to 2012-10-16  
**Date of Issue:** 2012-10-25

<b>Test Result:</b>	<b>PASS *</b>
---------------------	---------------

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang  
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

## 2 Test Summary

Test Item	Test Requirement	Test method	Result
<b>Antenna Requirement</b>	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2009	PASS
<b>AC Power Line Conducted Emission</b>	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2009	PASS
<b>Conducted Peak Output Power</b>	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	KDB558074 D01	PASS
<b>6dB Occupied Bandwidth</b>	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	KDB558074 D01	PASS
<b>Power Spectral Density</b>	47 CFR Part 15, Subpart C Section 15.247 (e)	KDB558074 D01	PASS
<b>Band-edge for RF Conducted Emissions</b>	47 CFR Part 15, Subpart C Section 15.247(d)	KDB558074 D01	PASS
<b>RF Conducted Spurious Emissions</b>	47 CFR Part 15, Subpart C Section 15.247(d)	KDB558074 D01	PASS
<b>Radiated Spurious Emissions</b>	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2009	PASS
<b>Band Edge (Radiated Emission)</b>	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2009	PASS

Remark:

Model No.: SP-438BLK, SP-438W, SP-438R, SP-438B

Only the model SP-438BLK was tested, since the electrical circuit design, layout, components used and internal wiring were identical for all above models, with difference being color and model name.

### 3 Contents

	Page
<b>1 COVER PAGE</b> .....	<b>1</b>
<b>2 TEST SUMMARY</b> .....	<b>2</b>
<b>3 CONTENTS</b> .....	<b>3</b>
<b>4 GENERAL INFORMATION</b> .....	<b>4</b>
4.1 CLIENT INFORMATION .....	4
4.2 GENERAL DESCRIPTION OF EUT .....	4
4.3 TEST ENVIRONMENT AND MODE .....	6
4.4 DESCRIPTION OF SUPPORT UNITS .....	6
4.5 TEST LOCATION .....	6
4.6 TEST FACILITY .....	7
4.7 DEVIATION FROM STANDARDS .....	7
4.8 ABNORMALITIES FROM STANDARD CONDITIONS .....	7
4.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	7
4.10 TEST INSTRUMENTS LIST.....	8
<b>5 TEST RESULTS AND MEASUREMENT DATA</b> .....	<b>10</b>
5.1 ANTENNA REQUIREMENT .....	10
5.2 CONDUCTED EMISSIONS .....	11
5.3 CONDUCTED PEAK OUTPUT POWER .....	15
5.4 6dB OCCUPY BANDWIDTH .....	22
5.5 POWER SPECTRAL DENSITY .....	30
5.6 BAND-EDGE FOR RF CONDUCTED EMISSIONS .....	38
5.7 RF CONDUCTED SPURIOUS EMISSIONS .....	43
5.8 RADIATED SPURIOUS EMISSIONS.....	50
5.8.1 <i>Radiated emission below 1GHz</i> .....	53
5.8.2 <i>Transmitter emission above 1GHz</i> .....	55
5.9 BAND EDGE (RADIATED EMISSION) .....	67-100

## 4 General Information

### 4.1 Client Information

Applicant:	SKYTEX Technology Inc.
Address of Applicant:	1900 Proforma Ave., #F1 Ontario, CA 91761
Manufacturer:	NEXGEN GLOBAL LIMITED
Address of Manufacturer:	FLAT/RM 2001 20/F CHINACHEM JOHNSTON PLAZA 186 JOHNSTON ROAD HK

### 4.2 General Description of EUT

Product Name:	MID PLAYER	
Model No.:	SP-438BLK, SP-438W, SP-438R, SP-438B	
Trade Mark:	SKYTEX	
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz	
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels	
Channel Separation:	5MHz	
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK,BPSK)	
Sample Type:	Portable production	
Test Power Grade:	34(manufacturer declare )	
Test Software of EUT:	adb (manufacturer declare )	
Antenna Type:	Integral	
Antenna Gain:	1.5dBi	
Power Supply:	AC Adapter:	Model: GFP051-0505-1 Input: 100-240V~50/60Hz 0.2A max Output: 5V 1000mA
	Battery:	3.7V 1400mAh
Test Voltage:	120V~ 60Hz	

Operation Frequency each of channel(802.11b/g/n HT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Operation Frequency each of channel(802.11n HT40)					
Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2422MHz	4	2437MHz	7	2452MHz
2	2427MHz	5	2442MHz		
3	2432MHz	6	2447MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

For 802.11b/g/n (HT20):

Channel	Frequency
The Lowest channel	2412MHz
The Middle channel	2437MHz
The Highest channel	2462MHz

For 802.11n (HT40):

Channel	Frequency
The Lowest channel	2422MHz
The Middle channel	2437MHz
The Highest channel	2452MHz

### 4.3 Test Environment and Mode

<b>Operating Environment:</b>	
Temperature:	27.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar
<b>Test mode:</b>	
Transmitting mode:	The EUT transmitted the continuous modulation test signal at the specific channel(s).
charge+Transmitting mode:	The EUT transmitted the continuous modulation test signal at the specific channel(s) and AC charge it.

### 4.4 Description of Support Units

The EUT has been tested independent unit.

### 4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,  
No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.  
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

## 4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **VCCI**

The 3m Semi-anechoic chamber, Full-anechoic Chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2197, G-416, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1.

## 4.7 Deviation from Standards

None.

## 4.8 Abnormalities from Standard Conditions

None.

## 4.9 Other Information Requested by the Customer

None.

## 4.10 Test Instruments List

Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	Shielding Room	ZhongYu Electron	GB-88	SEL0042	2013-06-10
2	LISN	Rohde & Schwarz	ENV216	SEL0152	2012-10-23
3	LISN	ETS-LINDGREN	3816/2	SEL0021	2013-5-17
4	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T8-02	SEL0162	2012-11-11
5	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T4-02	SEL0163	2012-11-11
6	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T2-02	SEL0164	2012-11-11
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEL0022	2013-5-17
8	Coaxial Cable	SGS	N/A	SEL0025	2013-05-29
9	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2012-10-23
10	Humidity/ Temperature Indicator	Shanghai Qixiang	ZJ1-2B	SEL0103	2012-10-27
11	Barometer	Chang Chun	DYM3	SEL0088	2013-05-24


RF connected test					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2012-10-23
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2012-10-27
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2012-10-23
4	Coaxial cable	SGS	N/A	SEL0178	2013-05-29
5	Coaxial cable	SGS	N/A	SEL0179	2013-05-29
6	Barometer	ChangChun	DYM3	SEL0088	2013-05-24
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2013-05-17
8	Band filter	amideon	82346	SEL0094	2013-05-17
9	POWER METER	R & S	NRVS	SEL0144	2012-10-23
10	Attenuator	Beijing feihang taida	TST-2-6dB	SEL0205	2013-05-17
11	Power Divider(splitter)	Agilent Technologies	11636B	SEL0130	2012-11-29

RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2013-06-10
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEL0023	2013-05-17
3	EMI Test software	AUDIX	E3	SEL0050	N/A
4	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2012-10-29
5	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2012-10-29
6	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2012-10-29
7	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2013-05-17
8	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2012-11-26
9	Coaxial cable	SGS	N/A	SEL0027	2013-05-59
10	Coaxial cable	SGS	N/A	SEL0189	2013-05-29
11	Coaxial cable	SGS	N/A	SEL0121	2013-05-29
12	Coaxial cable	SGS	N/A	SEL0178	2013-05-29
13	Band filter	Amindeon	82346	SEL0094	2013-05-17
14	Barometer	Chang Chun	DYM3	SEL0088	2013-05-24
15	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2012-10-23
16	Humidity/ Temperature Indicator	Shanghai Qixiang	ZJ1-2B	SEL0103	2012-10-27
17	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2013-05-17
18	Signal Generator	Rohde & Schwarz	SMY01	SEL0155	2012-10-23
19	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2013-06-04

## 5 Test results and Measurement Data


### 5.1 Antenna Requirement

<b>Standard requirement:</b>	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement:	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
15.247(b) (4) requirement:	The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
<b>EUT Antenna:</b>	
	The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 1.5dBi.



## 5.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2009		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)		Limit (dBuV)
			Quasi-peak
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	<ol style="list-style-type: none"><li>1) The mains terminal disturbance voltage test was conducted in a shielded room.</li><li>2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a <math>50\Omega/50\mu\text{H} + 5\Omega</math> linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.</li><li>3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,</li><li>4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.</li><li>5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2009 on conducted measurement.</li></ol>		


Test Setup:	
Test Mode:	charge+Transmitting mode
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass

### Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.


Live Line:



Site : Shielding Room  
 Condition : 47 CFR PART 15 B QP CE LINE  
 Job No : 4946RF  
 Mode : TX

Freq	Cable	LISN	Read	Limit	Over			
	Loss	Factor	Level	Level	Line	Limit	Remark	
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.25000	0.02	9.70	42.00	51.72	61.76	-10.04 QP	
2	0.25000	0.02	9.70	23.00	32.72	51.76	-19.04 Average	
3	0.31700	0.01	9.72	41.00	50.73	59.79	-9.06 QP	
4	0.31700	0.01	9.72	25.00	34.73	49.79	-15.06 Average	
5	0.35600	0.01	9.76	41.00	50.77	58.82	-8.05 QP	
6	0.35600	0.01	9.76	23.00	32.77	48.82	-16.05 Average	
7	0.43600	0.01	9.80	39.00	48.81	57.14	-8.33 QP	
8	0.43600	0.01	9.80	17.00	26.81	47.14	-20.33 Average	
9	0.50300	0.01	9.80	18.00	27.81	46.00	-18.19 Average	
10	0.50300	0.01	9.80	37.00	46.81	56.00	-9.19 QP	
11	0	1.240	0.02	9.80	42.00	51.82	56.00	-4.18 QP
12		1.240	0.02	9.80	29.00	38.82	46.00	-7.18 Average

Neutral Line:




Site : Shielding Room  
Condition : 47 CFR PART 15 B QP CE NEUTRAL  
Job No : 4946RF  
Mode : TX

Freq	Cable	LISN	Read	Limit	Over	Remark	
	Loss	Factor	Level				
	MHz	dB	dB	dBuV	dBuV	dB	
1	0.19300	0.02	9.70	27.00	36.72	53.91	-17.19 Average
2	0.19300	0.02	9.70	41.00	50.72	63.91	-13.19 QP
3	0.23500	0.02	9.70	40.00	49.72	62.27	-12.56 QP
4	0.23500	0.02	9.70	30.00	39.72	52.27	-12.56 Average
5	0.29300	0.01	9.70	41.00	50.71	60.44	-9.73 QP
6	0.29300	0.01	9.70	17.00	26.71	50.44	-23.73 Average
7	0.33300	0.01	9.74	26.00	35.75	49.38	-13.63 Average
8	0.33300	0.01	9.74	41.00	50.75	59.38	-8.63 QP
9	0.56000	0.01	9.80	34.00	43.81	56.00	-12.19 QP
10	0.56000	0.01	9.80	21.00	30.81	46.00	-15.19 Average
11	1.140	0.02	9.80	34.00	43.82	56.00	-12.18 QP
12	1.140	0.02	9.80	20.00	29.82	46.00	-16.18 Average

## Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.

### 5.3 Conducted Peak Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	KDB558074 D01
Test Setup:	
	<i>Remark:</i> <i>Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</i>
Test Instruments:	Refer to section 4.10 for details
Exploratory Test Mode:	Transmitting mode
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6Mbps of rate is the worst case of 802.11n(HT20) ; 6Mbps of rate is the worst case of 802.11n(HT40)
Limit:	30dBm
Test Results:	Pass

Pre-scan under all rate at lowest channel 1								
Mode	802.11b							
Data Rate	1Mbps	2Mbps	5.5Mbps	11Mbps				
Power (dBm)	10.70	10.20	9.81	9.76				
Mode	802.11g							
Data Rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
Power (dBm)	9.13	9.09	8.92	8.88	8.76	8.73	8.69	8.65
Mode	802.11n(HT20)							
Data Rate	6.5Mbps	13Mbps	19.5Mbps	26Mbps	39Mbps	52Mbps	58.5Mbps	65Mbps
Power (dBm)	9.84	9.79	9.72	9.68	9.59	9.51	9.48	9.43
Mode	802.11n(HT40)							
Data Rate	13.5Mbps	27Mbps	40.5Mbps	54Mbps	81Mbps	108Mbps	121.5Mbps	135Mbps
Power	9.95	9.82	9.75	9.63	9.60	9.52	9.46	9.34

Through Pre-scan, 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).

**Measurement Data**

802.11b mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	10.70	30.00	Pass
Middle	10.78	30.00	Pass
Highest	10.58	30.00	Pass

802.11g mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	9.13	30.00	Pass
Middle	9.36	30.00	Pass
Highest	9.94	30.00	Pass


802.11n(HT20)mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	9.84	30.00	Pass
Middle	9.98	30.00	Pass
Highest	10.08	30.00	Pass


802.11n(HT40)mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	9.95	30.00	Pass
Middle	10.19	30.00	Pass
Highest	10.13	30.00	Pass

**Test plot as follows:**


Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------




Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------




Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------




Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------




Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------



Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------



Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------



Test mode:	802.11n(HT20)	Test channel:	Middle
------------	---------------	---------------	--------




Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------




"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."


Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------




Test mode:	802.11n(HT40)	Test channel:	Middle
------------	---------------	---------------	--------



Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------



## 5.4 6dB Occupy Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	KDB558074 D01
Test Setup:	
Instruments Used:	Refer to section 4.10 for details
Exploratory Test Mode:	Transmitting mode
Final Test Mode:	Through Pre-scan, 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).
Limit:	$\geq 500$ kHz
Test Results:	Pass

**Measurement Data**

802.11b mode			
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	10.64	≥500	Pass
Middle	10.56	≥500	Pass
Highest	10.68	≥500	Pass

802.11g mode			
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	16.80	≥500	Pass
Middle	16.62	≥500	Pass
Highest	16.68	≥500	Pass


802.11n(HT20) mode			
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	17.82	≥500	Pass
Middle	17.82	≥500	Pass
Highest	17.76	≥500	Pass


802.11n(HT40) mode			
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	36.00	≥500	Pass
Middle	36.00	≥500	Pass
Highest	36.00	≥500	Pass

**Test plot as follows:**


Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------




Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------




Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------




Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------




Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------




Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------




Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------




Test mode:	802.11n(HT20)	Test channel:	Middle
------------	---------------	---------------	--------




Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------




Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------




Test mode:	802.11n(HT40)	Test channel:	Middle
------------	---------------	---------------	--------



Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------



## 5.5 Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	KDB558074 D01
Test Setup:	 <p><b>Spectrum Analyzer</b>  <b>E.U.T</b>  <b>Non-Conducted Table</b>  <b>Ground Reference Plane</b></p> <p><i>Remark:</i>  <i>Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</i></p>
Test Instruments:	Refer to section 4.10 for details
Exploratory Test Mode:	Transmitting mode
Final Test Mode:	Through Pre-scan, 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).
Limit:	$\leq 8.00 \text{ dBm}$
Test Results:	Pass
Remark:	Scale the observed power level to an equivalent level in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where: $\text{BWCF} = 10 \log (3\text{kHz}/100 \text{ kHz}) = -15.2 \text{ dB}$ .



**Measurement Data**

802.11b mode			
Test channel	Power Spectral Density (dBm)	Limit (dBm)	Result
Lowest	-19.96	≤8.00	Pass
Middle	-19.67	≤8.00	Pass
Highest	-19.95	≤8.00	Pass

802.11g mode			
Test channel	Power Spectral Density (dBm)	Limit (dBm)	Result
Lowest	-26.17	≤8.00	Pass
Middle	-25.83	≤8.00	Pass
Highest	-25.83	≤8.00	Pass


802.11n(HT20) mode			
Test channel	Power Spectral Density (dBm)	Limit (dBm)	Result
Lowest	-28.04	≤8.00	Pass
Middle	-27.75	≤8.00	Pass
Highest	-27.38	≤8.00	Pass


802.11n(HT40) mode			
Test channel	Power Spectral Density (dBm)	Limit (dBm)	Result
Lowest	-30.58	≤8.00	Pass
Middle	-30.11	≤8.00	Pass
Highest	-30.00	≤8.00	Pass

**Test plot as follows:**


Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------




Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------




Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------




Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------




Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------




Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------




Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------




Test mode:	802.11n(HT20)	Test channel:	Middle
------------	---------------	---------------	--------




Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------




Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------




Test mode:	802.11n(HT40)	Test channel:	Middle
------------	---------------	---------------	--------



Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------




## 5.6 Band-edge for RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	KDB558074 D01
Test Setup:	 <p><b>Remark:</b>  <i>Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</i></p>
Exploratory Test Mode:	Transmitting mode
Final Test Mode:	Through Pre-scan, 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass

**Test plot as follows:**


Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------




Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------




Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------




Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------




Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------




Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------




Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------



Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------




## 5.7 RF Conducted Spurious Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	KDB558074 D01
Test Setup:	 <p><b>Remark:</b>  <i>Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</i></p>
Exploratory Test Mode:	Transmitting mode
Final Test Mode:	Through Pre-scan, 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass

**Test plot as follows:**


Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------




Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------




Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------




Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------




Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------




Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------




Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------




Test mode:	802.11n(HT20)	Test channel:	Middle
------------	---------------	---------------	--------




Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------




Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------



Test mode:	802.11n(HT40)	Test channel:	Middle
------------	---------------	---------------	--------



Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------



## 5.8 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 2009				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.					




Test Setup:	
Figure 1. Below 30MHz	
Figure 2. 30MHz to 1GHz	
Figure 3. Above 1 GHz	
Test Procedure:	<ol style="list-style-type: none"> <li>The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters(for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB</li> </ol>

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

	<p>margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p> <p>g. Test the EUT in the lowest channel ,the middle channel ,the Highest channel</p> <p>h. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, Only the test worst case mode is recorded in the report.</p> <p>i. Repeat above procedures until all frequencies measured was complete.</p>
Exploratory Test Mode:	Through Pre-scan Transmitting mode and charge+ Transmitting mode, find the worst case is charge+ Transmitting mode,only the worst case data was recorded in the report.
Final Test Mode:	Through Pre-scan, 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass

### 5.8.1 Radiated emission below 1GHz

30MHz~1GHz (QP)		
Test mode:	Transmitting	Vertical




Condition : 47 CFR PART 15 B 3m 3142C VERTICAL

JOB NO : 4946RF

mode: : TX

	Cable		Antenna	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level			
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	44.550	0.70	9.61	27.31	53.19	36.19	40.00	-3.81
2	141.550	1.30	8.24	26.95	56.78	39.37	43.50	-4.13
3	163.860	1.34	9.56	26.84	54.94	39.00	43.50	-4.50
4	478.140	2.52	17.80	27.60	45.24	37.96	46.00	-8.04
5	812.790	3.26	22.25	27.23	40.54	38.82	46.00	-7.18
6	960.000	3.66	23.60	26.51	41.31	42.06	46.00	-3.94

Test mode:	Transmitting	Horizontal
------------	--------------	------------



Condition : 47 CFR PART 15 B 3m 3142C HORIZONTAL

JOB NO : 4946RF

mode: TX

Freq	Cable		Antenna	Preamp	Read	Limit	Over	
	Loss	Factor	Factor	Level	Level			
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	141.550	1.30	8.24	26.95	48.20	30.80	43.50	-12.70
2	163.860	1.34	9.56	26.84	48.01	32.07	43.50	-11.43
3	234.670	1.60	11.81	26.58	46.96	33.79	46.00	-12.21
4	493.660	2.58	17.80	27.68	38.79	31.48	46.00	-14.52
5	815.700	3.27	22.29	27.20	40.57	38.93	46.00	-7.07
6	959.260	3.66	23.60	26.51	41.76	42.51	46.00	-3.49

**5.8.2 Transmitter emission above 1GHz**

Test mode:		802.11b		Test channel:		Lowest		Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)		Polarization	
1435.431	3.84	28.01	39.33	54.98	47.50	74	-26.50		Vertical	
3026.195	5.09	33.39	40.33	49.56	47.71	74	-26.29		Vertical	
4824.000	7.45	34.68	41.64	56.17	56.66	74	-17.34		Vertical	
5910.798	7.93	35.56	41.01	49.86	52.34	74	-21.66		Vertical	
7099.747	8.58	35.84	39.97	48.71	53.16	74	-20.84		Vertical	
8527.851	9.49	36.23	38.73	47.74	54.73	74	-19.27		Vertical	
1435.431	3.84	28.01	39.33	52.46	44.98	74	-29.02		Horizontal	
1894.450	4.24	31.06	39.52	48.93	44.71	74	-29.29		Horizontal	
3208.660	5.35	33.32	40.45	49.50	47.72	74	-26.28		Horizontal	
4824.000	7.45	34.68	41.64	55.61	56.10	74	-17.90		Horizontal	
7190.687	8.69	35.88	39.89	49.59	54.27	74	-19.73		Horizontal	
10165.290	9.97	37.90	37.51	47.75	58.11	74	-15.89		Horizontal	

Test mode:		802.11b		Test channel:		Lowest		Remark:		Average
Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Over Limit (dB)		Polarization	
1435.431	3.84	28.01	39.33	45.89	38.41	54	-15.59		Vertical	
3026.195	5.09	33.39	40.33	41.24	39.39	54	-14.61		Vertical	
4824.000	7.45	34.68	41.64	45.00	45.49	54	-8.51		Vertical	
5910.798	7.93	35.56	41.01	38.21	40.69	54	-13.31		Vertical	
7099.747	8.58	35.84	39.97	39.61	44.06	54	-9.94		Vertical	
8527.851	9.49	36.23	38.73	41.24	48.23	54	-5.77		Vertical	
1435.431	3.84	28.01	39.33	36.50	29.02	54	-24.98		Horizontal	
1894.450	4.24	31.06	39.52	39.65	35.43	54	-18.57		Horizontal	
3208.660	5.35	33.32	40.45	40.19	38.41	54	-15.59		Horizontal	
4824.000	7.45	34.68	41.64	44.40	44.89	54	-9.11		Horizontal	
7190.687	8.69	35.88	39.89	37.96	42.64	54	-11.36		Horizontal	
10165.290	9.97	37.90	37.51	38.15	48.51	54	-5.49		Horizontal	



# SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM120800494601

Page: 56 of 100

Test mode:		802.11b		Test channel:		Middle		Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)		Polarization	
1435.431	3.84	28.01	39.33	57.27	49.79	74	-24.21		Vertical	
3445.704	5.68	33.22	40.63	49.78	48.05	74	-25.95		Vertical	
4871.103	7.48	34.59	41.68	54.27	54.66	74	-19.34		Vertical	
5850.919	7.91	35.45	41.06	51.36	53.66	74	-20.34		Vertical	
7413.726	8.99	35.97	39.69	49.69	54.96	74	-19.04		Vertical	
8527.851	9.49	36.23	38.73	48.04	55.03	74	-18.97		Vertical	
1435.431	3.84	28.01	39.33	51.05	43.57	74	-30.43		Horizontal	
3143.979	5.27	33.34	40.41	49.67	47.87	74	-26.13		Horizontal	
4874.000	7.48	34.59	41.68	58.62	59.01	74	-14.99		Horizontal	
6109.670	8.01	35.84	40.83	50.13	53.15	74	-20.85		Horizontal	
8104.559	9.36	36.04	39.10	48.75	55.05	74	-18.95		Horizontal	
9370.083	9.65	37.03	37.99	46.15	54.84	74	-19.16		Horizontal	

Test mode:		802.11b		Test channel:		Middle		Remark:		Average
Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Over Limit (dB)		Polarization	
1435.431	3.84	28.01	39.33	46.56	39.08	54	-14.92		Vertical	
3445.704	5.68	33.22	40.63	38.68	36.95	54	-17.05		Vertical	
4871.103	7.48	34.59	41.68	43.65	44.04	54	-9.96		Vertical	
5850.919	7.91	35.45	41.06	42.99	45.29	54	-8.71		Vertical	
7413.726	8.99	35.97	39.69	43.49	48.76	54	-5.24		Vertical	
8527.851	9.49	36.23	38.73	39.86	46.85	54	-7.15		Vertical	
1435.431	3.84	28.01	39.33	40.35	32.87	54	-21.13		Horizontal	
3143.979	5.27	33.34	40.41	37.57	35.77	54	-18.23		Horizontal	
4874.000	7.48	34.59	41.68	43.44	43.83	54	-10.17		Horizontal	
6109.670	8.01	35.84	40.83	38.56	41.58	54	-12.42		Horizontal	
8104.559	9.36	36.04	39.10	37.56	43.86	54	-10.14		Horizontal	
9370.083	9.65	37.03	37.99	37.55	46.24	54	-7.76		Horizontal	

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Test mode:		802.11b		Test channel:	Highest		Remark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
1435.431	3.84	28.01	39.33	56.72	49.24	74	-24.76	Vertical
3588.939	5.88	33.30	40.73	49.31	47.76	74	-26.24	Vertical
4920.955	7.50	34.51	41.71	51.92	52.22	74	-21.78	Vertical
5910.798	7.93	35.56	41.01	50.35	52.83	74	-21.17	Vertical
7547.013	9.14	36.00	39.57	49.29	54.86	74	-19.14	Vertical
10348.050	10.10	38.12	37.59	46.99	57.62	74	-16.38	Vertical
1435.431	3.84	28.01	39.33	43.52	36.04	74	-37.96	Horizontal
3184.250	5.32	33.33	40.44	49.24	47.45	74	-26.55	Horizontal
4096.875	6.59	34.08	41.11	49.95	49.51	74	-24.49	Horizontal
4924.000	7.51	34.51	41.72	58.32	58.62	74	-15.38	Horizontal
6299.178	8.08	36.06	40.66	50.64	54.12	74	-19.88	Horizontal
7941.185	9.31	36.00	39.24	49.10	55.17	74	-18.83	Horizontal

Test mode:		802.11b		Test channel:	Highest		Remark:	Average
Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Over Limit (dB)	Polarization
1435.431	3.84	28.01	39.33	48.56	41.08	54	-12.92	Vertical
3588.939	5.88	33.30	40.73	37.67	36.12	54	-17.88	Vertical
4920.955	7.50	34.51	41.71	43.54	43.84	54	-10.16	Vertical
5910.798	7.93	35.56	41.01	39.48	41.96	54	-12.04	Vertical
7547.013	9.14	36.00	39.57	37.52	43.09	54	-10.91	Vertical
10348.050	10.10	38.12	37.59	34.77	45.40	54	-8.60	Vertical
1435.431	3.84	28.01	39.33	32.19	24.71	54	29.29	Horizontal
3184.250	5.32	33.33	40.44	38.78	36.99	54	-17.01	Horizontal
4096.875	6.59	34.08	41.11	37.65	37.21	54	-16.79	Horizontal
4924.000	7.51	34.51	41.72	42.98	43.28	54	-10.72	Horizontal
6299.178	8.08	36.06	40.66	38.69	42.17	54	-11.83	Horizontal
7941.185	9.31	36.00	39.24	39.48	45.55	54	-8.45	Horizontal



# SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM120800494601

Page: 58 of 100

Test mode:	802.11g		Test channel:		Lowest		Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
1435.431	3.84	28.01	39.33	55.97	48.49	74	-25.51	Vertical	
3241.498	5.40	33.30	40.48	49.32	47.54	74	-26.46	Vertical	
4834.046	7.46	34.65	41.65	54.93	55.39	74	-18.61	Vertical	
5850.919	7.91	35.45	41.06	51.38	53.68	74	-20.32	Vertical	
7547.013	9.14	36.00	39.57	48.16	53.73	74	-20.27	Vertical	
10269.320	10.04	38.02	37.56	46.37	56.87	74	-17.13	Vertical	
1435.431	3.84	28.01	39.33	54.23	46.75	74	-27.25	Horizontal	
1435.431	3.84	28.01	39.33	54.23	46.75	74	-27.25	Horizontal	
3080.601	5.17	33.37	40.37	49.51	47.68	74	-26.32	Horizontal	
4824.700	7.45	34.68	41.64	58.90	59.39	74	-14.61	Horizontal	
6283.164	8.07	36.04	40.68	50.03	53.46	74	-20.54	Horizontal	
8042.903	9.34	36.01	39.15	47.50	53.70	74	-20.30	Horizontal	

Test mode:	802.11g		Test channel:		Lowest		Remark:		Average
Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Over Limit (dB)	Polarization	
1435.431	3.84	28.01	39.33	43.50	36.02	54	-17.98	Vertical	
3241.498	5.40	33.30	40.48	37.40	35.62	54	-18.38	Vertical	
4834.046	7.46	34.65	41.65	43.78	44.24	54	-9.76	Vertical	
5850.919	7.91	35.45	41.06	37.99	40.29	54	-13.71	Vertical	
7547.013	9.14	36.00	39.57	35.58	41.15	54	-12.85	Vertical	
10269.320	10.04	38.02	37.56	33.58	44.08	54	-9.92	Vertical	
1435.431	3.84	28.01	39.33	42.13	34.65	54	-19.35	Horizontal	
3080.601	5.17	33.37	40.37	37.69	35.86	54	-18.14	Horizontal	
4223.950	6.74	34.45	41.21	40.59	40.57	54	-13.43	Horizontal	
4824.700	7.45	34.68	41.64	42.36	42.85	54	-11.15	Horizontal	
6283.164	8.07	36.04	40.68	41.89	45.32	54	-8.68	Horizontal	
8042.903	9.34	36.01	39.15	36.90	43.10	54	-10.90	Horizontal	

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



# SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM120800494601

Page: 59 of 100

Test mode:		802.11g		Test channel:		Middle		Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)		Polarization	
1435.431	3.84	28.01	39.33	53.61	46.13	74	-27.87		Vertical	
3498.735	5.75	33.20	40.67	49.83	48.11	74	-25.89		Vertical	
4874.103	7.48	34.59	41.68	58.50	58.89	74	-15.11		Vertical	
5910.798	7.93	35.56	41.01	50.61	53.09	74	-20.91		Vertical	
7319.964	8.87	35.93	39.77	49.31	54.34	74	-19.66		Vertical	
9370.083	9.65	37.03	37.99	48.21	56.90	74	-17.10		Vertical	
1435.431	3.84	28.01	39.33	54.36	46.88	74	-27.12		Horizontal	
3709.691	6.05	33.45	40.83	49.46	48.13	74	-25.87		Horizontal	
4874.000	7.48	34.59	41.68	58.90	59.29	74	-14.71		Horizontal	
6347.466	8.10	36.12	40.63	49.94	53.53	74	-20.47		Horizontal	
8725.477	9.55	36.37	38.55	49.34	56.71	74	-17.29		Horizontal	
10480.590	10.19	38.28	37.65	47.59	58.41	74	-15.59		Horizontal	

Test mode:		802.11g		Test channel:		Middle		Remark:		Average
Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Over Limit (dB)		Polarization	
1435.431	3.84	28.01	39.33	41.60	34.12	54	-19.88		Vertical	
3498.735	5.75	33.20	40.67	38.45	36.73	54	-17.27		Vertical	
4874.103	7.48	34.59	41.68	45.23	45.62	54	-8.38		Vertical	
5910.798	7.93	35.56	41.01	37.69	40.17	54	-13.83		Vertical	
7319.964	8.87	35.93	39.77	36.89	41.92	54	-12.08		Vertical	
9370.083	9.65	37.03	37.99	35.51	44.20	54	-9.80		Vertical	
1435.431	3.84	28.01	39.33	41.52	34.04	54	-19.96		Horizontal	
3709.691	6.05	33.45	40.83	37.36	36.03	54	-17.97		Horizontal	
4874.000	7.48	34.59	41.68	45.38	45.77	54	-8.23		Horizontal	
6347.466	8.10	36.12	40.63	37.56	41.15	54	-12.85		Horizontal	
8725.477	9.55	36.37	38.55	37.89	45.26	54	-8.74		Horizontal	
10480.590	10.19	38.28	37.65	38.56	49.38	54	-4.62		Horizontal	

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

Test mode:		802.11g		Test channel:		Highest		Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization		
1435.431	3.84	28.01	39.33	53.33	45.85	74	-28.15	Vertical		
3342.042	5.55	33.26	40.55	49.13	47.39	74	-26.61	Vertical		
4455.890	7.03	35.06	41.37	49.23	49.95	74	-24.05	Vertical		
5925.863	7.94	35.59	40.99	51.02	53.56	74	-20.44	Vertical		
7643.683	9.23	36.00	39.49	49.09	54.83	74	-19.17	Vertical		
9346.262	9.65	37.01	38.03	47.11	55.74	74	-18.26	Vertical		
1435.431	3.84	28.01	39.33	48.68	41.20	74	-32.80	Horizontal		
3561.636	5.85	33.28	40.72	49.77	48.18	74	-25.82	Horizontal		
4924.497	7.51	34.51	41.72	54.43	54.73	74	-19.27	Horizontal		
5850.919	7.91	35.45	41.06	50.22	52.52	74	-21.48	Horizontal		
7027.823	8.49	35.81	40.03	49.20	53.47	74	-20.53	Horizontal		
8462.975	9.47	36.19	38.78	47.62	54.50	74	-19.50	Horizontal		

Test mode:		802.11g		Test channel:		Highest		Remark:		Average
Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Over Limit (dB)	Polarization		
1435.431	3.84	28.01	39.33	41.26	33.78	54	-20.22	Vertical		
3342.042	5.55	33.26	40.55	38.54	36.80	54	-17.20	Vertical		
4455.890	7.03	35.06	41.37	34.56	35.28	54	-18.72	Vertical		
5925.863	7.94	35.59	40.99	37.87	40.41	54	-13.59	Vertical		
7643.683	9.23	36.00	39.49	37.88	43.62	54	-10.38	Vertical		
9346.262	9.65	37.01	38.03	34.55	43.18	54	-10.82	Vertical		
1435.431	3.84	28.01	39.33	36.70	29.22	54	-24.78	Horizontal		
3561.636	5.85	33.28	40.72	37.41	35.82	54	-18.18	Horizontal		
4924.497	7.51	34.51	41.72	41.25	41.55	54	-12.45	Horizontal		
5850.919	7.91	35.45	41.06	39.57	41.87	54	-12.13	Horizontal		
7027.823	8.49	35.81	40.03	37.40	41.67	54	-12.33	Horizontal		
8462.975	9.47	36.19	38.78	34.79	41.67	54	-12.33	Horizontal		



"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



# SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM120800494601

Page: 61 of 100

Test mode:		802.11n(HT20)		Test channel:		Lowest		Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)		Polarization	
1435.431	3.84	28.01	39.33	54.13	46.65	74	-27.35		Vertical	
3049.394	5.12	33.38	40.34	49.61	47.77	74	-26.23		Vertical	
4821.757	7.45	34.68	41.64	51.49	51.98	74	-22.02		Vertical	
6299.178	8.08	36.06	40.66	50.16	53.64	74	-20.36		Vertical	
8022.456	9.34	36.01	39.16	48.26	54.45	74	-19.55		Vertical	
9441.913	9.66	37.14	37.94	47.08	55.94	74	-18.06		Vertical	
1435.431	3.84	28.01	39.33	51.16	43.68	74	-30.32		Horizontal	
2957.654	5.02	33.33	40.27	48.50	46.58	74	-27.42		Horizontal	
4223.950	6.74	34.45	41.21	49.74	49.72	74	-24.28		Horizontal	
5865.832	7.92	35.48	41.04	50.33	52.69	74	-21.31		Horizontal	
7413.726	8.99	35.97	39.69	49.27	54.54	74	-19.46		Horizontal	
10269.320	10.04	38.02	37.56	45.81	56.31	74	-17.69		Horizontal	

Test mode:		802.11n(HT20)		Test channel:		Lowest		Remark:		Average
Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Over Limit (dB)		Polarization	
1435.431	3.84	28.01	39.33	39.69	32.21	54	-21.79		Vertical	
3049.394	5.12	33.38	40.34	37.67	35.83	54	-18.17		Vertical	
4821.757	7.45	34.68	41.64	40.78	41.27	54	-12.73		Vertical	
6299.178	8.08	36.06	40.66	38.69	42.17	54	-11.83		Vertical	
8022.456	9.34	36.01	39.16	36.97	43.16	54	-10.84		Vertical	
9441.913	9.66	37.14	37.94	36.57	45.43	54	-8.57		Vertical	
1435.431	3.84	28.01	39.33	37.58	30.10	54	-23.90		Horizontal	
2957.654	5.02	33.33	40.27	35.21	33.29	54	-20.71		Horizontal	
4223.950	6.74	34.45	41.21	40.59	40.57	54	-13.43		Horizontal	
5865.832	7.92	35.48	41.04	37.58	39.94	54	-14.06		Horizontal	
7413.726	8.99	35.97	39.69	37.57	42.84	54	-11.16		Horizontal	
10269.320	10.04	38.02	37.56	32.58	43.08	54	-10.92		Horizontal	

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Test mode:		802.11n(HT20)		Test channel:		Middle		Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)		Polarization	
1435.431	3.84	28.01	39.33	55.93	48.45	74	-25.55		Vertical	
3893.520	6.31	33.68	40.95	49.35	48.39	74	-25.61		Vertical	
5244.295	7.65	34.65	41.58	49.69	50.41	74	-23.59		Vertical	
6956.627	8.41	35.85	40.08	49.37	53.55	74	-20.45		Vertical	
8187.502	9.38	36.08	39.03	48.20	54.63	74	-19.37		Vertical	
10165.290	9.97	37.90	37.51	47.11	57.47	74	-16.53		Vertical	
1435.431	3.84	28.01	39.33	49.51	42.03	74	-31.97		Horizontal	
4024.520	6.50	33.89	41.05	49.55	48.89	74	-25.11		Horizontal	
4871.103	7.48	34.59	41.68	52.02	52.41	74	-21.59		Horizontal	
6428.771	8.12	36.20	40.55	49.81	53.58	74	-20.42		Horizontal	
7941.185	9.31	36.00	39.24	49.09	55.16	74	-18.84		Horizontal	
9562.854	9.67	37.27	37.83	47.26	56.37	74	-17.63		Horizontal	

Test mode:		802.11n(HT20)		Test channel:		Middle		Remark:		Average
Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Over Limit (dB)		Polarization	
1435.431	3.84	28.01	39.33	42.50	35.02	54	-18.98		Vertical	
3893.520	6.31	33.68	40.95	37.57	36.61	54	-17.39		Vertical	
5244.295	7.65	34.65	41.58	37.79	38.51	54	-15.49		Vertical	
6956.627	8.41	35.85	40.08	38.78	42.96	54	-11.04		Vertical	
8187.502	9.38	36.08	39.03	36.87	43.30	54	-10.70		Vertical	
10165.290	9.97	37.90	37.51	35.67	46.03	54	-7.97		Vertical	
1435.431	3.84	28.01	39.33	37.98	30.50	54	-23.50		Horizontal	
4024.520	6.50	33.89	41.05	36.80	36.14	54	-17.86		Horizontal	
4871.103	7.48	34.59	41.68	41.78	42.17	54	-11.83		Horizontal	
6428.771	8.12	36.20	40.55	36.79	40.56	54	-13.44		Horizontal	
7941.185	9.31	36.00	39.24	37.69	43.76	54	-10.24		Horizontal	
9562.854	9.67	37.27	37.83	35.58	44.69	54	-9.31		Horizontal	



Test mode:		802.11n(HT20)		Test channel:		Highest		Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)		Polarization	
1435.431	3.84	28.01	39.33	55.15	47.67	74	-26.33		Vertical	
3738.129	6.11	33.49	40.84	50.19	48.95	74	-25.05		Vertical	
5631.725	7.82	35.09	41.24	50.84	52.51	74	-21.49		Vertical	
7470.558	9.05	35.99	39.64	49.07	54.47	74	-19.53		Vertical	
9538.543	9.67	37.23	37.86	47.05	56.09	74	-17.91		Vertical	
10999.950	10.56	38.50	37.86	47.61	58.81	74	-15.19		Vertical	
1435.431	3.84	28.01	39.33	49.44	41.96	74	-32.04		Horizontal	
3738.129	6.11	33.49	40.84	50.01	48.77	74	-25.23		Horizontal	
4547.561	7.14	35.12	41.44	49.24	50.06	74	-23.94		Horizontal	
5674.896	7.83	35.18	41.20	50.67	52.48	74	-21.52		Horizontal	
6974.358	8.43	35.83	40.08	49.25	53.43	74	-20.57		Horizontal	
9181.198	9.64	36.81	38.16	47.44	55.73	74	-18.27		Horizontal	

Test mode:		802.11n(HT20)		Test channel:		Highest		Remark:		Average
Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Over Limit (dB)		Polarization	
1435.431	3.84	28.01	39.33	43.57	36.09	54	-17.91		Vertical	
3738.129	6.11	33.49	40.84	37.57	36.33	54	-17.67		Vertical	
5631.725	7.82	35.09	41.24	37.80	39.47	54	-14.53		Vertical	
7470.558	9.05	35.99	39.64	37.61	43.01	54	-10.99		Vertical	
9538.543	9.67	37.23	37.86	36.58	45.62	54	-8.38		Vertical	
10999.950	10.56	38.50	37.86	35.25	46.45	54	-7.55		Vertical	
1435.431	3.84	28.01	39.33	37.60	30.12	54	-23.88		Horizontal	
3738.129	6.11	33.49	40.84	41.77	40.53	54	-13.47		Horizontal	
4547.561	7.14	35.12	41.44	36.86	37.68	54	-16.32		Horizontal	
5674.896	7.83	35.18	41.20	37.83	39.64	54	-14.36		Horizontal	
6974.358	8.43	35.83	40.08	36.89	41.07	54	-12.93		Horizontal	
9181.198	9.64	36.81	38.16	36.52	44.81	54	-9.19		Horizontal	



# SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM120800494601

Page: 64 of 100

Test mode:	802.11n(HT40)		Test channel:		Lowest		Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
1435.431	3.84	28.01	39.33	51.84	44.36	74	-29.64	Vertical	
3151.992	5.27	33.34	40.41	49.77	47.97	74	-26.03	Vertical	
4501.492	7.07	35.20	41.40	49.43	50.30	74	-23.70	Vertical	
6156.505	8.03	35.88	40.79	49.26	52.38	74	-21.62	Vertical	
7470.558	9.05	35.99	39.64	48.71	54.11	74	-19.89	Vertical	
10453.950	10.17	38.24	37.64	46.92	57.69	74	-16.31	Vertical	
1435.431	3.84	28.01	39.33	51.03	43.55	74	-30.45	Horizontal	
3588.939	5.88	33.30	40.73	49.00	47.45	74	-26.55	Horizontal	
5022.194	7.55	34.43	41.76	49.69	49.91	74	-24.09	Horizontal	
6428.771	8.12	36.20	40.55	48.95	52.72	74	-21.28	Horizontal	
8377.241	9.44	36.15	38.87	47.89	54.61	74	-19.39	Horizontal	
9960.375	9.83	37.67	37.48	46.66	56.68	74	-17.32	Horizontal	

Test mode:	802.11n(HT40)		Test channel:		Lowest		Remark:		Average
Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Over Limit (dB)	Polarization	
1435.431	3.84	28.01	39.33	40.87	33.39	54	-20.61	Vertical	
3151.992	5.27	33.34	40.41	37.54	35.74	54	-18.26	Vertical	
4501.492	7.07	35.20	41.40	37.40	38.27	54	-15.73	Vertical	
6156.505	8.03	35.88	40.79	36.89	40.01	54	-13.99	Vertical	
7470.558	9.05	35.99	39.64	37.82	43.22	54	-10.78	Vertical	
10453.950	10.17	38.24	37.64	32.36	43.13	54	-10.87	Vertical	
3588.939	5.88	33.30	40.73	34.57	33.02	54	-20.98	Horizontal	
5022.194	7.55	34.43	41.76	37.80	38.02	54	-15.98	Horizontal	
6428.771	8.12	36.20	40.55	37.11	40.88	54	-13.12	Horizontal	
8377.241	9.44	36.15	38.87	35.40	42.12	54	-11.88	Horizontal	
9960.375	9.83	37.67	37.48	37.49	47.51	54	-6.49	Horizontal	
1435.431	3.84	28.01	39.33	40.87	33.39	54	-20.61	Horizontal	

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



# SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM120800494601

Page: 65 of 100

Test mode:	802.11n(HT40)		Test channel:		Middle		Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
1435.431	3.84	28.01	39.33	57.77	50.29	74	-23.71	Vertical	
3184.250	5.32	33.33	40.44	49.52	47.73	74	-26.27	Vertical	
4455.890	7.03	35.06	41.37	50.34	51.06	74	-22.94	Vertical	
6109.670	8.01	35.84	40.83	49.35	52.37	74	-21.63	Vertical	
7190.687	8.69	35.88	39.89	48.29	52.97	74	-21.03	Vertical	
9346.262	9.65	37.01	38.03	48.05	56.68	74	-17.32	Vertical	
1435.431	3.84	28.01	39.33	55.39	47.91	74	-26.09	Horizontal	
3216.838	5.37	33.32	40.47	49.98	48.20	74	-25.80	Horizontal	
4594.102	7.18	35.06	41.47	49.32	50.09	74	-23.91	Horizontal	
5910.798	7.93	35.56	41.01	49.93	52.41	74	-21.59	Horizontal	
7470.558	9.05	35.99	39.64	49.38	54.78	74	-19.22	Horizontal	
9228.060	9.64	36.87	38.13	47.37	55.75	74	-18.25	Horizontal	

Test mode:	802.11n(HT40)		Test channel:		Middle		Remark:		Average
Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Over Limit (dB)	Polarization	
1435.431	3.84	28.01	39.33	45.58	38.10	54	-15.90	Vertical	
3184.250	5.32	33.33	40.44	35.74	33.95	54	-20.05	Vertical	
4455.890	7.03	35.06	41.37	37.86	38.58	54	-15.42	Vertical	
6109.670	8.01	35.84	40.83	34.78	37.80	54	-16.20	Vertical	
7190.687	8.69	35.88	39.89	37.57	42.25	54	-11.75	Vertical	
9346.262	9.65	37.01	38.03	37.61	46.24	54	-7.76	Vertical	
1435.431	3.84	28.01	39.33	42.54	35.06	54	-18.94	Horizontal	
3216.838	5.37	33.32	40.47	37.45	35.67	54	-18.33	Horizontal	
4594.102	7.18	35.06	41.47	37.47	38.24	54	-15.76	Horizontal	
5910.798	7.93	35.56	41.01	34.79	37.27	54	-16.73	Horizontal	
7470.558	9.05	35.99	39.64	37.88	43.28	54	-10.72	Horizontal	
9228.060	9.64	36.87	38.13	39.88	48.26	54	-5.74	Horizontal	

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

Test mode:		802.11n(HT40)		Test channel:		Highest		Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization		
1435.431	3.84	28.01	39.33	55.17	47.69	74	-26.31	Vertical		
3700.260	6.05	33.45	40.81	49.06	47.75	74	-26.25	Vertical		
5073.591	7.57	34.48	41.73	49.27	49.59	74	-24.41	Vertical		
6219.512	8.05	35.96	40.73	49.61	52.89	74	-21.11	Vertical		
8022.456	9.34	36.01	39.16	48.38	54.57	74	-19.43	Vertical		
9562.854	9.67	37.27	37.83	47.42	56.53	74	-17.47	Vertical		
1655.354	4.04	29.33	39.42	51.58	45.53	74	-28.47	Horizontal		
3561.636	5.85	33.28	40.72	50.33	48.74	74	-25.26	Horizontal		
4366.067	6.92	34.83	41.30	50.00	50.45	74	-23.55	Horizontal		
5191.168	7.62	34.60	41.62	50.69	51.29	74	-22.71	Horizontal		
5850.919	7.91	35.45	41.06	50.25	52.55	74	-21.45	Horizontal		
9346.262	9.65	37.01	38.03	43.75	52.38	74	-21.62	Horizontal		
Test mode:		802.11n(HT40)		Test channel:		Highest		Remark:		Average

Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Over Limit (dB)	Polarization
1435.431	3.84	28.01	39.33	42.47	34.99	54	-19.01	Vertical
3700.260	6.05	33.45	40.81	35.87	34.56	54	-19.44	Vertical
5073.591	7.57	34.48	41.73	37.58	37.90	54	-16.10	Vertical
6219.512	8.05	35.96	40.73	37.21	40.49	54	-13.51	Vertical
8022.456	9.34	36.01	39.16	39.64	45.83	54	-8.17	Vertical
9562.854	9.67	37.27	37.83	35.25	44.36	54	-9.64	Vertical
1655.354	4.04	29.33	39.42	44.54	38.49	54	-15.51	Horizontal
3561.636	5.85	33.28	40.72	37.81	36.22	54	-17.78	Horizontal
4366.067	6.92	34.83	41.30	40.09	40.54	54	-13.46	Horizontal
5191.168	7.62	34.60	41.62	41.58	42.18	54	-11.82	Horizontal
5850.919	7.91	35.45	41.06	42.79	45.09	54	-8.91	Horizontal
9346.262	9.65	37.01	38.03	34.49	43.12	54	-10.88	Horizontal

**Remark:**

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

2) The disturbance above 11GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

## 5.9 Band Edge (Radiated Emission)

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10 2009		
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m @3m)	Remark
	30MHz-88MHz	40.0	Quasi-peak Value
	88MHz-216MHz	43.5	Quasi-peak Value
	216MHz-960MHz	46.0	Quasi-peak Value
	960MHz-1GHz	54.0	Quasi-peak Value
	Above 1GHz	54.0	Average Value
		74.0	Peak Value
Test Setup:			




Figure 1. 30MHz to 1GHz





Figure 2. Above 1 GHz

Test Procedure:	<ol style="list-style-type: none"><li>a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</li><li>b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li><li>c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li><li>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</li><li>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li><li>f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel</li><li>g. Test the EUT in the lowest channel , the Highest channel</li><li>h. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.</li><li>i. Repeat above procedures until all frequencies measured was complete.</li></ol>
Exploratory Test Mode:	Transmitting mode
Final Test Mode:	Through Pre-scan, 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass

**Test plot as follows:**

Worse case mode:	802.11b	Test channel:	Lowest	Remark:	Peak	Vertical
------------------	---------	---------------	--------	---------	------	----------




Condition : FCC PART15(&gt;1G) PK 3m VERTICAL

EUT : 4946RF

No. : b 2412 bandedge

		Cable	Antenna	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 0	2390.010	2.98	32.51	39.85	50.85	46.49	74.00	-27.51
2 0	2411.955	2.99	32.54	39.86	107.43	103.10	74.00	29.10

Worse case mode:	802.11b	Test channel:	Lowest	Remark:	Peak	Horizontal
------------------	---------	---------------	--------	---------	------	------------



Condition : FCC PART15(&gt;1G) PK 3m HORIZONTAL

EUT : 4946RF


No. : b 2412 bandegde

		Cable	Antenna	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	0	2390.010	2.98	32.51	39.85	51.44	47.09	74.00 -26.91
2	0	2411.535	2.99	32.54	39.86	107.70	103.37	74.00 29.37



"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

Worse case mode:	802.11b	Test channel:	Lowest	Remark:	Average	Vertical
------------------	---------	---------------	--------	---------	---------	----------




Condition : FCC PART15(>1G) AV 3m VERTICAL

EUT : 4946RF

No. : b 2412 bandedge

	Cable	Antenna	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Level	Level	Line	Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 0	2390.010	2.98	32.51	39.85	39.95	35.60	54.00	-18.40
2 0	2412.795	2.99	32.54	39.86	98.87	94.54	54.00	40.54


Worse case mode:	802.11b	Test channel:	Lowest	Remark:	Average	Horizontal
------------------	---------	---------------	--------	---------	---------	------------



Condition : FCC PART15(>1G) AV 3m HORIZONTAL  
EUT : 4946RF  
No. : b 2412 bandedge

	Freq	Cable		Antenna	Preamp	Read	Limit	Over		
		Loss	Factor	Factor		Level				
	MHz	dB	dB/m			dB	dBuV	dBuV/m	dBuV/m	dB
1 0	2390.010	2.98	32.51	39.85	38.48	34.12	54.00	54.00	-19.88	
2 0	2412.795	2.99	32.54	39.86	95.92	91.59	54.00	54.00	37.59	

Worse case mode:	802.11b	Test channel:	Highest	Remark:	Peak	Vertical
------------------	---------	---------------	---------	---------	------	----------




Condition : FCC PART15(&gt;1G) PK 3m VERTICAL

EUT : 4946RF

No. : b 2462 bandedge

	Freq	Cable Loss	Antenna Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 0	2461.500	3.02	32.64	39.91	108.01	103.77	74.00	29.77
2 0	2483.500	3.03	32.67	39.92	58.05	53.83	74.00	-20.17

Worse case mode:	802.11b	Test channel:	Highest	Remark:	Peak	Horizontal
------------------	---------	---------------	---------	---------	------	------------




Condition : FCC PART15(>1G) PK 3m HORIZONTAL

EUT : 4946RF

No. : b 2462 bandedge

		Cable	Antenna	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	0	2461.900	3.02	32.64	39.91	107.98	103.73	74.00	29.73
2	0	2483.500	3.03	32.67	39.92	57.82	53.60	74.00	-20.40

Worse case mode:	802.11b	Test channel:	Highest	Remark:	Average	Vertical
------------------	---------	---------------	---------	---------	---------	----------




Condition : FCC PART15(>1G) AV 3m VERTICAL

EUT : 4946RF

No. : b 2462 bandedge

	Freq	Cable	Antenna	Preamp	Read	Limit	Over	
		Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 0	2462.700	3.02	32.64	39.91	97.28	93.03	54.00	39.03
2 0	2483.500	3.03	32.67	39.92	47.60	43.38	54.00	-10.62

Worse case mode:	802.11b	Test channel:	Highest	Remark:	Average	Horizontal
------------------	---------	---------------	---------	---------	---------	------------




Condition : FCC PART15(>1G) AV 3m HORIZONTAL

EUT : 4946RF

No. : b 2462 bandedge

	Freq	Cable	Antenna	Preamp	Read	Limit	Line	Over
		Loss	Factor	Factor	Level			Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 0	2462.700	3.02	32.64	39.91	97.70	93.45	54.00	39.45
2 0	2483.500	3.03	32.67	39.92	48.35	44.13	54.00	-9.87

Worse case mode:	802.11g	Test channel:	Lowest	Remark:	Peak	Vertical
------------------	---------	---------------	--------	---------	------	----------




Condition : FCC PART15(&gt;1G) PK 3m VERTICAL

EUT : 4946RF

No. : g 2412 bandedge

	Freq	Cable Loss	Antenna Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit
	MHz	dB	dB/m		dBuV	dBuV/m	dBuV/m	dB
1	2390.080	2.98	32.51	39.85	56.62	52.27	74.00	-21.73
2	2415.050	2.99	32.54	39.86	101.32	97.00	74.00	23.00

Worse case mode:	802.11g	Test channel:	Lowest	Remark:	Peak	Horizontal
------------------	---------	---------------	--------	---------	------	------------




Condition : FCC PART15(>1G) PK 3m HORIZONTAL

EUT : 4946RF

No. : g 2412 bandedge

	Freq	Cable	Antenna	Preamp	Read	Limit	Over	
		Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.080	2.98	32.51	39.85	53.08	48.73	74.00	-25.27
2	2415.050	2.99	32.54	39.86	100.17	95.84	74.00	21.84

Worse case mode:	802.11g	Test channel:	Lowest	Remark:	Average	Vertical
------------------	---------	---------------	--------	---------	---------	----------




Condition : FCC PART15(>1G) AV 3m VERTICAL

EUT : 4946RF

No. : g 2412 bandedge

		Cable	Antenna	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.080	2.98	32.51	39.85	39.22	34.87	54.00	-19.13
2	2415.380	2.99	32.54	39.86	90.38	86.05	54.00	32.05

Worse case mode:	802.11g	Test channel:	Lowest	Remark:	Average	Horizontal
------------------	---------	---------------	--------	---------	---------	------------



Condition : FCC PART15(>1G) AV 3m HORIZONTAL

EUT : 4946RF


No. : g 2412 bandedge

	Freq	Cable	Antenna	Preamp	Read	Limit	Over	
		Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.080	2.98	32.51	39.85	36.86	32.50	54.00	-21.50
2	2415.490	2.99	32.54	39.86	85.38	81.06	54.00	27.06



"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

Worse case mode:	802.11g	Test channel:	Highest	Remark:	Peak	Vertical
------------------	---------	---------------	---------	---------	------	----------




Condition : FCC PART15(&gt;1G) PK 3m VERTICAL

EUT : 4946RF

No. : g 2462 bandedge

Freq	Cable	Antenna	Preamp	Read	Limit	Over		
	Loss	Factor	Factor	Level				
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2465.150	3.02	32.64	39.91	103.06	98.82	74.00	24.82
2	2483.500	3.03	32.67	39.92	67.44	63.22	74.00	-10.78

Worse case mode:	802.11g	Test channel:	Highest	Remark:	Peak	Horizontal
------------------	---------	---------------	---------	---------	------	------------




Condition : FCC PART15(>1G) PK 3m HORIZONTAL

EUT : 4946RF

No. : g 2462 bandedge

	Freq	Cable Loss	Antenna Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 0	2456.300	3.01	32.64	39.91	101.62	97.36	74.00	23.36
2	2483.500	3.03	32.67	39.92	66.24	62.02	74.00	-11.98

Worse case mode:	802.11g	Test channel:	Highest	Remark:	Average	Vertical
------------------	---------	---------------	---------	---------	---------	----------




Condition : FCC PART15(&gt;1G) AV 3m VERTICAL

EUT : 4946RF

No. : g 2462 bandedge

		Cable	Antenna	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	0	2465.350	3.02	32.64	39.91	92.25	88.00	54.00	34.00
2		2483.500	3.03	32.67	39.92	50.89	46.67	54.00	-7.33

Worse case mode:	802.11g	Test channel:	Highest	Remark:	Average	Horizontal
------------------	---------	---------------	---------	---------	---------	------------




Condition : FCC PART15(>1G) AV 3m HORIZONTAL

EUT : 4946RF

No. : g 2462 bandedge

	Freq	Cable		Antenna	Preamp	Read	Limit	Over
		Loss	Factor	Factor	Level	Level		
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 0	2457.300	3.02	32.64	39.91	84.22	79.97	54.00	25.97
2	2483.500	3.03	32.67	39.92	41.88	37.66	54.00	-16.34

Worse case mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Peak	Vertical
------------------	---------------	---------------	--------	---------	------	----------




Condition : FCC PART15(>1G) PK 3m VERTICAL

EUT : 4946RF

No. : n(ht20) 2412 bandedge

Freq	Cable		Antenna	Preamp	Read	Limit	Over	
	Loss	Factor	Factor	Level	Level			
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.080	2.98	32.51	39.85	55.05	50.69	74.00	-23.31
2	2407.570	2.99	32.54	39.86	100.26	95.93	74.00	21.93

Worse case mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Peak	Horizontal
------------------	---------------	---------------	--------	---------	------	------------



Condition : FCC PART15(>1G) PK 3m HORIZONTAL

EUT : 4946RF

No. : n(ht20) 2412 bandedge

	Cable	Antenna	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Level	Level	Line	Limit

	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
--	-----	----	------	----	------	--------	--------	----

1	2390.080	2.98	32.51	39.85	52.08	47.72	74.00	-26.28
2 X	2407.570	2.99	32.54	39.86	96.39	92.07	74.00	18.07

Worse case mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Average	Vertical
------------------	---------------	---------------	--------	---------	---------	----------




Condition : FCC PART15(>1G) AV 3m VERTICAL

EUT : 4946RF

No. : n(ht20) 2412 bandedge

	Freq	Cable		Antenna	Preamp	Read	Limit	Over	
		Loss	Factor	Factor	Level	Level	Line	Limit	
	MHz	dB	dB/m		dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.080	2.98	32.51	39.85	40.12	35.76	54.00	-18.24	
2	2415.930	2.99	32.54	39.88	89.73	85.39	54.00	31.39	

Worse case mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Average	Horizontal
------------------	---------------	---------------	--------	---------	---------	------------




Condition : FCC PART15(>1G) AV 3m HORIZONTAL

EUT : 4946RF

No. : n(ht20) 2412 bandedge

	Freq	Cable Loss	Antenna Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.080	2.98	32.51	39.85	38.28	33.93	54.00	-20.07
2	2415.930	2.99	32.54	39.88	86.31	81.97	54.00	27.97

Worse case mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Peak	Vertical
------------------	---------------	---------------	---------	---------	------	----------




Condition : FCC PART15(>1G) PK 3m VERTICAL

EUT : 4946RF

No. : n(ht20) 2462 bandedge

		Cable	Antenna	Preamp	Read	Limit	Over		
		Freq	Loss	Factor	Level	Level	Line	Limit	
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	0	2457.610	3.02	32.64	39.91	102.68	98.43	74.00	24.43
2		2483.485	3.03	32.67	39.92	70.48	66.26	74.00	-7.74

Worse case mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Peak	Horizontal
------------------	---------------	---------------	---------	---------	------	------------

**Data: 21**
**Level (dBuV/m)**

**Condition** : FCC PART15(>1G) PK 3m HORIZONTAL


**EUT** : 4946RF

**No.** : n(ht20) 2462 bandedge

	Freq	Cable	Antenna	Preamp	Read	Limit	Over	
		Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2457.430	3.02	32.64	39.91	100.65	96.40	74.00	22.40
2	2483.530	3.03	32.67	39.92	67.65	63.43	74.00	-10.57



Worse case mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Average	Vertical
------------------	---------------	---------------	---------	---------	---------	----------




Condition : FCC PART15(>1G) AV 3m VERTICAL

EUT : 4946RF

No. : n(ht20) 2462 bandedge

	Freq	Cable	Antenna	Preamp	Read	Limit	Over	
		Loss	Factor	Factor	Level			
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2457.250	3.02	32.64	39.91	88.63	84.39	54.00	30.39
2	2483.530	3.03	32.67	39.92	48.66	44.44	54.00	-9.56

Worse case mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Average	Horizontal
------------------	---------------	---------------	---------	---------	---------	------------




Condition : FCC PART15(>1G) AV 3m HORIZONTAL

EUT : 4946RF

No. : n(ht20) 2462 bandedge

Freq	Cable		Antenna	Preamp	Read	Limit	Over	
	Loss	Factor	Factor	Level	Level			
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	0	2465.935	3.02	32.64	39.91	82.61	78.36	54.00 24.36
2		2483.530	3.03	32.67	39.92	46.71	42.50	54.00 -11.50

Worse case mode:	802.11n(HT40)	Test channel:	Lowest	Remark:	Peak	Vertical
------------------	---------------	---------------	--------	---------	------	----------




Condition : FCC PART15(&gt;1G) PK 3m VERTICAL

EUT : 4946RF

No. : n(ht40)2422 bandedge

	Freq	Cable Loss	Antenna Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.080	2.98	32.51	39.85	59.10	54.75	74.00	-19.25
2 X	2436.230	3.00	32.58	39.89	95.18	90.86	74.00	16.86

Worse case mode:	802.11n(HT40)	Test channel:	Lowest	Remark:	Peak	Horizontal
------------------	---------------	---------------	--------	---------	------	------------




Condition : FCC PART15(>1G) PK 3m HORIZONTAL

EUT : 4946RF

No. : n(ht40)2422 bandedge

	Cable	Antenna	Preamp	Read	Limit	Over		
	Freq	Loss	Factor	Level	Level	Line	Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.080	2.98	32.51	39.85	60.55	56.20	74.00	-17.80
2	2432.590	3.00	32.58	39.88	97.22	92.92	74.00	18.92


Worse case mode:	802.11n(HT40)	Test channel:	Lowest	Remark:	Average	Vertical
------------------	---------------	---------------	--------	---------	---------	----------



Condition : FCC PART15(>1G) AV 3m VERTICAL  
EUT : 4946RF  
No. : n(ht40)2422 bandedge

	Freq	Cable Loss	Antenna Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m		dBuV	dBuV/m	dBuV/m	dB
1	2390.080	2.98	32.51	39.85	42.40	38.05	54.00	-15.95
2	2425.700	3.00	32.58	39.88	80.23	75.92	54.00	21.92

Worse case mode:	802.11n(HT40)	Test channel:	Lowest	Remark:	Average	Horizontal
------------------	---------------	---------------	--------	---------	---------	------------




Condition : FCC PART15(>1G) AV 3m HORIZONTAL

EUT : 4946RF

No. : n(ht40)2422 bandedge

	Freq	Cable		Antenna	Preamp	Read	Limit	Over
		Loss	Factor	Factor	Level	Level		
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.080	2.98	32.51	39.85	43.16	38.81	54.00	-15.19
2	2412.310	2.99	32.54	39.86	80.22	75.89	54.00	21.89

Worse case mode:	802.11n(HT40)	Test channel:	Highest	Remark:	Peak	Vertical
------------------	---------------	---------------	---------	---------	------	----------




Condition : FCC PART15(>1G) PK 3m VERTICAL

EUT : 4946RF

No. : n(ht40)2452 bandedge

	Freq	Cable	Antenna	Preamp	Read	Limit	Over	
		Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2462.300	3.02	32.64	39.91	100.52	96.28	74.00	22.28
2	2483.500	3.03	32.67	39.92	73.14	68.93	74.00	-5.07

Worse case mode:	802.11n(HT40)	Test channel:	Highest	Remark:	Peak	Horizontal
------------------	---------------	---------------	---------	---------	------	------------



Condition : FCC PART15(>1G) PK 3m HORIZONTAL

EUT : 4946RF


No. : n(ht40)2452 bandedge

	Freq	Cable	Antenna	Preamp	Read	Limit	Over	
		Loss	Factor	Factor	Level			
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 0	2462.300	3.02	32.64	39.91	100.47	96.22	74.00	22.22
2	2483.500	3.03	32.67	39.92	71.58	67.36	74.00	-6.64

Worse case mode:	802.11n(HT40)	Test channel:	Highest	Remark:	Average	Vertical
------------------	---------------	---------------	---------	---------	---------	----------

Data: 32

Level (dBuV/m)




Condition : FCC PART15(&gt;1G) AV 3m VERTICAL

EUT : 4946RF

No. : n(ht40)2452 bandedge

	Freq	Cable		Antenna	Preamp	Read	Limit	Over	
		Loss	Factor	Factor	Level	Level			
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	0	2467.750	3.02	32.64	39.91	83.84	79.59	54.00	25.59
2		2483.500	3.03	32.67	39.92	55.09	50.87	54.00	-3.13

Worse case mode:	802.11n(HT40)	Test channel:	Highest	Remark:	Average	Horizontal
------------------	---------------	---------------	---------	---------	---------	------------



Condition : FCC PART15(>1G) AV 3m HORIZONTAL

EUT : 4946RF

No. : n(ht40)2452 bandedge

	Freq	Cable		Antenna	Preamp	Read	Limit	Over
		Loss	Factor	Factor	Level	Level		
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2450.150	3.01	32.61	39.89	89.02	84.74	54.00	30.74
2	2483.500	3.03	32.67	39.92	55.04	50.82	54.00	-3.18

**Note:**

*The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:*

*Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor*

