

Prüfbericht - Nr.: 14030055 001		Seite 1 von 17	
<i>Test Report No.:</i>		<i>Page 1 of 17</i>	
Auftraggeber: <i>Client:</i>		G-star industrial Co., Ltd. 3F, No.646, Sec.5, Chunghsin Rd. Sanchong District New Taipei City Taiwan	
Gegenstand der Prüfung: <i>Test Item:</i>		Bluetooth Wireless Headphone	
Bezeichnung: <i>Identification:</i>	BT-020	Serien-Nr.: <i>Serial No.:</i>	Engineering sample
Wareneingangs-Nr.: <i>Receipt No.:</i>	00120518017-004	Eingangsdatum: <i>Date of Receipt:</i>	18.05.2012
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of test item at delivery:</i>		Test samples received are sufficient for testing and not damaged.	
Prüfört: <i>Testing Location:</i>		Hong Kong Productivity Council HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong TÜV Rheinland Hong Kong Ltd. 8/F., First Group Centre, 14 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong	
Prüfgrundlage: <i>Test Specification:</i>		FCC Part 15 Subpart C ANSI C63.4-2003 CISPR 22:1997	
Prüfergebnis: <i>Test Results:</i>		Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben genannter Prüfgrundlage. The above mentioned product was tested and passed .	
Prüflaboratorium: <i>Testing Laboratory:</i>		TÜV Rheinland Hong Kong Ltd. 8 - 10/F., Goldin Financial Global Square, 7 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong	
geprüft/ tested by:		kontrolliert/ reviewed by:	
13.06.2012 Mika Chan Senior Project Engineer		13.06.2012 Sharon Li Section Manager	
Datum <i>Date</i>	Name/Stellung <i>Name/Position</i>	Unterschrift <i>Signature</i>	Datum <i>Date</i>
			
Sonstiges: <i>Other Aspects</i>		FCCID: G6OBT-020	
Abkürzungen: <i>P(ass) = entspricht Prüfgrundlage</i> <i>F(ail) = entspricht nicht Prüfgrundlage</i> <i>N/A = nicht anwendbar</i> <i>N/T = nicht getestet</i>		Abbreviations: <i>P(ass) = passed</i> <i>F(ail) = failed</i> <i>N/A = not applicable</i> <i>N/T = not tested</i>	
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.</i>			

Table of Content

	Page
Cover Page	1
Table of Content	2
Product information	4
Manufacturers declarations.....	4
Product function and intended use	5
Submitted documents.....	5
Remark.....	5
Special accessories and auxiliary equipment	5
List of Test and Measurement Instruments.....	6
Results FCC Part 15 – Subpart C	7
Subclause 15.203 – Antenna Information.....	Pass7
Subclause 15.204 – Antenna Information.....	Pass7
Subclause 15.207 – Disturbance Voltage on AC Mains	Pass7
Subclause 15.247 (a)(1) – Carrier Frequency Separation	Pass8
Subclause 15.247 (a)(1)(iii) – Number of hopping channels	Pass8
Subclause 15.247 (a)(1)(iii) – Time of Occupancy (Dwell Time).....	Pass9
Subclause 15.247 (a) – 20 dB Bandwidth.....	Pass10
Subclause 15.247 (a) – Hopping Sequence.....	Pass11
Subclause 15.247 (a) – Equal Hopping Frequency Use	Pass12
Subclause 15.247 (a) – Receiver Input Bandwidth.....	Pass13
Subclause 15.247 (a) – Receiver Hopping Capability	Pass13
Subclause 15.247 (b)(1) – Peak Output Power.....	Pass13
Subclause 15.247 (d) – Band edge compliance of conducted emissions	Pass14
Subclause 15.205 – Band edge compliance of radiated emissions	Pass14
Subclause 15.247 (d) – Spurious Conducted Emissions.....	Pass15
Subclause 15.247 (c) – Spurious Radiated Emissions	Pass16

Appendix 1 – Test protocols	26 pages
Appendix 2 – Test setup	3 pages
Appendix 3 – Photo documentation	8 pages
Appendix 4 – Product documentation	11 pages

Product information

Manufacturers declarations

	Transceiver
Operating frequency range	2402 - 2480 MHz
Type of modulation	GFSK; Pi/4 DQPSK; 8 DPSK
Number of channels	79
Channel separation	1 MHz
Type of antenna	PCB Antenna
Antenna gain (dBi)	1.2
Power level	fix
Type of equipment	stand alone radio device
Connection to public utility power line	No
Nominal voltage	V_{nor} : 3.7V
Independent Operation Modes	Page scan Inquiry scan Connection state - ACL Link Connection state - SCO Link

Product function and intended use

The test item is a Bluetooth wireless headphone based on the Bluetooth technology.

Bluetooth is a short-range radio link intended to be a cable replacement between portable and/or fixed electronic devices.

Bluetooth operates in the unlicensed ISM Band at 2.4GHz. With the introduction of the enhanced data rate (EDR) feature, the data rates can be up to 3 Mb/s.

An increase in the peak data rate beyond the basic rate of 1 Mb/s is achieved by modulating the RF carrier using phase shift keying (PSK) techniques, resulting in an increase of two to three times the number of bits per symbol. The 2 Mb/s EDR packets use a Pi/4-DQPSK modulation and the 3 Mb/s EDR packets use 8DPSK modulation. The USB connector is for charging only, no data exchange supported.

Submitted documents

Circuit Diagram
Block Diagram
Bill of material
User Manual
Label Artwork

Remark

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases.

Special accessories and auxiliary equipment

IBM Laptop Computer
Model: T40
SN: TZ04C57204a

AC/DC Adapter
Model: 08K8202
Input: 100-240VAC, 1.5-0.9A
Output: 16VDC, 4.5A

List of Test and Measurement Instruments

Hong Kong Productivity Council (Registration number: 90656)

Equipment	Manufacturer	Type	S/N	Due Date
Semi-anechoic Chamber	Frankonia	Nil	Nil	12-Apr-13
Test Receiver	R & S	ESU26	100050	05-Jan-13
Bi-conical Antenna	R & S	HK116	100241	05-May-13
Log Periodic Antenna	R & S	HL223	841516/020	06-May-13
Coaxial cable 50ohm	Rosenberger	RTK081-05S-05S-10m	LA2-001-10M / 001	15-Nov-13
Microwave amplifier 0.5-26.5GHz, 25dB gain	HP	83017A	3950M00241	03-Oct-13
High Pass Filter (cutoff freq. =1000MHz)	Trilithic	23042	9829213	30-Oct-13
Horn Antenna	EMCO	3115	9002-3351	11-May-13
FSP 30 Spectrum Analyser	R & S	FSP 30	100286	17-Sep-12
Active Loop Antenna	EMCO	6502	9107-2651	05-May-13

Results FCC Part 15 – Subpart C

Subclause 15.203 – Antenna Information		Pass
Requirement:	No antenna other than that furnished by the responsible party shall be used with the device	
Results:	Permanent attached antenna	
Verdict:	Pass	

Subclause 15.204 – Antenna Information		Pass
Requirement:	Provide information for every antenna proposed for the use with the EUT	
Results:	a) Antenna type: PCB antenna b) Manufacturer and model no: N.A. c) Gain with reference to an isotropic radiator: 1.2 dBi	
Verdict:	Pass	

Subclause 15.207 – Disturbance Voltage on AC Mains						Pass
Test Port: Laptop Computer AC Adaptor Applied voltage: 120VAC Mode of operation: Charging and Music playing Mode						
Live measurement						
Frequency range (MHz)	Frequency (MHz)	Quasi-peak (dBµV)	Average (dBµV)	Limit QP (dBµV)	Limit AV (dBµV)	Verdict
0,15 – 0,5	0.150	55.3	23.0	66 - 56	56 - 46	Pass
> 0,5 - 5	0.252	50.9	29.7	56	46	Pass
	1.626	35.4	35.3	56	46	Pass
> 5 - 30	---	---	---	60	50	Pass
Neutral measurement						
Frequency range (MHz)	Frequency (MHz)	Quasi-peak (dBµV)	Average (dBµV)	Limit QP (dBµV)	Limit AV (dBµV)	Verdict
0,15 – 0,5	0.186	56.2	36.8	66 - 56	56 - 46	Pass
> 0,5 - 5	0.378	43.3	23.7	56	46	Pass
	3.150	30.5	27.4	56	46	Pass
> 5 - 30	---	---	---	60	50	Pass
Results: The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150kHz to 30MHz does not exceed the limits. For test Results plots refer to Appendix 1, page 2-3.						

Subclause 15.247 (a)(1) – Carrier Frequency Separation		Pass
Requirement:	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 2/3*20dB bandwidth of the hopping channel, whichever is greater.	
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (hopping on), 8DPSK Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 1 MHz / 3 MHz Supply voltage : 3.7VDC from DC power supply Temperature : 23°C Humidity : 50%		
Results:	Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types. The centre frequencies of the hopping channels are separated by more than the 2/3*20dB bandwidth. For test Results plots refer to Appendix 1, page 4.	
Verdict:	Pass	

Subclause 15.247 (a)(1)(iii) – Number of hopping channels		Pass
Requirement:	Frequency hopping systems operating in the 2400MHz-2483.5MHz bands shall use at least 15 hopping frequencies.	
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (hopping on), 8DPSK Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 1 MHz / 3 MHz Supply voltage : 3.7VDC from DC power supply Temperature : 23°C Humidity : 50%		
Results:	The total number of hopping frequencies is more than 15. For test Results plots refer to Appendix 1, page 5.	
Verdict:	Pass	

Subclause 15.247 (a)(1)(iii) – Time of Occupancy (Dwell Time)		Pass
Requirement:	Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.	
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (hopping on), DH5 packet Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 1 MHz / 3 MHz Supply voltage : 3.7VDC from DC power supply Temperature : 23°C Humidity : 50%		
Results: Time period calculation = $0.4 \times 79 = 31.6\text{s}$ Dwell time = $64 \times 2.912 \times 10^{-3} = 186.37 \times 10^{-3} \text{ s}$ $\leq 400 \times 10^{-3} \text{ s}$ For test protocols please refer to Appendix 1, page 6.		
Verdict:	Pass	


Subclause 15.247 (a) – 20 dB Bandwidth		Pass	
Requirement:	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 2/3*20dB bandwidth of the hopping channel, whichever is greater.		
Test Specification :	FCC Part 15 Subpart A – Subclause 15.31		
Mode of operation :	Tx mode (2402MHz, 2441MHz, 2480MHz)		
Port of testing :	Temporary antenna port		
Detector :	Peak		
RBW/VBW :	30 kHz / 100 kHz		
Supply voltage :	3.7VDC from DC power supply		
Temperature :	23°C		
Humidity :	50%		
Results:	Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types. For test protocols refer to Appendix 1, page 7-9.		
GFSK Modulation			
Frequency (MHz)	20 dB left (MHz)	20 dB right (MHz)	20dB bandwidth (MHz)
2402	0.456	0.492	0.948
2441	0.462	0.486	0.948
2480	0.468	0.552	1.020
8DPSK Modulation			
Frequency (MHz)	20 dB left (MHz)	20 dB right (MHz)	20dB bandwidth (MHz)
2402	0.654	0.630	1.284
2441	0.642	0.624	1.266
2480	0.642	0.624	1.266

Subclause 15.247 (a) – Hopping Sequence
Pass

Requirement: The hopping sequence is generated and provided with an example.

Hopping sequence

The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master. The X input determines the phase in the 32-hop segment, whereas Y1 and Y2 selects between master-to-slave and slave-to-master transmission. The inputs A to D determine the ordering within the segment, the inputs E and F determine the mapping onto the hop frequencies.



Example data:

Hop sequence {k} for CONNECTION STATE:

CLK start: 0x0000010

ULAP: 0x00000000

#ticks: 00 02 | 04 06 | 08 0a | 0c 0e | 10 12 | 14 16 | 18 1a | 1c 1e |

0x0000010:	08 66	10 70	12 19	14 23	16 01	18 05	20 33	22 37
0x0000030:	24 03	26 07	28 35	30 39	32 72	34 76	36 25	38 29
0x0000050:	40 74	42 78	44 27	46 31	48 09	50 13	52 41	54 45
0x0000070:	56 11	58 15	60 43	62 47	32 17	36 19	34 49	38 51
0x0000090:	40 21	44 23	42 53	46 55	48 33	52 35	50 65	54 67
0x00000b0:	56 37	60 39	58 69	62 71	64 25	68 27	66 57	70 59
0x00000d0:	72 29	76 31	74 61	78 63	01 41	05 43	03 73	07 75
0x00000f0:	09 45	13 47	11 77	15 00	64 49	66 53	68 02	70 06
0x0000110:	01 51	03 55	05 04	07 08	72 57	74 61	76 10	78 14
0x0000130:	09 59	11 63	13 12	15 16	17 65	19 69	21 18	23 22
0x0000150:	33 67	35 71	37 20	39 24	25 73	27 77	29 26	31 30
0x0000170:	41 75	43 00	45 28	47 32	17 02	21 04	19 34	23 36
0x0000190:	33 06	37 08	35 38	39 40	25 10	29 12	27 42	31 44
0x00001b0:	41 14	45 16	43 46	47 48	49 18	53 20	51 50	55 52
0x00001d0:	65 22	69 24	67 54	71 56	57 26	61 28	59 58	63 60
0x00001f0:	73 30	77 32	75 62	00 64	49 34	51 42	57 66	59 74
0x0000210:	53 36	55 44	61 68	63 76	65 50	67 58	73 03	75 11
0x0000230:	69 52	71 60	77 05	00 13	02 38	04 46	10 70	12 78
0x0000250:	06 40	08 48	14 72	16 01	18 54	20 62	26 07	28 15
0x0000270:	22 56	24 64	30 09	32 17	02 66	06 74	10 19	14 27
0x0000290:	04 70	08 78	12 23	16 31	18 03	22 11	26 35	30 43
0x00002b0:	20 07	24 15	28 39	32 47	34 68	38 76	42 21	46 29
0x00002d0:	36 72	40 01	44 25	48 33	50 05	54 13	58 37	62 45
0x00002f0:	52 09	56 17	60 41	64 49	34 19	36 35	50 51	52 67
0x0000310:	38 21	40 37	54 53	56 69	42 27	44 43	58 59	60 75
0x0000330:	46 29	48 45	62 61	64 77	66 23	68 39	03 55	05 71
0x0000350:	70 25	72 41	07 57	09 73	74 31	76 47	11 63	13 00
0x0000370:	78 33	01 49	15 65	17 02	66 51	70 67	03 04	07 20
0x0000390:	68 55	72 71	05 08	09 24	74 59	78 75	11 12	15 28
0x00003b0:	76 63	01 00	13 16	17 32	19 53	23 69	35 06	39 22
0x00003d0:	21 57	25 73	37 10	41 26	27 61	31 77	43 14	47 30
0x00003f0:	29 65	33 02	45 18	49 34	19 04	21 08	23 20	25 24

Subclause 15.247 (a) – Equal Hopping Frequency Use
Pass

Requirement: Each of the transmitter's hopping channels is used equally on average.

Equal hopping frequency use

The EUT complies with the Bluetooth RF specifications. For details refer to the Bluetooth standard.

Subclause 15.247 (a) – Receiver Input Bandwidth		Pass
Requirement:	The associated receiver(s) complies with the requirement that its input bandwidth matches the bandwidth of the transmitted signal.	
Receiver input bandwidth		
The receiver bandwidth is equal to the receiver bandwidth in the 79 hopping channel mode, which is 1 MHz. The receiver bandwidth was verified during Bluetooth RF conformance testing.		

Subclause 15.247 (a) – Receiver Hopping Capability		Pass
Requirement:	The associated receiver has the ability to shift frequencies in synchronisation with the transmitted signals.	
Receiver hopping Capability		
The EUT complies with the Bluetooth RF specifications. For details refer to the Bluetooth standard.		

Subclause 15.247 (b)(1) – Peak Output Power					Pass
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz) Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 3 MHz / 10 MHz Supply voltage : 3.7VDC from DC power supply Temperature : 23°C Humidity : 50%					
Requirement:		For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 Watt. For all other frequency hopping systems in the 2400 – 2483.5 MHz band: 0.125 Watts.			
Results:		For test protocols please refer to Appendix 1, page 10-14.			
GFSK Modulation					
Frequency (MHz)	Maximum peak output power (dBm)	Cable attenuation (dB)	Output power (dBm)	Limit (W/dBm)	Verdict
2402	2.86	0.00	2.860	0.125 / 21.0	Pass
2441	3.10	0.00	3.100	0.125 / 21.0	Pass
2480	3.01	0.00	3.010	0.125 / 21.0	Pass
Pi/4 DQPSK Modulation					
Frequency (MHz)	Maximum peak output power (dBm)	Cable attenuation (dB)	Output power (dBm)	Limit (W/dBm)	Verdict
2402	4.63	0.00	4.630	0.125 / 21.0	Pass

2441	4.38	0.00	4.380	0.125 / 21.0	Pass
2480	3.99	0.00	3.990	0.125 / 21.0	Pass
8DPSK Modulation					
Frequency (MHz)	Maximum peak output power (dBm)	Cable attenuation (dB)	Output power (dBm)	Limit (W/dBm)	Verdict
2402	4.81	0.00	4.810	0.125 / 21.0	Pass
2441	4.60	0.00	4.600	0.125 / 21.0	Pass
2480	4.26	0.00	4.260	0.125 / 21.0	Pass

Subclause 15.247 (d) – Band edge compliance of conducted emissions		Pass
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (2402MHz, 2480MHz), 8DPSK Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 100 kHz / 300 kHz Supply voltage : 3.7VDC from DC power supply Temperature : 23°C Humidity : 50%		
Requirement:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.	
Results:	Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types. There is no peak found outside any 100 kHz bandwidth of the operating frequency band. For test protocols refer to Appendix 1, page 15-16.	

Subclause 15.205 – Band edge compliance of radiated emissions		Pass
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (2402MHz, 2480MHz), 8DPSK Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 1 MHz / 3 MHz Supply voltage : 3.7VDC from DC power supply Temperature : 23°C Humidity : 50%		
Requirement:	Radiated emissions which fall in the restricted bands, as defined in 15.205 (a), must also comply with the radiated emission limits specified in 15.209(a).	
Results:	There is no peak found in the restricted bands. For test protocols refer to Appendix 1, page 17-24.	

Subclause 15.247 (d) – Spurious Conducted Emissions					Pass
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), 8DPSK Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 100 kHz / 300 kHz Supply voltage : 3.7VDC from DC power supply Temperature : 23 °C Humidity : 50 %					
Requirement: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.					
Results: Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types. There is no peak found outside any 100kHz bandwidth of the operating frequency band in the three transmit frequency. All three transmit frequency modes comply with the limit stated in subclause 15.247(d). For test protocols refer to Appendix 1, page 25-26.					
Operating frequency (MHz)	Spurious frequency (MHz)	Spurious Level (dBm)	Reference value (dBm)	Delta (dB)	Verdict
2402	4800	-41.12	3.90	45.02	Pass
2441	4850	-46.17	3.62	49.79	Pass
2480	6600	-50.78	2.44	53.22	Pass

Subclause 15.247 (c) – Spurious Radiated Emissions			Pass
Test Specification : ANSI C63.4 – 2003 Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), GFSK Port of testing : Enclosure Detector : Peak RBW/VBW : 100 kHz / 300 kHz for $f < 1$ GHz 1 MHz / 3 MHz for $f > 1$ GHz Supply voltage : 3.7VDC from internal battery Temperature : 23°C Humidity : 50%			
Requirement: In any 100kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in section 15.205(a), must also comply with the radiated emission limits specified in section 15.205(c).			
Results: Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types. All three transmit frequency modes comply with the field strength within the restricted bands. There is no spurious found below 30MHz.			
Tx frequency 2402MHz Vertical Polarization			
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
186.180	29.50	43.5 / QP	
371.030	44.10	46 / QP	
439.100	39.40	46 / QP	
4804.333	68.97	74.0 / PK	
4803.965	43.87	54.0 / AV	
Tx frequency 2402MHz Horizontal Polarization			
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
187.740	35.40	43.5 / QP	
377.390	33.30	46 / QP	
1601.497	45.88	74.0 / PK	
1601.321	42.47	54.0 / AV	
4804.135	66.57	74.0 / PK	
4804.022	43.10	54.0 / AV	
Tx frequency 2441MHz Vertical Polarization			
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
188.340	30.70	43.5 / QP	
364.460	42.80	46 / QP	
458.750	37.90	46 / QP	
1627.420	47.16	74.0 / PK	
1627.260	41.07	54.0 / AV	
4881.623	67.44	74.0 / PK	
4881.940	43.32	54.0 / AV	

Tx frequency 2441MHz			Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
188.250	36.30	43.5 / QP	187.410	29.10	43.5 / QP
382.040	32.90	46 / QP	366.080	42.60	46 / QP
4881.619	71.15	74.0 / PK	435.080	40.30	46 / QP
4881.987	44.71	54.0 / AV	1653.269	50.76	74.0 / PK
Tx frequency 2480MHz			Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
187.410	29.10	43.5 / QP	1653.333	47.75	54.0 / AV
366.080	42.60	46 / QP	4960.221	71.21	74.0 / PK
435.080	40.30	46 / QP	4959.916	46.37	54.0 / AV
1653.269	50.76	74.0 / PK	Tx frequency 2480MHz		
1653.333	47.75	54.0 / AV	Horizontal Polarization		
4960.221	71.21	74.0 / PK	Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
4959.916	46.37	54.0 / AV	188.550	32.30	43.5 / QP
Tx frequency 2480MHz			375.770	32.50	46 / QP
Horizontal Polarization			1653.253	48.91	74.0 / PK
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	1653.317	44.75	54.0 / AV
188.550	32.30	43.5 / QP	4959.663	67.12	74.0 / PK
375.770	32.50	46 / QP	4960.016	43.59	54.0 / AV
1653.253	48.91	74.0 / PK			
1653.317	44.75	54.0 / AV			
4959.663	67.12	74.0 / PK			
4960.016	43.59	54.0 / AV			