

FCC Test Report (BT-LE)

Report No.: RF161201C02-5

FCC ID: G95-MGM0110VZN

Equipment Name: LTE Router

Trade Name: technicolor

Model Number: MBHA10

Product Code: DSLMVZ011GM

Received Date: Dec. 01, 2016

Test Date: Dec. 01, 2016 to Jan. 10, 2017

Issued Date: Mar. 08, 2017

Applicant: Technicolor Connected Home USA LLC

Address: 5030 Sugarloaf Parkway Building Lawrenceville Georgia United States
30044

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	4
1 Certificate of Conformity.....	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Modification Record	6
3 General Information.....	7
3.1 Basic Description of Equipment Under Test (BT-LE).....	7
3.2 Accessories	8
3.3 Feature of Equipment Under Test	8
3.4 Information Provided by the Manufacturer	8
3.5 General Description of Applied Standards	9
3.6 Cabling Attached to the Equipment.....	10
3.7 Panel Drawing	11
3.8 Transmit Operating Mode.....	12
3.9 Antenna Requirements	12
3.10 Antenna Information	13
3.11 Table for Carrier Frequency.....	14
3.12 Table for Test Modes.....	15
3.13 Parameters of Test Software Setting	16
3.14 On Time and Duty Cycle.....	17
3.15 Testing Location Information.....	18
3.16 EUT Diagram and Support Equipment	19
4 Test Types and Results	21
4.1 AC Power Conducted Emissions Measurement	21
4.1.1 Limit	21
4.1.2 Measuring Instruments and Setting.....	21
4.1.3 Test Procedures.....	21
4.1.4 Test Setup Layout.....	22
4.1.5 Test Deviation	22
4.1.6 EUT Operating during Test	23
4.1.7 Test Results of AC Power Conducted Emissions	23
4.2 Maximum Conducted Output Power Measurement	25
4.2.1 Limit	25
4.2.2 Measuring Instruments and Setting.....	25
4.2.3 Test Procedures.....	25
4.2.4 Test Setup Layout.....	26
4.2.5 Test Deviation	26
4.2.6 EUT Operating Conditions.....	26
4.2.7 Test Results of Maximum Conducted Output Power	27
4.3 Power Spectral Density Measurement.....	28
4.3.1 Limit	28
4.3.2 Measuring Instruments and Setting.....	28
4.3.3 Test Procedures.....	28
4.3.4 Test Setup Layout.....	29
4.3.5 Test Deviation	29
4.3.6 EUT Operating Conditions.....	29
4.3.7 Test Results of Power Spectral Density	30
4.4 6dB Bandwidth Measurement	31
4.4.1 Limit	31
4.4.2 Measuring Instruments and Setting.....	31
4.4.3 Test Procedures.....	31
4.4.4 Test Setup Layout.....	32
4.4.5 Test Deviation	32

4.4.6	EUT Operating Conditions.....	32
4.4.7	Test Results of 6dB Bandwidth.....	33
4.5	Occupied Bandwidth Measurement.....	34
4.5.1	Measuring Instruments and Setting.....	34
4.5.2	Test Procedure	34
4.5.3	Test Setup Layout.....	34
4.5.4	Test Deviation	35
4.5.5	EUT Operating Conditions.....	35
4.5.6	Test Results of Occupied Bandwidth.....	36
4.6	Radiated Emissions Measurement	37
4.6.1	Limit	37
4.6.2	Measuring Instruments and Setting.....	37
4.6.3	Test Procedure	38
4.6.4	Test Setup Layout.....	39
4.6.5	Test Deviation	40
4.6.6	EUT Operating Conditions.....	40
4.6.7	Test Results of Radiated Emissions	41
4.7	Band Edge and Fundamental Emissions Measurement.....	49
4.7.1	Limit	49
4.7.2	Measuring Instruments and Setting.....	49
4.7.3	Test Procedure	49
4.7.4	Test Setup Layout.....	50
4.7.5	Test Deviation	51
4.7.6	EUT Operating Conditions.....	51
4.7.7	Test Results of Band Edge and Fundamental Emissions	52
4.7.8	Test Results of Band Edge and Emissions not in Restricted Bands	58
4.8	List of Test Instruments	60
Appendix A. Information on the Testing Laboratories.....		63

Release Control Record

Issue No.	Description	Date Issued
RF161201C02-5	Original release.	Mar. 08, 2017

1 Certificate of Conformity

Equipment Name: LTE Router

Trade Name: technicolor

Test Model: MBHA10

Product Code: DSLMVZ011GM

Sample Status: Product Unit

Applicant: Technicolor Connected Home USA LLC

Test Date: Dec. 01, 2016 to Jan. 10, 2017

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF EMI characteristics under the conditions specified in this report.


Prepared by :



Date: Mar. 08, 2017

Claire Kuan / Specialist

Approved by :



Date: Mar. 08, 2017

May Chen / Manager

2 Summary of Test Results

Applied Standard: 47 CFR FCC Part 15 Subpart C					
Section	Ref. Std. Clause	Description	Measured	Limit	Result
3.9	15.203	Antenna Requirements	-	-	PASS
4.1	15.207	AC Power Conducted Emissions	Margin is -8.27dB at 0.15391MHz.	-	PASS
4.2	15.247(b)(3)	Maximum Conducted Output Power	Power [dBm]: 8.01 dBm	30 dBm	PASS
4.3	15.247(e)	Power Spectral Density	PSD [dBm/10kHz]: -11.20 dBm/10kHz	8dBm/10kHz	PASS
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Bandwidth [MHz]: 1.89 MHz	≥500kHz	PASS
4.5	-	Occupied Bandwidth	Bandwidth [MHz]: 2.23 MHz	-	-
4.6	15.247(d)	Radiated Emissions	Margin is -3.9dB at 281.25MHz.	-	PASS
4.7	15.247(a)(2)	Band Edge Emissions	Margin is -11.0dB at 2483.50MHz.	-	PASS

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.83 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	5.19 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	3.43 dB
	6GHz ~ 18GHz	3.49 dB
	18GHz ~ 40GHz	4.11 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 Basic Description of Equipment Under Test (BT-LE)

Items	Description		
Equipment Name	LTE Router		
Trade Name	technicolor		
Model Number	MBHA10		
Product Code	DSL MVZ011GM		
FCC ID	G95-MGM0110VZN		
Power Type	From power adapter		
Antenna	Refer section 3.10		
EUT Stage	☒ Product Unit	☐ Pre-Sample	
Operating Band and Conducted Output Power	2400~2483.5MHz	☒ Bluetooth LE : 8.37 dBm	
Product Type	For Bluetooth LE :(1TX, 1RX)		
Nominal Bandwidth	1MHz		
Modulation	GFSK		
Data Rate (Mbps)	Bluetooth LE :1Mbps		
I/O Ports	LAN Port x 1 RJ31 Port x 1 FXS Port x 1 SIM Port x1 Console Port x 1 (For engineer debug use only)		
Hardware Version	FGR1		
Software Version	16.4.7446-3130000-20161220230657-aa636a7383f23e65d07560e3fbe49cd6cbe d2ce0		

3.2 Accessories

Li-ion Battery:

Model	BP-MGM0110
Manufacturer	GETAC TECHNOLOGY CORP.
Rating	3.7V, 2500mAh / 9.25Wh

Power supply:

Model	WAE002
P/N	DSL37544940
Manufacturer	AcBel
Input	100/240Vac , 50/60Hz , 0.7A
Output	12Vdc , 2A
DC power cord	1.5m

3.3 Feature of Equipment Under Test

Please refer to user manual.

3.4 Information Provided by the Manufacturer

Interface Availability

Interface Model	DC 12Vdc	RJ31-X Alarm	Ethernet 10/100 Mbps	FXS	SIM	Zigbee	Z-Wave	BT	GPS	LTE (4G)	WLAN 802.11a/b/g/n/ac (2.4GHz 2*2) (5GHz 2*2 ac)
MBHA10	● (2A)	● (1 port)	● (1 port)	● (1 port)	● (1 port)	●	●	●	●	●	●

● : Equipped

○ : Not Equipped

3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)

KDB 558074 D01 DTS Meas Guidance v03r05, 04/08/2016

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.


NOTE: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.6 Cabling Attached to the Equipment

Cable and Interconnection

Interface	Cable Type	Cable Length Delivered with the Modem	"Real Life" Cable Length that can be Attached to this Type of Interface	Cable Length to be used for Testing	Internal/ External Connection
ETH1	UTP Cat 5	1 meter	> 10 meter	10 meter	Internal
RJ31-X Alarm	UTP Cat 3	1 meter	> 10 meter	10 meter	Internal
FXS1	UTP Cat 3	1 meter	> 10 meter	10 meter flat cable	Internal
AC power	-	-	-	-	External

3.7 Panel Drawing



3.8 Transmit Operating Mode

Transmit Operating Mode		Transmit Multiple Antennas	
■	Operating mode 1 (single antenna)	■	1TX

3.9 Antenna Requirements

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

3.10 Antenna Information

Antenna Information					
Ant.	Brand	Model No.	Antenna Type	Connector	Cable Length
BT-LE	INPAQ	WA-F-LB-04-005	FPCB Antenna	I-PEX	204 mm



For 2400~2483.5MHz

Frequency	Antenna Gain (dBi)
	Ant. 1 (J709)
2402MHz	2.89
2440MHz	2.74
2480MHz	2.85

3.11 Table for Carrier Frequency

40 channels are provided for Bluetooth LE:

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400MHz ~ 2483.5MHz	00	2402 MHz	20	2442 MHz
	01	2404 MHz	21	2444 MHz
	02	2406 MHz	22	2446 MHz
	03	2408 MHz	23	2448 MHz
	04	2410 MHz	24	2450 MHz
	05	2412 MHz	25	2452 MHz
	06	2414 MHz	26	2454 MHz
	07	2416 MHz	27	2456 MHz
	08	2418 MHz	28	2458 MHz
	09	2420 MHz	29	2460 MHz
	10	2422 MHz	30	2462 MHz
	11	2424 MHz	31	2464 MHz
	12	2426 MHz	32	2466 MHz
	13	2428 MHz	33	2468 MHz
	14	2430 MHz	34	2470 MHz
	15	2432 MHz	35	2472 MHz
	16	2434 MHz	36	2474 MHz
	17	2436 MHz	37	2476 MHz
	18	2438 MHz	38	2478 MHz
	19	2440 MHz	39	2480 MHz

3.12 Table for Test Modes

Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Note	Channel	Data Rate	Antenna
AC Power Line Conducted Emissions	Bluetooth LE	GFSK	19	-	1
Conducted Output Power	Bluetooth LE	GFSK	00/19/39	1Mbps	1
Power Spectral Density	Bluetooth LE	GFSK	00/19/39	1Mbps	1
6dB Bandwidth	Bluetooth LE	GFSK	00/19/39	1Mbps	1
Band Edge Emissions	Bluetooth LE	GFSK	00/19/39	1Mbps	1
Radiated Emissions Above 1GHz	Bluetooth LE	GFSK	00/19/39	1Mbps	1
Radiated Emissions Below 1GHz	Bluetooth LE	GFSK	19	-	1

Note:

1. The device with multiple operating mode, measurements on the middle channel were tested to determine the worst case mode.

3.13 Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

The Power Setting Parameter					
Test Software Version	16.4.7446-3130000-20161220230657-aa636a7383f23e65d07560e3fbe49cd6cbcd2ce0				
Worst Modulation Mode	Number of Transmit Chains (NTX)	Frequency (MHz)	Maximum Output Power (dBm)	Power Setting	Data Rate / MCS
Bluetooth LE	1	2402	7.71	9	1Mbps
		2440	8.01	9	1Mbps
		2480	6.31	9	1Mbps


3.14 On Time and Duty Cycle

Mode	On Time (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T Minimum VBW (kHz)
Bluetooth LE	100	0	100	-	-

Note:

- Power measurement using sweep trigger and gating of the power meter, duty factor is not required.
- Duty cycle of test signal is $\geq 98\%$, duty factor is not required

Duty Cycle



3.15 Testing Location Information

Test Site Location					
Address	(1) E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan R.O.C.				
TEL	886-3-6668565				
FAX	886-3-6668323				
Test Site No.	Site Category	Location	FCC Reg. No.	IC Reg. No.	VCCI Reg. No
Conduction 1	Conduction	Hsinchu	-	-	-
Chamber 3	966 Chamber	Hsinchu	147459	20331-1	-
Oven 2	Oven	Hsinchu	-	-	-

3.16 EUT Diagram and Support Equipment

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Laptop	DELL	E6440	F9LYQ32	FCC DoC	Provided by Lab
B.	Phone	WONDER	WD-303	8C17DA02763	NA	Provided by Lab
C.	SIM Card	R&S	CRT-Z3	NA	NA	Provided by Lab

Note:

1. All power cords of the above support units are non-shielded (1.8m).

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Internal/external connection	Remarks
1.	RJ-45 Cable	1	10	No	0	External	Provided by Lab
2.	DC Cable	1	1.8	No	0	Internal	Supplied by client
3.	RJ-11 Cable	1	10	No	0	External	Provided by Lab
4.	RJ-31 Cable	1	10	No	0	External	Provided by Lab

EUT Diagram



4 Test Types and Results

4.1 AC Power Conducted Emissions Measurement

4.1.1 Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

4.1.2 Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

4.1.3 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4 Test Setup Layout



1. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
2. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
3. EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
 - 3.1 All other equipment powered from additional LISN(s).
 - 3.2 Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - 3.3 LISN at least 80 cm from nearest part of EUT chassis.
4. Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
5. Non-EUT components of EUT system being tested.
6. Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop. Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5 Test Deviation

There are no deviations with the original standard.

4.1.6 EUT Operating during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7 Test Results of AC Power Conducted Emissions

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25°C, 75%RH
Tested by	Andy Ho		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.20	47.35	33.76	57.55	43.96	66.00	56.00	-8.45	-12.04
2	0.16562	10.20	43.48	24.20	53.68	34.40	65.18	55.18	-11.50	-20.78
3	0.19297	10.20	39.28	27.89	49.48	38.09	63.91	53.91	-14.43	-15.82
4	0.32969	10.23	27.05	9.28	37.28	19.51	59.46	49.46	-22.18	-29.95
5	3.29297	10.30	25.59	20.39	35.89	30.69	56.00	46.00	-20.11	-15.31
6	6.93359	10.52	22.40	17.01	32.92	27.53	60.00	50.00	-27.08	-22.47

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25°C, 75%RH
Tested by	Andy Ho		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBUV)		Emission Level (dBUV)		Limit (dBUV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	10.19	47.33	35.23	57.52	45.42	65.79	55.79	-8.27	-10.37
2	0.17344	10.18	42.06	22.39	52.24	32.57	64.79	54.79	-12.55	-22.22
3	0.18906	10.17	40.23	27.83	50.40	38.00	64.08	54.08	-13.68	-16.08
4	0.22812	10.18	34.20	22.75	44.38	32.93	62.52	52.52	-18.14	-19.59
5	0.33750	10.22	31.17	22.49	41.39	32.71	59.26	49.26	-17.87	-16.55
6	3.51563	10.24	25.93	20.03	36.17	30.27	56.00	46.00	-19.83	-15.73

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



4.2 Maximum Conducted Output Power Measurement

4.2.1 Limit

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm). The limit has to be reduced by the amount in dB that the gain of the antenna exceeds 6dBi. For point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

4.2.2 Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Power Measurement	Average(RMS), Peak
Rise Time	<8 ns typical 12ns maximum
Sensor Model	MA2411B

4.2.3 Test Procedures

- 1 Test was performed in accordance with Measurement of Digital Transmission Systems Operating under KDB558074 D01 DTS Meas Guidance v03r05, in section “Maximum conducted output power Method AVGPM-G”, 04/08/2016
- 2 The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the average power sensor and enable the trigger function to get the all on time transmission . Record the average power level.
- 3 When measuring maximum conducted output power with multiple antenna systems, add every result of the values by mathematic formula.

4.2.4 Test Setup Layout



4.2.5 Test Deviation

There are no deviations with the original standard.

4.2.6 EUT Operating Conditions

The EUT was programmed to be in continuously transmitting mode.

4.2.7 Test Results of Maximum Conducted Output Power

Temperature	25°C	Humidity	60%
Test Engineer	Anderson Chen		

Channel	Frequency (MHz)	Conducted Power (dBm)	Directional Gain (dBi)	Max. Limit (dBm)	Result
0	2402	8.00	2.89	30	PASS
19	2440	8.37	2.74	30	PASS
39	2480	6.63	2.85	30	PASS

Note.1. Directional Gain <6dBi, so the limit doesn't reduce.

4.3 Power Spectral Density Measurement

4.3.1 Limit

For digitally modulated systems, the conductive measured power spectral density(PSD) shall not be greater than 8 dBm in any 3 kHz bandwidth during any time interval of continuous transmission.

4.3.2 Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RBW	Set the RBW ≥ 3 kHz
VBW	Set the VBW $\geq 3 \times$ RBW
Detector	RMS
Trace	Average sweep count 100
Sweep Time	Auto couple

4.3.3 Test Procedures

- 1 The transmitter output (antenna port) was connected to the spectrum analyzer.
- 2 Test was performed in accordance with Measurement of Digital Transmission Systems Operating under KDB558074 D01 DTS Meas Guidance v03r05, in section "Maximum power spectral density level in the fundamental emissions Method AVGPS-1", 04/08/2016.
- 3 This procedure may be used when the maximum (average) conducted output power was used to demonstrate compliance to the output power limit. The EUT must be configured to transmit continuously (duty cycle $\geq 98\%$) to ensure that measurements are made only when the EUT is transmitting at its maximum power control level (no transmitter off time is to be considered).
- 4 Ensure that the number of measurement points in the sweep $\geq 2 \times$ span/RBW (use of a greater number of measurement points than this minimum requirement is recommended).
- 5 When measuring first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and so on up to the Nth output to obtain the value for the first frequency bin of the summed spectrum. The summed spectrum value for each of the other frequency bins is computed in the same way.

4.3.4 Test Setup Layout



4.3.5 Test Deviation

There are no deviations with the original standard.

4.3.6 EUT Operating Conditions


The EUT was programmed to be in continuously transmitting mode.

4.3.7 Test Results of Power Spectral Density

Temperature	20°C	Humidity	62%
Test Engineer	Anderson Chen		

Channel	Frequency (MHz)	Power Density (dBm/3kHz)	Directional Gain (dBi)	Limit (dBm/3kHz)	Result
0	2402	-11.20	2.89	8	PASS
19	2440	-11.29	2.74	8	PASS
39	2480	-12.77	2.85	8	PASS

Note.1. Directional Gain <6dBi, so the limit doesn't reduce.



4.4 6dB Bandwidth Measurement

4.4.1 Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz

4.4.2 Measuring Instruments and Setting


The following table is the setting of the Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RBW	100KHz
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

4.4.3 Test Procedures

- 1 The transmitter output (antenna port) was connected to the spectrum analyzer in peak, Max hold mode.
- 2 For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier frequency. A peak reading was taken; two markers were set 6 dB below the maximum level on the right and the left side of the emissions.
- 3 The 6 dB bandwidth is the frequency difference between the two markers

4.4.4 Test Setup Layout



4.4.5 Test Deviation

There are no deviations with the original standard.


4.4.6 EUT Operating Conditions

The EUT was programmed to be in continuously transmitting mode.

4.4.7 Test Results of 6dB Bandwidth

Temperature	20°C	Humidity	62%
Test Engineer	Anderson Chen		

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.89	0.5	PASS
19	2440	1.90	0.5	PASS
39	2480	1.90	0.5	PASS



4.5 Occupied Bandwidth Measurement

4.5.1 Measuring Instruments and Setting


The following table is the setting of the Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
RBW	1% to 5% of the anticipated emission bandwidth
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

4.5.2 Test Procedure

- 1 The transmitter output (antenna port) was connected to the spectrum analyzer in peak, Max hold mode.
- 2 For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier frequency. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to peak.
- 3 The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

4.5.3 Test Setup Layout



4.5.4 Test Deviation

There are no deviations with the original standard.


4.5.5 EUT Operating Conditions

The EUT was programmed to be in continuously transmitting mode.

4.5.6 Test Results of Occupied Bandwidth

Temperature	20°C	Humidity	62%
Test Engineer	Anderson Chen		

CHANNEL	FREQUENCY (MHz)	OCCUPIED BANDWIDTH (MHz)
0	2402	2.23
19	2440	2.24
39	2480	2.23



4.6 Radiated Emissions Measurement

4.6.1 Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emissions fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency Range (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

4.6.2 Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.


Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emissions in restricted band)	1MHz / 3MHz for Peak, 1 MHz / 1/T for Average
RBW / VBW (Emissions in non-restricted band)	100kHz / 300kHz for peak

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

4.6.3 Test Procedure

- 1 Configure the EUT according to ANSI C63.10. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2 Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3 The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4 For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5 Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode
- 6 For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer for Duty $\geq 98\%$, 1MHz RBW and VBW is $\geq 1/T$ for average reading in spectrum analyzer for Duty $< 98\%$.
- 7 When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
- 8 If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9 For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10 As the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.6.4 Test Setup Layout



4.6.5 Test Deviation

There are no deviations with the original standard.

4.6.6 EUT Operating Conditions

The EUT was programmed to be in continuously transmitting mode.

4.6.7 Test Results of Radiated Emissions

Temperature	23°C	Humidity	70%
Test Engineer	Weiwei Lo		

Radiated Emissions Range 9kHz~30MHz

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Radiated Emissions Range 30MHz~1GHz

CHANNEL	TX Channel 19	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	178.14	33.50 PK	43.50	-10.00	1.50 H	91	43.30	-9.80
2	215.61	32.90 PK	43.50	-10.60	1.00 H	206	44.20	-11.30
3	281.25	42.10 PK	46.00	-3.90	1.00 H	347	50.20	-8.10
4	365.64	35.60 PK	46.00	-10.40	1.00 H	56	41.40	-5.80
5	478.12	33.80 PK	46.00	-12.20	2.00 H	330	36.90	-3.10
6	534.38	33.70 PK	46.00	-12.30	1.50 H	360	35.80	-2.10

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 19	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	109.08	30.60 PK	43.50	-12.90	1.00 V	173	41.90	-11.30
2	215.63	38.00 PK	43.50	-5.50	1.00 V	348	49.30	-11.30
3	300.00	38.20 PK	46.00	-7.80	2.00 V	360	45.50	-7.30
4	328.13	36.20 PK	46.00	-9.80	1.50 V	360	42.60	-6.40
5	384.39	34.40 PK	46.00	-11.60	1.00 V	360	39.70	-5.30
6	506.25	39.10 PK	46.00	-6.90	2.00 V	352	41.40	-2.30

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value




Radiated Emission Range 1GHz~10th Harmonic

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	4804.00	39.10 PK	74.00	-34.90	1.91 H	193	36.80	2.30
2	4804.00	29.20 AV	54.00	-24.80	1.91 H	193	26.90	2.30

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	4804.00	38.70 PK	74.00	-35.30	1.56 V	329	36.40	2.30
2	4804.00	27.20 AV	54.00	-26.80	1.56 V	329	24.90	2.30

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 19	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	4880.00	39.60 PK	74.00	-34.40	1.97 H	194	37.10	2.50
2	4880.00	29.40 AV	54.00	-24.60	1.97 H	194	26.90	2.50
3	7320.00	41.00 PK	74.00	-33.00	1.85 H	333	32.10	8.90
4	7320.00	34.30 AV	54.00	-19.70	1.85 H	333	25.40	8.90

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 19	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	4880.00	39.10 PK	74.00	-34.90	1.56 V	341	36.60	2.50
2	4880.00	27.40 AV	54.00	-26.60	1.56 V	341	24.90	2.50
3	7320.00	43.10 PK	74.00	-30.90	2.56 V	359	34.20	8.90
4	7320.00	38.90 AV	54.00	-15.10	2.56 V	359	30.00	8.90

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	4960.00	39.80 PK	74.00	-34.20	1.99 H	181	37.30	2.50
2	4960.00	29.90 AV	54.00	-24.10	1.99 H	181	27.40	2.50
3	7440.00	40.60 PK	74.00	-33.40	1.80 H	319	31.10	9.50
4	7440.00	34.20 AV	54.00	-19.80	1.80 H	319	24.70	9.50

R REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	4960.00	38.70 PK	74.00	-35.30	1.52 V	331	36.20	2.50
2	4960.00	27.20 AV	54.00	-26.80	1.52 V	331	24.70	2.50
3	7440.00	42.80 PK	74.00	-31.20	2.56 V	360	33.30	9.50
4	7440.00	38.50 AV	54.00	-15.50	2.56 V	360	29.00	9.50

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value



4.7 Band Edge and Fundamental Emissions Measurement

4.7.1 Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emissions fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed

Frequency range (MHz)	Field Strength (mV/meter)	Measurement Distance (m)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.7.2 Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emissions in restricted band)	1MHz / 3MHz for Peak, 1 MHz / 1/T for Average
RBW / VBW (Emissions in non-restricted band)	100kHz / 300kHz for peak

4.7.3 Test Procedure

- 1 The test procedure is the same as section 4.6.3; only the frequency range investigated is 2310MHz to 2500MHz
- 2 Test for Emissions in non-restricted band was performed in accordance with KDB 558074 D01 v03r05 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 11 Unwanted Emissions into Non-Restricted Frequency Bands Measurement Procedure.

4.7.4 Test Setup Layout



4.7.5 Test Deviation

There are no deviations with the original standard.

4.7.6 EUT Operating Conditions

The EUT was programmed to be in continuously transmitting mode.

4.7.7 Test Results of Band Edge and Fundamental Emissions


Temperature	20°C	Humidity	66%
Test Engineer	Gary Cheng		

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	48.50 PK	74.00	-25.50	1.76 H	43	52.70	-4.20
2	2390.00	35.60 AV	54.00	-18.40	1.76 H	43	39.80	-4.20
3	*2402.00	94.30 PK			1.76 H	43	98.40	-4.10
4	*2402.00	90.20 AV			1.76 H	43	94.30	-4.10

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. " * ": Fundamental frequency.




CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	46.80 PK	74.00	-27.20	1.72 V	220	51.00	-4.20
2	2390.00	36.60 AV	54.00	-17.40	1.72 V	220	40.80	-4.20
3	*2402.00	104.10 PK			1.72 V	220	108.20	-4.10
4	*2402.00	100.10 AV			1.72 V	220	104.20	-4.10

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. " * ": Fundamental frequency.




CHANNEL	TX Channel 19	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2390.00	59.10 PK			1.67 H	42	63.30	-4.20
2	*2390.00	41.40 AV			1.67 H	42	45.60	-4.20
3	2440.00	94.70 PK	134.00	-39.30	1.67 H	42	98.70	-4.00
4	2440.00	90.60 AV	114.00	-23.40	1.67 H	42	94.60	-4.00
5	2483.50	47.40 PK	74.00	-26.60	1.67 H	42	51.40	-4.00
6	2483.50	35.90 AV	54.00	-18.10	1.67 H	42	39.90	-4.00

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. " * ": Fundamental frequency.




CHANNEL	TX Channel 19	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2390.00	47.00 PK			1.06 V	277	51.20	-4.20
2	*2390.00	35.30 AV			1.06 V	277	39.50	-4.20
3	2440.00	106.60 PK	134.00	-27.40	1.06 V	277	110.60	-4.00
4	2440.00	102.60 AV	114.00	-11.40	1.06 V	277	106.60	-4.00
5	2483.50	55.50 PK	74.00	-18.50	1.06 V	277	59.50	-4.00
6	2483.50	41.60 AV	54.00	-12.40	1.06 V	277	45.60	-4.00

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. " * ": Fundamental frequency.




CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	93.70 PK			1.49 H	43	97.70	-4.00
2	*2480.00	89.50 AV			1.49 H	43	93.50	-4.00
3	2483.50	48.70 PK	74.00	-25.30	1.49 H	43	52.70	-4.00
4	2483.50	37.30 AV	54.00	-16.70	1.49 H	43	41.30	-4.00

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. " * ": Fundamental frequency.




CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	104.60 PK			1.23 V	0	108.60	-4.00
2	*2480.00	100.50 AV			1.23 V	0	104.50	-4.00
3	2483.50	58.40 PK	74.00	-15.60	1.23 V	280	62.40	-4.00
4	2483.50	43.00 AV	54.00	-11.00	1.23 V	280	47.00	-4.00

REMARKS:


1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. " * ": Fundamental frequency.




4.7.8 Test Results of Band Edge and Emissions not in Restricted Bands

Below 30dB of the highest emissions level of operating band (in 100kHz Resolution Bandwidth).


CH 0




CH 19



CH 39





4.8 List of Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESCS 30	847124/029	Oct. 24, 2016	Oct. 23, 2017
Line-Impedance Stabilization Network (for EUT) R&S	ESH3-Z5	848773/004	Oct. 26, 2016	Oct. 25, 2017
RF Cable	5D-FB	COCCAB-001	Sep. 30, 2016	Sep. 29, 2017
10 dB PAD Mini-Circuits	HAT-10+	CONATT-004	June 20, 2016	June 19, 2017
Software BVADT	BVADT_Cond_ V7.3.7.4	NA	NA	NA

Note:

1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. 1.
3. Tested Date: Dec. 01, 2016

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Agilent	N9038A	MY50010156	Aug. 18, 2016	Aug. 17, 2017
Pre-Amplifier ^(*) EMCI	EMC001340	980142	Jan. 20, 2016	Jan. 19, 2018
Loop Antenna ^(*) Electro-Metrics	EM-6879	264	Dec. 16, 2014	Dec. 15, 2016
RF Cable	NA	LOOPCAB-001 LOOPCAB-002	Jan. 18, 2016	Jan. 17, 2017
Pre-Amplifier Mini-Circuits	ZFL-1000VH2 B	AMP-ZFL-05	May 07, 2016	May 06, 2017
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-156	Jan. 04, 2016	Jan. 03, 2017
RF Cable	8D	966-3-1 966-3-2 966-3-3	Apr. 02, 2016	Apr. 01, 2017
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-3-01	Oct. 05, 2016	Oct. 04, 2017
Horn_Antenna SCHWARZBECK	BBHA9120-D	9120D-406	Jan. 20, 2016	Jan. 19, 2017
Pre-Amplifier Agilent	8449B	3008A02465	Apr. 05, 2016	Apr. 04, 2017
RF Cable	EMC104-SM- SM-2000 EMC104-SM- SM-5000 EMC104-SM- SM-5000	150317 150321 150322	Mar. 30, 2016	Mar. 29, 2017
Spectrum Analyzer Keysight	N9030A	MY54490520	July 29, 2016	July 28, 2017
Pre-Amplifier EMCI	EMC184045	980143	Jan. 15, 2016	Jan. 14, 2017
Horn_Antenna SCHWARZBECK	BBHA 9170	BBHA9170608	Jan. 08, 2016	Jan. 07, 2017
RF Cable	SUCOFLEX 102	36432/2 36433/2	Jan. 16, 2016	Jan. 15, 2017
Software	ADT_Radiated _V8.7.08	NA	NA	NA
Antenna Tower & Turn Table Max-Full	MF-7802	MF780208406	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. *The calibration interval of the above test instruments is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. The test was performed in 966 Chamber No. 3.
4. The FCC Site Registration No. is 147459
5. The CANADA Site Registration No. is 20331-1
6. Tested Date: Dec. 06 to 14, 2016

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer R&S	FSV40	100964	June 28, 2016	June 27, 2017
Spectrum Analyzer Agilent	E4446A	MY48250253	Dec. 21, 2016	Dec. 20, 2017
Power meter Anritsu	ML2495A	1014008	May 5, 2016	May 4, 2017
Power sensor Anritsu	MA2411B	0917122	May 5, 2016	May 4, 2017
AC Power Source Extech Electronics	6205	1440452	NA	NA
Temperature & Humidity Chamber Giant Force	GTH-150-40-SP-AR	MAA0812-008	Jan. 15, 2016	Jan. 14, 2017
DC Power Supply Topward	6603D	795558	NA	NA
Digital Multimeter FLUKE	87III	73680266	Nov. 10, 2016	Nov. 09, 2017
ESG Vector signal generator Agilent	E4438C	MY45094468/005 506 602 UK6 UNJ	Nov. 25, 2016	Nov. 24, 2017
Mech Switch Absorptive Mini-Circuits	MSP4TA-18+	0140	Mar. 19, 2016	Mar. 18, 2017
FXD ATTEN Mini-Circuits	BW-S3W2+	MN71981	Mar. 19, 2016	Mar. 18, 2017
Software	ADT_RF Test Software V6.6.5.4	NA	NA	NA

- NOTE:**
1. The test was performed in Oven room 2.
 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 3. Tested Date: Jan. 10, 2017

Appendix A. Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---