

RF Exposure Report

Report No.: SA160818E07

FCC ID: G95TCA301

Test Model: TCA301TCH1

Series Model: TCA301TCH2, TCA301ROG1, TCA301COX2, TCA301BHN2,
TCA301CMP2, TCA301TWC2

Received Date: Aug. 06, 2016

Test Date: Aug. 23, 2016

Issued Date: Dec. 15, 2016

Applicant: Technicolor Connected Home USA LLC

Address: 5030 Sugarloaf Parkway, Building 6, Lawrenceville, GA 30044

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
1 Certificate of Conformity.....	4
2 RF Exposure.....	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
2.5 Calculation Result of Maximum Conducted Power.....	8

Release Control Record

Issue No.	Description	Date Issued
SA160818E07	Original release.	Dec. 15, 2016

1 Certificate of Conformity

Product: Integrated Device

Brand: Technicolor

Test Model: TCA301TCH1

Series Model: TCA301TCH2, TCA301ROG1, TCA301COX2, TCA301BHN2, TCA301CMP2,
TCA301TWC2

Sample Status: ENGINEERING SAMPLE

Applicant: Technicolor Connected Home USA LLC

Test Date: Aug. 23, 2016

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06


IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : 

Claire Kuan / Specialist

, **Date:** Dec. 15, 2016

Approved by : 

May Chen / Manager

, **Date:** Dec. 15, 2016

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

1 The antennas provided to the EUT, please refer to the following table:

WLAN & BT Antenna Spec.

Antenna No.	Transmitter Circuit	Max Gain(dBi) Including cable loss	Frequency range (MHz)	Antenna Type	Antenna Connector
WiFi 1 & BT	Chain (0)	2.29	2400~2500	FPCB	i-pex(MHF)
		3.36	5150~5250		
		3.66	5250~5350		
		3.77	5470~5725		
		3.36	5725~5850		
WiFi 2	Chain (1)	2.34	2400~2500	PCB	i-pex(MHF)
		3.62	5150~5250		
		3.55	5250~5350		
		2.86	5470~5725		
		2.99	5725~5850		

Zigbee Antenna Spec.

Antenna No.	Gain(dBi) Including cable loss	Frequency range (MHz)	Antenna Type	Antenna Connector
Zigbee-A	2.33	2400~2500	PCB	i-pex(MHF)
Zigbee- Thread	2.5	2400~2500	PCB	i-pex(MHF)

WWAN Antenna Spec.

Antenna No.	Gain(dBi) Including cable loss	Frequency range (MHz)	Antenna Type	Antenna Connector
WWAN 1	1.62 2.36	704~894 1710~2170	PCB	i-pex(MHF)
WWAN 2	0.63 1.66	704~894 1710~2170	FPCB	i-pex(MHF)

2 The detail information of WLAN antenna gain as below table:

2.4GHz

	Channel	SISO 1S1T Ant 1	SISO 1S1T Ant 2	CCD mode for power gain 1S2T (1&2)	CCD mode for PSD gain 1S2T (1&2)
BW20	2412	1.29	1.90	1.90	4.17
	2437	1.65	1.98	1.98	4.28
	2462	2.15	2.15	2.15	4.60
BW40	2422	1.39	1.94	1.94	4.22
	2437	1.65	1.98	1.98	4.28
	2452	2.03	2.09	2.09	4.51

5GHz

	Channel	SISO 1S1T Ant 1	SISO 1S1T Ant 2	CCD mode for power gain 1S2T (1&2)	CCD mode for PSD gain 1S2T (1&2)
BW20	5180	2.66	3.38	3.38	4.57
	5200	2.81	3.38	3.38	4.59
	5240	3.32	3.55	3.55	4.72
	5260	3.43	3.54	3.54	4.81
	5300	3.53	3.25	3.53	4.48
	5320	3.66	3.08	3.66	4.26
	5500	3.76	2.59	3.76	3.38
	5580	3.34	2.37	3.34	3.31
	5700	3.24	2.73	3.24	3.24
	5745	3.26	2.94	3.26	3.50
	5785	3.23	2.84	3.23	3.55
	5825	1.68	2.86	2.86	3.34
BW40	5190	3.73	3.31	3.31	4.51
	5230	3.36	3.62	3.62	4.77
	5270	3.45	3.5	3.50	4.76
	5310	3.46	3.07	3.46	4.28
	5510	3.78	2.45	3.78	3.33
	5550	3.55	2.06	3.55	3.47
	5670	3.21	2.65	3.21	3.06
	5755	3.28	2.99	3.28	3.57
	5795	2.56	2.86	2.86	3.31

2.5 Calculation Result

WLAN

Frequency Band (MHz)	Max. Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2412 ~ 2462	154.565	4.60	20	0.08868	1
5180 ~ 5240, 5260 ~ 5320, 5500 ~ 5580 & 5660 ~ 5700, 5745 ~ 5825	170.674	4.81	20	0.10278	1

BT-EDR

Frequency Band (MHz)	Max. Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2402 ~ 2480	2.118	2.29	0.2	0.00071	1

BT-LE

Frequency Band (MHz)	Max. Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2402 ~ 2480	1.442	2.29	0.2	0.00049	1

Zigbee

Frequency Band (MHz)	Max. Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2405 ~ 2475	170.216	2.33	20	0.05791	1

Zigbee Thread

Frequency Band (MHz)	Max. Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2405 ~ 2475	151.356	2.33	0.2	0.05355	1

WWAN

Frequency Band (MHz)	Time average power (mW)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
824MHz ~849MHz	568.775 ^(Note)	0.2	0.18564	0.5495

Note

Operation Mode	The Worst Case			Total Peak. Power Output		Time average power (mW)	Power Density (mW/cm ²)	
	Mode	Channel Number	Freq. (MHz)	mW	dBm		Value	Limit
850 band (e.r.p.)	GPRS	128	824.2	2275.1	33.57	933.125	0.30445	0.5495
1900 band (e.i.r.p.)	GPRS	512	1850.2	1279.38	31.07	319.845	0.06363	1

Note: Calculations for RF Exposure compliance in the cellular and PCS bands are base on the maximum source based time-average power obtained from 2-Slot GPRS operation. The resulting duty cycle factor is 2/8, or 6.02dB.

Conclusion:

The formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

Simultaneously transmission condition.

Condition	Technology				
1	WLAN (2.4GHz)	Bluetooth	Zigbee	Zigbee Thread	WWAN (2G/3G/4G)
2	WLAN (5GHz)	Bluetooth	Zigbee	Zigbee Thread	WWAN (2G/3G/4G)

Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.

Condition 1: 0.08868/1 + 0.00071/1 + 0.05791/1 + 0.05355/1 + 0.18564/0.5495 = 0.53871

Condition 2: 0.010278/1 + 0.00071/1 + 0.05791/1 + 0.05355/1 + 0.18564/0.5495 = 0.55281

Therefore the maximum calculations of above situations are less than the "1" limit.

--- END ---