

**FCC RF EXPOSURE REQUIREMENTS****General Information**

FCC ID: G9H2-8021A 5.8GHz FHSS (Base and Handset)

Device Category:

EUT: Base Unit: Mobile per Part 2.1091  
EUT: Handset Unit: Portable per Part 2.1093

Environment: General Population/Uncontrolled Exposure

**Operating Configurations and Exposure Conditions:**

The EUT base unit is normally operated at least 20 cm away from the human body.

The EUT handset is operated close to the head and to the body with belt clip. Refer to Exhibit A(9) for the SAR Test Report.

**Maximum Permissible Exposure Calculation: BASE UNIT**

The minimum separation distance, for compliance with the limit, is calculated as follows:

$$E (V/m) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power density: } P_d (mW/cm^2) = \frac{E^2}{3770}$$

The limit for general population/uncontrolled exposure environment above 1500MHz is 1mW/cm<sup>2</sup>

Separation Distance	Antenna Gain (dBi)	
	Integral	
Time Division Source Based Average Power EIRP (mW)	(in)	(cm)
152.9 mW	1.37	3.49

**BASE UNIT**

**RF Exposure Calculations**

1. The limit for general population/uncontrolled environment above 1500 MHz is 1.0 mW/cm<sup>2</sup>.
2. The Field Strength  $E$  (V/M) =  $\sqrt{1.0 \times 3770} = 61.4$
3. The distance  $d$  to achieve the 1.0 mW/cm<sup>2</sup> power density is as follows

$$d = \frac{\sqrt{30 \times P \times G}}{E}$$
$$d = \frac{\sqrt{30 \times 0.1529 \text{ W} \times 1}}{61.4} = \frac{2.1417}{61.4} = 3.49 \text{ cm}$$

**RF Field Strength Calculations:**

1. F. S. = 120.84 dB $\mu$ V/m
2.  $F.S. = \text{antilog } \frac{120.84}{20} = \text{antilog } 6.042 = 1.1015 \text{ V/M}$
3.  $ERP = \frac{(1.1015)^2 \times 9}{49.2} = 222 \text{ mW}$
4. EIRP =  $222 \times 1.64 = 364 \text{ mW}$
5. Time Division Source Based Average Power  
 $= 364 \times \frac{1.05 \text{ mS (on time 1 + 4 slots)}}{10 \text{ mS}} = 364 \times 0.42 = 152.9 \text{ mW}$

**Conclusion:**

The device complies with the MPE requirements by providing a safe separation distance between the antenna, including any radiating structure, and any persons (human body excluding hands, wrists, ankles, and feet).

**Proposed RF Exposure Safety Information to Include in User's Manual:**

**“RF Radiation Exposure Statement**

This equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20 centimeters between the radiator and your body. This transmitter must not be co-located in conjunction with any other antenna or transmitter.”

**HANDSET UNIT**

**Test Data:**

Refer to SAR Report - Exhibit A(9)-1 to Exhibit A(9)-67.

**Proposed RF Exposure Safety Information to Include in User's Manual:**

**“FCC RF Exposure Requirements**

For body worn operation, this phone has been tested and meets the FCC RF exposure guidelines when used with the belt clip supplied with this product. Use of other accessories may not ensure compliance with FCC RF exposure guidelines.”