

Test Laboratory: Compliance Certification Services Inc.

D5GHz V2 SN 1004

DUT: Dipole 5GHz ; Type: D5GHz V2; Serial: 1004

Communication System: CW5GHz; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5800 \text{ MHz}$; $\sigma = 5.4 \text{ mho/m}$; $\epsilon_r = 36.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Air Temperature: 25.5 deg C; Liquid Temperature: 24.5 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(4.28, 4.28, 4.28);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 34; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Pin=250mW,d=10mm f=5800MHz/Area Scan (8x8x1): Measurement

grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 46.5 mW/g

Pin=250mW,d=10mm f=5800MHz/Zoom Scan (8x8x8)/Cube 0:

Measurement grid: dx=4.3mm, dy=4.3mm, dz=3mm

Reference Value = 77.7 V/m; Power Drift = -0.012 dB

Peak SAR (extrapolated) = 64.2 W/kg

SAR(1 g) = 19.3 mW/g; SAR(10 g) = 4.9 mW/g

Maximum value of SAR (measured) = 41.5 mW/g

Pin=250mW,d=10mm f=5800MHz/Z Scan (1x1x51): Measurement grid:

dx=20mm, dy=20mm, dz=2mm

Maximum value of SAR (measured) = 34.9 mW/g

