

APPLICANT: Thomson Consumer Electronics

FCC ID: G9H2-9920B

TABLE OF CONTENTS

TEST REPORT:

PAGE 1.....LETTER EXPLAINING PURPOSE OF APPLICATION
PAGE 1A.....15.214(d) - SECURITY CODING INFORMATION
PAGE 2-3.....TEST EQUIPMENT LIST AND TEST PROCEDURE
PAGE 4-5.....CIRCUIT DESCRIPTIONS
PAGE 6.....RADIATION INTERFERENCE TEST DATA - BASE
PAGE 7.....RADIATION INTERFERENCE TEST DATA - HANDSET
PAGE 8.....OCCUPIED BANDWIDTH TEST DATA
PAGE 9.....POWERLINE CONDUCTED TEST DATA

EXHIBITS:

EXHIBIT 1.....POWER OF ATTORNEY
EXHIBIT 2A.....BASE RF SCHEMATIC
EXHIBIT 2B.....BASE VCO SCHEMATIC
EXHIBIT 2C.....BASE MAIN CIRCUIT SCHEMATIC
EXHIBIT 3A.....HANDSHET RF SCHEMATIC
EXHIBIT 3B.....HANDSET VCO SCHEMATIC
EXHIBIT 3C.....HANDSET MAIN CIRCUIT SCHEMATIC
EXHIBIT 4.....FCC ID LABEL SAMPLES
EXHIBIT 5A-5H.....INTERNAL PHOTOGRAPHS
EXHIBIT 6.....LINE 1 POWERLINE CONDUCTED PLOT - BASE
EXHIBIT 7.....LINE 2 POWERLINE CONDUCTED PLOT - BASE
EXHIBIT 8.....OCCUPIED BANDWIDTH PLOT - CW - BASE
EXHIBIT 9.....OCCUPIED BANDWIDTH PLOT - 2500 HZ TONE - BASE
EXHIBIT 10.....OCCUPIED BANDWIDTH PLOT - NO MOD - HANDSET
EXHIBIT 11.....OCCUPIED BANDWIDTH PLOT - LOUD VOICE - HANDSET

APPLICANT: Thomson Consumer Electronics

FCC ID: G9H2-9920B

REPORT #: F:\CUS\T\TELIAN\TEL213C8.RPT

PAGE #: TABLE OF CONTENTS

28 JULY 1998

Federal Communication Commission
Authorization and Evaluation Division
7435 Oakland Mills Road
Columbia, MD 21046

SUBJECT: FCC ID: G9H2-9920B
Thomson Consumer Electronics

REFERENCE: REQUEST FOR CLASS II PERMISSIVE CHANGE

TO WHOM IT MAY CONCERN:

This letter is a request for a Class II Permissive change. The applicant wishes to make the following modifications to their unit:

They have modified, changed vendors, on the RF tuner portion of the telephone.

Attached you will find test data from the modified device.

Should you have any questions or require any further information, please feel free to contact me at 1-888-472-2424 or E-Mail at info@timcoengr.com

Sincerely,

S. S. Sanders

SSS/sh
Encl.

APPLICANT: Thomson Consumer Electronics
FCC ID: G9H2-9920B
REPORT #: F:\CUS\T\TELIAN\TEL213C8.RPT
PAGE #: 1

SECURITY CODING INFORMATION

APPLICANT: Thomson Consumer Electronics

FCC ID: G9H2-9920B

15.214(d) - THIS DEVICE COMPLIES WITH THE SECURITY CODE REQUIREMENTS OF 15.214(d)(1)(2) AND (3) BY MEANS OF THE FOLLOWING:

THIS PHONE IS EQUIPPED WITH A DIGITAL SECURITY SYSTEM WITH OVER 1 MILLION CODE COMBINATIONS.

WHEN MAKING A CALL, THE TELEPHONE SEARCHES THROUGH ITS 32 AVAILABLE CHANNELS AUTO CHANNEL SCAN TO FIND THE CLEARER ONE.

THE RECEIVER PORTION OF THIS TELEPHONE, FCC ID: G9H2-9920B, WAS TESTED WITH PASSING RESULTS. A VERIFICATION REPORT HAS BEEN ISSUED PER FCC RULES PART 15.109.

APPLICANT: Thomson Consumer Electronics

FCC ID: G9H2-9920B

REPORT #: F:\CUS\T\TELIAN\TEL213C8.RPT

PAGE #: 1A

APPLICANT: Thomson Consumer Electronics
FCC ID: G9H2-9920B

TEST EQUIPMENT LIST

1. Spectrum Analyzer: Hewlett Packard 8566B, with preselector HP 85685A, & Quasi-Peak Adapter HP 85650A, & HP 8449B OPT H02
Cal. 9/30/97
2. Eaton Biconnical Antenna Model 94455-1
20-200 MHz Serial No. 0997 Cal. 9/17/97
3. Electro-Metric Dipole Kit, 20-1000 MHz, Model TDA 25 cal. 5/15/97
4. Electro-Metric Horn 1-18 GHz, Model RGA-180, Cal. 9/24/97
5. Electro-Metric Antennas Model TDS-25-1, TDS-25-2, 9/3/97
6. Electro-Metric Line Impedance Stabilization Network Model
No. EM-7821, Serial No. 101; 100KHz-30MHz 50uH. 9/30/97
7. Electro-Metric Line Impedance Stabilization Network Model
No. EM-7820, Serial No. 2682; 10KHz-30MHz 50uH. 9/30/97

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz. The ambient temperature of the UUT was 89oF with a humidity of 86%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz)	METER READING + ACF = FS
33	20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.4-1992 using a 50uH LISN. Both lines were observed. The bandwidth of the spectrum analyzer was 10kHz with an appropriate sweep speed. The ambient temperature of the UUT was 89oF with a humidity of 86%.

APPLICANT: Thomson Consumer Electronics
FCC ID: G9H2-9920B
REPORT #: F:\CUS\T\TELIAN\TEL213C8.RPT
PAGE #: 2

APPLICANT: Thomson Consumer Electronics
FCC ID: G9H2-9920B

TEST PROCEDURES CONTINUED

ANSI STANDARD C63.4-1992 10.1.7 MEASUREMENT PROCEDURES: The UUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The UUT was placed flush with the back of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

The situation was similar for the conducted measurement except that the table did not rotate. The EUT was setup as described in ANSIC63.4-1992 with the EUT 40 cm from the vertical ground wall.

APPLICANT: Thomson Consumer Electronics
FCC ID: G9H2-9920B
REPORT #: F:\CUS\T\TELIAN\TEL213C8.RPT
PAGE #: 3

APPLICANT: Thomson Consumer Electronics
FCC ID: G9H2-9920B

CIRCUIT_DESCRIPTION:

BASE UNIT

The incoming signal comes in on the antenna and is fed through the duplexer to the LNA, Q500 and then to a SAW bandpass filter, FL501. The frequency range of the base receiver is 926-928MHz. From the bandpass filter the signal is fed to the mixer, Q501 which converts the signal down to 26.05MHz. From Q501 the signal is fed to the IF filter FL502 and then to the integrated circuit U500. In the U500 the signal is converted down to 450KHz and then to the detector for FM signal. From the detector the audio is fed to a low pass filter and to the Channel Detector Indicator. From the low pass filter the audio is fed into another low pass filter and shaper and then to the CPU, U311. From the CPU, U311, the audio is fed to a speaker amplifier and the telephone line depending which is selected. From the CPU the line audio is fed to U305A and then to U305B then to the telephone coupling transformer, T301. The CPU also compares the SECURITY CODES and provides the outgoing SECURITY CODE.

On the transmitting side, when a ring signal is detected the transmitter is turned on by photo coupler integrated circuit U301 and the ring detect signal is fed into the CPU, U306, which in turn triggers the transmitter and send a ring signal to the handset. The base transmit frequency range is 902-904MHz. When the handset answers the base unit connects to the phone line and telephone line audio is fed into the speech network and then to an audio amplifier, Q304. The audio is then fed into the compressor U311. From U311 the audio is fed into the VCO, VT which modulated the outgoing carrier. From the VCO the signal is fed through a series of amplifiers, Q508 & Q509. From Q508 the signal is fed to the antenna.

APPLICANT: Thomson Consumer Electronics
FCC ID: G9H2-9920B
REPORT #: F:\CUS\T\TELIAN\TEL213C8.RPT
PAGE #: 4

APPLICANT: Thomson Consumer Electronics
FCC ID: G9H2-9920B

CIRCUIT_DESCRIPTIONS CONTD.

HANDSET

The incoming signal comes in on the antenna and is fed through the duplexer to the LNA, Q100 and then to a SAW 903MHz bandpass filter. The frequency range of the handset receiver is 902-904MHz. From the bandpass filter the signal is fed to the mixer, Q101 which converts the signal down to 26.05MHz. From Q101 the signal is fed to the IF filter FL102 and then to the integrated circuit U100. In the U100 the signal is converted down to 450KHz and then to the detector for FM signal. From the detector, p/o U100 the audio is fed to a low pass filter and to the RING Detector Indicator. From the low pass filter the audio is fed simultaneously to the earphone element and to the CPU, U101. The earphone audio is fed into U2 and then to U4 then to the receiver element, RC1. The CPU uses the data to continuously monitor the security code.

The transmitter frequency range is 926-928MHz. The outgoing audio is picked up by the microphone and fed to the audio integrated circuit U2. This audio integrated circuit feeds a low pass filter then feed the signal to the VCO, VT. From the VCO the signal is fed in to the amplifier Q107 and Q108 to the duplexer and then to the antenna.

ANTENNA_AND_GROUND_CIRCUITRY

This unit makes use of a short, antenna. The antenna is inductively coupled. The antenna is self contained, no provision is made for an external antenna.

No ground connection is provided. The unit relies on the ground track of the printed circuit board.

APPLICANT: Thomson Consumer Electronics
FCC ID: G9H2-9920B
REPORT #: F:\CUS\T\TELIAN\TEL213C8.RPT
PAGE #: 5

APPLICANT: Thomson Consumer Electronics

FCC ID: G9H2-9920B (BASE)

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NO.: 15.249

REQUIREMENTS: Carrier frequency will not exceed 94.0 dBuV/m

FREQUENCY	LEVEL
____MHz____	____dBuV/M____
902- 928 MHz:	54.0 dBuV/M
ABOVE 960 MHz:	54.0 dBuV/M

TEST DATA:

EMISSION FREQ. MHz	METER READING @ 3m dBuV	COAX LOSS dB	ACF dB	FIELD STRNGTH dBuV/m	MARGIN dB	ANT.
--------------------------	-------------------------------	--------------------	-----------	----------------------------	--------------	------

TUNED FREQUENCY 926.95

926.95	56.90	2.90	24.12	83.92	10.08	V
1853.19	3.70	1.01	27.41	32.12	21.88	V
2779.88R	-0.40	1.15	29.95	30.70	23.30	H
3706.51R	2.30	1.29	32.27	35.85	18.15	V
4633.10R	-3.80	1.43	33.71	31.34	22.66	V
5559.69	-7.10	1.56	34.75	29.22	24.78	H
7412.87R	-4.20	1.84	36.84	34.48	19.52	H

TUNED FREQUENCY 927.61

927.61	55.70	2.90	24.12	82.72	11.28	V
1855.22	3.10	1.01	27.42	31.53	22.47	V
2782.83R	-3.40	1.15	29.96	27.70	26.30	V
3710.44R	2.00	1.29	32.28	35.56	18.44	H
4638.05R	-4.00	1.43	33.72	31.14	22.86	V
5565.66	-7.20	1.57	34.76	29.13	24.87	V
6493.27	1.00	1.70	35.80	38.51	15.46	V
7420.88R	-5.20	1.84	36.85	33.49	20.51	V

SAMPLE CALCULATION:

FSdBuV/m = MR(dBuV) + ACFdB.

METHOD OF MEASUREMENT: The procedure used was ANSI STANDARD. Measurements were made at Timco Engineering, Inc. 6051 N.W. 19th Lane, Gainesville, FL 32605.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: _____ DATE: 28 JULY 1998

APPLICANT: Thomson Consumer Electronics
FCC ID: G9H2-9920B
REPORT #: F:\CUS\T\TELIAN\TEL213C8.RPT
PAGE #: 6

APPLICANT: Thomson Consumer Electronics
 FCC ID: G9H2-9920B (HANDSET)
 NAME OF TEST: RADIATION INTERFERENCE
 RULES PART NO.: 15.249
 REQUIREMENTS: Carrier frequency will not exceed 94.0 dBuV/m

FREQUENCY	LEVEL
____MHz____	____dBuV/M____
902- 928 MHz:	54.0 dBuV/M
ABOVE 960 MHz:	54.0 dBuV/M

TEST DATA:

EMISSION FREQ. MHz	METER READING @ 3m dBuV	COAX LOSS dB	ACF dB	FIELD STRNGTH dBuV/m	MARGIN dB	ANT.
TUNED FREQUENCY 902.91						
902.91	46.00	2.90	24.19	73.09	20.91	V
1805.82	4.10	1.00	27.22	32.32	21.68	H
2708.80R	7.90	1.14	29.77	38.81	15.19	V
3611.76R	8.90	1.27	32.03	42.20	11.80	H
4514.67R	4.90	1.41	33.58	39.89	14.11	V
5417.58R	-3.60	1.54	34.59	32.54	21.46	H
6320.49	-2.30	1.68	35.61	34.99	19.01	V
7223.40	-0.70	1.81	36.63	37.74	16.26	H
903.61	47.30	2.90	24.19	74.39	19.61	V
1807.22	5.20	1.00	27.23	33.43	20.57	H
2710.84R	8.10	1.14	29.78	39.01	14.99	V
3614.46R	9.80	1.27	32.04	43.11	10.89	H
4518.10R	5.60	1.41	33.58	40.59	13.41	V
5421.69R	-2.60	1.54	34.60	33.54	20.46	H
6325.30	-1.80	1.68	35.62	35.50	18.50	V

SAMPLE CALCULATION:

FSdBuV/m = MR(dBuV) + ACFdB.

METHOD OF MEASUREMENT: The procedure used was ANSI STANDARD C63.4-1992 with the following exception: the unit was operated into its own antenna with the antenna at a height of four feet. Measurements were made at Timco Engineering, Inc. 6051 N.W. 19th Lane, Gainesville, FL 32605.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: _____ DATE: 28 JULY 1998

APPLICANT: Thomson Consumer Electronics
 FCC ID: G9H2-9920B
 REPORT #: F:\CUS\T\TELIAN\TEL213C8.RPT
 PAGE #: 7

APPLICANT: Thomson Consumer Electronics
FCC ID: G9H2-9920B
NAME OF TEST: Occupied Bandwidth
RULES PART NO.: 15.233
REQUIREMENTS: The field strength of any emissions appearing between the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 26 dB below the level of the unmodulated carrier or to the general limits of 15.209, whichever permits the higher emission levels.

THE GRAPHS IN EXHIBITS 8-11 REPRESENT THE EMISSIONS TAKEN FOR THIS DEVICE.

METHOD OF MEASUREMENT: A small sample of the transmitter output was fed into the spectrum analyzer and the above photo was taken. The vertical scale is set to -10 dBm per division. The horizontal scale is set to 5 kHz per division.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: _____ 28 JULY 1998

APPLICANT: Thomson Consumer Electronics
FCC ID: G9H2-9920B
REPORT #: F:\CUS\T\TELIAN\TEL213C8.RPT
PAGE #: 8

APPLICANT: Thomson Consumer Electronics
FCC ID: G9H2-9920B
NAME OF TEST: POWER LINE CONDUCTED INTERFERENCE
RULES PART NUMBER: 15.207
MINIMUM REQUIREMENTS: FREQUENCY LEVEL
 ___MHz___ __uV__
 0.450-30 250
TEST PROCEDURE: ANSI STANDARD C63.4-1992

THE HIGHEST EMISSION READ FOR LINE 1 WAS 17.357 uV @ 800 KHz.
THE HIGHEST EMISSION READ FOR LINE 2 WAS 13.167 uV @ 25.15 MHz.

THE GRAPHS IN EXHIBITS 6-7 REPRESENT THE EMISSIONS READ FOR
POWERLINE CONDUCTED FOR THIS DEVICE.

TEST RESULTS: Both lines were observed. The measurements indicate that the unit DOES appear to meet the FCC requirements for this class of equipment.

PERFORMED BY: _____ DATE: 28 JULY 1998

APPLICANT: Thomson Consumer Electronics
FCC ID: G9H2-9920B
REPORT #: F:\CUS\T\TELIAN\TEL213C8.RPT
PAGE #: 9