



M. Flom Associates, Inc. - Global Compliance Center

3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176

www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

ar_____

Date of Report: June 14, 2002
Date of Submission: June 25, 2002

Federal Communications Commission
Via: Electronic Filing

Attention: Authorization & Evaluation Division

Applicant: Honeywell International Inc.

Equipment: MODEL NC-861A consisting of COM Transmitter
and VOR/LOC Receiver, Glide Slope Receiver,
Marker Beacon Receiver and COM Receiver

FCC ID: GB8NC861A

FCC Rules: 1, 2, 15, 87

Gentlemen:

On behalf of the Applicant, enclosed please find Application Form 731, Engineering Test Report and all pertinent documentation, the whole for approval of the referenced equipment as shown.

Filing fees are attached.

We trust the same is in order. Should you need any further information, kindly contact the writer who is authorized to act as agent.

Sincerely yours,

A handwritten signature in black ink, appearing to read 'M. Flom P. Eng.' The signature is written in a cursive style with a horizontal line underneath the name.

Morton Flom, P. Eng.

enclosure(s)
cc: Applicant
MF/cvr

LIST OF EXHIBITS
(FCC **CERTIFICATION** (TRANSMITTERS) - REVISED 9/28/98)

APPLICANT: Honeywell International Inc.

FCC ID: GB8NC861A

BY APPLICANT:

1. LETTER OF AUTHORIZATION	x
2. IDENTIFICATION DRAWINGS, 2.1033(c)(11)	
<u>x</u> LABEL	
<u>x</u> LOCATION OF LABEL	
<u>x</u> COMPLIANCE STATEMENT	
<u>x</u> LOCATION OF COMPLIANCE STATEMENT	
3. PHOTOGRAPHS, 2.1033(c)(12)	x
4. DOCUMENTATION: 2.1033(c)	
(3) USER MANUAL	x
(9) TUNE UP INFO	x
(10) SCHEMATIC DIAGRAM	x
(10) CIRCUIT DESCRIPTION	x
BLOCK DIAGRAM	x
PARTS LIST	x
ACTIVE DEVICES	x
5. MPE REPORT	x

BY M.F.A. INC.

A. TESTIMONIAL & STATEMENT OF CERTIFICATION
B. STATEMENT OF QUALIFICATIONS



M. Flom Associates, Inc. - Global Compliance Center

3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176

www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

T R A N S M I T T E R C E R T I F I C A T I O N

of

FCC ID: GB8NC861A

MODEL: NC-861A consisting of COM Transmitter and VOR/LOC Receiver,
Glide Slope Receiver, Marker Beacon Receiver and COM Receiver

to

FEDERAL COMMUNICATIONS COMMISSION

Rule Part(s) 1, 2, 15, 87

DATE OF REPORT: June 14, 2002

ON THE BEHALF OF THE APPLICANT:

Honeywell International Inc.
Commercial Electronic Systems Inc. - Phoenix

AT THE REQUEST OF:

P.O. x302677L-06B

Honeywell Inc.
Business, Regional & General Aviation
5353 W. Bell Road, MS 2DD80
Glendale, AZ 85308

Attention of:

Robert H. Fuller, Technical Mgr, EPIC Eng'g
(602) 436-4715; FAX: -4040
bob.fuller@honeywell.com
and/or Charles Dosdall, Manager
(602) 436-4653

SUPERVISED BY:



Morton Flom, P. Eng.

THE APPLICANT HAS BEEN CAUTIONED AS TO THE FOLLOWING:

15.21 INFORMATION TO USER.

The users manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) SPECIAL ACCESSORIES.

Equipment marketed to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer, without additional charge.

Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.

TABLE OF CONTENTS

<u>RULE</u>	<u>DESCRIPTION</u>	<u>PAGE</u>
	Test Report	1
2.1033(c)	General Information Required	2
2.1033(c)(14)	Rule Summary	5
	Standard Test Conditions and Engineering Practices	6
2.1046(a)	Carrier Output Power (Conducted)	7
2.1046(a)	ERP Carrier Power (Radiated)	9
2.1051	Unwanted Emissions (Transmitter Conducted)	10
2.1053(a)	Field Strength of Spurious Radiation	13
2.1049(c)(1)	Emission Masks (Occupied Bandwidth)	19
2.1047(a)	Audio Low Pass Filter (Voice Input)	25
2.1047(a)	Audio Frequency Response	28
2.1047(b)	Modulation Limiting	30
2.1055(a)(1)	Frequency Stability (Temperature Variation)	32
2.1055(b)(1)	Frequency Stability (Voltage Variation)	35
2.202(g)	Necessary Bandwidth and Emission Bandwidth	36

PAGE NO.

1 of 36.

Required information per ISO/IEC Guide 25-1990, paragraph 13.2:

a) TEST REPORT

b) Laboratory: M. Flom Associates, Inc.
(FCC: 31040/SIT) 3356 N. San Marcos Place, Suite 107
(Canada: IC 2044) Chandler, AZ 85225

c) Report Number: d0260029

d) Client: Honeywell Inc.
Business, Regional & General Aviation
5353 W. Bell Road, MS 2DD80
Glendale, AZ 85308

e) Identification: NC-861A
FCC ID: GB8NC861A
EUT Description: VHF FM Mobile Transceiver

f) EUT Condition: Not required unless specified in individual tests.

g) Report Date: June 14, 2002
EUT Received: April 15, 2002

h, j, k): As indicated in individual tests.

i) Sampling method: No sampling procedure used.

l) Uncertainty: In accordance with MFA internal quality manual.

m) Supervised by:


Morton Flom, P. Eng.

n) Results: The results presented in this report relate only to the item tested.

o) Reproduction: This report must not be reproduced, except in full, without written permission from this laboratory.

PAGE NO.

2 of 36.

LIST OF GENERAL INFORMATION REQUIRED FOR CERTIFICATIONIN ACCORDANCE WITH FCC RULES AND REGULATIONS,
VOLUME II, PART 2 AND TO

1, 2, 15, 87

Sub-part 2.1033(c)(1): NAME AND ADDRESS OF APPLICANT:

Honeywell International Inc.
Commercial Electronic Systems Inc. - Phoenix
2111 North 19th Avenue
Phoenix, AZ 85027

MANUFACTURER:

Honeywell Inc.
Business, Regional & General Aviation
5353 W. Bell Road, MS 2DD80
Glendale, AZ 85308

(c)(2): FCC ID: GB8NC861AMODEL NO: NC-861A consisting of COM Transmitter and
VOR/LOC Receiver, Glide Slope Receiver,
Marker Beacon Receiver and COM Receiver(c)(3): INSTRUCTION MANUAL(S):


PLEASE SEE ATTACHED EXHIBITS

(c)(4): TYPE OF EMISSION: 6K00A3E(c)(5): FREQUENCY RANGE, MHz: 117.975 to 152.0(c)(6): POWER RATING, Watts: 22
____ Switchable ____ Variable N/A(c)(7): MAXIMUM POWER RATING, Watts: 100DUT RESULTS: Passes Fails _____

PAGE NO.

3 of 36.

M. Flom Associates, Inc. is accredited by the American Association for Laboratory Accreditation (A2LA) as shown in the scope below.



"This laboratory is accredited by the American Association for Laboratory Accreditation (A2LA) and the results shown in this report have been determined in accordance with the laboratory's terms of accreditation unless stated otherwise in the report."

Should this report contain any data for tests for which we are not accredited, or which have been undertaken by a subcontractor that is not A2LA accredited, such data would not be covered by this laboratory's A2LA accreditation.

PAGE NO.

4 of 36.

Subpart 2.1033 (continued)

(c)(8): VOLTAGES & CURRENTS IN ALL ELEMENTS IN FINAL R. F. STAGE,
INCLUDING FINAL TRANSISTOR OR SOLID STATE DEVICE:

COLLECTOR CURRENT, A = per manual
COLLECTOR VOLTAGE, Vdc = per manual
SUPPLY VOLTAGE, Vdc = 28

(c)(9): TUNE-UP PROCEDURE:

PLEASE SEE ATTACHED EXHIBITS

(c)(10): CIRCUIT DIAGRAM/CIRCUIT DESCRIPTION:

Including description of circuitry & devices provided for determining and stabilizing frequency, for suppression of spurious radiation, for limiting modulation and limiting power.

PLEASE SEE ATTACHED EXHIBITS

(c)(11): LABEL INFORMATION:

PLEASE SEE ATTACHED EXHIBITS

(c)(12): PHOTOGRAPHS:

PLEASE SEE ATTACHED EXHIBITS

(c)(13): DIGITAL MODULATION DESCRIPTION:

 ATTACHED EXHIBITS
 x N/A

(c)(14): TEST AND MEASUREMENT DATA:

FOLLOWS

PAGE NO.

5 of 36.

Sub-part

2.1033(c)(14):TEST AND MEASUREMENT DATA

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Volume II; Part 2, Sub-part J, Sections 2.947, 2.1033(c), 2.1041, 2.1046, 2.1047, 2.1079, 2.1051, 2.1053, 2.1055, 2.1057 and the following individual Parts:

- ____ 21 - Domestic Public Fixed Radio Services
- ____ 22 - Public Mobile Services
- ____ 22 Subpart H - Cellular Radiotelephone Service
- ____ 22.901(d) - Alternative technologies and auxiliary services
- ____ 23 - International Fixed Public Radiocommunication services
- ____ 24 - Personal Communications Services
- ____ 74 Subpart H - Low Power Auxiliary Stations
- ____ 80 - Stations in the Maritime Services
- ____ 80 Subpart E - General Technical Standards
- ____ 80 Subpart F - Equipment Authorization for Compulsory Ships
- ____ 80 Subpart K - Private Coast Stations and Marine Utility Stations
- ____ 80 Subpart S - Compulsory Radiotelephone Installations for Small Passenger Boats
- ____ 80 Subpart T - Radiotelephone Installation Required for Vessels on the Great Lakes
- ____ 80 Subpart U - Radiotelephone Installations Required by the Bridge-to-Bridge Act
- ____ 80 Subpart V - Emergency Position Indicating Radiobeacons (EPIRB'S)
- ____ 80 Subpart W - Global Maritime Distress and Safety System (GMDSS)
- ____ 80 Subpart X - Voluntary Radio Installations
- x 87 - Aviation Services
- ____ 90 - Private Land Mobile Radio Services
- ____ 94 - Private Operational-Fixed Microwave Service
- ____ 95 Subpart A - General Mobile Radio Service (GMRS)
- ____ 95 Subpart C - Radio Control (R/C) Radio Service
- ____ 95 Subpart D - Citizens Band (CB) Radio Service
- ____ 95 Subpart E - Family Radio Service
- ____ 95 Subpart F - Interactive Video and Data Service (IVDS)
- ____ 97 - Amateur Radio Service
- ____ 101 - Fixed Microwave Services

PAGE NO.

6 of 36.

STANDARD TEST CONDITIONS
and
ENGINEERING PRACTICES

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992/2000 Draft, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst case measurements.

PAGE NO. 7 of 36.
NAME OF TEST: Carrier Output Power (Conducted)
SPECIFICATION: 47 CFR 2.1046(a)
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.1
TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT was connected to a resistive coaxial attenuator of normal load impedance, and the unmodulated output power was measured by means of an R. F. Power Meter.
2. Measurement accuracy is $\pm 3\%$.

MEASUREMENT RESULTS
(Worst case)


FREQUENCY OF CARRIER, MHz = 134.875, 118.0, 151.975

POWER SETTING	R. F. POWER, WATTS
High	22

PERFORMED BY:  Doug Noble, B.A.S. E.E.T.

TRANSMITTER POWER CONDUCTED MEASUREMENTS

TEST 1: R. F. POWER OUTPUT
 TEST 2: FREQUENCY STABILITY



Asset Description (as applicable)	s/n
(1) COAXIAL ATTENUATOR	
i00122 Narda 766-10	7802
i00123 Narda 766-10	7802A
i00069 Bird 8329 (30 dB)	1006
i00113 Sierra 661A-3D	1059
(2) POWER METERS	
i00014 HP 435A	1733A05836
i00039 HP 436A	2709A26776
i00020 HP 8901A POWER MODE	2105A01087
(3) FREQUENCY COUNTER	
i00042 HP 5383A	1628A00959
i00019 HP 5334B	2704A00347
i00020 HP 8901A FREQUENCY MODE	2105A01087

PAGE NO.

9 of 36.

NAME OF TEST:

ERP Carrier Power (Radiated)


SPECIFICATION:

TIA/EIA 603A (Substitution Method)

2.2.17.1 Definition: The average radiated power of a licensed device is the equivalent power required, when delivered to a half-wave dipole or horn antenna, to produce at a distant point the same average received power as produced by the licensed device.

2.2.17.2 Method of Measurement:

a) Connect the equipment as illustrated. Place the transmitter to be tested on the turntable in the standard test site.



b) Raise and lower the test antenna from 1m to 6 m with the transmitter facing the antenna and record the highest received signal in dB as LVL.

c) Repeat step b) for seven additional readings at 45° interval positions of the turntable.

d) Replace the transmitter under test with a half-wave or horn vertically polarized antenna. The center of the antenna should be at the same location as the transmitter under test. Connect the antenna to a signal generator with a known output power and record the path loss in dB or LOSS.

e) Calculate the average radiated output power from the readings in step c) and d) by the following:

$$\text{average radiated power} = 10 \log_{10} \sum 10(\text{LVL} - \text{LOSS})/10 \text{ (dBm)}$$

	RESULTS					
	118.00 MHz		134.875 MHz		157.975 MHz	
	LVL, dbm	Path Loss, db	LVL, dbm	Path Loss, db	LVL, dbm	Path Loss, db
0°	43.8	+0.1	39.6	-1.2	41.1	-0.6
45°	42.6	+0.1	39.5	-1.2	41.1	-0.6
90°	44.2	+0.1	38.5	-1.2	41.6	-0.6
135°	41.8	+0.1	39.4	-1.2	42.0	-0.6
180°	43.4	+0.1	40.7	-1.2	41.9	-0.6
225°	42.0	+0.1	40.0	-1.2	39.2	-0.6
270°	43.7	+0.1	38.9	-1.2	39.9	-0.6
315°	42.3	+0.1	40.2	-1.2	41.7	-0.6

	118.00 MHz	134.875 MHz	151.975 MHz
Av. Radiated Power:	42.9 dbm	40.8 dbm	41.7 dbm

PAGE NO. 10 of 36.

NAME OF TEST: Unwanted Emissions (Transmitter Conducted)

SPECIFICATION: 47 CFR 2.1051

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.13

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The emissions were measured for the worst case as follows:
 - (a): within a band of frequencies defined by the carrier frequency plus and minus one channel.
 - (b): from the lowest frequency generated in the EUT and to at least the 10th harmonic of the carrier frequency, or 40 GHz, whichever is lower.
2. The magnitude of spurious emissions that are attenuated more than 20 dB below the permissible value need not be specified.
3. MEASUREMENT RESULTS: ATTACHED FOR WORST CASE

FREQUENCY OF CARRIER, MHz = 134.875, 118.0, 151.975

SPECTRUM SEARCHED, GHz = 0 to 10 x F_c

MAXIMUM RESPONSE, Hz = 282

ALL OTHER EMISSIONS = \geq 20 dB BELOW LIMIT

PERFORMED BY:



Doug Noble, B.A.S. E.E.T.

PAGE NO.

11 of 36.

TRANSMITTER SPURIOUS EMISSION

TEST A. OCCUPIED BANDWIDTH (IN-BAND SPURIOUS)
 TEST B. OUT-OF-BAND SPURIOUS



Asset Description (as applicable)	s/n
(1) <u>AUDIO OSCILLATOR/GENERATOR</u>	
i00010 HP 204D	1105A04683
i00017 HP 8903A	2216A01753
i00012 HP 3312A	1432A11250
(2) <u>COAXIAL ATTENUATOR</u>	
i00122 Narda 766-10	7802
i00123 Narda 766-10	7802A
i00069 Bird 8329 (30 dB)	1006
i00113 Sierra 661A-3D	1059
(3) <u>FILTERS; NOTCH, HP, LP, BP</u>	
i00126 Eagle TNF-1	100-250
i00125 Eagle TNF-1	50-60
i00124 Eagle TNF-1	250-850
(4) <u>SPECTRUM ANALYZER</u>	
i00048 HP 8566B	2511A01467
i00029 HP 8563E	3213A00104

PAGE NO.

12 of 36.

NAME OF TEST:

Unwanted Emissions (Transmitter Conducted)

LIMIT(S), dBc

-(43+10xLOG P) = -56 (22 Watts)

STATE: 2:High Power g0240028: 2002-Apr-18 Thu 08:58:00

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	LEVEL, dBm	LEVEL, dBc	MARGIN, dB
118.000000	236.186500	-41.7	-85.2	-28.7
134.875000	269.743500	-41.3	-84.8	-28.3
151.975000	303.955000	-41.6	-85.1	-28.6
118.000000	354.152000	-41.6	-85.1	-28.6
134.875000	404.738500	-41	-84.5	-28
151.975000	455.849500	-40.9	-84.4	-27.9
118.000000	471.780000	-41.3	-84.8	-28.3
134.875000	539.512500	-39.9	-83.4	-26.9
118.000000	590.163000	-40.3	-83.8	-27.3
151.975000	607.872000	-41.1	-84.6	-28.1
134.875000	674.480000	-40.4	-83.9	-27.4
118.000000	708.026000	-40.4	-83.9	-27.4
151.975000	759.903500	-40.6	-84.1	-27.6
134.875000	809.036500	-40.4	-83.9	-27.4
118.000000	826.038500	-40.6	-84.1	-27.6
151.975000	911.751500	-41.3	-84.8	-28.3
118.000000	943.823500	-40.7	-84.2	-27.7
134.875000	943.883500	-40.4	-83.9	-27.4
118.000000	1062.070000	-39.4	-82.9	-26.4
151.975000	1063.781500	-40.8	-84.3	-27.8
134.875000	1079.166500	-40.9	-84.4	-27.9
118.000000	1180.138500	-40.6	-84.1	-27.6
134.875000	1213.708500	-41.4	-84.9	-28.4
151.975000	1215.974500	-41.6	-85.1	-28.6
118.000000	1297.830500	-40.4	-83.9	-27.4
134.875000	1348.883000	-40.9	-84.4	-27.9
151.975000	1367.847500	-39.1	-82.6	-26.1
118.000000	1416.055000	-40.1	-83.6	-27.1
134.875000	1483.746500	-40.6	-84.1	-27.6
151.975000	1519.835000	-40.9	-84.4	-27.9
118.000000	1534.082500	-40.9	-84.4	-27.9
134.875000	1618.398500	-39.7	-83.2	-26.7
118.000000	1652.243500	-40.9	-84.4	-27.9
151.975000	1671.777000	-39	-82.5	-26
134.875000	1753.480000	-40.2	-83.7	-27.2
118.000000	1770.195000	-40.6	-84.1	-27.6
151.975000	1823.621500	-41	-84.5	-28
134.875000	1888.209000	-40	-83.5	-27
151.975000	1975.600000	-40.6	-84.1	-27.6
134.875000	2023.260500	-39.7	-83.2	-26.7
151.975000	2127.452000	-40.1	-83.6	-27.1
151.975000	2279.737500	-39.1	-82.6	-26.1

PERFORMED BY:

Doug Noble, B.A.S. E.E.T.

PAGE NO. 13 of 36.

NAME OF TEST: Field Strength of Spurious Radiation

SPECIFICATION: 47 CFR 2.1053(a)


GUIDE: ANSI/TIA/EIA-603-1992/2001, Paragraph 1.2.12 and Table 16, 47 CFR 22.917

MEASUREMENT PROCEDURE

1.2.12.1 Definition: Radiated spurious emissions are emissions from the equipment when transmitting into a non-radiating load on a frequency or frequencies which are outside an occupied band sufficient to ensure transmission of information of required quality for the class of communications desired.

1.2.12.2 Method of Measurement

- A) Connect the equipment as illustrated
- B) Adjust the spectrum analyzer for the following settings:
 - 1) Resolution Bandwidth 100 kHz (<1 GHZ), 1 MHZ (> 1GHz).
 - 2) Video Bandwidth \geq 3 times Resolution Bandwidth, or 30 kHz (22.917)
 - 3) Sweep Speed \leq 2000 Hz/second
 - 4) Detector Mode = Mean or Average Power
- C) Place the transmitter to be tested on the turntable in the standard test site. The transmitter is transmitting into a non-radiating load which is placed on the turntable. The RF cable to this load should be of minimum length.



PAGE NO.


14 of 36.

NAME OF TEST: Field Strength of Spurious Radiation (Cont.)

D) For each spurious measurement the test antenna should be adjusted to the correct length for the frequency involved. This length may be determined from a calibration ruler supplied with the equipment. Measurements shall be made from the lowest radio frequency generated in the equipment to the tenth harmonic of the carrier, except for the region close to the carrier equal to \pm the test bandwidth (see section 1.3.4.4).

E) For each spurious frequency, raise and lower the test antenna from 1 m to 4 m to obtain a maximum reading on the spectrum analyzer with the test antenna at horizontal polarity. Repeat this procedure to obtain the highest possible reading. Record this maximum reading.

F) Repeat step E) for each spurious frequency with the test antenna polarized vertically.



G) Reconnect the equipment as illustrated.

H) Keep the spectrum analyzer adjusted as in step B).

I) Remove the transmitter and replace it with a substitution antenna (the antenna should be half-wavelength for each frequency involved). The center of the substitution antenna should be approximately at the same location as the center of the transmitter. At lower frequencies, where the substitution antenna is very long, this will be impossible to achieve when the antenna is polarized vertically. In such case the lower end of the antenna should be 0.3 m above the ground.

PAGE NO.

15 of 36.

NAME OF TEST: Field Strength of Spurious Radiation (Cont.)

J) Feed the substitution antenna at the transmitter end with a signal generator connected to the antenna by means of a non-radiating cable. With the antennas at both ends horizontally polarized and with the signal generator tuned to a particular spurious frequency, raise and lower the test antenna to obtain a maximum reading at the spectrum analyzer. Adjust the level of the signal generator output until the previously recorded maximum reading for this set of conditions is obtained. This should be done carefully repeating the adjustment of the test antenna and generator output.

K) Repeat step J) with both antennas vertically polarized for each spurious frequency.

L) Calculate power in dBm into a reference ideal half-wave dipole antenna by reducing the readings obtained in steps J) and K) by the power loss in the cable between the generator and the antenna and further corrected for the gain of the substitution antenna used relative to an ideal half-wave dipole antenna.

M) The levels recorded in step L) are absolute levels of radiated spurious emissions in dBm. The radiated spurious emissions in dB can be calculated by the following:

Radiated spurious emissions dB =
 $10\log_{10}(\text{TX power in watts}/0.001) - \text{the levels in step 1})$

NOTE: It is permissible that other antennas provided can be referenced to a dipole.

Test Equipment:

Asset	Description (as applicable)	s/n	Cycle	Last Cal	
Per ANSI C63.4-1992/2000 Draft, 10.1.4					
<u>TRANSDUCER</u>					
i00088	EMCO 3109-B 25MHz-300MHz	2336	12 mo.	Sep-01	
i00065	EMCO 3301-B Active Monopole	2635	12 mo.	Sep-01	
i00089	Aprel 2001 200MHz-1GHz	001500	12 mo.	Sep-01	
i00103	EMCO 3115 1GHz-18GHz	9208-3925	12 mo.	Sep-01	
<u>AMPLIFIER</u>					
i00028	HP 8449A	2749A00121	12 mo.	Mar-02	
SPECTRUM ANALYZER					
i00029	HP 8563E	3213A00104	12 mo.	Jan-02	
i00033	HP 85462A	3625A00357	12 mo.	Jan-02	
i00048	HP 8566B	2511AD1467	6 mo.	Jan-02	
<u>MICROPHONE, ANTENNA PORT, AND CABLING</u>					
Microphone	Yes	Cable Length	1.0	Meters	
Antenna Port Terminated	Yes	Load	N/A	Antenna Gain	3 dB
All Ports Terminated by	N/A	Peripheral	N/A		

PAGE NO.

16 of 36.

NAME OF TEST: Field Strength of Spurious Radiation
 g0240016: 2002-Apr-16 Tue 08:54:00
 STATE: 2:High Power

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	ERP, dBm	MARGIN, dB
134.875000	269.758000	-71.6	≤ -102.03
134.875000	404.626500	-71.3	≤ -102.03
134.875000	539.501500	-71.2	≤ -102.03
134.875000	674.374380	-66.6	≤ -102.03
134.875000	809.248800	-66.5	≤ -102.03
134.875000	944.123800	-61.7	≤ -102.03
134.875000	1079.001000	-64.5	≤ -102.03
134.875000	1213.876000	-63.1	≤ -102.03
134.875000	1348.751000	-59.8	≤ -102.03
134.875000	1483.626800	-61.6	≤ -102.03
134.875000	1618.501800	-58.5	≤ -102.03
134.875000	1753.376800	-58.7	≤ -102.03

SUPERVISED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO. 17 of 36.

NAME OF TEST: Radiated Spurious Emissions

GPS BAND: 1559-1610 MHz
FAA Limit = -60 dbm ± 1 MHz

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	dbm
120.925	1559.025	-66.6
	1572.025	-66.7
	1585.025	-66.9
121.175	1562.275	-71.1
	1575.275	-69.2
	1588.275	-69.4
123.825	1596.725	-68.4
	1609.725	-68.2
	1622.725	-68.0
130.625	1555.500	-66.9
	1567.500	-66.1
	1579.500	-65.8
131.275	1563.300	-65.6
	1575.300	-65.3
	1587.300	-65.5
134.150	1597.800	-64.8
	1609.800	-64.6
	1621.800	-64.2

PAGE NO. 18 of 36.

NAME OF TEST: Spurious Emission Levels

IN GPS BAND (1559 to 1610 MHz)

Limit = \leq -60 dbm

FREQUENCY TUNED, MHz	LEVEL, dbm	
	12 th HARMONIC	13 th HARMONIC
117.00	-66.6	-70.2
118.00	-66.5	-70.6
119.00	-64.3	-70.7
133.875	-68.5	-69.2
134.875	-67.3	-68.9
135.875	-69.4	-68.5
150.875	-68.3	-69.2
151.875	-68.7	-66.8
152.875	-69.4	-65.5

PAGE NO. 19 of 36.

NAME OF TEST: Emission Masks (Occupied Bandwidth)

SPECIFICATION: 47 CFR 2.1049(c)(1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.11

TEST EQUIPMENT: As per previous page


MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page, with the Spectrum Analyzer connected.
2. For EUTs supporting audio modulation, the audio signal generator was adjusted to the frequency of maximum response and with output level set for $\pm 2.5/\pm 1.25$ kHz deviation (or 50% modulation). With level constant, the signal level was increased 16 dB.
3. For EUTs supporting digital modulation, the digital modulation mode was operated to its maximum extent.
4. The Occupied Bandwidth was measured with the Spectrum Analyzer controls set as shown on the test results.
5. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

20 of 36.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0240023: 2002-Apr-17 Wed 13:34:00
 STATE: 2:High Power




PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO.

21 of 36.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0240024: 2002-Apr-17 Wed 13:56:00
 STATE: 2:High Power



POWER:
 MODULATION:

HIGH
 VOICE: 2500 Hz SINE WAVE
 MAX MODULATION @ 86.3 % AM


PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO.

22 of 36.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0240025: 2002-Apr-17 Wed 13:58:00
 STATE: 2:High Power



POWER:
 MODULATION:

HIGH
 VOICE: 2500 Hz SINE WAVE
 99 % POWER BANDWIDTH


PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO.

23 of 36.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0240026: 2002-Apr-17 Wed 14:00:00
 STATE: 2:High Power



POWER:
 MODULATION:

HIGH
 VOICE: 2500 Hz SINE WAVE
 BANDWIDTH EDGES @ 86.3 % AM
 MODULATION


PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO.

24 of 36.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0240027: 2002-Apr-17 Wed 14:05:00
 STATE: 2:High Power



POWER:
 MODULATION:

HIGH
 VOICE: 2500 Hz SINE WAVE
 MAX MODULATION @ 86.3 % AM

PERFORMED BY:

Doug Noble, B.A.S. E.E.T.

PAGE NO. 25 of 36.

NAME OF TEST: Audio Low Pass Filter (Voice Input)

SPECIFICATION: 47 CFR 2.1047(a)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.15

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE


1. The EUT and test equipment were set up such that the audio input was connected at the input to the modulation limiter, and the modulated stage.
2. The audio output was connected at the output to the modulated stage.
3. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

26 of 36.

TRANSMITTER TEST SET-UP

TEST A. MODULATION CAPABILITY/DISTORTION
 TEST B. AUDIO FREQUENCY RESPONSE
 TEST C. HUM AND NOISE LEVEL
 TEST D. RESPONSE OF LOW PASS FILTER
 TEST E. MODULATION LIMITING




Asset (as applicable)	Description	s/n
(1) <u>Audio Oscillator</u>		
i00010	HP 204D	1105A04683
i00017	HP 8903A	2216A01753
i00118	HP 33120A	US36002064
(2) <u>COAXIAL ATTENUATOR</u>		
i00122	NARDA 766-10	7802
i00123	NARDA 766-10	7802A
i00113	SIERRA 661A-3D	1059
i00069	BIRD 8329 (30 dB)	10066
(3) <u>MODULATION ANALYZER</u>		
i00020	HP 8901A	2105A01087
(4) <u>AUDIO ANALYZER</u>		
i00017	HP 8903A	2216A01753

PAGE NO.

27 of 36.

NAME OF TEST: Audio Low Pass Filter (Voice Input)
g0240002: 2002-Apr-17 Wed 15:17:00
STATE: 0:General



PERFORMED BY:



Doug Noble, B.A.S. E.E.T.

PAGE NO. 28 of 36.

NAME OF TEST: Audio Frequency Response

SPECIFICATION: 47 CFR 2.1047(a)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.6

TEST EQUIPMENT: As per previous page


MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page.
2. The audio signal generator was connected to the audio input circuit/microphone of the EUT.
3. The audio signal input was adjusted to obtain 20% modulation at 1 kHz, and this point was taken as the 0 dB reference level.
4. With input levels held constant and below limiting at all frequencies, the audio signal generator was varied from 100 Hz to 50 kHz.
5. The response in dB relative to 1 kHz was then measured, using the HP 8901A Modulation Analyzer.
6. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

29 of 36.

NAME OF TEST: Audio Frequency Response
 g0240001: 2002-Apr-17 Wed 15:11:00
 STATE: 0:General



Frequency of Maximum Audio Response, Hz = 282

Additional points:

FREQUENCY, Hz	LEVEL, dB
300	4.13
20000	-32.61
30000	-32.17
50000	-32.16

PERFORMED BY:



Doug Noble, B.A.S. E.E.T.

PAGE NO. 30 of 36.

NAME OF TEST: Modulation Limiting

SPECIFICATION: 47 CFR 2.1047(b)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.3

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The signal generator was connected to the input of the EUT as for "Frequency Response of the Modulating Circuit."
2. The modulation response was measured for each of three frequencies (one of which was the frequency of maximum response), and the input voltage was varied and was observed on an HP 8901A Modulation Analyzer.
3. The input level was varied from 30% modulation (± 1.5 kHz deviation) to at least 20 dB higher than the saturation point.
4. Measurements were performed for both negative and positive modulation and the respective results were recorded.


5. MEASUREMENT RESULTS: ATTACHED

PAGE NO.


31 of 36.

NAME OF TEST: Modulation Limiting
g0240006: 2002-Apr-17 Wed 15:58:00
STATE: 0:General

Positive Peaks:



Negative Peaks:



PERFORMED BY:


Doug Noble, B.A.S. E.E.T.

PAGE NO. 32 of 36.

NAME OF TEST: Frequency Stability (Temperature Variation)

SPECIFICATION: 47 CFR 2.1055(a)(1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

TEST CONDITIONS: As Indicated

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE


1. The EUT and test equipment were set up as shown on the following page.
2. With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was noted within one minute.
3. With power OFF, the temperature was raised in 10°C steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.
4. The temperature tests were performed for the worst case.
5. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

33 of 36.

TRANSMITTER TEST SET-UP

TEST A. OPERATIONAL STABILITY
 TEST B. CARRIER FREQUENCY STABILITY
 TEST C. OPERATIONAL PERFORMANCE STABILITY
 TEST D. HUMIDITY
 TEST E. VIBRATION
 TEST F. ENVIRONMENTAL TEMPERATURE
 TEST G. FREQUENCY STABILITY: TEMPERATURE VARIATION
 TEST H. FREQUENCY STABILITY: VOLTAGE VARIATION




Transmitter Test Set Up

Asset Description (as applicable)		s/n
(1) TEMPERATURE, HUMIDITY, VIBRATION		
i00027 Tenney Temp. Chamber		9083-765-234
i00 Weber Humidity Chamber		
i00 L.A.B. RVH 18-100		
(2) COAXIAL ATTENUATOR		
i00122 NARDA 766-10		7802
i00123 NARDA 766-10		7802A
i00113 SIERRA 661A-3D		1059
i00069 BIRD 8329 (30 dB)		10066
(3) R.F. POWER		
i00014 HP 435A POWER METER		1733A05839
i00039 HP 436A POWER METER		2709A26776
i00020 HP 8901A POWER MODE		2105A01087
(4) FREQUENCY COUNTER		
i00042 HP 5383A		1628A00959
i00019 HP 5334B		2704A00347
i00020 HP 8901A		2105A01087

PAGE NO.

34 of 36.

NAME OF TEST: Frequency Stability (Temperature Variation)
g0240008: 2002-Apr-18 Thu 10:26:39
STATE: 0:General



PERFORMED BY:



Doug Noble, B.A.S. E.E.T.

PAGE NO. 35 of 36.

NAME OF TEST: Frequency Stability (Voltage Variation)

SPECIFICATION: 47 CFR 2.1055(d)(1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The EUT was placed in a temperature chamber at $25\pm5^{\circ}\text{C}$ and connected as for "Frequency Stability - Temperature Variation" test.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

RESULTS: Frequency Stability (Voltage Variation)

g0240029: 2002-Apr-18 Thu 09:35:19

STATE: 0:General

LIMIT, ppm	= 5
LIMIT, Hz	= 674
BATTERY END POINT (Voltage)	= 22.4

% of STV	Voltage	Frequency, MHz	Change, Hz	Change, ppm
85	23.8	134.874990	-10	-0.07
100	28	134.875000	0	0.00
115	32.2	134.874980	-20	-0.15
80	22.4	134.874980	-20	-0.15

PERFORMED BY:


Doug Noble, B.A.S. E.E.T.

PAGE NO. 36 of 36.

NAME OF TEST: Necessary Bandwidth and Emission Bandwidth

SPECIFICATION: 47 CFR 2.202(g)

MODULATION = 6K00A3E

NECESSARY BANDWIDTH CALCULATION:

MAXIMUM MODULATION (M), kHz	= 3
MAXIMUM DEVIATION (D), kHz	= 0
CONSTANT FACTOR (K)	= 1
NECESSARY BANDWIDTH (B _N), kHz	= (2xM)+(2xDxK)
	= 6

PERFORMED BY:



Doug Noble, B.A.S. E.E.T.

END OF TEST REPORT

TESTIMONIAL
AND
STATEMENT OF CERTIFICATION

THIS IS TO CERTIFY THAT:

1. THAT the application was prepared either by, or under the direct supervision of, the undersigned.
2. THAT the technical data supplied with the application was taken under my direction and supervision.
3. THAT the data was obtained on representative units, randomly selected.
4. THAT, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

CERTIFYING ENGINEER:



Morton Flom, P. Eng.