

1	FCC Type Acceptance Report for ATC Mode "S" Transponder XS-950S/I Honeywell Inc. Drawing EB7517857, Rev. Original - Test Report Data - Functions of Semiconductors - Circuit Descriptions - Equipment Photographs - Personnel Qualifications
2	Honeywell Inc. Integrated Test Specification for the XS-850 Mode "S" Transponder, Drawing No. IT7517800, Rev. M
3	Honeywell Inc., Circuit Card Assembly, A1 Interconnect, Drawing No. 7517820-902, Rev. B
4	Honeywell Inc., Circuit Card Assembly, A2 Processor, Drawing No. 7517826-941, Rev. Original
5	Honeywell Inc., Circuit Card Assembly, XMTR/RCVR A3, Drawing No. 7517835-904, Rev. D
6	Honeywell Inc., Circuit Card Assembly, ATDL Power Supply Unit A4, Drawing No. 7517830-903, Rev. Original
7	Honeywell Inc., XS-950S/I Data Link Transponder Unit Assembly, Drawing No. 7519350, Rev. A
8	Honeywell Inc., Identification Plate (-45, -46), Drawing No. 7021570, Rev. AR with C.O. 103913 and 103927
9	Honeywell Inc., Outline and Installation XS-950S/I, Drawing No. 7519356, Rev. Original
10	Honeywell Inc., Interconnection Diagram – Transponder XS-950S/I, Publication No. 34-52-07 pages 423 thru 431.

<b>ENGINEERING SPECIFICATION</b>		SECURITY NOTATION	SPEC NO. <b>EB7517857</b>	-
<b>ENGINEERING BULLETIN</b>		CLASS <b>A</b>	CAGE CODE <b>55939</b>	REV LTR
DIVISION <b>CAS</b>	DEPARTMENT NO. <b>5810</b>	PRODUCT LINE NO. <b>3839</b>	INITIAL RELEASE DATE <b>31-AUG-1999</b>	
<b>TITLE</b> <b>XS-950S/I FCC TYPE ACCEPTANCE TEST REPORT</b>				
PREPARED BY <i>Jim Proxel</i>		DATE <b>31-AUG-1999</b>	APVD BY TECHNICAL MANAGER <i>P. Bobrowitz</i>	DATE <b>31-AUG-1999</b>
APVD FOR SCM <i>for Jim Proxel</i>		DATE	APVD FOR SQA	DATE
REF AWAEB/PSAEB NO.	CHECKER	PRODUCT DESIGN CHECKER (FOR REF, SPCL CONT PER EPM I-A-40)		COGNIZANCE OF QE SUPVR (FOR REF, SPCL CONT PER EPM I-A-40)

FOR PAGE INDEX, SEE CR-2. REVISION RECORD FOLLOWS PAGE INDEX

PROPRIETARY NOTICE	
<p>THIS DOCUMENT AND THE INFORMATION DISCLOSED HEREIN ARE PROPRIETARY DATA OF HONEYWELL INC. NEITHER THIS DOCUMENT NOR THE INFORMATION CONTAINED HEREIN SHALL BE REPRODUCED, USED OR DISCLOSED TO OTHERS WITHOUT THE WRITTEN AUTHORIZATION OF HONEYWELL INC.</p>	
NOTICE	
<p>FREEDOM OF INFORMATION ACT (5 USC 552) AND DISCLOSURE OF CONFIDENTIAL INFORMATION GENERALLY (18 USC 1905)</p>	
<p>THIS DOCUMENT IS BEING FURNISHED IN CONFIDENCE BY HONEYWELL INC. THE INFORMATION DISCLOSED HEREIN FALLS WITHIN EXEMPTION (b) (4) OF 5 USC 552 AND THE PROHIBITIONS OF 18 USC 1905.</p>	

Copyright 1999 Honeywell Inc.  
All Rights Reserved

<b>Honeywell</b>	COPY NO.	SECURITY NOTATION	AW/PS CRITICAL NOTATION	CR-1 TITLE PAGE
------------------	----------	-------------------	-------------------------	--------------------

47 CFR 2.995d  
47 CFR 87.133

FREQUENCY STABILITY  
Primary Power Supply  
Variation

40

**TABLE OF CONTENTS**

<u>SECTION</u>	<u>Reference Specification</u>	<u>TITLE</u>	<u>Page</u>
I		INTRODUCTION	1
II		REFERENCES AND ATTACHMENTS	2
III	47 CFR 2.905	TEST CERTIFICATION	3
IV	47 CFR 2.983	GENERAL INFORMATION	4
	1. Type Designation	4	
	2. Service and Rule	4	
	3. Description of Equipment	4	
	4. Photographs	9	
V	47 CFR 2.999	TEST PROCEDURES AND DATA	17
	47 CFR 2.985a	POWER OUTPUT	18
	47 CFR 2.985c		
	47 CFR 87.131		
	47 CFR 2.987d	MODULATION CHARACTERISTICS	20
	47 CFR 87.141c		
	47 CFR 2.989	OCCUPIED BANDWIDTH AND IN	
	47 CFR 87.135	CLOSE SPURIOUS	23
	47 CFR 87.139		
	47 CFR 2.991	SPURIOUS EMISSIONS	
	47 CFR 2.993	(Conducted)	27
	47 CFR 87.139		
	47 CFR 2.991	SPURIOUS EMISSIONS	
	47 CFR 2.993	(Radiated)	35
	47 CFR 87.139		
	47 CFR 2.995a	FREQUENCY STABILITY	
	47 CFR 87.133	Temperature Variation	38

---

**SECTION I****INTRODUCTION**

This report consists of data establishing the conformance of the Honeywell Inc. XS-950S/I IFF and Mode S Data Link Transponder to the requirements established by the Federal Communications Commission in its rules and regulations (as referenced in Section II of this paper).

This Transponder is a derivative product from the XS-950 Mode S Transponder built by Honeywell. The XS-950S/I was retested and this new report submitted due to modifications to 3 transistors. The XS-950 Acceptance Test Report was released on 26 May 95, Specification No. EB7517808.

---

**SECTION II****REFERENCES AND ATTACHMENTS****1.0 References**

Code of Federal Regulations, Title 47

Part 2, Subpart J

Part 87, Subpart D

XS-950 FCC TYPE ACCEPTANCE TEST REPORT, EB7517808

Environmental Conditions and Test Procedures for Airborne Equipment, RTCA DO-160D

**2.0 Attachments**

XS-950S/I End Item Assembly 7519350

Circuit Card Assembly - A1 Interconnect 7517820

Circuit Card Assembly - A2 Processor 7517826

Circuit Card Assembly - A3 Transmitter/Receiver 7517835

Circuit Card Assembly - A4 Power Supply / Modulator 7517830

Integrated Test Specification for the XS-950 Mode S Data Link Transponder IT7517800

Outline and Installation, 7519356  
XS-950S/I Mode S/IFF Transponder

Interconnect Diagram, XS-950S/I Mode S/IFF A15-3839-001  
Transponder

Plate, Identification (115 VAC VERSION) 7021570-45

Plate, Identification (28 VDC VERSION) 7021570-46

---

**SECTION III****TEST CERTIFICATION**

I do hereby certify that to the best of my knowledge the technical test data contained in this report are true and correct.

SIGNED:

**TEST ENGINEER****TEST ENGINEER QUALIFICATION****Pete Bobrowitz****1984 B.S.E.E. University of Wisconsin - Milwaukee****15 Years Experience In Commercial Avionics**

**SECTION IV****GENERAL INFORMATION****1.0 TYPE DESIGNATION**

The equipment has been designated by Honeywell Inc., Commercial Aviation Systems, as an XS-950S/I Mode S and IFF Transponder.

**2.0 SERVICE AND RULE FOR INTENDED OPERATION**

Air Traffic Control

Part 87, Subpart A

**3.0 DESCRIPTION OF EQUIPMENT**


3.1	Type of Emission:	18MOP1D
3.2	Frequency Range:	1090 $\pm$ 1 MHz
3.3	Power Rating:	250 Watts Minimum, (Pulse)
3.4	Final Power Amplifier:	Solid State Class C amplifier using a pair of MRF10502 silicon bipolar transistors.

3.5 Transistor Functions:

<u>Function</u>	<u>Transistor</u>	<u>Manufacturer</u>
Oscillator	AT00535	Hewlett Packard
Buffer Amplifier	CGY-50	Siemens
Buffer Amplifier	CGY-50	Siemens
Class A Amplifier	MRF1000MB	Motorola
Class C Amplifier	MRF10005	Motorola
Class C Amplifier	MRF10031	Motorola
Class C Amplifier	MRF10120	Motorola
Class C Final Amplifier	MRF10502	Motorola
Pulse Modulator	IRFR220	International Rectifier
Envelope Modulator	IRFR9220	International Rectifier

	Voltage Regulator	IRF9540	International Rectifier
3.6	Circuit Diagram:		See attached schematics.
3.7	Instruction Book:		To Be Supplied As Soon As Possible
3.8	Tune-Up Procedure:		No field tuning is normally required. Tuning is done during manufacturing.
3.9	Oscillator Circuit:		The carrier frequency of 1090.0 MHz is generated by a varactor-tuned oscillator located on the Transmitter board. The primary frequency determining element is a ceramic coaxial resonator which provides good temperature stability and noise performance. The output of the oscillator is buffered by a Monolithic Microwave Integrated Circuit (MMIC) amplifier. This 1090 MHz RF signal is divided in frequency by 128 to 8.515625 MHz where it is compared in frequency and phase to a 8.515625 MHz crystal controlled reference oscillator. Any frequency or phase error is amplified by an active loop filter and corrections to the 1090 MHz oscillator are made by varying the varactor tuning voltage.
3.10	Frequency Stabilization:		Single channel phase-locked-loop synthesizer referenced to a crystal oscillator.
3.11	Modulation Limiting:		Not applicable
3.12	Radiated Interference Suppression:		Transmitter low-pass filter consisting of microstrip printed circuit elements (See Transmitter Schematic 7517835).


## 3.13 Reply Transmission Pulse Train



Pulse Widths (50% - 50%):  $0.45 \pm 0.1 \mu\text{s}$

Rise Time (10% - 90%):  $\leq 0.1 \mu\text{s}$



Fall Time (10% - 90%):  $\leq 0.2 \mu\text{s}$




Pulse Widths:  $0.5 \pm 0.05 \mu\text{s}$  or  $1.0 \pm 0.05 \mu\text{s}$

Rise Time (10% - 90%):  $\leq 0.1 \mu\text{s}$

Fall Time (10% - 90%):  $\leq 0.2 \mu\text{s}$



Mode 4 Pulse Train Diagram



### Mode 1 and 2 Pulse Trains

#### 4.0 PHOTOGRAPHS

<u>Photograph Number</u>	<u>View</u>	<u>Page</u>
DCP-00780	Unit Front with Nameplate Showing	10
DCP-00779	Unit Rear	11
DCP-00778	View of Unit Front with A2 Processor Assembly	12
DCP-00773	View of Unit Side with A4 Power Supply/Modulator Assembly Showing	13
DCP-00776	View of Unit Side A2 Processor Assembly Showing	14
DCP-00770	View of Unit Side With A2 Processor Removed Showing A3 Transmitter/Receiver Assembly With Cover	15
DCP-00769	View of Unit Side with A3 Transmitter/Receiver Cover Removed.	16
DCP-00767	View of Unit Side With A3 Transmitter/Receiver Shield Removed	17

## SECTION V

TEST PROCEDURES AND DATA


<u>Test Number</u>	<u>Description</u>	<u>Page</u>
1	Power Output	18
2	Modulation Characteristics	20
3	Occupied Bandwidth and in Close Spurious	23
4A	Spurious Emissions (Conducted) 0-700 MHz	27
4B	Spurious Emissions (Conducted) 700 MHz --- 2000 MHz	30
4C	Spurious Emissions (Conducted) 2000 MHz --- 11500 MHz	32
5	Spurious Emissions (Radiated)	35
6	Frequency Stability (Temperature Variation)	38
7	Frequency Stability (Primary Power Variation)	40

TEST NO: 1  
Page NO: 1 OF 21.0 DESCRIPTION OF TEST: Power Output2.0 SPECIFICATIONS: 47 CFR 2.985a  
47 CFR 2.985c  
47 CFR 87.131

3.0 EQUIPMENT REQUIRED:

	<u>TYPE</u>	<u>MANUFACTURER</u>	<u>MODEL</u>	<u>SER. NO</u>
A	Transponder	Honeywell	XS-950S/I	101
B	Power Supply	CAL. INST.	501TC	AV 52189
C	Personal Computer	DELL	OPTIPLEX	
D	Directional Coupler	WAVECOM	L-918-10	61
E	RF Generator	IFR	11404	D400485
F	Peak Power Analyzer	HP	8990A	D400012
G	Attenuator	Narda	776, 768	32114
I				
J				
K				
L				
M				
N				

4.0 BLOCK DIAGRAM OF TEST SETUP:



TEST NO: 1  
Page NO: 2 OF 2

## 5.0 PROCEDURE:

1. Connect the equipment as shown in the block diagram in Section 4.0 of this document.
2. Using the peak power meter, record the transponder output power under minimum and maximum reply pulse conditions. Note the frequency deviations relating to a change of the output power. (Mode-S rate 60/sec.; Mode A, C, 1, 2, 4 rate 1100/sec.)
3. Compute actual power using measured losses for coupler and attenuator.

## 6.0 DATA

## 6.1 Top Antenna measurements

TDR Mode	Reply Code	Path Loss	Actual Power	Freq
C	0000	52.0 dB	554 W	1090.33
A	7777	52.0 dB	554 W	1090.33
S	56 bit DF-11	52.0 dB	570 W	1090.31
IFF MODE 4	CODE A	52.0 dB	558 W	1090.31
IFF MODE 2	0000	52.0 dB	558 W	1090.32
IFF MODE 1	00	52.0 dB	558 W	1090.31

## 6.2 Bottom Antenna measurements

TDR Mode	Reply Code	Path Loss	Actual Power	Freq
C	0000	52.0 dB	538 W	1090.36
A	7777	52.0 dB	538 W	1090.35
S	56 bit DF-11	52.0	538 W	1090.31
IFF MODE 4	CODE A	52.0	538 W	1090.37
IFF MODE 2	0000	52.0	538 W	1090.36
IFF MODE 1	00	52.0	538 W	1090.36


TEST PERFORMED BY: Royal D. LummisDATE: 9/3/99

TEST NO: 2  
Page NO: 1 OF 31.0 DESCRIPTION OF TEST: Modulation Characteristics2.0 SPECIFICATIONS: 47 CFR 2.987d  
47 CFR 87.141c

3.0 EQUIPMENT REQUIRED:

	<u>TYPE</u>	<u>MANUFACTURER</u>	<u>MODEL</u>	<u>SER. NO</u>
A	Transponder	Honeywell	XS-950S/I	101
B	Power Supply	CAL INST.	501TC	AV 52189
C	Personal Computer	DELL	OPTIPLEX	
D	Attenuator	Narda	757C	32114
E	Peak Power Analyzer	HP	8990A	D400012
F				
G				
H				
I				
J				
K				
L				
M				
N				

4.0 BLOCK DIAGRAM OF TEST SETUP:



TEST NO: 2  
Page NO: 2 OF 3

## 5.0 PROCEDURE:


1. Connect the equipment as shown in the block diagram in Section 4.0 of this document.
2. Interrogate the Transponder at a 500 Hz rate and set the reply code to 7777.
3. Record the output pulse characteristics using the Peak Power Analyzer.

## 6.0 DATA

Pulse Characteristic	Measurement	Specification
Rise Time	91 nS	$\leq 100$ nS
Fall Time	77 nS	$\leq 200$ nS
Pulse Width	419 nS	$450 \pm 100$ nS
Pulse Jitter	50 nS	$\leq 100$ nS

TEST NO: 2  
Page NO: 3 OF 3

## 6.0 DATA (Cont.)



TEST PERFORMED BY: Robert D. Seminis


DATE: 9/3/99

TEST NO: 3  
Page NO: 1 OF 41.0 DESCRIPTION OF TEST: Occupied Bandwidth and In Close Spurious2.0 SPECIFICATIONS: 47 CFR 2.989  
47 CFR 87.135  
47 CFR 87.139

3.0 EQUIPMENT REQUIRED:

	<u>TYPE</u>	<u>MANUFACTURER</u>	<u>MODEL</u>	<u>SER. NO</u>
A	Transponder	Honeywell	XS-950S/I	101
B	Power Supply	CAL INST.	501TC	AV 52189
C	Personl Computer	DELL	OPTIPLEX	
D	Attenuator	Narda	757C	32114
E	Spectrum Analyzer	HP	8566B	19065
F				
G				
H				
I				
J				
K				
L				
M				
N				

4.0 BLOCK DIAGRAM OF TEST SETUP:



TEST NO: 3  
 Page NO: 2 OF 4

## 5.0 PROCEDURE:

1. Connect the equipment as shown in the block diagram in Section 4.0 of this document.
2. Insert sufficient attenuation as required for maximum dynamic range.
3. Use 300 kHz IF bandwidth on the Spectrum Analyzer and record spectrum level, for 1 MHz intervals from -25 MHz to +25 MHz.
4. Calculate the spectral energy density using the BASIC program listed below.

## 6.0 DATA:

```
DATA -9.66,-3.19,-18.13,-12.5,-19.42,-16.09,-24.23,-19.2,-19.69,
DATA -21.55,-33.19,-25.85,-27.08,-29.62,-35.49,-29.16,-34.23,
DATA -34.33,-35.52,-29.16,-42.14,-36.9,-35.82,-36.43,-39.65,-40.83,
DATA -35.97,-38.1,-38.21,-38.51,-38.28,-42.0,-38.37,-51.82,-39.91,
DATA -44.66,-40.59,-53.26,-41.06,-45.68,-44.77,-50.74,-43.33,
DATA -46.16,-45.14,-51.29,-49.02,-48.1,-50.81,-49.44
```

```
OPEN "OBW" FOR OUTPUT AS #1
110 DIM X(50)
120 DIM Y(50)
140 INPUT "ENTER CARRIER LEVEL"; X(0)
150 INPUT "ENTER NUMBER OF FREQ INCREMENTS"; K
160 A = 1
170 FOR I = 1 TO 2 * K - 1 STEP 2
180 READ X(I), X(I + 1)
190 X(I) = X(0) + X(I)
200 X(I + 1) = X(0) + X(I + 1)
210 Y(I) = 10 ^ (X(I) / 10)
220 Y(I + 1) = 10 ^ (X(I + 1) / 10)
230 A = A + Y(I) + Y(I + 1)
240 NEXT I
250 INC = 1
260 PRINT #1, "FREQ OFFSET (MHZ)"      LEVEL (DBC)      FREQ OFFSET (MHZ)      LEVEL
(DBC)"
270 FOR I = 1 TO K
280 J = I * INC
290 PRINT #1, USING "      +##.#"      +##.#      "; -J; X(2 * I - 1); J;
X(2 * I)
300 NEXT I
310 PRINT #1,
320 PRINT #1, "PERCENT TOTAL ENERGY"      OCCUPIED BANDWIDTH (MHZ)"
330 B = 1
340 PRINT #1, USING "      +###.#"      +##.#      "; B / A * 100; INC
350 FOR I = 1 TO K
360 B = B + Y(2 * I - 1) + Y(2 * I)
370 PRINT #1, USING "      +##.#"      +##.#      "; B / A * 100; (2
* I + 1) * INC
380 NEXT I
390 END
```

TEST NO: 3  
PAGE NO: 3 OF 4


## 6.0 DATA (Cont.)

FREQ OFFSET (MHZ)	LEVEL (dbc)	FREQ OFFSET (MHZ)	LEVEL (dbc)
-1.0	-9.66	+1.0	-3.19
-2.0	-18.13	+2	-12.5
-3.0	-19.42	+3.0	-16.09
-4.0	-24.23	+4.0	-19.2
-5.0	-19.69	+5.0	-21.55
-6.0	-33.19	+6.0	-25.85
-7.0	-27.08	+7.0	-29.62
-8.0	-35.49	+8.0	-29.16
-9.0	-34.23	+9.0	-34.33
-10.0	-35.52	+10.0	-29.16
-11.0	-42.14	+11.0	-36.9
-12.0	-35.82	+12.0	-36.43
-13.0	-39.65	+13.0	-40.83
-14.0	-35.97	+14.0	-38.1
-15.0	-38.21	+15.0	-38.51
-16.0	-38.28	+16.0	-42.0
-17.0	-38.37	+17.0	-51.82
-18.0	-39.91	+18.0	-44.66
-19.0	-40.59	+19.0	-53.26
-20.0	-41.06	+20.0	-45.68
-21.0	-44.77	+21.0	-50.74
-22.0	-43.33	+22.0	-46.16
-23.0	-45.14	+23.0	-51.29
-24.0	-49.02	+24.0	-48.1
-25.0	-50.81	+25.0	-49.44

+57.4	+1.0
+91.2	+3.0
+95.3	+5.0
+97.4	+7.0
+98.3	+9.0
+99.3	+11.0
+99.5	+13.0
+99.6	+15.0
+99.7	+17.0
+99.8	+19.0
+99.9	+21.0
+99.9	+23.0
+99.9	+25.0
+99.9	+27.0
+99.9	+29.0
+99.9	+31.0
+100.0	+33.0
+100.0	+35.0
+100.0	+37.0
+100.0	+39.0
+100.0	+41.0
+100.0	+43.0
+100.0	+45.0
+100.0	+47.0
+100.0	+49.0
+100.0	+51.0

TEST NO: 3  
Page NO: 4 OF 4

## 6.0 DATA (Cont.)


TEST PERFORMED BY: Royal D. LummisDATE: 9/3/99

TEST NO: 4A  
PAGE NO: 1 OF 31.0 DESCRIPTION OF TEST: Spurious Emissions (Conducted)  
0 - 700 MHz2.0 SPECIFICATIONS: 47 CFR 2.991  
47 CFR 2.993  
47 CFR 87.139

3.0 EQUIPMENT REQUIRED:

	<u>TYPE</u>	<u>MANUFACTURER</u>	<u>MODEL</u>	<u>SER. NO</u>
A	Transponder	Honeywell	XS-950S/I	101
B	Power Supply	CAL INST	501TC	AV 52189
C	Personal Computer	DELL	OPTIPLEX	
D	Attenuator (10dB)	Arra	4410-10	978
E	Low Pass Filter	MicroLab/FXR	LA-07T	None
F	Spectrum Analyzer	HP	8566B	19065
H				
I				
J				
K				
L				
M				
N				

4.0 BLOCK DIAGRAM OF TEST SETUP:



TEST NO: 4A  
PAGE NO: 2 OF 3

## 5.0 PROCEDURE

1. Connect equipment as shown.
2. Adjust spectrum analyzer so that no signal exceeds the analyzer's dynamic range.
3. Measure and record all spurious emissions below 700 MHz (corrected for pad/filter/cable losses).

Mean Transmitter Power Calculation:

$$\begin{aligned}P_o &= 550 \text{ Watts} \\P_y &= P_o \cdot T_w \cdot N \cdot R \\P_y &= (550 \text{ W})(0.45 \mu\text{s})(15)(1100 \text{ Hz}) = 4.08 \text{ Watts}\end{aligned}$$

Where:

$P_y$  = Mean output power (Watts)  
 $P_o$  = Peak output power (Watts)  
 $T_w$  = Pulse width (Seconds)  
 $N$  = Number of pulses  
 $R$  = Reply rate (Hz)

Therefore:

$$\begin{aligned}\text{Limit} &= 43 + 10\log_{10}(P_y) \\&= 43 + 10\log_{10}(4.08 \text{ W}) \\&= 43 + 6.1 \\&= 49.1 \text{ dB}\end{aligned}$$

Spurious outputs must be attenuated at least 49.1dB.

TEST NO: 4A  
PAGE NO: 3 OF 3

## Peak Spurious Output Power Calculation:

$$\begin{aligned}
 P_o(\text{dBm}) &= 10\log_{10}(P_o \text{ W} * 1000 \text{ mW/W}) \\
 &= 10\log_{10}(550 \text{ W} * 1000 \text{ mW/W}) \\
 &= 57.4 \text{ dBm}
 \end{aligned}$$

$$\begin{aligned}
 P_s &= P_o(\text{dBm}) - \text{Limit(dBm)} \\
 &= 57.4 \text{ dBm} - 49.1 \text{ dBm} \\
 &= 8.3 \text{ dBm}
 \end{aligned}$$

Where:

 $P_s$  = Peak Spurious Output Power

Therefore:

The peak output power of any spurious outputs must be lower than 8.3 dBm

## 6.0 DATA:

Frequency	Top Antenna Spurious Output Level (Corrected for Pad etc)	Bottom Antenna Spurious Output Level (Corrected for Pad etc)	Spurious Output Limit
52.5 MHz	-43.62 dBm	-45.15 dBm	+8.3 dBm
135.6 MHz	-69.2 dBm	-79 dBm	+8.3 dBm

TEST PERFORMED BY:


*Royal D. Ammons*DATE: 9/3/89

TEST NO: 4B  
PAGE NO: 1 OF 2

1.0 DESCRIPTION OF TEST: Spurious Emissions (Conducted)  
700 MHz - 2000 MHz

### 3.0 EQUIPMENT REQUIRED:

#### 4.0 BLOCK DIAGRAM OF TEST SETUP:



TEST NO: 4B  
PAGE NO: 2 OF 2

## 5.0 PROCEDURE

1. Connect equipment as shown.
2. Adjust spectrum analyzer so that no signal exceeds the analyzer's dynamic range.
3. Measure and record all spurious emissions between 700 MHz and 2000 MHz (corrected for pads and cable losses).

## 6.0 DATA:

Frequency	Top Antenna Spurious Output Level (Corrected for Pad etc)	Bottom Antenna Spurious Output Level (Corrected for Pad etc)	Spurious Output Limit
1090 MHz *	-80.5 dBm	-85 dBm	+8.3 dBm

\* Transmitter in standby to measure Local Oscillator leakage.


TEST PERFORMED BY: Royal D. HammomDATE: 7/3/99

TEST NO: 4C  
PAGE NO: 1 OF 31.0 DESCRIPTION OF TEST: Spurious Emissions (Conducted)  
2000 MHz - 11500 MHz2.0 SPECIFICATIONS: 47 CFR 2.991  
47 CFR 2.993  
47 CFR 87.139

## 3.0 EQUIPMENT REQUIRED:

	<u>TYPE</u>	<u>MANUFACTURER</u>	<u>MODEL</u>	<u>SER. NO</u>
A	Transponder	Honeywell	XS-950S/I	101
B	Power Supply	CAL INST.	501TC	AV52189
C	Personal Computer	DELL	OPTIPLEX	
D	Attenuator (10dB)	Narda	3042B-10	07022
E	Hi Pass Filter(2GHz)	Microlab/FXR	HD-20N	None
F	Hi Pass Filter(4GHz)	Microlab/FXR	HD-40N	None
G	Hi Pass Filter(6GHz)	Microlab/FXR	HD-60N	None
I	Spectrum Analyzer	HP	8566B	19065
I	Plotter	HP	7475A	AV58285
J				
K				
L				
M				
N				

## 4.0 BLOCK DIAGRAM OF TEST SETUP:



TEST NO: 4C  
PAGE NO: 2 OF 3

## 5.0 PROCEDURE

1. Connect equipment as shown.
2. Adjust spectrum analyzer so that no signal exceeds the analyzer's dynamic range. Resolution bandwidth should be set to 3 MHz.
3. Measure and record all spurious emissions between 2 GHz and 4 GHz using the 2 GHz High Pass filter.
4. Measure and record all spurious emissions between 4 GHz and 8 GHz using the 4 GHz High Pass filter.
5. Measure and record all spurious emissions between 8 GHz and 14 GHz using the 6 GHz High Pass filter.
6. Measure and record Pad/Filter/Cable losses for all spurious emissions.

## 6.0 CALIBRATION DATA:

Frequency	Applicable Filter Type	Calibration Factor (Pad/Filter/Cable)
2180 MHz	2000 MHz	12.0 dB
3270 MHz	2000 MHz	12.0 dB
4360 MHz	4000 MHz	12.4 dB
5450 MHz	4000 MHz	12.5 dB
6540 MHz	4000 MHz	12.9 dB
7630 MHz	4000 MHz	12.9 dB
8720 MHz	6000 MHz	13.3 dB
9810 MHz	6000 MHz	13.7 dB
10900 MHz	6000 MHz	12.8 dB
11990 MHz	6000 MHz	15.8 dB
13080 MHz	6000 MHz	14.1 dB

TEST NO: 4C  
PAGE NO: 3 OF 3

## 6.0 MEASUREMENT DATA (Cont.)

Frequency	Top Antenna Spurious Output Level (Corrected for Pad etc)	Bottom Antenna Spurious Output Level (Corrected for Pad etc)	Spurious Output Limit
2180 MHz	Not Observed	Not Observed	+8.3 dBm
3270 MHz	-61.0 dBm	-60.0 dBm	+8.3 dBm
4360 MHz	Not Observed	Not Observed	+8.3 dBm
5450 MHz	Not Observed	Not Observed	+8.3 dBm
6540 MHz	Not Observed	Not Observed	+8.3 dBm
7630 MHz	Not Observed	Not Observed	+8.3 dBm
8720 MHz	Not Observed	Not Observed	+8.3 dBm
9810 MHz	Not Observed	Not Observed	+8.3 dBm
10900 MHz	Not Observed	Not Observed	+8.3 dBm
11990 MHz	Not Observed	Not Observed	+8.3 dBm
13080 MHz	Not Observed	Not Observed	+8.3 dBm


TEST PERFORMED BY: Boyd D. HammDATE: 9/3/99

TEST NO: 5  
PAGE NO: 1 OF 31.0 DESCRIPTION OF TEST: Spurious Emissions  
(Radiated)2.0 SPECIFICATIONS: 47 CFR 2.991  
47 CFR 2.993  
47 CFR 87.139

3.0 EQUIPMENT REQUIRED:

	<u>TYPE</u>	<u>MANUFACTURER</u>	<u>MODEL</u>	<u>SER. NO</u>
A	Transponder	Honeywell	XS-950	E3
B	Power Supply	Kepco	ATE36-30M	63529
C	Personal Computer	DELL	OPTIPLEX	
D	Amplified Rod to 30MHz	Ailtech	94607-1	302
E	Ant. Horn 2-3.6 GHz	Ailtech	91889-2	E2430-103
F	Ant. Horn 3.6 - 7.5 GHz	Ailtech	94613-1	AV00842
G	Amt/ Cone 200MHz - 1 GHz	Ailtech	93490-1	0815
I	Field Int Meter 9-32 MHz	Carnel Lab	NM-17/27B	91-0117R
I	Field Int Meter 20MHz-1GHz	Carnel Lab	NM-37/57B	91-0770R
J	Field Int Meter 1-18GHz	Carnel Lab	NM-67B	91-0115R
K				
L				
M				
N				

4.0 BLOCK DIAGRAM OF TEST SETUP:



TEST NO 5  
PAGE NO: 2 OF 3

## 5.0 PROCEDURE:

1. Connect equipment as shown in an open area.
2. Measure and record all spurious emissions using the appropriate antenna at a distance of 3 meters.
3. Calculate field strength using the recorded power measurement, antenna factor, and cable losses for each frequency.

## 6.0 DATA:

## Transmitter field strength calculation:

(The transmitter field strength is calculated rather than measured for safety reasons)

$$p_{3m} = \frac{P_o G_t}{4\pi r^2} = \frac{(550) (1.66)}{4\pi (3)^2} = 8.07 \quad \frac{\text{Watts}}{\text{meter}^2}$$

$$e_{3m} = \sqrt{p_{3m} Z_o} = \sqrt{(8.07) (377)} = 55.2 \quad \frac{\text{Volts}}{\text{meter}}$$

$$e_{3m} = 20 \log_{10} \left[ e_3 \frac{V}{m} 10^6 \right] = 20 \log_{10} [(47.0) (10^6)] = 153.4 \quad \frac{dB\mu V}{\text{meter}}$$

Where:

 $e_{3m}$  = Field strength at 3 meters $G_t$  = Transmitter Antenna Gain = 2.2 dB for monopole over ground plane = 1.66 multiplication factor. $P_o$  = Peak Output Power = 550 Watts for this unit $p_{3m}$  = Power density at 3 meters $Z_o$  = Characteristic impedance of free space = 377 Ohms

In the previous section, we determined that spurious outputs must be attenuated by at least 49.1 dB.

Therefore the field strength of transmitted spurious shall be  $154.8 dB\mu V - 49.1 dB = 105.7 dB\mu V$ 

'Note: Tests were performed with antenna to unit spacing of 1 Meter per RTCA DO-160 D.


TEST NO 5  
PAGE NO: 3 OF 3

## 6.0 DATA (Cont.)

Frequency (MHz)	Level (dB $\mu$ V/m)	Limit dB $\mu$ V/m
28	27	105.7
32	26	105.7
144	30	105.7
160	33	105.7
220	36	105.7
280	28	105.7
320	26	105.7
350	26	105.7
520	35	105.7
550	36	105.7
1090 (1)	97	NONE
2180 (1)	76	105.7
3270 (1)	75	105.7

(1) Transmitter Transmitting into dummy load

TEST PERFORMED BY:


DATE: 7/3/99

TEST NO 6  
PAGE NO: 1 OF 21.0 DESCRIPTION OF TEST: Frequency Stability  
(Temperature Variation)2.0 SPECIFICATIONS: 47 CFR 2.995a  
47 CFR 87.133

3.0 EQUIPMENT REQUIRED:

	<u>TYPE</u>	<u>MANUFACTURER</u>	<u>MODEL</u>	<u>SER. NO</u>
A	Transponder	Honeywell	XS-950S/I	101
B	Power Supply	Kepco	ATE36-30M	63529
C	Personal Computer	DELL	OPTIPLEX	
D				
E	RF Generator	IFR	1400/1404	D400485
F	Attenuator (30 dB)	Narda	757C	NONE
G	Frequency Counter	IFR	1400A/1404	D400485

4.0 BLOCK DIAGRAM OF TEST SETUP:



TEST NO 6  
PAGE NO: 2 OF 2


## 5.0 PROCEDURE:

1. Connect the equipment as shown in the block diagram in section 4.0 of this document.
2. Set the temperature chamber to -20°C and allow the transmitter (non-operating) temperature to stabilize.
3. Record the transmission frequency for both the top and bottom antennas.
4. Repeat steps 2 and 3 at -10°C, 0°C, +10°C, +20°C, +30°C, and +40°C, and +50°C.

## 6.0 DATA

Temperature	Measured Frequency (Top Ant)	Measured Frequency (Bot Ant)	Frequency Limit
-20°C	1090.31 MHz	1090.37 MHz	1090 ± 1 MHz
-10°C	1090.31 MHz	1090.37 MHz	1090 ± 1 MHz
0°C	1090.36 MHz	1090.30 MHz	1090 ± 1 MHz
+10°C	1090.32 MHz	1090.36 MHz	1090 ± 1 MHz
+20°C	1090.32 MHz	1090.37 MHz	1090 ± 1 MHz
+30°C	1090.32 MHz	1090.37 MHz	1090 ± 1 MHz
+40°C	1090.33 MHz	1090.36 MHz	1090 ± 1 MHz
+50°C	1090.33 MHz	1090.36 MHz	1090 ± 1 MHz

TEST PERFORMED BY:


DATE: 9/3/99

TEST NO 7  
PAGE NO: 1 OF 21.0 DESCRIPTION OF TEST: Frequency Stability  
(Primary Power Variation)2.0 SPECIFICATIONS: 47 CFR 2.995d  
47 CFR 87.133

3.0 EQUIPMENT REQUIRED:

	<u>TYPE</u>	<u>MANUFACTURER</u>	<u>MODEL</u>	<u>SER. NO</u>
A	Transponder	Honeywell	XS-950S/I	101
B	Power Supply (115VAC)	CAL INST	1501TPM	L38383
C	Personal Computer	DELL	433/MX	O2255A
D	RF Generator	IFR	1400/1404	D400485
E	Power Supply (28VDC)	Sorenson	QRD40-2	AV4074
F				
G				
H				
I				
J				
K				
L				
M				
N				

4.0 BLOCK DIAGRAM OF TEST SETUP:



TEST NO 7  
PAGE NO: 2 OF 2

## 5.0 PROCEDURE:

1. Connect the equipment as shown in the block diagram in section 4.0 of this document.
2. For the 115VAC unit, vary the power supply voltage from -15% to + 15% of the nominal 115 VAC and record the transmitted frequency.
3. For the 28VDC unit, vary the power supply voltage from -15% to +15% of the nominal 27.5 VDC and record the transmitted frequency

## 6.0 DATA

115 VAC				
Power Supply Voltage ( Vrms )	Power Supply Frequency ( HZ )	Measured Frequency Top Antenna ( MHZ )	Measured Frequency Bottom Antenna ( MHZ )	Frequency Limit ( MHZ )
97.75	392	1090.32	1090.37	1090 ± 1
	408	1090.32	1090.37	1090 ± 1
115	392	1090.32	1090.37	1090 ± 1
	408	1090.32	1090.37	1090 ± 1
132.25	392	1090.32	1090.37	1090 ± 1
	408	1090.32	1090.37	1090 ± 1

TEST PERFORMED BY:

DATE: 9/3/99

# ENGINEERING SPECIFICATION

SECURITY NOTATION

SPEC  
NO.

IT7517800

M  
REV LTR

CAGE

CODE 55939

TYPE

CLASS

INITIAL RELEASE DATE

IT

A

29 SEP 95

DIVISION

DEPARTMENT NO.

PRODUCT LINE NO.

CONTRACT NO.

BCAS

5810

3839

TITLE

## INTEGRATED TEST SPECIFICATION FOR THE XS-950 MODE S DATA LINK TRANSPONDER

PREPARED BY J. Troxel	DATE 9/28/95	APVD BY TECHNICAL MANAGER R. Fuller	DATE 9/28/95	APVD BY TECHNICAL MANAGER	DATE
--------------------------	-----------------	--	-----------------	---------------------------	------

APVD FOR SCM	DATE	APVD FOR SQA	DATE	APVD FOR	DATE
--------------	------	--------------	------	----------	------

REF AWAEB/PSAEB NO. EB7517801	CHECKER	PRODUCT DESIGN CHECKER (FOR REF, SPCL CONT PER EPM 1-A-40)	COGNIZANCE OF QE SUPVR (FOR REF, SPCL CONT PER EPM 1-A-40)
----------------------------------	---------	---	---

FOR PAGE INDEX, SEE CR-2. REVISION RECORD FOLLOWS PAGE INDEX

### PROPRIETARY NOTICE

THIS DOCUMENT AND THE INFORMATION DISCLOSED HEREIN ARE PROPRIETARY DATA OF HONEYWELL INC. NEITHER THIS DOCUMENT NOR THE INFORMATION CONTAINED HEREIN SHALL BE REPRODUCED, USED OR DISCLOSED TO OTHERS WITHOUT THE WRITTEN AUTHORIZATION OF HONEYWELL INC.

### NOTICE

FREEDOM OF INFORMATION ACT (5 USC 552) AND  
DISCLOSURE OF CONFIDENTIAL INFORMATION GENERALLY  
(18 USC 1905)

THIS DOCUMENT IS BEING FURNISHED IN CONFIDENCE BY HONEYWELL INC. THE INFORMATION DISCLOSED HEREIN FALLS WITHIN EXEMPTION (D) (4) OF 5 USC 552 AND THE PROHIBITIONS OF 18 USC 1905.

Copyright 1994 Honeywell Inc.  
All Rights Reserved

Honeywell

COPY NO.

SECURITY NOTATION

AW/PS CRITICAL NOTATION

CR-1  
TITLE PAGE

**ENGINEERING SPECIFICATION  
PAGE INDEX**
**SECURITY NOTATION**
**SPEC  
NO.**
**IT7517800**
**M**
**CAGE  
CODE**
**55939**
**REV LTR**
**SEE FIRST PAGE FOR PROPRIETARY OR DATA RIGHTS NOTATIONS**

<u>Page</u>	<u>Rev Ltr</u>								
Title		34	-	A-4	K	C-29	-		
CR-1	M	35	-			C-30	-		
		36	-	Appendix B		C-31	-		
Page Index		37	-	B-0	-	C-32	-		
CR-2	M	38	-	B-1	-	C-33	-		
		39	-	B-2	K				
Revision		40	-	B-3	-	TOTAL			
Record		41	-	B-4	-	PAGES: 124			
CR-3	K	42	-	B-5	-				
CR-4	M	43	-	B-6	-				
		44	-	B-7	-				
1	K	45	-	B-8	-				
2	M	46	-	B-9	-				
3	L	47	-						
4	-	48	-	Appendix C					
5	-	49	-	C-0	-				
6	-	50	-	C-1	-				
7	A	51	-	C-2	-				
8	-	52	M	C-3	-				
9	-	53	-	C-4	-				
10	K	54	-	C-5	-				
11	-	55	-	C-6	-				
12	K	56	-	C-7	-				
13	K	57	L	C-8	-				
14	K	58	K	C-9	-				
15	-	59	L	C-10	-				
16	-	60	L	C-11	-				
17	-	61	L	C-12	-				
18	-	62	L	C-13	-				
19	-	63	L	C-14	-				
20	-	64	L	C-15	-				
21	-	65	L	C-16	-				
22	-	66	L	C-17	-				
23	-	67	M	C-18	-				
24	-	68	K	C-19	-				
25	-	69	L	C-20	-				
26	-	70	L	C-21	-				
27	-	71	L	C-22	-				
28	-			C-23	-				
29	-	Appendix A		C-24	-				
30	-	A-0	-	C-25	-				
31	-	A-1	M	C-26	-				
32	-	A-2	-	C-27	-				
33	-	A-3	K	C-28	-				

**Honeywell**
**SECURITY NOTATION**
**PAGE INDEX**
**CR- 2**
**PAGE**

ENGINEERING SPECIFICATION REVISION RECORD		SECURITY NOTATION	SPEC NO. IT7517800	K
			CAGE CODE 55939	REV LTR

SEE FIRST PAGE FOR PROPRIETARY OR DATA RIGHTS NOTATIONS

REV LTR	PAGE	DESCRIPTION	DATE AND APPROVAL
A	SEE PAGE INDEX SHEET CR-2	C.O. 68772 (MAKE)	J. M. 1 Nov 95
B	SEE PAGE INDEX SHEET CR-2	C.O. 68773 (MAKE)	K. M. 18 Jan 96
C	SEE PAGE INDEX SHEET CR-2	C.O. 95464 (MAKE)	K. M. 9 Aug 96
D	SEE PAGE INDEX SHEET CR-2	C.O. 94595 (NA)	K. M. 13 Nov 96
E	SEE PAGE INDEX SHEET CR-2	C.O. 95469 (MAKE)	K. M. 13 Nov 96
F	SEE PAGE INDEX SHEET CR-2	C.O. 96015 (NA)	K. M. 24 Dec 97
G	SEE PAGE INDEX SHEET CR-2	C.O. 95925 (MAKE)	K. M. 24 Dec 97
H	SEE PAGE INDEX SHEET CR-2	C.O. 98669 (MAKE)	K. M. 13 Jan 98
J	SEE PAGE INDEX SHEET CR-2	C.O. 98671 (MAKE)	K. M. 13 Jan 98
K	SEE PAGE INDEX SHEET CR-2	C.O. 102079 (BREAK IN*)	K. M. 19 Feb 99

Honeywell

SECURITY NOTATION

REVISION RECORD

CR-3

PAGE

<b>ENGINEERING SPECIFICATION REVISION RECORD</b>	<b>SECURITY NOTATION</b>	<b>SPEC NO.</b> IT7517800	<b>M REV LTR</b>
		<b>CAGE CODE</b> 55939	

SEE FIRST PAGE FOR PROPRIETARY OR DATA RIGHTS NOTATIONS

REV LTR	PAGE	DESCRIPTION	DATE AND APPROVAL
L	SEE PAGE INDEX SHEET CR-2	C.O. 97456 (BREAK IN*)	<i>Ken Reeves O'Dell</i> 19 Feb 99
M	SEE PAGE INDEX SHEET CR-2	C.O. 103706 (NA)	<i>Ken Reeves O'Dell</i> 6 May 99

**Honeywell**

SECURITY NOTATION

REVISION RECORD

CR-4

PAGE

<b>ENGINEERING SPECIFICATION</b>	<b>SECURITY NOTATION</b>	<b>SPEC. NO.</b>	IT7517800	<b>K</b>
		<b>CAGE CODE</b>	55939	

<b>REV LTR</b>	<b>SEE FIRST PAGE FOR PROPRIETARY OR DATA RIGHTS NOTATIONS.</b>
--------------------	---

**TITLE: INTEGRATED TEST SPECIFICATION FOR THE XS-950 TRANSPONDER  
PART NO. 7517800**

### 5 1.0 SCOPE

10 This Integrated Test Specification establishes the manufacturing and operational requirements that the Transponder (7517800) must meet to ensure that the equipment is in proper operation condition. This specification contains the test procedure and calls out all the necessary tests to insure 15 compliance with Appendix F Part 43 of the Federal Air Regulations.

20 This test specification covers the following Transponder part numbers:

<u>Honeywell P/N</u>	<u>Model Number/Description</u>
7517800-10xxx thru 54xxx	XS-950 Mode S Data Link Transponder with 115VAC power supply.
7517800-55xxx thru 99xxx	XS-950 Mode S Data Link Transponder with 28VDC power supply.

### 25 2.0 REFERENCE DOCUMENTS

30 Reference documents are not required for performance of the test procedures. The purpose of these documents is to provide an aid for fault isolation should any discrepancies occur during the tests.

7517800	Mode S Data Link Transponder Assembly
7517820-90X	A1 Interconnect CCA
7517826-90X	A2 Processor CCA
7517835-90X	A3 Transmitter/Receiver CCA
7517830-90X	A4 Power Supply/Modulator CCA
7517802	Mode S Data Link Transponder Wiring Diagram
7517840	W1 XS-950 ARINC 615 Harness Assembly
EB7021584	XS-950 Transponder System Requirements Document
EB7517804	Configuration Listing of Product Test Software

### 3.0 GENERAL INFORMATION

3.1 All tests shall be performed at a temperature of  $25 \pm 10$  °C with less than 90 percent relative humidity and at a atmospheric pressure of 20 to 32 inches of mercury.

3.2 No warm-up period is required for the module.

<b>ENGINEERING SPECIFICATION</b>	<b>SECURITY NOTATION</b>	<b>SPEC. NO.</b>	IT7517800	<b>M</b>  <b>REV LTR</b>
		<b>CAGE CODE</b>	55939	

<b>REV LTR</b>	<b>SEE FIRST PAGE FOR PROPRIETARY OR DATA RIGHTS NOTATIONS.</b>			
	3.3 To limit interference and power loss, it is recommended that transponder antenna cables be made of RG-214, or equivalent, 2 to 3 feet in length.			
5	3.4 The transponder power output is specified at the antenna port. All power readings shall be corrected for antenna cable losses and variations in power meter specifications.			
10	3.5 Where two antenna cables are required for testing diversity antenna operations, the two antenna cables shall be matched so that the cable loss between the two cables is within 0.2dB, and the propagation delay at 1090 MHz is within 10nsec.			
15	<b>4.0 POWER AND SIGNAL REQUIREMENTS</b>			
20	<b>4.1 Power Required</b>			
25	115 Vac. 400 $\pm$ 10Hz / 200W minimum. Voltage variable from 90 to 140 Vac. 28 Vdc / 200W minimum. Voltage variable from 16 to 35 Vdc.			
30	<b>4.1 Signals</b>			
35	All required signals are generated by the test equipment specified in this document.			
40	<b>5.0 TEST EQUIPMENT</b>			
45	<b>5.1 Honeywell Test Equipment</b>			
M	T336167 Manual Test Station or 4067839-901 Mode S Manual Test Station (MTS) Interface Panel. T336093-901 Mode S MTS Adaptor Panel T336094-901 XS-950 MTS Tray Assembly T336097-901 XS-950 DLP Test CCA T336098-901 XS-950 DLP Test Harness MT7517800 XS-950 Manufacturing Test Software			
F	<b>5.2 Commercial Test Equipment</b>			
45	Personal Computer, IBM compatible, (80386 microprocessor) or better with the following minimum configuration:			
K	<ul style="list-style-type: none"> <li>• 8 MB of RAM</li> <li>• VGA color monitor</li> <li>• Math co-processor</li> <li>• One serial port</li> <li>• 20MHz clock speed</li> <li>• Procomm Plus for Windows, Version 2.0 or later</li> </ul>			

**Honeywell**

SECURITY NOTATION

SUPPLEMENTS

2  
PAGE

<b>ENGINEERING SPECIFICATION</b>	<b>SECURITY NOTATION</b>	<b>SPEC. NO.</b>	IT7517800	<b>L</b>
		<b>CAGE CODE</b>	55939	

<b>REV LTR</b>	<b>SEE FIRST PAGE FOR PROPRIETARY OR DATA RIGHTS NOTATIONS.</b>
--------------------	---

5 DVM. FLUKE 8840 or equivalent.

10 Oscilloscope, Tektronix 2465A or equivalent.

15 NOTE: A Tektronix 2430A digital storage oscilloscope or equivalent is recommended for testing.

20 Transponder Test Set, IFR ATC-1400A

25 Mode S Auxiliary Unit, IFR Mode S-1403

30 Current meter, or DVM with current capability

35 ARINC 429 Test Set, JC AIR 429E or equivalent

40 4.99K, 0.5% 1/4 W resistor (Honeywell Part Number 2500169-459)

45 Power Supply, HP6205B or equivalent

5.3 OPTIONAL Test Equipment For Troubleshooting and Repair

55 T336096-901 XS-950 Boot Test Assembly

60 Fluke 9100 with 9132FT-90960CA Pod.

<b>Honeywell</b>	<b>SECURITY NOTATION</b>	<b>SUPPLEMENTS</b>	<b>PAGE</b>
------------------	--------------------------	--------------------	-------------

<b>ENGINEERING SPECIFICATION</b>	<b>SECURITY NOTATION</b>	<b>SPEC. NO.</b>	<b>IT7517800</b>	<b>REV LTR</b>
		<b>CAGE CODE</b>	<b>55939</b>	

<b>REV</b>	<b>SEE FIRST PAGE FOR PROPRIETARY OR DATA RIGHTS NOTATIONS.</b>
<b>TR</b>	

**6.0 TEST EQUIPMENT SETUP BLOCK DIAGRAM**

5  
10  
15  
20  
25  
30  
35  
40  
45

**Figure 1**

<b>Honeywell</b>	<b>SECURITY NOTATION</b>	<b>SUPPLEMENTS</b>	<b>4</b> <b>PAGE</b>
------------------	--------------------------	--------------------	-------------------------

<b>ENGINEERING SPECIFICATION</b>	<b>SECURITY NOTATION</b>	SPEC. NO. IT7517800	<b>REV LTR</b> -
		CAGE CODE 55939	

<b>REV LTR</b>	<b>SEE FIRST PAGE FOR PROPRIETARY OR DATA RIGHTS NOTATIONS.</b>
--------------------	---

7.0 TEST EQUIPMENT SETUP

7.1 TEST SETUP #1

The following equipment settings define TEST SETUP #1:

Table #7-1 MTS Interface Panel and Adaptor Default Switch Positions  
 Table #7-4 MTS Connections for Synchro Input Testing  
 Table #7-5 MTS Connections for ARINC 429 Receiver Input Testing  
 Table #7-6 Default Settings for ATC 1400A and S1403 Test Sets  
 Table #7-7 Default Settings for JC-AIR 429 Test Set  
 Table #7-8 Default PC Settings (PROCOMM)

7.2 Table #7-1 - MTS Interface Panel and MTS Adaptor Panel Default Switch Positions

For each panel, an "U" specifies switch is up, "D" specifies switch is down.

MTS Interface Panel Switch Settings

MODE S ADDR (1 to 24):	UDUD UDUD UDUD UDUD UDUD
ANT PGM:	U
ANT CABLE DELAY:	DUD
GILHAM ALT 1 & 2 (A1 A2 A4 B1 B2 B4 C1 C2 C4 D2 D4):	DUD UDU UDU DU
ANT BITE:	U
FUNC TEST:	U
STBY/ON:	U
SYNC ALT FLAG (1,2)	UD
ALT COMP:	D
ALT SRC:	D
ALT TYPE SEL:	UD
MAX AIRSPEED (15, 16, 17):	UDU
SDI (B, A):	UD
DATA LINK:	U
CNTL PNL:	D
AIR/GND (1, 2):	UD
26VAC POL:	(+) U

MTS Adaptor Panel Switch Settings

DISCRETE IN (1 to 4):	UDUD
ADL LINK A:	D
PDL LINK A:	D
PDL FUNC DISC (1 to 4):	UDUD
XPDR OFF(NO):	D

ENGINEERING SPECIFICATION		SECURITY NOTATION	SPEC. NO. IT7517800	REV LTR	
REV LTR	SEE FIRST PAGE FOR PROPRIETARY OR DATA RIGHTS NOTATIONS.				
7.3	<u>Table #7-2 - MTS Interface Panel and MTS Adaptor Panel Complement Switch Positions</u>				
5	For each panel, an "U" specifies switch is up, "D" specifies switch is down.				
	<u>MTS Interface Panel Switch Settings</u>				
10	MODE S ADDR (1 to 24):	DUDU DUDU DUDU DUDU DUDU			
	ANT PGM:	D			
	ANT CABLE DELAY:	UDU DUD DUD UD			
	GILHAM ALT 1 & 2 (A1 A2 A4 B1 B2 B4 C1 C2 C4 D2 D4):	UDU DUD DUD UD			
15	ANT BITE:	D			
	FUNC TEST:	D			
	STBY/ON:	DU			
	SYNC ALT FLAG (1,2)	U			
	ALT COMP:	U			
	ALT SRC:	DU			
20	ALT TYPE SEL:	DUD			
	MAX AIRSPEED (15, 16, 17):	DU			
	SDI (B, A):	D			
	DATA LINK:	U			
	CNTL PNL:	DU			
	AIR/GND (1, 2):	DU			
25	26VAC POL:	(+)			
	<u>MTS Adaptor Panel Switch Settings</u>				
30	DISCRETE IN (1 to 4):	DUDU			
	ADL LINK A:	U			
	PDL LINK A:	U			
	PDL FUNC DISC (1 to 4):	DUDU			
	XPDR OFF(NO):	D			
35					
40					
45					

<b>ENGINEERING SPECIFICATION</b>	<b>SECURITY NOTATION</b>	<b>SPEC. NO.</b>	<b>IT7517800</b>	<b>A</b>
		<b>CAGE CODE</b>	<b>55939</b>	

<b>REV LTR</b>	<b>SEE FIRST PAGE FOR PROPRIETARY OR DATA RIGHTS NOTATIONS.</b>
--------------------	---

**7.4 Table #7-3 - MTS Interface Panel and MTS Adaptor Panel Switch Positions for Software Programming**

For each panel, an "U" specifies switch is up. "D" specifies switch is down.

Use the switch settings in Table #1 with the following exceptions:

**MTS Interface Panel Switch Settings**

FUNC TEST:

SYNC ALT FLAG (1,2)

D  
UU  
UD  
DD  
(-) D

ALT TYPE SEL:

AIR/GND (1, 2):

26VAC POL:

**MTS Adaptor Panel Switch Settings**

DISCRETE IN (1 to 4):

DDDD  
D  
U

ADL LINK A:

PDL LINK A:

**7.5 Table #7-4 - MTS Connections for Synchro Input Testing**

Connect the following signals on the MTS Interface Panel using test jumper cables:

26VAC REF H to SYNC ALT 1/2 RH.

26VAC REF C to SYNC ALT 1/2 RC.

TEST VAC H to SYNC ALT 1/2 FX, FY, CX and CY.

TEST VAC C to SYNC ALT 1/2 FZ and CZ.

Adjust the amplitude of the TEST VAC signal to 9V RMS.

<b>ENGINEERING SPECIFICATION</b>	<b>SECURITY NOTATION</b>	<b>SPEC. NO.</b>	<b>IT7517800</b>	<b>REV LTR</b>
		<b>CAGE CODE</b>	<b>55939</b>	

<b>REV LTR</b>	<b>SEE FIRST PAGE FOR PROPRIETARY OR DATA RIGHTS NOTATIONS.</b>
--------------------	---

**7.6 Table #7-5 - MTS Connections for ARINC 429 Receiver Input Testing**

Connect the output of the ARINC 429 test set (A and B as appropriate) to the following signals on the MTS Panels using test jumper cables:

**MTS Interface Panel:**

DATA LINK IN A/B	(J1A-2A/2B)
TX COORD A/B	(J1A-5E/5F)
MAINT DATA IN A/B	(J1B-6A/6B)
575 ADC 1 A/B	(J1A-6H/6J)
575 ADC 2 A/B	(J1B-5C/5D)
429 ADC 1 A/B	(J1A-7H/7J)
429 ADC 2 A/B	(J1B-5A/5B)
CNTL DATA A A/B	(J1A-7A/7B)
CNTL DATA B A/B	(J1A-7E/7F)
FLT ID A/B	(J1A-6A/6B)

**MTS Adaptor Panel:**

COM C/D IN A/B	(J1A-2C/2D)
ADL IN A/B	(J1A-6C/6D)
ADS IN A/B	(J1B-6J/7K)
MODE S ADDR IN A/B	(J1A-3F/3G)
PDL IN A/B	(W1J1-1/2)

<b>ENGINEERING SPECIFICATION</b>	<b>SECURITY NOTATION</b>	<b>SPEC. NO.</b>	<b>IT7517800</b>	<b>REV LTR</b>
		<b>CAGE CODE</b>	<b>55939</b>	

<b>REV LTR</b>	<b>SEE FIRST PAGE FOR PROPRIETARY OR DATA RIGHTS NOTATIONS.</b>
--------------------	---

**7.7 Table #7-5 - Default Settings for ATC 1400A and S1403 Test Sets**

**ATC 1400A Test Set**

<b>FREQ/FUNCT:</b>	1030 Mhz, XPDR
<b>DELTA F:</b>	0.00, OFF
<b>PRF/SQTR:</b>	100, ON
<b>INTP PULSE:</b>	000.0 OFF
<b>DISPLAY SELECT:</b>	XPDR CODE
<b>DME REPLY EFF:</b>	100
<b>XPDR MODE:</b>	A
<b>RF LEVEL:</b>	-73, CW/NORM/OFF: NORM
<b>TACAN:</b>	OFF
<b>IDENT:</b>	OFF
<b>F2/P2-F1/P1:</b>	F1/P1
<b>TO/TAC/TD:</b>	TO
<b>XDPR P2/P3 DEV:</b>	0.00
<b>P2:</b>	CAL
<b>P3:</b>	CAL
<b>DME P2 DEV:</b>	0.0
<b>P2:</b>	CAL
<b>XPDR PULSEWIDTH:</b>	0.00, CAL
<b>SLS/ECHO:</b>	-0, OFF
<b>CAL MARKS:</b>	1.45 Us
<b>CAL <math>\phi</math>:</b>	FULL CW
<b>INTRF PULSE WIDTH:</b>	FULL CCW
<b>SUPPRESSOR:</b>	OFF
<b>VAR:</b>	Set for +18V pulse amplitude.
<b>RANGE/VEL/ACCEL:</b>	00000, IN/OUT: OUT, NORM/-1NM: -1NM

<b>ENGINEERING SPECIFICATION</b>	<b>SECURITY NOTATION</b>	<b>SPEC. NO.</b> IT7517800	<b>K</b>
	<b>CAGE CODE</b>	55939	<b>REV LTR</b>

REV LTR	SEE FIRST PAGE FOR PROPRIETARY OR DATA RIGHTS NOTATIONS.					
<b>S1403 Test Set</b>						
SMENU: (1) : FMT D, UF#16, RL=1, AQ=0, MU=0..0, ADD=00000001						
SMENU: (2) : FMT L, UF#16, Data=2525252525252525252525252525. ADD=52525252						
SMENU: (3) : FMT L, UF#23, Data=125252525252525252525252525252525252525. ADD=25252525						
SMENU: (1) ON						
SMENU: (2) through (16), OFF						
CMENU: (1)						
: Func: (2) SEQ (Mode S Only)						
: RFLvl: +CABLE LOSS (dB)						
: P6: CAL, Wd= CAL, Dv= CAL						
: P2: CAL						
: AntB: OFF						
CMENU: (2)						
: Prepulse: OFF						
: Ext. Sync.: Out= OFF, Dv= +0.00; In = OFF						
: Pulse Power Gate:P 1						
: Ext. Mod. In: OFF						
NOTE: Average cable loss in dB for RF cables in test set should be put in the RFLvl command field as a positive quantity.						
<b>7.8 Table #7-7 - Default Settings JC-AIR 429 Test Set</b>						
TX PARITY: ODD						
TX SPEED: HIGH						
RX SPEED: HIGH						
DISPLAY: DATA						
TRANSMIT MODE						
LABEL = 125						
DATA = 2AAAAA						
WORD RATE = 25 Milliseconds						
<b>7.9 Table #7-8 - Default PC Settings (PROCOMM)</b>						
The PROCOMM program should be set up for the following settings (ALT-P) menu:						
Baud Rate 38,400 Baud						
Data Bits 8						
Parity None						
Stop Bit 1						
Port Appropriate COM Port						
When uploading software, the XMODEM protocol should be used.						

<b>Honeywell</b>	<b>SECURITY NOTATION</b>	<b>SUPPLEMENTS</b>	<b>10 PAGE</b>
------------------	--------------------------	--------------------	--------------------

<b>ENGINEERING SPECIFICATION</b>	<b>SECURITY NOTATION</b>	<b>SPEC. NO.</b>	<b>IT7517800</b>	<b>REV LTR</b>
		<b>CAGE CODE</b>	<b>55939</b>	

<b>REV</b>	<b>SEE FIRST PAGE FOR PROPRIETARY OR DATA RIGHTS NOTATIONS.</b>
<b>LTR</b>	

8.0 **GENERAL TEST REQUIREMENTS.**

8.1 Initial Settings

Appendix A contains a procedure for making the initial adjustments to the transponder prior to testing. This procedure is intended as guideline only and it is not a requirement that it be followed exactly. The settings given are nominal values. Tolerance build-ups on any given module may make it desirable to deviate slightly from the given levels in order to meet the required Integrated Test specifications.

8.2 Test Sequence

For final testing the test sequence is based on functional requirements, it is required that the tests be performed in the order given.

8.3 Test Procedure

The Integrated Test Specification shall be performed in its entirety upon completion of any modifications or repairs to the unit under test.

8.5 I.T. Test Procedure Convention

In the Procedure section, switch position column, of the Integrated Test Specification document the statement "TEST SETUP # 1" will be encountered at the beginning of each test section. This statement is included to allow the operator to break-in at any given section for troubleshooting. When encountered during the final testing of the module the operator will ignore the function and continue on with the next statement.

<b>ENGINEERING SPECIFICATION</b>	<b>SECURITY NOTATION</b>	<b>SPEC. NO.</b>	<b>IT7517800</b>	<b>K</b>
		<b>CAGE CODE</b>	<b>55939</b>	

REV LTR SEE FIRST PAGE FOR PROPRIETARY OR DATA RIGHTS NOTATIONS.

## 8.6 Boot Software Part Numbers and CRCs

For each end item dash number (7517800-xxxxx) and minimum hardware mod level, the corresponding BOOT software part number and Boot software CRC is shown in the table.

Table 8-1 - Boot Software

<b>ENGINEERING SPECIFICATION</b>	<b>SECURITY NOTATION</b>	<b>SPEC. NO.</b>	<b>IT7517800</b>	<b>K</b>
		<b>CAGE CODE</b>	<b>55939</b>	

<b>REV LTR</b>	<b>SEE FIRST PAGE FOR PROPRIETARY OR DATA RIGHTS NOTATIONS.</b>
--------------------	---

8.7 Operational Software Part Numbers and CRCs

For each end item dash number (7517800-xxxx) and software mod level, the corresponding Operational software part number and CRCs are shown. The operational CRCs are comprised of three segments, OPER, COMP and XLNX.

Table 8-2 - Operational Software

<b>Dash No.</b>	<b>Software Mod</b>	<b>OPER S/W (Part Number)</b>	<b>OPER CRC</b>	<b>COMP CRC</b>	<b>XLNX CRC</b>
10001	-	PS7021601-901	4F3E	E3B2	A80E
10002	B	PS7021601-903	AE1E	E3B2	4E4E
10002	C	PS7021601-904	18A6	E3B2	4E4E
10002	D	PS7021601-905	6B39	E3B2	4E4E
10003	E	PS4087090-907	E6CE	E3B2	4E4E
20012	F	PS7021601-906	7CEO	E3B2	4E4E
55001	-	PS7021601-901	4FE3	E3B2	A80E
55002	B	PS7021601-903	AE1E	E3B2	4E4E
55002	C	PS7021601-904	18A6	E3B2	4E4E
55002	D	PS7021601-905	6B39	E3B2	4E4E
65012	F	PS7021601-906	7CEO	E3B2	4E4E

<b>ENGINEERING SPECIFICATION</b>	<b>SECURITY NOTATION</b>	<b>SPEC. NO.</b>	<b>IT7517800</b>	<b>K</b>
		<b>CAGE CODE</b>	<b>55939</b>	

<b>REV LTR</b>	<b>SEE FIRST PAGE FOR PROPRIETARY OR DATA RIGHTS NOTATIONS.</b>																		
	<b>8.8 Test Format Description</b>																		
	<table> <thead> <tr> <th style="text-align: left;"><b>Column</b></th> <th style="text-align: left;"><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>Rev Ltr</td><td>This column is used to identify revised material.</td></tr> <tr> <td>Test No.</td><td>Tests are numbered in sequence.</td></tr> <tr> <td>Opr Limits</td><td>Unit under test (UUT) shall meet these limits when tested at other than manufacturing facility. When an item is marked OPTIONAL, the corresponding test is not required except as an aid in troubleshooting.</td></tr> <tr> <td>Test Description</td><td>These items are the parameters to which the UUT was designed and aid in troubleshooting by specifying the input and output signal terminals. All conditions required are not repeated for each test, and conditions established in previous test also apply.</td></tr> <tr> <td>Switch Pos</td><td>Positions to which switches must be set are listed in required order and are grouped to correspond to applicable Work Steps.</td></tr> <tr> <td>Work Steps</td><td>This column defines the operations necessary to perform a test and achieve a result. Set switches to designated positions before performing corresponding work step.</td></tr> <tr> <td>Mfg Limits</td><td>UUT shall meet these limits at final buyoff before customer delivery.</td></tr> </tbody> </table>			<b>Column</b>	<b>Description</b>	Rev Ltr	This column is used to identify revised material.	Test No.	Tests are numbered in sequence.	Opr Limits	Unit under test (UUT) shall meet these limits when tested at other than manufacturing facility. When an item is marked OPTIONAL, the corresponding test is not required except as an aid in troubleshooting.	Test Description	These items are the parameters to which the UUT was designed and aid in troubleshooting by specifying the input and output signal terminals. All conditions required are not repeated for each test, and conditions established in previous test also apply.	Switch Pos	Positions to which switches must be set are listed in required order and are grouped to correspond to applicable Work Steps.	Work Steps	This column defines the operations necessary to perform a test and achieve a result. Set switches to designated positions before performing corresponding work step.	Mfg Limits	UUT shall meet these limits at final buyoff before customer delivery.
<b>Column</b>	<b>Description</b>																		
Rev Ltr	This column is used to identify revised material.																		
Test No.	Tests are numbered in sequence.																		
Opr Limits	Unit under test (UUT) shall meet these limits when tested at other than manufacturing facility. When an item is marked OPTIONAL, the corresponding test is not required except as an aid in troubleshooting.																		
Test Description	These items are the parameters to which the UUT was designed and aid in troubleshooting by specifying the input and output signal terminals. All conditions required are not repeated for each test, and conditions established in previous test also apply.																		
Switch Pos	Positions to which switches must be set are listed in required order and are grouped to correspond to applicable Work Steps.																		
Work Steps	This column defines the operations necessary to perform a test and achieve a result. Set switches to designated positions before performing corresponding work step.																		
Mfg Limits	UUT shall meet these limits at final buyoff before customer delivery.																		
K 35	<b>8.9 The XS-950 Transponder shall be tested using test software as specified in EB7517804.</b>																		
40																			
45																			

**Honeywell**

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO. IT7517800		REV LTR	
					CAGE CODE 55939			
REV LTR	TEST NO.	SPECIFICATION			PROCEDURE			SPECIFICATION
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	MFG LIMITS
5	1.0			<u>POWER ON CURRENT TEST</u> (-10xxx to -54xxx)	Test Setup #1		Connect Equipment per Figure 1 for Test Setup #1	
10				Apply 115 $\pm$ 2 Vac to unit.	<u>MTS Panel</u> 115VAC: ON		<u>POWER ON CURRENT TEST</u> (-10xxx to -54xxx)	
15	1.1	0.3 to 1.0 Amps (RMS)		With the voltage applied and the unit in standby the current draw shall be as specified.	<u>MTS Adaptor</u> 115VAC: ON		115VAC on MTS Panel	
20				Set the transponder for the maximum DELM reply rate of 10 16-segment DELM/second. Set +66V supply for the nominal voltage.			115VAC on MTS Adaptor Panel	
25							Apply power to the transponder module. The amp meter on the power supply shall be as specified.	0.3 to 1.0 Amps (RMS)
30	1.2	0000		Verify the PWR FAIL warning signal is not active.			Type on PC: "DAC 80" "XREP M D16 10" "MON"	
35	1.3	50.0 to 60.0 Vdc (55.0 nom)		Verify the +66VDC Power supply monitor is within specified limits.			The PWR FAIL display on the PC shall be as specified.	0000
40				Apply 97 $\pm$ 2 Vac to unit (LOW Line Voltage).			The +66V display in the ON column shall be as specified.	50.0 to 60.0 Vdc (55.0 nom)
45	1.4	0000		Verify the PWR FAIL warning signal is not active.			Adjust the supply to 97 Vac.	0000
							The PWR FAIL display on the PC shall be as specified.	

Honeywell

SECURITY NOTATION

SUPPLEMENTS

15

PAGE

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO. IT7517800		REV LTR	
					CAGE CODE 55939			
REV LTR	TEST NO.	SPECIFICATION			PROCEDURE			SPECIFICATION
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	MFG LIMITS
1.5	5	50.0 to 60.0 Vdc (55.0 nom)		Verify the +66VDC Power supply monitor is within specified limits.  Apply 134 ± 2 Vac to unit (HIGH Line Voltage).			The +66V display in the ON column shall be as specified.  Adjust the supply to 134 Vac.	50.0 to 60.0 Vdc (55.0 nom)
1.6	10	50.0 to 60.0 Vdc (55.0 nom)		Verify the +66VDC Power supply monitor is within specified limits.  Apply 115 ± 2 Vac to unit (Nominal Line Voltage).  Set the transponder to normal operational mode.			The +66V display in the ON column shall be as specified.  Adjust the supply to 115 Vac.  Type on PC: "ESC" "XON 1"	50.0 to 60.0 Vdc (55.0 nom)
15	20							
25	30							
35	40							
45								

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO. IT7517800		REV LTR		
CAGE CODE		55939							
REV LTR	TEST NO.	SPECIFICATION			PROCEDURE		SPECIFICATION		
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	MFG LIMITS	
5	2.0				Test Setup #1		Connect Equipment per Figure 1 for Test Setup #1		
10				<u>POWER ON CURRENT TEST</u> (-55xxx to -99xxx)			<u>POWER ON CURRENT TEST</u> (-55xxx to -99xxx)		
15				Turn 115 Vac on for MTS circuitry	<u>MTS Panel</u> 115VAC: ON		115VAC on MTS Panel		
20	2.1	0.7 to 1.3 Amp		Apply +27.5 Vdc to unit.	<u>MTS Adaptor</u> 115VAC: ON		115VAC on MTS Adaptor Panel		
25					<u>MTS Adaptor</u> 28VDC: ON		+27.5 Vdc to unit		
30				With the voltage applied and the unit in standby the current draw shall be as specified.			Apply power to the transponder module. The amp meter on the power supply shall be as specified.	0.7 to 1.3 Amps	
35				Set the transponder for the maximum DELM reply rate of 10 16-segment DELM/second. Set +66V supply for the nominal voltage.			Type on PC: "DAC 80" "XREP M D16 10" "MON"		
40	2.2	0000		Verify the PWR FAIL warning signal is not active.			The PWR FAIL display on the PC shall be as specified.	0000	
45	2.3	50.0 to 60.0 Vdc (55.0 nom)		Verify the +66VDC Power supply monitor is within specified limits.			The +66V display in the ON column shall be as specified.	50.0 to 60.0 Vdc (55.0 nom)	
				Apply 18 ± 0.5 Vdc to unit (LOW Line Voltage).			Adjust the supply to 18 Vdc.		

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO. IT7517800		-
					CAGE CODE 55939		REV LTR
REV LTR	TEST NO.	SPECIFICATION			PROCEDURE		SPECIFICATION
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	MFG LIMITS
5	2.4	0000		Verify the PWR FAIL warning signal is not active.		The PWR FAIL display on the PC shall be as specified.	0000
10	2.5	50.0 to 60.0 Vdc (55.0 nom)		Verify the +66VDC Power supply monitor is within specified limits.  Apply 33 ± 0.5 Vdc to unit (HIGH Line Voltage).		The +66V display in the ON column shall be as specified.  Adjust the supply to 33 Vdc.	50.0 to 60.0 Vdc (55.0 nom)
15	2.6	50.0 to 60.0 Vdc (55.0 nom)		Verify the +66VDC Power supply monitor is within specified limits.  Apply 27.5 ± 0.5 Vdc to unit (Nominal Line Voltage).  Set the transponder to normal operational mode.		The +66V display in the ON column shall be as specified.  Adjust the supply to 27.5 Vdc.  Type on PC: "ESC" "XON 1"	50.0 to 60.0 Vdc (55.0 nom)
20							
25							
30							
35							
40							
45							

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO. IT7517800		-
					CAGE CODE 55939		REV LTR
REV LTR	TEST NO.	SPECIFICATION			PROCEDURE		
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS
							MFG LIMITS
3.0				<u>RF SELF TEST</u>	Test Setup # 1		<u>RF SELF TEST</u>
5				Turn RF signal generator off.	ATC 1400A: RF LEVEL: OFF		
10				Activate Long Mode S RF self-test interrogations			Type on PC "XRF L"
15	3.1	0000 0000		Verify self-test passes with no errors.			Wait a minimum of 15 seconds. The error count on PC shall be as specified.
20				Return to normal operational mode			Type on PC "<ESC>" "XON 1"
25				Turn RF signal generator on.	ATC 1400A: RF LEVEL: ON		
30							
35							
40							
45							

Honeywell

SECURITY NOTATION

SUPPLEMENTS

19

PAGE

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO. IT7517800			
REV LTR	TEST NO.	SPECIFICATION			PROCEDURE		SPECIFICATION	
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	MFG LIMITS
4.0				<u>MONITOR TEST</u>	Test Setup #1		<u>MONITOR TEST</u>	
				Set the transponder for 100 Long Mode S replies/second			Type on PC " <ESC> " " XREP M L 100 " " DAC 00 " " MON "	
4.1	23.0 to 37.0 Vdc			Verify the input voltage (VIN) Monitor when transmitting is within specified limits.			The VIN monitor in the ON column shall be as specified.	24.0 to 36.0 Vdc
4.2	61.0 to 73.0 Vdc (67.0 nom)			With the +66V set to the maximum voltage, verify the +66VDC Power Supply Monitor when transmitting is within specified limits.			The +66V monitor in the ON column shall be as specified.	62.0 to 72.0 Vdc (67.0 nom)
				Set the transponder for the nominal +66V power supply voltage.			Type on PC " <ESC> " " DAC 80 " " MON "	
4.3	55.0 to 67.0 Vdc (61.0 nom)			With the +66V set to the nominal voltage, verify the +66VDC Power Supply Monitor when transmitting is within specified limits.			The +66V monitor in the ON column shall be as specified.	56.0 to 66.0 Vdc (61.0 nom)
4.4	35.0 to 44.0 Vdc (39.5 nom)			Verify the +40VDC Power Supply Monitor when transmitting is within specified limits.			The +40V monitor in the ON column shall be as specified.	36.0 to 43.0 Vdc (39.5 nom)
4.5	28.0 to 38.0 Vdc (33.0 nom)			Verify the +33VDC Power Supply Monitor when transmitting is within the specified limits.			The +33V monitor in the ON column shall be as specified.	29.5 to 36.5 Vdc (33.0 nom)

**ENGINEERING  
SPECIFICATION**
**SECURITY NOTATION**
**SPEC.  
NO.**
**IT7517800**
**CAGE  
CODE**
**55939**
**-**
**REV LTR**

REV LTR	TEST NO.	SPECIFICATION		PROCEDURE		SPECIFICATION		
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	MFG LIMITS
5	4.6	23.0 to 33.0 Vdc (28.0 nom)	C	Verify the +28VDC Power Supply Monitor when transmitting is within the specified limits.			The +28V monitor in the ON column shall be as specified.	24.5 to 31.5 Vdc (28.0 nom)
10	4.7	12.5 to 17.0 Vdc (14.5 nom)	C	Verify the +15VDC Power Supply Monitor when transmitting is within the specified limits.			The +15V monitor in the ON column shall be as specified.	13.0 to 16.5 Vdc (14.5 nom)
15	4.8	-6.0 to -3.5 Vdc (-4.4 nom)	C	Verify the -5VDC Power Supply Monitor when transmitting is within the specified limits.			The -5V monitor in the ON column shall be as specified.	-5.5 to -3.75 Vdc (-4.4 nom)
20	4.9	-17.0 to -12.5 Vdc (-14.4 nom)	C	Verify the -15VDC Power Supply Monitor when transmitting is within the specified limits.			The -15V monitor in the ON column shall be as specified.	-16.5 to -13.0 Vdc (-14.4 nom)
25	4.10	-100.0 to -170.0 Vdc (-125.0 nom)	C	Verify the -150VDC Power Supply Monitor when transmitting is within the specified limits.			The -150V monitor in the ON column shall be as specified.	-105.0 to -165.0 Vdc (-125.0 nom)
30	4.11	-2.0 to +12.0 Vdc (5.0 nom)	C	Verify the Transmitter Top PIN monitor when not transmitting is within the specified limits.			The Top PIN display in the OFF column shall be as specified.	0.0 to +10.0 Vdc (5.0 nom)
35	4.12	-175.0 to -90.0 Vdc (-120.0 nom)	C	Verify the Transmitter Top PIN monitor when transmitting is within the specified limits.			The Top PIN display in the ON column shall be as specified.	-170.0 to -95.0 Vdc (-120.0 nom)
40								
45								

**Honeywell**
**SECURITY NOTATION**
**SUPPLEMENTS**
**21**
**PAGE**

# ENGINEERING SPECIFICATION

## SECURITY NOTATION

SPEC. NO. IT7517800

CAGE CODE 55939

REV LTR

REV LTR	TEST NO.	SPECIFICATION		PROCEDURE		SPECIFICATION	
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS		MFG LIMITS
5	4.13	-2.0 to +12.0 Vdc (5.0 nom)		Verify the Transmitter Bottom PIN monitor when not transmitting is within the specified limits.		The Bot PIN display in the OFF column shall be as specified.	0.0 to +10.0 Vdc (5.0 nom)
10	4.14	-175.0 to -90.0 Vdc (-120.0 nom)		Verify the Transmitter Bottom PIN monitor when transmitting is within the specified limits.		The Bot PIN display in the ON column shall be as specified.	-170.0 to -95.0 Vdc (-120.0 nom)
15	4.15	Less than +0.3 Vdc (0.0 nom)		Verify the Transmitter top forward power monitor when not transmitting is within the specified limits.		The Top pwr display in the OFF column shall be as specified.	Less than +0.2 Vdc (0.0 nom)
20	4.16	Greater than +1.0 Vdc (3.0 nom)		Verify the Transmitter top forward power monitor when transmitting is within the specified limits.		The Top pwr display in the ON column shall be as specified.	Greater than +1.5 Vdc (3.0 nom)
25	4.17	Less than +0.3 Vdc (0.0 nom)		Verify the Transmitter bottom forward power monitor when not transmitting is within the specified limits.		The Bot pwr display in the OFF column shall be as specified.	Less than +0.2 Vdc (0.0 nom)
30	4.18	Greater than +1.0 Vdc (3.0 nom)		Verify the Transmitter bottom forward power monitor when transmitting is within the specified limits.		The Bot pwr display in the ON column shall be as specified.	Greater than +1.5 Vdc (3.0 nom)
35	4.19	+18.0 to +32.0 Vdc (+22.0 nom)		Verify the Transmitter pulse modulation monitor when transmitting is within the specified limits.		The Pul mod display in the ON column shall be as specified.	+18.5 to +31.0 Vdc (+22.0 nom)

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO. IT7517800		REV LTR	
					CAGE CODE 55939			
REV LTR	TEST NO.	SPECIFICATION			PROCEDURE			SPECIFICATION
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	
5	4.20	+20.0 to +32.0 Vdc (+26.0 nom)		Verify the Transmitter envelope modulation monitor when transmitting is within the specified limits.			The Env mod display in the ON column shall be as specified.	+22.0 to +30.0 Vdc (+26.0 nom)
13	4.21	0.5 to 4.0 Vdc (2.0 nom)		Verify the Local Oscillator Level monitor when transmitting is within the specified limits.			The LO Level display in the ON column shall be as specified.	0.75 to 3.5 Vdc (2.0 nom)
15	4.22	1.5 to 10.5 Vdc (6.5 nom)		Verify the Local Oscillator VCO tuning voltage monitor when transmitting is within the specified limits.			The VCO volt display in the ON column shall be as specified.	1.5 to 10.0 Vdc (6.5 nom)
23	4.23	3.0 to 5.5 Vdc (4.1 nom)		Verify the Synthesizer Lock Detector monitor when transmitting is within the specified limits.			The Syn lock display in the ON column shall be as specified.	3.0 to 5.5 Vdc (4.1 nom)
25	4.24	Less than 2.0 Vdc (1.0 nom)		Verify the Top Antenna Monitor is within the specified limits.			The Top Ant Mon display shall be as specified.	Less than 1.5 Vdc (1.0 nom)
30	4.25	Less than 2.0 Vdc (1.0 nom)		Verify the Bottom Antenna Monitor is within the specified limits.			The Bot Ant Mon display shall be as specified.	Less than 1.5 Vdc (1.0 nom)
35	4.26	20.0 to 70.0 Deg C.		Verify the Temperature Monitor is within the specified limits.			The Temp display shall be as specified.	20.0 to 70.0 Deg C.
40	4.27	3.5 to 5.5 Vdc (4.1 nom)		Verify the Warm/Cold Detector is within the specified limits.			The Warm/Cold display shall be as specified.	3.5 to 5.5 Vdc (4.1 nom)
45				Return to normal operational mode			Type on PC * <u>ESC</u> * * <u>XON 1</u> *	

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO. IT7517800		REV LTR	
					CAGE CODE 55939			
REV LTR	TEST NO.	SPECIFICATION			PROCEDURE			
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	MFG LIMITS
5.0				<u>TRANSMITTER FREQUENCY AND OUTPUT POWER</u>	Test Setup #1		<u>TRANSMITTER FREQUENCY AND OUTPUT POWER</u>	
5.1	1089.0 to 1091.0 MHz (1090.0 nominal)		C	<u>TRANSMITTER FREQUENCY</u> Verify Transmitter Frequency on the BOTTOM Antenna is within the specified limits.			<u>TRANSMITTER FREQUENCY</u> The XMTR/FREQ display on the ATC 1400A shall be as specified.	1089.25 to 1090.75 MHz (1090.0 nominal)
10				<u>TRANSMITTER POWER OUTPUT</u>			<u>TRANSMITTER POWER OUTPUT</u>	
15				Set ATC test set to measure first pulse of a Long Mode S Reply.	ATC 1400A: F1/P1 F2/P2: F2/P2		Set IFR 1400A to measure F2/P2.	
20					S1403: C MENU: 2 Pulse Power Gate:P 1		Set the S1403 to measure first pulse in the reply. NOTE: All attenuations for cable losses must be compensated for when making power measurements per paragraph 3.4.	
25								
30	5.2	250 to 630 Watts		Verify Transmitter power on the BOTTOM Antenna, First Pulse of reply is within the specified limits.			The XMTR PWR display on the ATC 1400A shall be as specified.	325 to 630 Watts
35				Set ATC test set to measure last pulse of a Long Mode S Reply.	S1403: Pulse Power Gate:P 115		Set the S1403 to measure the last pulse in the reply.	
40								
45								

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO. IT7517800		REV LTR
CAGE CODE		55939					
REV LTR	TEST NO.	SPECIFICATION		PROCEDURE		SPECIFICATION	REV LTR
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	MFG LIMITS	
5	5.3	250 to 630 Watts		Verify Transmitter power on the BOTTOM Antenna, Last Pulse of reply is within specified limits.		The XMTR PWR display on the ATC 1400A shall be as specified.	325 to 630 Watts
10	5.4	-2.0dB to +2.0dB		Verify the pulse droop (first to last pulse) of the reply is within the specified limits.		Calculate the ratio in dB between the power in test 5.2 and 5.3 according to the following formula: $10 \cdot \log_{10} [\text{Power 5.2}/\text{Power 5.3}]$	-1.5dB to +1.5dB
15				Connect TOP antenna cable to 1400A.		The ratio shall be as specified.	
20				Set ATC test set to measure first pulse of a Long Mode S Reply.	<u>S1403:</u> Pulse Power Gate:P 1	Connect TOP antenna cable to ATC 1400A.	
25	5.5	250 to 630 Watts		Verify Transmitter power on the TOP Antenna, First Pulse of reply is within the specified limits.		Set the S1403 to measure the first pulse in the reply.	325 to 630 Watts
30				Set ATC test set to measure last pulse of a Long Mode S Reply.	<u>S1403:</u> Pulse Power Gate:P 115	The XMTR PWR display on the ATC 1400A shall be as specified.	
35	5.6	250 to 630 Watts		Verify Transmitter power on the TOP Antenna, Last Pulse of reply is within specified limits.		Set the S1403 to measure the last pulse in the reply.	325 to 630 Watts
40						The XMTR PWR display on the ATC 1400A shall be as specified.	
45							

# ENGINEERING SPECIFICATION

## SECURITY NOTATION

SPEC.  
NO.

IT7517800

CAGE  
CODE

55939

REV LTF

REV LTR	TEST NO.	SPECIFICATION			PROCEDURE			SPECIFICATION MFG LIMITS
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	
5	5.7	-2.0dB to +2.0dB		Verify the pulse droop (first to last pulse) of the reply is within the specified limits.			Calculate the ratio in dB between the power in test 5.5 and 5.6 according to the following formula: $10 \cdot \log_{10} (\text{Power 5.5}/\text{Power 5.6})$ The ratio shall be as specified.	-1.5dB to +1.5dB
10								
15				Re-connect BOTTOM antenna cable to 1400A and TOP antenna cable to S1403.			Connect TOP antenna cable to S1403 and BOTTOM antenna cable to ATC 1400A.	
20				Set ATC test set to measure first pulse of a Long Mode S Reply.	<u>S1403:</u> Pulse Power Gate:P 1		Set the S1403 to measure the first pulse in the reply.	
25					<u>ATC 1400A:</u> F1/P1 F2/P2: F1/P1		Set IFR 1400A to measure F1/P1.	
30								
35								
40								
45								

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO. IT7517800		REV LTR	
			CAGE CODE 55939					
REV LTR	TEST NO.	SPECIFICATION			PROCEDURE		SPECIFICATION	
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	MFG LIMITS
6.0				<u>TRANSMITTER REPLY PULSE WIDTH, RISE AND FALL TIME</u>  Select the TOP antenna.	Test Setup #1		<u>TRANSMITTER REPLY PULSE WIDTH, RISE AND FALL TIME</u>  NOTE: The XMTR Detector on the S1403 <u>MUST</u> be used to measure transmitter reply pulse characteristics.	
				With the transponder set to reply to 100 Long Mode S replies/second, connect the test equipment to measure the transmitter reply pulse characteristics.			Setup the oscilloscope for the following configuration: CH1: S1403 XMTR Det CH2: OFF TRIGGER A: CH1, Slope+ A-SWP: 20usec B-SWP: 50nsec B-Delayed mode.	
6.1	50 nsec to 100 nsec			Check the rise time (time between 10% to 90% voltage point on the pulse) of the second preamble pulse of the reply.			Set B-Delay to measure the rising edge of the second preamble pulse of the reply. The rise time (time between 10% to 90% voltage points) on the oscilloscope shall be as specified.	50 nsec to 100 nsec
6.2	450 nsec to 550 nsec (500 nominal)			Check the pulse width (time between 50% to 50% voltage point on the pulse) of the second preamble pulse of the reply.			Set B-SWP to 100nsec and B-Delay to measure the pulse width of the second preamble pulse of the reply. The pulse width (time between 50% to 50% voltage points) on the oscilloscope shall be as specified.	450 nsec to 550 nsec (500 nominal)

**ENGINEERING  
SPECIFICATION**
**SECURITY NOTATION**
**SPEC.  
NO.**
**IT7517800**
**CAGE  
CODE**
**55939**
**REV LTR**

REV LTR	TEST NO.	SPECIFICATION			PROCEDURE			SPECIFICATION
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	
6.3	50 nsec to 200 nsec			Check the fall time (time between 90% to 10% voltage point on the pulse) of the second preamble pulse of the reply.			Set the B-SWP to 50nsec and B-Delay to measure the falling edge of the second preamble pulse of the reply. The fall time (time between 90% to 10% voltage points) on the oscilloscope shall be as specified.	50 nsec to 200 nsec
6.4	50 nsec to 100 nsec			Check the rise time (time between 10% to 90% voltage point on the pulse) of the last pulse of the reply.			Set B-Delay to measure the rising edge of the last pulse of the reply. The rise time (time between 10% to 90% voltage points) on the oscilloscope shall be as specified.	50 nsec to 100 nsec
6.5	450 nsec to 550 nsec (500 nominal)			Check the pulse width (time between 50% to 50% voltage point on the pulse) of the last pulse of the reply.			Set B-SWP to 100nsec and B-Delay to measure the pulse width of the last pulse of the reply. The pulse width (time between 50% to 50% voltage points) on the oscilloscope shall be as specified.	450 nsec to 550 nsec (500 nominal)
6.6	50 nsec to 200 nsec			Check the fall time (time between 90% to 10% voltage point on the pulse) of the last pulse of the reply.			Set the B-SWP to 50nsec and B-Delay to measure the falling edge of the last pulse of the reply. The fall time (time between 90% to 10% voltage points) on the oscilloscope shall be as specified.	50 nsec to 200 nsec
				Turn the TOP antenna off.	S1403: C MENU: 1 AntB: OFF		Antenna B OFF	

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO. IT7517800		REV LTR	
					CAGE CODE 55939			
REV LTR	TEST NO.	SPECIFICATION			PROCEDURE		SPECIFICATION	
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	MFG LIMITS
7.0				<u>ATCRBS CODE</u> <u>VERIFICATION, REPLY</u> <u>DELAY AND JITTER</u>  Interrogate the transponder with 1000 ATCRBS Mode A Interrogations at -40 dBm.	Test Setup #1		<u>ATCRBS CODE</u> <u>VERIFICATION, REPLY</u> <u>DELAY AND JITTER</u>  ATC (ATCRBS Only) mode.	
7.1	55% to 75% (65% nominal)			Verify the transponder limits replies to ATCRBS interrogations.			The XPDR %REPLY display on the ATC 1400A shall be as specified.	55% to 75% (65% Nominal)
7.2	3.0 to 3.4 usec			Interrogate the transponder with 100 ATCRBS Mode A Interrogations at MTL+3dB.	ATC 1400A: PRF/SQTR: 100 RF LEVEL: -73 dBm		100 Interrogations/sec  -73dBm	3.0 to 3.4 usec
7.3	Less than 0.2 usec			Verify the P3 to F1 reply delay is within the specified limits.			The RpDly display on the S1403 shall be as specified.	Less than 0.175 usec
7.4	2525			Verify the reply jitter over at least a 10 second interval is within the specified limits.  Set ATC CODE to 2525.			The absolute value of the difference between the minimum value and maximum value of the RpDly display on the S1403 over a 10 second period of time shall be as specified.  Type on PC "XATC 2525 2525"	2525
				Verify the ATC CODE of the Mode A Reply is as specified.			The ATC CODE display of the 1400A shall be as specified.	

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO.		REV LTR	
					IT7517800			
REV LTR	TEST NO.	SPECIFICATION			PROCEDURE			SPECIFICATION
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	
5	7.5	ID5252		<p>Set ATC CODE to 5252 with IDENT.</p> <p>Verify the ATC CODE of the Mode A Reply is as specified.</p> <p>Interrogate the transponder with ATCRBS Mode C Interrogations.</p> <p>Set Mode C code to 2525.</p>			<p>Type on PC "XATC I 5252 2525"</p> <p>The ATC CODE display of the 1400A shall be as specified.</p> <p>Mode C</p>	ID5252
10	7.6	2525		<p>Verify the ATC CODE of the Mode C Reply is as specified.</p> <p>Set Mode C code to 5252.</p>			<p>The ATC CODE display of the 1400A shall be as specified.</p> <p>Type on PC "XATC 0000 5252"</p>	2525
15	7.7	5252		<p>Verify the ATC CODE of the Mode C Reply is as specified.</p> <p>Interrogate the transponder with Mode S Interrogations</p>	<u>ATC 1400A:</u> <u>XPDR MODE: C</u>	<u>S1403:</u> <u>C MENU: 1</u> <u>FUNC: 2</u>	<p>The ATC CODE display of the 1400A shall be as specified.</p> <p>SEQ (Mode S) mode.</p>	5252
20							Mode A	
25								
30								
35								
40								
45								

ENGINEERING SPECIFICATION		SECURITY NOTATION		SPEC. NO.	IT7517800	REV LTR
				CAGE CODE	55939	
REV LTR	TEST NO.	SPECIFICATION		PROCEDURE		SPECIFICATION
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	MFG LIMITS
8.0				<u>MODE S CODE</u> <u>VERIFICATION, REPLY</u> <u>DELAY AND JITTER</u>	Test Setup # 1	<u>MODE S CODE</u> <u>VERIFICATION, REPLY</u> <u>DELAY AND JITTER</u>
9				Set Mode S Interrogation for alternating 1/0 pattern.	S1403: S MENU: (1) OFF (2) ON	Type on PC "XON AAAAAA"
10				Set the transponder to reply to Mode S Interrogations		
11				Verify the Mode S Reply to a UP=16 interrogation is correct.		The reply data on the S-1403 display shall be as specified.
12	DP16, Data=2525252 525252525252 525252525 ADD= 52525252			Set Mode S Interrogation for the complement alternating 1/0 pattern.	S1403: S MENU: (2) OFF (3) ON	DP16, Data=2525252 525252525252 525252525 ADD= 52525252
13				Set the transponder to reply to Mode S Interrogations		Type on PC "XON 555555"
14				Verify the Mode S Reply to a UP=23 interrogation is correct.		The reply data on the S-1403 display shall be as specified.
15	DP23, Data= 125252525252 525252525252 5252 ADD= 25252525			Set Mode S for default interrogation	S1403: S MENU: (3) OFF (1) ON	DP23, Data= 125252525252 525252525252 5252 ADD= 25252525
16				Set the transponder to default state		Type on PC "XON 1"

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO. IT7517800		REV LTR	
					CAGE CODE 55939			
REV LTR	TEST NO.	SPECIFICATION			PROCEDURE			SPECIFICATION
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	
8.3	127.75 to 128.25 usec (128.0 nominal)	Measure the SPR to First Preamble Pulse Reply Delay on the BOTTOM receiver.					The RpDly display on the S-1403 shall be as specified.	127.80 to 128.20 usec (128.0 nominal)
8.4	Less than 0.15 usec	Verify the reply jitter over at least a 10 second interval is within the specified limits.					The absolute value of the difference between the minimum value and maximum value of the RpDly display on the S1403 over a 10 second period of time shall be as specified.	Less than 0.125 usec
		Interrogate the transponder with ATCRBS Mode A/Mode S Interrogations		<u>S1403:</u> C MENU: 1 FUNC: 4			ACL (ATCRBS/Mode S All Call) mode	
8.5	127.50 to 128.50 usec (128.0 nominal)	Measure the Leading edge of P4 to the First Preamble Pulse Reply Delay.					The RpDly display on the S-1403 shall be as specified.	127.60 to 128.40 usec (128.00 nominal)
8.6	Less than 0.20 usec	Verify the reply jitter over at least a 10 second interval is within the specified limits.					The absolute value of the difference between the minimum value and maximum value of the RpDly display on the S1403 over a 10 second period of time shall be as specified.	Less than 0.175 usec
		Interrogate the transponder with Mode S Interrogations		<u>S1403:</u> C MENU: 1 FUNC: 2			SEQ (Mode S) mode	

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO. IT7517800		REV LTR	
					CAGE CODE 55939			
REV LTR	TEST NO.	SPECIFICATION			PROCEDURE			
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	MFG LIMITS
9.0				<u>RECEIVER MTL, DYNAMIC RANGE AND LOW LEVEL REPLY RATIO</u>  Interrogate the transponder with ATCRBS Mode A Interrogations	Test Setup #1		<u>RECEIVER MTL, DYNAMIC RANGE AND LOW LEVEL REPLY RATIO</u>  ATC (ATCRBS Only) mode.	
9.1	-78 to -74 dBm (-76 nom)			Verify the BOTTOM receiver MTL for ATCRBS Mode A Interrogations.	S1403: C MENU: 1 FUNC: 1		Adjust the RF level until the *Reply:ATC display on the S1403 shows 90% average reply. The RF Level display on the 1400A shall be as specified.	-78 to -74 dBm (-76 nom)
9.2	Greater than or equal to 90%			Verify the BOTTOM receiver Dynamic range for ATCRBS Mode A interrogations between MTL+3dB and -24dBm.			Adjust the RF level from -73dBm to -23dBm in 10dB steps. At each signal level, the *Reply:ATC on the S1403 display shall be as specified.	Greater than or equal to 99%
9.3	Less than or equal to 10%			Verify the BOTTOM receiver Low-level reply ratio for ATCRBS Mode A interrogations at -81dBm.  Interrogate the transponder with Mode S Interrogations	ATC 1400A: RF LEVEL: -81dBm  S1403: C MENU: 1 FUNC: 2		The *Reply:ATC on the S1403 display shall be as specified.  SEQ (Mode S Only) mode.	Less than or equal to 1%

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO. IT7517800		REV LTR		
CAGE CODE		55939							
REV LTR	TEST NO.	SPECIFICATION			PROCEDURE		SPECIFICATION		
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	MFG LIMITS		
5	9.4	-78 to -74 dBm (-76 nom)	C	Verify the BOTTOM receiver MTL for Mode S Interrogations.			Adjust the RF level until the %Reply:S display on the S1403 shows 90% average reply. The RF Level display on the 1400A shall be as specified.		
10	9.5	Greater than or equal to 99%	C	Verify the BOTTOM receiver Dynamic range for MODE S interrogations between MTL+3dB and -24dBm.			Adjust the RF level from -73dBm to -23dBm in 10dB steps. At each signal level, the %Reply:S on the S1403 display shall be as specified.		
15				Connect TOP antenna cable to 1400A.			Connect TOP antenna cable to ATC 1400A.		
20				Interrogate the transponder with ATCRBS Mode C Interrogations	<u>S1403:</u> C MENU: 1 FUNC: 1		ATC (ATCRBS Only) mode.		
25					<u>ATC 1400A:</u> XPDR MODE: C		Mode C		
30	9.6	-78 to -74 dBm (-76 nom)	C	Verify the TOP receiver MTL for ATCRBS Mode C Interrogations.			Adjust the RF level until the %Reply:ATC display on the S1403 shows 90% average reply. The RF Level display on the 1400A shall be as specified.		
35	9.7	Greater than or equal to 90%	C	Verify the TOP receiver Dynamic range for ATCRBS Mode C interrogations between MTL+3dB and -24dBm.			Adjust the RF level from -73dBm to -23dBm in 10dB steps. At each signal level, the %Reply:ATC on the S1403 display shall be as specified.		
40									
45									

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO. IT7517800		REV LTR	
CAGE CODE		55939						
REV LTR	TEST NO.	SPECIFICATION		PROCEDURE		SPECIFICATION		
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	MFG LIMITS
9.8		Less than or equal to 10%		Verify the TOP receiver Low-level reply ratio for ATCRBS Mode C interrogations at -81dBm.	ATC 1400A: RF LEVEL: -81dBm		The #Reply:ATC on the S1403 display shall be as specified.	Less than or equal to 1%
				Interrogate the transponder with Mode S Interrogations	ATC 1400A: XPDR MODE: A		Mode A	
					S1403: C MENU: 1 FUNC: 2		SBQ (Mode S Only) mode.	
9.9	-78 to -74 dBm (-76 nom)			Verify the TOP receiver MTL for Mode S Interrogations.			Adjust the RF level until the #Reply:S display on the S1403 shows 90% average reply. The RF Level display on the 1400A shall be as specified.	-78 to -74 dBm (-76 nom)
9.10	Greater than or equal to 99%			Verify the TOP receiver Dynamic range for MODE S interrogations between MTL+3dB and -24dBm.			Adjust the RF level from -73dBm to -23dBm in 10dB steps. At each signal level, the #Reply:S on the S1403 display shall be as specified.	Greater than or equal to 99%
				Re-connect BOTTOM antenna cable to 1400A and TOP antenna cable to S1403.			Connect TOP antenna cable to S1403 and BOTTOM antenna cable to ATC 1400A	

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO. IT7517800		REV LTR	
					CAGE CODE 55939			
REV LTR	TEST NO.	SPECIFICATION			PROCEDURE		SPECIFICATION	
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	MFG LIMITS
10.0				<u>RECEIVER BANDWIDTH</u>  Interrogate the transponder with ATCRBS Mode A Interrogations	Test Setup #1  <u>S1403:</u> C MENU: 1 FUNC: 1		<u>RECEIVER BANDWIDTH</u>  ATC (ATCRBS Only) mode.	
10.1	Less than or equal to 90%			Verify the BOTTOM receiver bandwidth response at 1005 MHz to ATCRBS Mode A interrogations	<u>ATC 1400A:</u> FREQ: 1005		The *Reply:ATC on the S1403 display shall be as specified.	Less than or equal to 10%
10.2	Less than or equal to 90%			Verify the BOTTOM receiver bandwidth response at 1055 MHz to ATCRBS Mode A interrogations	<u>ATC 1400A:</u> FREQ: 1055		The *Reply:ATC on the S1403 display shall be as specified.	Less than or equal to 10%
10.3	Less than or equal to 90%			Connect TOP antenna cable to 1400A.			Connect TOP antenna cable to ATC 1400A.	
10.4	Less than or equal to 90%			Verify the TOP receiver bandwidth response at 1055 MHz to ATCRBS Mode A interrogations	<u>ATC 1400A:</u> FREQ: 1005		The *Reply:ATC on the S1403 display shall be as specified.	Less than or equal to 10%
10.5				Verify the TOP receiver bandwidth response at 1005 MHz to ATCRBS Mode A interrogations			The *Reply:ATC on the S1403 display shall be as specified.	Less than or equal to 10%

ENGINEERING SPECIFICATION		SECURITY NOTATION		SPEC. NO.	TT7517800	REV LTR
				CAGE CODE	55939	
REV LTR	TEST NO.	SPECIFICATION		PROCEDURE		SPECIFICATION
		OPR LIMITS	TEST DESCRIPTION	SWITCH POS	C	
5			Set the RF test set for standard interrogations.	ATC 1400A: FREQ: 1030 RF LEVEL: -73 dBm  S1403: C MENU: 1 FUNC: 2		Frequency 1030 MHz RF Level -73dBm  SEQ (Mode S)
10			Re-connect BOTTOM antenna cable to 1400A and TOP antenna cable to S1403.			Connect TOP antenna cable to S1403 and BOTTOM antenna cable to ATC 1400A.
15						
20						
25						
30						
35						
40						
45						
50						
55						
60						
65						
70						
75						
80						
85						
90						
95						

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO. IT7517800		REV LTR
					CAGE CODE 55939		
REV LTR	TEST NO.	SPECIFICATION			PROCEDURE		SPECIFICATION
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	MFG LIMITS
11.0				<u>MODE S AND ATCRBS SIDE LOBE SUPPRESSION (SLS)</u>	Test Setup #1	<u>MODE S AND ATCRBS SIDE LOBE SUPPRESSION (SLS)</u>	
5				Interrogate the transponder with ATCRBS Mode A Interrogations	S1403: C MENU: 1 FUNC: 1	ATC (ATCRBS Only) mode.	
11.1	Less than or equal to 10%			Verify the BOTTOM receiver SLS pulse recognition for ATCRBS Mode A Interrogations with P2 = P1	ATC 1400A SLS/ECHO: -0, ON	Adjust the RF level from -73dBm to -23dBm in 10dB steps. At each signal level, the <b>#Reply:ATC</b> on the S1403 display shall be as specified.	Less than or equal to 5%
11.2	Greater than or equal to 90%			Verify the BOTTOM receiver SLS pulse NON-recognition for ATCRBS Mode A Interrogations with P2 = P1 - 9dB	ATC 1400A SLS/ECHO: -9, ON	Adjust the RF level from -73 dBm to -23dBm in 10dB steps. At each signal level, the <b>#Reply:ATC</b> on the S1403 display shall be as specified.	Greater than or equal to 95%
11.3	Less than or equal to 10%			Connect TOP antenna cable to 1400A.		Connect TOP antenna cable to ATC 1400A.	
11.4	Greater than or equal to 90%			Verify the TOP receiver SLS pulse recognition for ATCRBS Mode C Interrogations with P2 = P1	ATC 1400A XPDR MODE: C SLS/ECHO: -0, ON	Adjust the RF level from -73dBm to -23dBm in 10dB steps. At each signal level, the <b>#Reply:ATC</b> on the S1403 display shall be as specified.	Less than or equal to 5%
11.5				Verify the TOP receiver SLS pulse NON-recognition for ATCRBS Mode C Interrogations with P2 = P1 - 9dB	ATC 1400A SLS/ECHO: -9, ON	Adjust the RF level from -73 dBm to -23dBm in 10dB steps. At each signal level, the <b>#Reply:ATC</b> on the S1403 display shall be as specified.	Greater than or equal to 95%

# ENGINEERING SPECIFICATION

## SECURITY NOTATION

SPEC.  
NO.

IT7517800

CAGE  
CODE

55939

REV LTR

REV LTR	TEST NO.	SPECIFICATION			PROCEDURE			SPECIFICATION
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	
5				Re-connect BOTTOM antenna cable to 1400A and TOP antenna cable to S1403.			Connect TOP antenna cable to S1403 and BOTTOM antenna cable to ATC 1400A.	
10				Set the RF test set for Mode S interrogations.	<u>ATC 1400A:</u> RF LEVEL: -67 dBm		RF Level -67 dBm.	
15					<u>S1403:</u> C MENU: 1 FUNC: 2		SEQ (Mode S Only) mode.	
20	11.5	Less than or equal to 10%		Verify no replies are generated for a Mode S interrogation with the P5 (SLS) pulse set to the P6 RF Level + 3dB	<u>ATC 1400A:</u> SLS/ECHO: +3, ON		The *Reply:S on the S1403 display shall be as specified.	Less than or equal to 5%
25	11.6	Greater than or equal to 99%		Verify replies are generated for a Mode S interrogation with the P5 (SLS) pulse set to the P6 RF Level - 12dB	<u>ATC 1400A:</u> SLS/ECHO: -12, ON		The *Reply:S on the S1403 display shall be as specified.	Greater than or equal to 99%
30				Set the RF test set for default interrogations.	<u>ATC 1400A:</u> RF LEVEL: -73 dBm SLS/ECHO: +0, OFF		RF Level -73 dBm.	
35								
40								
45								

# ENGINEERING SPECIFICATION

## SECURITY NOTATION

SPEC.  
NO. IT7517800

CAGE  
CODE 55939

REV LTR

REV LTR	TEST NO.	SPECIFICATION			PROCEDURE			SPECIFICATION
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	
12.0				<u>P4 PULSE LEVEL, ATCRBS/MODE S AND ATCRBS ONLY ALL CALL</u>	Test Setup #1		<u>P4 PULSE LEVEL, ATCRBS/MODE S AND ATCRBS ONLY ALL CALL</u>	
12.1	Greater than or equal to 90%			Interrogate the transponder with ATCRBS Mode A/Mode S All Call Interrogations	S1403: C MENU: 1 FUNC: 4 P4: VAR		ACL (ATCRBS/Mode S All Call) mode. P4 level VARIABLE	Greater than or equal to 99%
12.2	Greater than or equal to 90%			Verify the BOTTOM receiver recognises interrogations as valid ATCRBS Mode A/Mode S All Call Interrogations when P4 = P3 - 1dB	ATC 1400A SLS/ECHO: -1, OFF		Adjust the RF level from -67dBm to -23dBm in 10dB steps. At each signal level, the &Reply:S on the S1403 display shall be as specified.	Greater than or equal to 99%
12.3	Less than or equal to 1%			Verify the BOTTOM receiver recognises as a valid ATCRBS Mode A Interrogations when P4 = P3 - 6dB	ATC 1400A SLS/ECHO: -6, OFF		Adjust the RF level from -67dBm to -23dBm in 10dB steps. At each signal level, the &Reply:ATC on the S1403 display shall be as specified.	Greater than or equal to 99%
				Interrogate the transponder with ATCRBS Mode C-Only All Call Interrogations	S1403: C MENU: 1 FUNC: 3 P4: VAR		ACS (ATCRBS-Only All Call) mode. P4 level VARIABLE	
					ATC 1400A: XPDR MODE: C		ATCRBS Mode C-Only All CALL Interrogations	
				Verify no replies are generated to ATCRBS-Only Mode C All Call interrogations on the BOTTOM receiver when: P4 = P3 - 1dB	ATC 1400A SLS/ECHO: -1, OFF		Adjust the RF level to -67dBm. The &Reply:ATC on the S1403 display shall be as specified.	Less than or equal to 1%

ENGINEERING SPECIFICATION		SECURITY NOTATION		SPEC. NO. IT7517800		REV LTR
				CAGE CODE 55939		
REV LTR	TEST NO.	SPECIFICATION		PROCEDURE		SPECIFICATION
		OPR LIMITS	C TEST DESCRIPTION	SWITCH POS	C WORK STEPS	
5	12.4	Less than or equal to 10%	Connect TOP antenna cable to 1400A.  Verify no replies are generated to ATCRBS-Only Mode A All Call interrogations on the TOP receiver when: $P4 = P3 - 1\text{dB}$	<u>ATC 1400A</u>  XPDR MODE: A	Connect TOP antenna cable to ATC 1400A.  The <b>*Reply:ATC</b> on the S1403 display shall be as specified.	Less than or equal to 1%
10	12.5	Greater than or equal to 90%	Verify the TOP receiver recognises interrogations as valid ATCRBS Mode C/Mode S All Call Interrogations when: $P4 = P3 - 1\text{dB}$	<u>ATC 1400A</u>  XPDR MODE: C  <u>S1403:</u> C MENU: 1 FUNC: 4 P4: VAR	Adjust the RF level from -67dBm to -23dBm in 10dB steps. At each signal level, the <b>*Reply:S</b> on the S1403 display shall be as specified.	Greater than or equal to 99%
15	12.6	Greater than or equal to 90%	Verify the TOP receiver recognises as a valid ATCRBS Mode C Interrogations when $P4 = P3 - 6\text{dB}$	<u>ATC 1400A</u>  SLS/ECHO: -6, OFF	Adjust the RF level from -67 dB to -23dBm in 10dB steps. At each signal level, the <b>*Reply:ATC</b> on the S1403 display shall be as specified.	Greater than or equal to 99%
20			Set the RF test set for standard interrogations.	<u>ATC 1400A:</u>  SLS/ECHO: -0, OFF RF LEVEL: -73 dBm  <u>S1403:</u> P4: CAL C MENU: 1 FUNC: 2	SLS 0dB, OFF  RF Level -73 dBm.  P4 Level CAL  SEQ (Mode S)	
25			Re-connect BOTTOM antenna cable to 1400A and TOP antenna cable to S1403.		Connect TOP antenna cable to S1403 and BOTTOM antenna cable to ATC 1400A.	
30						
35						
40						
45						

**ENGINEERING  
SPECIFICATION**
**SECURITY NOTATION**
**SPEC.  
NO.**
**IT7517800**
**CAGE  
CODE**
**55939**
**REV LTR**

REV LTR	TEST NO.	SPECIFICATION			PROCEDURE			SPECIFICATION
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	
13.0				<u>P4 PULSE POSITION</u>	Test Setup # 1		<u>P4 PULSE POSITION</u>	
5					<u>S1403:</u> CMENU: 1 FUNC (4)		ACL (ATCRBS/Mode S All-Call) mode	
10					<u>ATC 1400A:</u> XPDR MODE: C		ATCRBS Mode C/Mode S All CALL Interrogations	
13.1	Greater than or equal to 90%			Verify the BOTTOM receiver does NOT recognise interrogations as ATCRBS Mode C/Mode S All Call when the P3 to P4 spacing is 1.7 usec. The transponder will reply with ATCRBS replies.	<u>S1403:</u> P4: Dv -0.30		The <u>Reply:ATC</u> on the S1403 display shall be as specified.	Greater than or equal to 99%
15								
20								
25	Greater than or equal to 90%			Verify the BOTTOM receiver DOES recognise interrogations as ATCRBS Mode C/Mode S All Call when the P3 to P4 spacing is 1.95 usec. The transponder will reply with Mode S replies.	<u>S1403:</u> P4: Dv -0.05		The <u>Reply:S</u> on the S1403 display shall be as specified.	Greater than or equal to 99%
30								
35	Greater than or equal to 90%			Verify the BOTTOM receiver DOES recognise interrogations as ATCRBS Mode C/Mode S All Call when the P3 to P4 spacing is 2.05 usec. The transponder will reply with Mode S replies.	<u>S1403:</u> P4: Dv +0.05		The <u>Reply:S</u> on the S1403 display shall be as specified.	Greater than or equal to 99%
40								
45								

**Honeywell**
**SECURITY NOTATION**
**SUPPLEMENTS**
**42**
**PAGE**

**ENGINEERING  
SPECIFICATION**
**SECURITY NOTATION**
**SPEC.  
NO.**
**IT7517800**
**CAGE  
CODE**
**55939**
**REV LTR**

REV LTR	TEST NO.	SPECIFICATION			PROCEDURE			SPECIFICATION
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	
5	13.4	Greater than or equal to 90%		Verify the BOTTOM receiver does NOT recognise interrogations as ATCRBS Mode C/Mode S All Call when the P3 to P4 spacing is 2.3 usec. The transponder will reply with ATCRBS replies.	<u>S1403:</u> P4: Dv +0.30		The <b>*Reply:ATC</b> on the S1403 display shall be as specified.	Greater than or equal to 99%
10				Connect TOP antenna cable to 1400A.			Connect TOP antenna cable to ATC 1400A.	
15	13.5	Greater than or equal to 90%		Verify the TOP receiver does NOT recognise interrogations as ATCRBS Mode A/Mode S All Call when the P3 to P4 spacing is 1.7 usec. The transponder will reply with ATCRBS replies.	<u>S1403:</u> P4: Dv -0.30	<u>ATC 1400A:</u> XPDR MODE: A	The <b>*Reply:ATC</b> on the S1403 display shall be as specified.	Greater than or equal to 99%
20								
25	13.6	Greater than or equal to 90%		Verify the TOP receiver DOES recognise interrogations as ATCRBS Mode A/Mode S All Call when the P3 to P4 spacing is 1.95 usec. The transponder will reply with Mode S replies.	<u>S1403:</u> P4: Dv -0.05		The <b>*Reply:S</b> on the S1403 display shall be as specified.	Greater than or equal to 99%
30								
35								
40								
45								

**Honeywell**
**SECURITY NOTATION**
**43**
**SUPPLEMENTS**
**PAGE**

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO. IT7517800		REV LTR
					CAGE CODE 55939		
REV LTR	TEST NO.	SPECIFICATION			PROCEDURE		SPECIFICATION
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	MFG LIMITS
13	13.7	Greater than or equal to 90%		Verify the TOP receiver DOES recognise interrogations as ATCRBS Mode A/Mode S All Call when the P3 to P4 spacing is 2.05 usec. The transponder will reply with Mode S replies.	S1403: P4: Dv +0.05		The %Reply:S on the S1403 display shall be as specified.
14	13.8	Greater than or equal to 90%		Verify the TOP receiver does NOT recognise interrogations as ATCRBS Mode A/Mode S All Call when the P3 to P4 spacing is 2.3 usec. The transponder will reply with ATCRBS replies.	S1403: P4: Dv +0.30		The %Reply:ATC on the S1403 display shall be as specified.
15				Set the RF test set for standard interrogations.	S1403: P4: Dv CAL  CMENU: 1 FUNC (2)		P4 Deviation: CAL  SEQ (Mode S)
16				Re-connect BOTTOM antenna cable to 1400A ant TOP antenna cable to S1403.			Connect TOP antenna cable to S1403 and BOTTOM antenna cable to ATC 1400A.
17							
18							
19							
20							
21							
22							
23							
24							
25							
26							
27							
28							
29							
30							
31							
32							
33							
34							
35							
36							
37							
38							
39							
40							
41							
42							
43							
44							
45							



**ENGINEERING  
SPECIFICATION**
**SECURITY NOTATION**
**SPEC.  
NO.**
**IT7517800**
**CAGE  
CODE**
**55939**
**REV LTR**

REV LTR	TEST NO.	SPECIFICATION		PROCEDURE		SPECIFICATION
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	
15.0				<u>DIVERSITY OPERATION</u>  Interrogate the unit with a Mode S interrogation on the TOP and BOTTOM antenna.	Test Setup #1	<u>DIVERSITY OPERATION</u>  <u>NOTE:</u> The TOP and BOTTOM antenna cables shall be matched per the requirement in paragraph 3.5.
15.1	Greater than or equal to 90%			Interrogate the transponder with: Mode S Interrogations TOP RF Level: -50dBm BOT RF Level: -47dBm DELAY: TOP 125nsec BEFORE BOT Verify transponder replies on the BOTTOM channel.	S1403: CMENU: 1 FUNC: 2 RF Lvl: +0.0 ANT B: -.15  <u>ATC1400A:</u> RF LEVEL: -47	The <u>*Reply:S</u> display on the S1403 shall be as specified.
15.2	Greater than or equal to 90%			Interrogate the transponder with: ATCRBS Mode A Interrogations. TOP RF Level: -50dBm BOT RF Level: -47dBm DELAY: TOP 125nsec BEFORE BOT Verify transponder replies on the BOTTOM channel.	S1403: CMENU: 1 FUNC: 1	The <u>*Reply:ATC</u> display on the S1403 shall be as specified.

**Honeywell**
**SECURITY NOTATION**
**SUPPLEMENTS**
**46**
**PAGE**

ENGINEERING SPECIFICATION		SECURITY NOTATION		SPEC. NO.	IT7517800	REV LTR
				CAGE CODE	55939	
REV LTR	TEST NO.	SPECIFICATION		PROCEDURE		SPECIFICATION
		OPR LIMITS	C	SWITCH POS	C	MFG LIMITS
5	15.3	Greater than or equal to 90%		S1403: CMENU: 1 FUNC: 2	The <b>Reply:AntB</b> display on the S1403 shall be as specified.	Greater than or equal to 99%
10	15.4	Greater than or equal to 90%		ATC1400A: RF LEVEL: -53		Greater than or equal to 99%
15				S1403: CMENU: 1 ANT B: +.15	The <b>Reply:AntB</b> display on the S1403 shall be as specified.	Greater than or equal to 99%
20						
25	15.5	Greater than or equal to 90%		S1403: CMENU: 1 FUNC: 1	The <b>Reply:AntB</b> display on the S1403 shall be as specified.	Greater than or equal to 99%
30						
35						
40						
45						

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO. IT7517800			
					CAGE CODE 55939		REV LTR	
REV LTR	TEST NO.	SPECIFICATION			PROCEDURE			SPECIFICATION
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	MFG LIMITS
5	15.6	Greater than or equal to 90%		Interrogate the transponder with: Mode S Interrogations TOP RF Level: -50dBm BOT RF Level: -47dBm DELAY: TOP 125nsec AFTER BOT. Verify transponder replies on the BOTTOM channel.	<u>S1403:</u> CMENU: 1 FUNC: 2  <u>ATC1400A:</u> RF LEVEL: -47		The <b>*Reply:S</b> display on the S1403 shall be as specified.	Greater than or equal to 99%
10	15.7	Greater than or equal to 90%		Interrogate the transponder with: Mode S Interrogations TOP RF Level: -50dBm BOT RF Level: MTL+3dB DELAY: TOP 375nsec AFTER BOT Verify transponder replies on the BOTTOM channel.	<u>S1403:</u> CMENU: 1 RF Lvl: +CABLE LOSS ANT B: .35  <u>ATC1400A:</u> RF LEVEL: -73		The <b>*Reply:S</b> display on the S1403 shall be as specified.	Greater than or equal to 99%
15				Connect TOP antenna cable to ATC 1400A and BOTTOM antenna cable to S1403.			Connect TOP antenna cable to ATC 1400A and BOTTOM antenna cable to S1403.	
20	15.8	Greater than or equal to 90%		Interrogate the transponder with: Mode S Interrogations TOP RF Level: MTL+3dB BOT RF Level: -50dBm DELAY: TOP 375nsec BEFORE BOT Verify transponder replies on the TOP channel.			The <b>*Reply:S</b> display on the S1403 shall be as specified.	Greater than or equal to 99%
25								
30								
35								
40								
45								

ENGINEERING SPECIFICATION		SECURITY NOTATION		SPEC. NO.		REV LTR
				CAGE CODE		
REV LTR	TEST NO.	SPECIFICATION		PROCEDURE		SPECIFICATION
		OPR LIMITS	C TEST DESCRIPTION	SWITCH POS	C WORK STEPS	MFG LIMITS
5			Set the RF test set for standard interrogations.	S1403: ANT B: OFF  ATC1400A: RF LEVEL: -73	ANT B OFF	
10			Re-connect BOTTOM antenna cable to 1400A and TOP antenna cable to S1403.		Connect TOP antenna cable to S1403 and BOTTOM antenna cable to ATC 1400A.	
15						
20						
25						
30						
35						
40						
45						
50						
55						
60						
65						
70						
75						
80						
85						
90						
95						

# ENGINEERING SPECIFICATION

## SECURITY NOTATION

SPEC. NO. IT7517800

CAGE CODE 55939

REV LTR

REV LTR	TEST NO.	SPECIFICATION		PROCEDURE		SPECIFICATION		
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	MFG LIMITS
16.0				<u>DATA LINK OPERATION</u>  Set the RF Generator for external modulation.	Test Setup #1  S1403: CMENU: 2 Ext Mod In: ON  ATC1400A: RF LEVEL: -67		<u>DATA LINK OPERATION</u>  Type on PC "XON 1"  Type "<ALT>-X" on PC  Type "COMM 8" on PC	
16.1	FAIL = 0			Set the transponder to reply to Mode S Interrogations  Exit PROCOMM, keeping the transponder on.  Set simulator to generate 8 COMM-C interrogations per second.  Verify valid replies are generated for the COMM-C interrogations.			Wait for a minimum of 400 interrogations to complete and verify the FAIL display on the PC is as specified.	FAIL = 0
16.2	FAIL = 0			Exit COMM-C simulator  Set simulator to generate 8 COMM-D interrogations per second.  Verify valid COMM-D replies are generated for the interrogations.			Wait for a minimum of 400 interrogations to complete and verify the FAIL display on the PC is as specified.	FAIL = 0

Honeywell

SECURITY NOTATION

SUPPLEMENTS

50

PAGE

# ENGINEERING SPECIFICATION

## SECURITY NOTATION

SPEC.  
NO. IT7517800

CAGE  
CODE 55939

REV LTR

REV LTR	TEST NO.	SPECIFICATION		PROCEDURE		SPECIFICATION
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	
5				Exit COMM-D simulator  Enter PROCOMM		Type "<ESC>" on PC  Type "PCPLUS" on PC Type "<RET>" after PROCOMM is running.
10				Set the RF Generator for <u>S1403:</u> internal modulation.	<u>C MENU: 2</u> <u>Ext Mod In:</u> <u>OFF</u>	
15					<u>ATC1400A:</u> <u>RF LEVEL:</u> <u>-73</u>	
20						
25						
30						
35						
40						
45						

Honeywell

SECURITY NOTATION

SUPPLEMENTS

51

PAGE

**ENGINEERING  
SPECIFICATION**
**SECURITY NOTATION**
**SPEC.  
NO.**
**IT7517800**
**M**
**CAGE  
CODE**
**55939**
**REV LTR**

REV LTR	TEST NO.	SPECIFICATION			PROCEDURE			SPECIFICATION MFG LIMITS
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	
	17.0			<u>MUTUAL SUPPRESSION</u>	Test setup #1		<u>MUTUAL SUPPRESSION</u>	
M	17.1	21.0 to 31.0 V (26.0 nominal)	C	Verify mutual suppression line goes active when replying to Mode S interrogations.			Monitor Suppression Pulse #2 with an oscilloscope. The amplitude of the mutual suppression pulse shall be as specified.	21.0 to 31.0 V (26.0 nominal)
	17.2	110 to 135 usec (123 nominal)	C	Verify the duration of the mutual suppression pulse.			The pulse width (50% to 50% voltage point) of the mutual suppression pulse shall be as specified.	110 to 135 usec (123 nominal)
M	17.3	Equal to 0%	C	Externally activate the mutual suppression line with a pulse amplitude of 18.0V. Verify no replies are generated.	ATC 1400A: INTF PULSE: INTRF+, 000.0 SUPP- RESSOR: ON		The %Reply:S on the S1403 display shall be as specified.	Equal to 0%
M			C	Disconnect mutual suppression output.	ATC 1400A: INTF PULSE: OFF, 000.0 SUPP- RESSOR:OFF		Disconnect the ATC 1400A suppression output from Suppression bus #2	
M	17.4	Greater than or equal to 99%	C	Verify the transponder replies to Mode S interrogations.			The %Reply:S on the S1403 display shall be as specified.	Greater than or equal to 99%

**Honeywell**
**SECURITY NOTATION**
**SUPPLEMENTS**
**52**
**PAGE**

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO. IT7517800		REV LTR	
					CAGE CODE 55939			
REV LTR	TEST NO.	SPECIFICATION			PROCEDURE			
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	MFG LIMITS
18.0				<u>DISCRETE INPUTS</u>	Test Setup #1		<u>DISCRETE INPUTS</u>	
5				Set all switches on alternating OPEN(0)/GROUND(1) patterns to the discrete input port for INPUT PORT 0 thru INPUT PORT 4			Set all switches on the MTS Interface panel and MTS Adapter panel to the positions in Table #7-1.	
10				Display discrete input ports			Type on PC "DIN"	
15	18.1	AAAA		Verify the input ports are reading the correct discrete status.			The first 5 words of data on the PC screen shall be as specified. (The 6th word is not used).	AAAA
		AAAA						AAAA
		AAAA						AAAA
		AAAA						AAAA
		EAAA						EAAA
20	18.2	AAAA		Verify the front panel test switch is operational.			Depress the front panel test switch.	AAAA
		AAAA					The first 5 words of data on the PC screen shall be as specified.	AAAA
		AAAA						AAAA
		AAAA						AAAA
		AAAA						AAAA
25								
30				Complement the setting of all switches to the discrete input port for INPUT PORT 0 thru INPUT PORT 4			Set all switches on the test set to the positions in table 2.	
35	18.3	5555		Verify the input ports are reading the correct discrete status.			The first 5 words of data on the PC screen shall be as specified. (The 6th word is not used).	5555
		5555						5555
		5555						5555
		5555						5555
		D555						D555
40								
45				Set the switches back to default settings.			Set all switches on the test set to the position in table 1.	

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO. IT7517800		REV LTR
					CAGE CODE 55939		
REV LTR	TEST NO.	SPECIFICATION			PROCEDURE		SPECIFICATION
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	MFG LIMITS
19.0				<u>DISCRETE OUTPUTS AND LEDS</u>  Set Discrete outputs to the "ON" state.	Test Setup #1	<u>DISCRETE OUTPUTS AND LEDS</u>  Type on PC "DOUT 1111"	
19.1	ON ON ON ON			Verify each of the discrete outputs are on.		The 4 LEDs on the MTS panel shall be as specified. XPDR FAIL 1, 2 ALT FAIL 1, 2	ON ON ON ON
19.2	0111			Verify the over-current monitors for each of the discrete outputs are in the normal mode.		The first 4 digits of the display on the PC screen shall be as specified. (The number after the first 4 digits is not used.)	0111
19.3	OFF OFF OFF OFF			Set Discrete outputs to the "OFF" state.		Type on PC "<ESC>" "DOUT 0000"	OFF OFF OFF OFF
19.4	0111			Verify each of the discrete outputs are off.		The 4 LEDs on the MTS panel shall be as specified. XPDR FAIL 1, 2 ALT FAIL 1, 2	
19.5	PASS			Verify the over-current monitors for each of the discrete outputs are in the normal mode.		The first 4 digits of the display on the PC screen shall be as specified. (The number after the first 4 digits is not used.)	0111
				Verify each of the front panel LED lights work.		The 6 LEDs on the unit front panel shall alternate ON and OFF at approximately a 1 second rate.	PASS
				Set unit to default mode		Type on PC "<ESC>"	

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO. IT7517800		-
					CAGE CODE 55939		REV LTR
REV LTR	TEST NO.	SPECIFICATION		PROCEDURE			SPECIFICATION
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS
20.0				<u>ADDITIONAL INTERFACES</u> (-55xxx to -99xxx ONLY)	Test Setup #1		<u>ADDITIONAL INTERFACES</u> (-55xxx to -99xxx ONLY)
5				Connect a DVM across the FAN outputs.			Connect DVM with (+) input to FAN +28V and (-) input to FAN RETURN(No) on MTS test set.
10				Set Discrete outputs to the "ON" state.			Type on PC "DOUT 11111"
15	20.1	Greater than 22Vdc		Measure the voltage across the FAN outputs with the FAN RETURN(No) output on.			The voltage on the DVM shall be as specified.
20	20.2	Less than 1.5 Vdc		Verify the over-current monitor for the fan is in the ON state.			The last number of the display (in Vdc) on the PC screen shall be as specified. (The first 4 digit number is not used.)
25				Set Discrete outputs to the "OFF" state.			Type on PC "DOUT 00000"
30	20.3	Less than 0.1Vdc		Measure the voltage across the FAN outputs with the FAN RETURN(No) output off.			The voltage on the DVM shall be as specified.
35	20.4	Greater than 3.0 Vdc		Verify the over-current monitor for the fan is in the OFF state.			The last number of the display (in Vdc) on the PC screen shall be as specified. (The first 4 digit number is not used.)
40							
45							

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO. IT7517800		REV LTR		
CAGE CODE 55939									
REV LTR	TEST NO.	SPECIFICATION		PROCEDURE			SPECIFICATION		
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	MFG LIMITS	
5	20.5	Less than 0.1A		Ground the XPDR OFF(NO) discrete output to turn the unit OFF.  Measure the input current to the unit to verify that the unit is off.  Remove ground from the XPDR OFF(NO) discrete output to turn the unit ON.  Set unit to default mode			Set the XPDR OFF(NO) switch to the up position.  The power supply input current to the unit shall be as specified.  Set the XPDR OFF(NO) switch to the down position.  Type on PC " <ESC> " " XON 1 "	Less than 0.1A	
10									
15									
20									
25									
30									
35									
40									
45									
50									
55									
60									

**ENGINEERING  
SPECIFICATION**
**SECURITY NOTATION**
**SPEC.  
NO.**
**IT7517800**
**K**
**CAGE  
CODE**
**55939**
**REV LTF**

REV LTR	TEST NO.	SPECIFICATION			PROCEDURE			SPECIFICATION
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	
21.7	359.0 to 1.0 Degrees	Verify the Course #2 synchro angle is within specification.					The Syn2 CA angle display on the PC screen shall be as specified.	359.0 to 1.0 Degrees
21.8	359.0 to 1.0 Degrees	Verify the Fine #2 synchro angle is within specification.					The Syn2 FA angle display on the PC screen shall be as specified.	359.0 to 1.0 Degrees
10		Change the polarity of the synchro reference input to the default setting.			MTS Panel 26VAC POL - +			
15		Set unit to default mode					Type on PC "<ESC>"	
20								
25								
30								
35								
40								
45								
50								

**Honeywell**
**SECURITY NOTATION**
**58**
**SUPPLEMENTS**
**PAGE**

**ENGINEERING  
SPECIFICATION**
**SECURITY NOTATION**
**SPEC.  
NO.**
**IT7517800**
**L**
**CAGE  
CODE**
**55939**
**REV LTR**

REV LTR	TEST NO.	SPECIFICATION		PROCEDURE		SPECIFICATION
		OPR LIMITS	C TEST DESCRIPTION	SWITCH POS	C WORK STEPS	
L 5	21.0		<u>SYNCHRO ALTITUDE INTERFACES</u>  (Steps 21.1 through 21.8 for -10xxx to -19xxx and -55xxx to -64xxx)	Test Setup #1	<u>SYNCHRO ALTITUDE INTERFACES</u>  (Steps 21.1 through 21.8 for -10xxx to -19xxx and -55xxx to -64xxx)	
L 10	21.1	179.0 to 181.0 Degrees	Monitor the output of the synchro circuit.		Type on PC "MON"	
L 15	21.2	179.0 to 181.0 Degrees	Verify the Course #1 synchro angle is within specification.		The Syn1 CA angle display on the PC screen shall be as specified.	179.0 to 181.0 Degrees
L 20	21.3	179.0 to 181.0 Degrees	Verify the Course #2 synchro angle is within specification.		The Syn1 FA angle display on the PC screen shall be as specified.	179.0 to 181.0 Degrees
L 25	21.4	179.0 to 181.0 Degrees	Verify the Fine #2 synchro angle is within specification.		The Syn2 CA angle display on the PC screen shall be as specified.	179.0 to 181.0 Degrees
L 30			Change the polarity of the synchro reference input.	MTS Panel 26VAC POL = -	The Syn2 FA angle display on the PC screen shall be as specified.	179.0 to 181.0 Degrees
L 35	21.5	359.0 to 1.0 Degrees	Verify the Course #1 synchro angle is within specification.		The Syn1 CA angle display on the PC screen shall be as specified.	359.0 to 1.0 Degrees
L 40	21.6	359.0 to 1.0 Degrees	Verify the Fine #1 synchro angle is within specification.		The Syn1 FA angle display on the PC screen shall be as specified.	359.0 to 1.0 Degrees
L 45						

**Honeywell**
**SECURITY NOTATION**
**57**
**SUPPLEMENTS**
**PAGE**

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO. IT7517800		L	
					CAGE CODE 55939		REV LTR	
REV LTR	TEST NO.	SPECIFICATION			PROCEDURE		SPECIFICATION	
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	MFG LIMITS
5	21.9			(Steps 21.9 through 21.22 for -20xxx and -65xxx)  Connect 4.99Kohm resistor between ARINC 600 BP2 and GROUND			(Steps 21.9 through 21.22 for -20xxx and -65xxx)  On the MTS, connect a 4.99Kohm resistor between ARINC 600 BP2 and GROUND	
10	11.5 VDC to 13.7 VDC			Verify the DC voltage between ARINC 600 BP2 and GROUND			Connect a DC DVM to ARINC 600 BP2 (H) and GROUND (L). The DVM shall read as specified.	11.5 VDC to 13.7 VDC
15				Remove 4.99Kohm resistor between ARINC 600 BP2 and GROUND			On the MTS, remove 4.99 Kohm resistor between ARINC 600 BP2 and GROUND	
20				Connect 4.99 Kohm resistor between ARINC 600 BP5 and GROUND			On the MTS, connect 4.99 Kohm resistor between ARINC 600 BP5 and GROUND	
21.	10	11.5 VDC to 13.7 VDC		Verify the DC voltage between ARINC 600 BP5 and GROUND			Connect a DC DVM to ARINC 600 BP5 (H) and GROUND (L). The DVM shall read as specified.	11.5 VDC to 13.7 VDC
25				Remove 4.99Kohm resistor between ARINC 600 BP5 and GROUND			On the MTS, remove 4.99 Kohm resistor between ARINC 600 BP5 and GROUND	
30				Connect SYNCRO ALT #1 CX, SYNCRO ALT #1 CY, SYNCRO ALT #2 CX, and SYNCRO ALT #2 CY together			On the MTS connect SYNC ALT 1/2 CX and SYNC ALT 1/2 CY	
35				Connect SYNCRO ALT #1 CZ, SYNCRO ALT #2 CZ, and GROUND together			On the MTS connect SYNC ALT 1/2 CZ and GROUND	
40								
45								

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO.		L
					IT7517800		
REV LTR	TEST NO.	SPECIFICATION			PROCEDURE		SPECIFICATION
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	MFG LIMITS
	5			Apply $12.00 \pm 0.05$ VDC between SYNCRO ALT #1 CX and GROUND		On the MTS, apply $12.00 \pm 0.05$ VDC between SYNC ALT 1/2 CX and GROUND	
	10			Monitor the output of the analog altimeter circuit		Type on PC "MON"	
	11	6.500 to 6.650 Volts		Verify the SYNCRO ALT #1 CX voltage is within specification		The SYN1 CX voltage on the PC screen shall be as specified	6.500 to 6.650 Volts
	12	6.500 to 6.650 Volts		Verify the SYNCRO ALT #1 CY voltage is within specification		The SYN1 CY voltage on the PC screen shall be as specified	6.500 to 6.650 Volts
	13	-0.010 to +0.010 Volts		Verify the difference between the SYNCRO ALT #1 CX voltage and the SYNCRO ALT #1 CY voltage is within specification		The difference between the SYN1 CX and the SYN1 CY voltage on the PC screen shall be as specified	-0.010 to +0.010 Volts
	14	6.500 to 6.650 Volts		Verify the SYNCRO ALT #2 CX voltage is within specification		The SYN2 CX voltage on the PC screen shall be as specified	6.500 to 6.650 Volts
	15	6.500 to 6.650 Volts		Verify the SYNCRO ALT #2 CY voltage is within specification		The SYN2 CY voltage on the PC screen shall be as specified	6.500 to 6.650 Volts
	16	-0.010 to +0.010 Volts		Verify the difference between the SYNCRO ALT #2 CX voltage and the SYNCRO ALT #2 CY voltage is within specification		The difference between the SYN2 CX and the SYN2 CY voltage on the PC screen shall be as specified	-0.010 to +0.010 Volts
	40			Apply $6.00 \pm 0.05$ VDC between SYNCRO ALT #1 and GROUND		On the MTS, apply $6.00 \pm 0.05$ VDC between SYNC ALT 1/2 CX and GROUND	
	45						

ENGINEERING SPECIFICATION			SECURITY NOTATION		SPEC. NO. IT7517800		L REV LTR		
CAGE CODE		55939							
REV LTR	TEST NO.	SPECIFICATION			PROCEDURE		SPECIFICATION		
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	C	WORK STEPS	MFG LIMITS	
	21.17	3.250 to 3.350 Volts		Verify the SYNCRO ALT #1 CX voltage is within specification			The SYN1 CX voltage on the PC screen shall be as specified	3.250 to 3.350 Volts	
	21.18	3.250 to 3.350 Volts		Verify the SYNCRO ALT #1 CY voltage is within specification			The SYN1 CY voltage on the PC screen shall be as specified	3.250 to 3.350 Volts	
	21.19	-0.010 to +0.010 Volts		Verify the difference between the SYNCRO ALT #1 CX voltage and the SYNCRO ALT #1 CY voltage is within specification			The difference between the SYN1 CX and the SYN1 CY voltage on the PC screen shall be as specified	-0.010 to +0.010 Volts	
	21.20	3.250 to 3.350 Volts		Verify the SYNCRO ALT #2 CX voltage is within specification			The SYN2 CX voltage on the PC screen shall be as specified	3.250 to 3.350 Volts	
	21.21	3.250 to 3.350 Volts		Verify the SYNCRO ALT #2 CY voltage is within specification			The SYN2 CY voltage on the PC screen shall be as specified	3.250 to 3.350 Volts	
	21.22	-0.010 to +0.010 Volts		Verify the difference between the SYNCRO ALT #2 CX voltage and the SYNCRO ALT #2 CY voltage is within specification			The difference between the SYN2 CX and the SYN2 CY voltage on the PC screen shall be as specified	-0.010 to +0.010 Volts	
	30								
	35								
	40								
	45								

Honeywell

SECURITY NOTATION

61

SUPPLEMENTS

PAGE

**ENGINEERING  
SPECIFICATION**
**SECURITY NOTATION**
**SPEC.  
NO.**
**IT7517800**
**L**
**CAGE  
CODE**
**55939**
**REV LTR**

REV LTR	TEST NO.	SPECIFICATION		PROCEDURE		SPECIFICATION
		OPR LIMITS	C	TEST DESCRIPTION	SWITCH POS	
L	22.0			<u>ARINC 429 BUS INTERFACES</u>	Test Setup #1	<u>ARINC 429 BUS INTERFACES</u>
S				Set the unit to generate internal ARINC 429 loop-back tests.	Type on the PC: "AS"	
L	22.1	00000000 00000000 00000000 00000000 0000 0000		Verify that no internal ARINC 429 errors occur.		The 6 words on the PC display shall be as specified.
10				Connect ARINC 429 Test signal (transmitter) output to ARINC 429 Receiver Inputs.		Connect the ARINC 429 Test signal (transmitter) output to the requirements in table 5.
15				Apply ARINC 429 signal to COM A/B In From ADLP bus (P1A-2A/2B).		Type on the PC: "<ESC>" "AR 0 H"
20				Verify the data words were received without errors.		The two data words on the PC display shall be as specified.
L	22.2	2AAAAAAA 0000		Apply ARINC 429 signal to COM C/D In From ADLP bus (P1A-2C/2D).		Type on the PC: "<ESC>" "AR 1 H"
25				Verify the data words were received without errors.		The two data words on the PC display shall be as specified.
30				Apply ARINC 429 signal to TX Coordination Bus (P1A-5E/5F).		Type on the PC: "<ESC>" "AR 2 H"
L	22.3	2AAAAAAA 0000		Verify the data words were received without errors.		The two data words on the PC display shall be as specified.
35				Apply ARINC 429 signal to Flight ID Input Bus (P1A-6A/6B).		Type on the PC: "<ESC>" "AR 3 H"
40						
L	22.4	2AAAAAAA 0000				
45						

**Honeywell**
**SECURITY NOTATION**
**62**
**SUPPLEMENTS**
**PAGE**