

TEST RESULT SUMMARY

FCC PART 15 SUBPART C

Section 15.225

FCC PART 15 SUBPART C

Section 15.207 Conducted Emission Requirements


MANUFACTURER'S NAME	DataCard
NAME OF EQUIPMENT	SP35
TYPE OF EQUIPMENT	13.56 MHz RF ID
MODEL NUMBER	SP35CIATUSBSC4/6
MANUFACTURER'S ADDRESS	11111 Bren Road West Minnetonka MN 55343
TEST REPORT NUMBER	NC205390
TEST DATE	11 & 22 October 2002

According to testing performed at TÜV Product Service Inc, the above-mentioned unit is in compliance with the electromagnetic compatibility requirements defined in FCC Part 15 Subpart C, Sections 15.207 and 15.225.

It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical characteristics. Any modifications necessary for compliance made during testing on the above mentioned date(s) must be implemented in all production units for compliance to be maintained.

TÜV Product Service Inc, as an independent testing laboratory, declares that the equipment tested as specified above conforms to the requirements of FCC Part 15 Subpart C, Sections 15.207 and 15.225.

Date: 02 December 2002



Location: Taylors Falls MN
USA

T. K. Swanson
Tested By

J. T. Schneider
Reviewed By

EMC EMISSION - TEST REPORT

Test Report File No. : **NC205390** Date of issue: 02 December 2002

Model - Serial No. : **SP35CIATUSBSC4/6 - D000044**

Product Name : **SP35**

Product Type : **13.56 MHz RF ID**

Applicant : **DataCard**

Manufacturer : **DataCard**

License holder : **DataCard**

Address : **11111 Bren Road West**

: **Minnetonka MN 55343**

Test Result : **Positive Negative**

Test Project Number
Reference(s) : **NC205390**

Total pages including
Appendices : **30**

TÜV Product Service Inc is a subcontractor to TÜV Product Service, GmbH according to the principles outlined in ISO/IEC Guide 25 and EN 45001.

TÜV Product Service Inc reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. TÜV Product Service Inc shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV Product Service Inc issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval. This report shall not be used by the client to claim product endorsement by NVLAP or any agency of the US government.

TÜV Product Service Inc and its professional staff hold government and professional organization certifications and are members of AAMI, ACIL, AEA, ANSI, IEEE, NVLAP, and VCCI

D I R E C T O R Y - E M I S S I O N S

	Page(s)
A) Documentation	
Test report	1 - 10
Directory	2
Test Regulations	3
Deviation from standard / Summary	10
Test-setups (Photos)	11 - 12
Test-setup (drawing)	Appendix A
B) Test data	
FCC 15.207 - Conducted emissions	10/150 kHz - 30 MHz
FCC 15.225 - Radiated emissions	5, 9
FCC 15.225 - Radiated emissions	10 kHz - 30 MHz
Interference power	30 MHz - 1000 MHz
Equivalent Radiated emissions	6, 9
Interference power	30 MHz - 300 MHz
Equivalent Radiated emissions	N/A
FCC 15.225 (c) - Frequency Tolerance of the Carrier Signal	N/A
Interference power	7, 9
C) Appendix A	
Test Data Sheets and Test Setup Drawing(s)	A2 - A9
D) Appendix B	
Constructional Data Form	B2 - B7
Product Information Form(s)	N/A
E) Appendix C	
Measurement Protocol	C1 - C2

EMISSIONS TEST REGULATIONS :

The emissions tests were performed according to following regulations:

- EN 50081-1 / 1991

- EN 55011 / 1991

- Group 1

- Group 2

- Class A

- Class B

- EN 55013 / 1990

- EN 55014 / 1987

- Household appliances and similar

- Portable tools

- Semiconductor devices

- EN 55014 / A2:1990

- EN 55014 / 1993

- Household appliances and similar

- Portable tools

- Semiconductor devices

- EN 55015 / 1987

- EN 55015 / A1:1990

- EN 55015 / 1993

- EN 55022 / 1987

- EN 55022 / 1994

- Class A

- Class B

- Class A

- Class B

- BS

- VCCI

- FCC Part 15 Subpart C Section 15.225

- FCC Part 15 Subpart C Section 15.207 Conducted Emission Requirements

- FCC Part 15 Subpart B

- Class A

- Class B

- CISPR 11 (1990)

- CISPR 22 (1993)

- Class A

- Class B

- Group 1

- Class B

- Class A

- Class B

- Class A

- Group 2

- Class B

- Class B

Environmental conditions in the lab:

	<u>Actual</u>
Temperature	: 15 - 23 °C
Relative Humidity	: 45 - 55 %
Atmospheric pressure	: 99.4 – 100.4 kPa
Power supply system	: 50/60 Hz – 230/115 VAC – 1 Phase

Sign Explanations:

- not applicable
- applicable



Emissions Test Conditions: CONDUCTED EMISSIONS [FCC 15.207]

The **CONDUCTED EMISSIONS (INTERFERENCE VOLTAGE)** measurements were performed at the following test location:

- Test not applicable

- Wild River Lab Large Test Site (Open Area Test Site)
- Wild River Lab Small Test Site (Open Area Test Site)
- Oakwood Lab (Open Area Test Site)
- Wild River Lab Screen Room
- New Brighton Lab Shielded Room

Test equipment used:

TUV ID	Model Number	Manufacturer	Description	Serial Number	Cal Due
■ - 2417	3825/2	Electro-Mechanics (EMCO)	50 Ω LISN	8812-1439	1-23-03
■ - 2420	ESHS-10	Rhode & Schwarz	EMI Receiver	828178/006	4-26-03

All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST) and is calibrated annually.

Emissions Test Conditions: RADIATED EMISSIONS [FCC 15.225 (a),(b) 10 kHz - 30 MHz]

The **RADIATED EMISSIONS (MAGNETIC FIELD)** measurements were performed at the following test location:

- Test not applicable

- Wild River Lab Large Test Site (Open Area Test Site)
- Wild River Lab Small Test Site (Open Area Test Site)
- Oakwood Lab (Open Area Test Site)

at a test distance of :

- 0.3 meters
- 1 meter
- 3 meter
- 10 meters
- 30 meters

Test equipment used :

TUV ID	Model Number	Manufacturer	Description	Serial Number	Cal Due
■ - 2420	ESHS-10	Rhode & Schwarz	EMI Receiver	828178/006	4-26-03
■ - 2517	HFH2-Z2	Polarad	Loop Antenna	879285/036	2-11-03

All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST) and is calibrated annually.

Emissions Test Conditions: RADIATED EMISSIONS [FCC 15.225 (b) Electric Field 30 - 1000 MHz]

The **RADIATED EMISSIONS (ELECTRIC FIELD)** measurements, in the frequency range of 30 MHz-1000 MHz, were tested in a horizontal and vertical polarization at the following test location:

- Test not applicable

- - Wild River Lab Large Test Site (Open Area Test Site) – NSA measurements made 7-02, due 7-03.
- Wild River Lab Small Test Site (Open Area Test Site)
- Oakwood Lab (Open Area Test Site)

at a test distance of :

- 3 meters
- - 10 meters
- 30 meters

Test equipment used :

TUV ID	Model Number	Manufacturer	Description	Serial Number	Cal Due
■ - 2665	ZHL-1042J	Mini-Circuits	Preamplifier	32296	10-15-03
■ - 3202	EM-6917B	Electro-Metrics	Biconicalog Periodic	102	10-04-03
■ - 2690	8566B	Hewlett-Packard	Spectrum Analyzer (Unit F)	2430A00930	11-19-02
■ - 2678	85662A	Hewlett-Packard	Analyzer Display (Unit F)	2403A08134	11-19-02
■ - 2684	85650A	Hewlett-Packard	Quasi-Peak Adapter (Unit F)	2521A01006	11-19-02

All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST) and is calibrated annually.

Emissions Test Conditions: INTERFERENCE POWER

The **INTERFERENCE POWER** measurements were performed by using the absorbing clamp on the mains and interface cables in the frequency range 30 MHz - 300 MHz at the following test location:

- Test not applicable

- Wild River Lab Large Test Site (Open Area Test Site)
- Wild River Lab Small Test Site (Open Area Test Site)
- Oakwood Lab (Open Area Test Site)
- Wild River Lab Screen Room
- New Brighton Lab Shielded Room

Emissions Test Conditions: RADIATED EMISSIONS Electric Field 1 to 100 GHz

The **EQUIVALENT RADIATED EMISSIONS** measurements in the frequency range 1 GHz - 100 GHz were performed in a horizontal and vertical polarization at the following test location:

- Test not applicable

- Wild River Lab Large Test Site (Open Area Test Site)
- Wild River Lab Small Test Site (Open Area Test Site)
- Oakwood Lab (Open Area Test Site)
- Wild River Lab Screen Room

at a test distance of:

- 1 meters
- 3 meters
- 10 meters

Emissions Test Conditions: FREQUENCY TOLERANCE OF THE CARRIER SIGNAL [FCC 15.225 (c)]

The **FREQUENCY TOLERANCE** measurements were performed at the following test location:

- Test not applicable

- Wild River Lab Large Test Site (Open Area Test Site)
- Wild River Lab Small Test Site (Open Area Test Site)
- Oakwood Lab (Open Area Test Site)
- Wild River Lab Screen Room
- DataCard

Test equipment used :

Model Number	Manufacturer	Description	Serial Number	Cal Due
■ - 8591E	Hewlett-Packard	Spectrum Analyzer	3501A03603	10-25-03
■- 901	Emco	Near Field Probe	7405-901	N/A
■- 1570	Ransco	Temperature Chamber		N/A
■- 2625A	Fluke	HydraData Logger	6256607	6-15-03

All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST) and is calibrated annually.

Equipment Under Test (EUT) Test Operation Mode - Emission tests :

The device under test was operated under the following conditions during emissions testing:

- Standby
 - Test program (H - Pattern)
 - Test program (color bar)
 - Test program (customer specific)
 - Practice operation
 - Normal Operating Mode
 - 1. FCC/ RTTE testing was done using a diagnostic program that ensure constant RF communications under the worst case circumstances, Highest power level, highest data duty cycle, high data transmission rate.
 2. SP35 testing all options except contacted smartcard option, this includes SP35 printing full color images, encoding data on the magnetic stripe and reading a contactless smartcard
 3. SP35 testing contacted smartcard option. The printer repeatedly issued smartcard transaction using the contacted smartcard option.
-

Configuration of the device under test:

- See Constructional Data Form in Appendix B - Page B2
- See Product Information Form in Appendix B - beginning on Page B3

The following peripheral devices and interface cables were connected during the measurement:

- _____
- _____
- _____
- _____
- _____
- _____
- _____
- _____
- _____

- Type : _____
- Type : _____
- Type : _____
- Type : _____
- Type : _____
- Type : _____
- Type : _____
- Type : _____

- unshielded power cable

- unshielded cables

- shielded cables

MPS.No.: _____

- customer specific cables

- _____
- _____

Emission Test Results:

FCC 15.207 - Conducted emissions 450 kHz - 30 MHz

The requirements are

- MET

- NOT MET

Minimum margin of compliance

4 dB

at 19.52 MHz

Maximum margin of non-compliance

_____ dB

at _____ MHz

Remarks: _____

FCC 15.225 (a)(b) - Radiated emissions (magnetic field) 10 kHz - 30 MHz

The requirements are

- MET

- NOT MET

Minimum limit margin for fundamental

43 dB

at 13.56 MHz

Minimum limit margin for spurious/harmonics

>10 dB

at _____ kHz

Remarks: The fundamental was measured to be 37 dB_uV/m (70.8 microvolts/meter) in Quasi-Peak mode at 30 meters. The limit is 80 dB_uV/m (10000 microvolts/meter) at 30 meters. No spurious emissions or other harmonics were detected within 10 dB of the 30 uV/m limit. For band edge compliance the carrier meets the spurious limits at 13.56065 MHz and 13.56180 MHz, at all other frequencies the carrier level is >10 dB below the spurious limit.

FCC 15.225 (b) - Radiated emissions (electric field) 30 MHz - 1000 MHz

The requirements are

- MET

- NOT MET

Minimum margin of compliance

>10 dB

at _____ MHz

Minimum limit margin for spurious

_____ dB

at _____ MHz

Remarks: No emissions detected within 10 dB of the limit. Testing done up to 1000 MHz due to oscillator frequency of card printer (non-RF device) RF ID is contained in. This report only addresses emissions from RF ID.

Interference Power at the mains and interface cables 30 MHz - 300 MHz

The requirements are

- MET

- NOT MET

- N/A

Remarks: _____

Equivalent Radiated emissions 1 GHz - 100 GHz

The requirements are

- MET

- NOT MET

- N/A

Remarks: _____

FCC 15.225 (c) - Frequency Tolerance of the Carrier Signal

The requirements are

- MET

- NOT MET

Remarks: Limit is $\pm 0.01\%$ of 13.56 MHz, or ± 1.356 kHz, so allowed band is 13.558644 MHz to 13.561356 MHz.

Frequency deviates from 13.56115 MHz to 13.56125 MHz from -20 to 50 degrees C and 102 to 138 VAC.

DEVIATIONS FROM STANDARD:

None.

GENERAL REMARKS:

The radiated measurements from 10 kHz to 30 MHz are made in quasi-peak detection, except for the levels noted between 110-490 kHz, which are made in average detection.

SUMMARY:

The requirements according to the technical regulations are

- met
- **not** met.

The device under test does

- fulfill the general approval requirements mentioned on page 3.
- **not** fulfill the general approval requirements mentioned on page 3.


Testing Start Date: 11 October 2002

Testing End Date: 22 October 2002

- TÜV PRODUCT SERVICE INC -



J. T. Schneider
Reviewed By



Tested By:
T. K. Swanson

Test-setup photo(s):
Conducted emission 450 kHz - 30 MHz

See Test Setup Exhibit



File No. NC205390, Page 11 of 12

Test-setup photo(s):
Radiated emission 10 kHz - 1000 MHz

See Test Setup Exhibit



Appendix A

Test Data Sheets

and

Test Setup Drawing(s)



TEST SETUP FOR EMISSIONS TESTING

WILD RIVER LAB
Screen Room

See Test Setup Exhibit



File No. NC205390, Page A2 of A9

TEST SETUP FOR EMISSIONS TESTING

WILD RIVER LAB
Large Test Site

See Test Setup Exhibit



File No. NC205390, Page A3 of A9

FCC Part 15.225 Radiated Emissions							
Customer Name: DataCard							
EUT: SP35							
Test Report # NC205390							
Test Date: 11 October 2002							
	dBuV/m	dBuV/m	dBuV/m	dBuV/m	dBuV/m	dBuV/m	margin
MHz	0.3 m	1 m	3 m	10 m	30 m	30 m Limit	dB
0.009						80	
0.49						80	
0.49						80	
1.705						80	
1.705						80	
13.56	107	90	70	51	37	80	43
30						80	
Quasi-Peak							
All Levels are measured - No extrapolations							
No further harmonics or spurious emission detected 10 kHz to 30 MHz							

FCC frequency stability

Limit is $\pm .01\%$ of 13.56 MHz, or ± 1.356 kHz, so allowed band is 13.558644 MHz to 13.561356 MHz.

-20 degrees C	13.56118 MHz
-10 degrees C	13.56123 MHz
0 degrees C	13.56125 MHz
10 degrees C	13.56125 MHz
20 degrees C	13.56123 MHz
30 degrees C	13.56120 MHz
40 degrees C	13.56118 MHz
50 degrees C	13.56115 MHz
102 VAC	13.56118 MHz
138 VAC	13.56118 MHz

Conducted Electromagnetic Emissions

Test Report #:	5390 Run 02	Test Area:	SCREEN ROOM
Test Method:	FCC	Test Date:	17-Dec-2002
EUT Model #:	SP35	EUT Power:	
EUT Serial #:	44	Temperature:	23 °C
Manufacturer:	DataCard	Relative Humidity:	45 %
EUT Description:	Table Top Printer with Mag Stripe & Smart Card		Air Pressure: 100.4 kPa
Notes:	Page: 1 of 3		

FREQ (MHz)	LEVEL (dBuV)	CABLE / LISN / ATTEN (dB)	FINAL (dBuV)	TEST POINT	DELTA1 FCC B	DELTA2 N/A
60 Hz 110 VAC						
19.52	56.2 Qp	0.3 / 0.2 / 0.0	56.7	Neutral	N/A	N/A
19.52	47.7 Av	0.3 / 0.2 / 0.0	48.2	Neutral	N/A	N/A
When QP reading is 6 dB higher than average reading the FCC allows a 13 dB relaxation for the QP reading and then compares to the limit						
19.52	43.2 Qp	0.3 / 0.2 / 0.0	43.7	Neutral	-4.3	N/A
16.53	54.5 Qp	0.3 / 0.3 / 0.0	55.1	Neutral	N/A	N/A
16.53	42.4 Av	0.3 / 0.3 / 0.0	43.0	Neutral	N/A	N/A
16.53 MHz relaxed by 13 dB						
16.53	41.5 Qp	0.3 / 0.3 / 0.0	42.1	Neutral	-5.9	N/A
0.535	42.3 Qp	0.1 / 0.1 / 0.0	42.4	Neutral	-5.6	N/A
0.485	39.1 Qp	0.0 / 0.1 / 0.0	39.2	Neutral	-8.8	N/A
0.485	37.3 Qp	0.0 / 0.1 / 0.0	37.4	Line 1	-10.6	N/A
0.535	42.7 Qp	0.1 / 0.1 / 0.0	42.8	Line 1	-5.2	N/A
16.53	43.0 Qp	0.3 / 0.3 / 0.0	43.6	Line 1	N/A	N/A
16.53	31.9 Av	0.3 / 0.3 / 0.0	32.5	Line 1	N/A	N/A
16.53 MHz relaxed by 13 dB						
16.53	30.0 Qp	0.3 / 0.3 / 0.0	30.6	Line 1	-17.4	N/A

Tested by: JCS



Printed

Signature

Reviewed by: TKS



Printed

Signature

Conducted Electromagnetic Emissions

Test Report #:	5390 Run 02	Test Area:	SCREEN ROOM
Test Method:	FCC	Test Date:	17-Dec-2002
EUT Model #:	SP35	EUT Power:	
EUT Serial #:	44	Temperature:	23 °C
Manufacturer:	DataCard	Relative Humidity:	45 %
EUT Description:	Table Top Printer with Mag Stripe & Smart Card	Air Pressure:	100.4 kPa
Notes:	Page: 2 of 3		

FREQ (MHz)	LEVEL (dBuV)	CABLE / LISN / ATTEN (dB)	FINAL (dBuV)	TEST POINT	DELTA1 FCC B	DELTA2 N/A
19.52	56.2 Qp	0.3 / 0.2 / 0.0	56.7	Line 1	N/A	N/A
19.52	45.6 Av	0.3 / 0.2 / 0.0	46.1	Line 1	N/A	N/A
19.52 MHz relaxed by 13 dB						
19.52	43.2 Qp	0.3 / 0.2 / 0.0	43.7	Line 1	-4.3	N/A

Tested by: JCS



Printed

Signature

Reviewed by: TKS



Printed

Signature

Conducted Electromagnetic Emissions

Test Report #:	5390 Run 02	Test Area:	SCREEN ROOM
Test Method:	FCC	Test Date:	17-Dec-2002
EUT Model #:	SP35	EUT Power:	
EUT Serial #:	44	Temperature:	23 °C
Manufacturer:	DataCard	Relative Humidity:	45 %
EUT Description:	Table Top Printer with Mag Stripe & Smart Card	Air Pressure:	100.4 kPa
Notes:	Page: 3 of 3		

FREQ (MHz)	LEVEL (dBuV)	CABLE / LISN / ATTEN (dB)	FINAL (dBuV)	TEST POINT	DELTA1 FCC B	DELTA2 N/A
---------------	-----------------	------------------------------	-----------------	------------	-----------------	---------------

***** MEASUREMENT SUMMARY *****						
19.52	43.2 Qp	0.3 / 0.2 / 0.0	43.7	Line 1	-4.3	N/A
0.535	42.7 Qp	0.1 / 0.1 / 0.0	42.8	Line 1	-5.2	N/A
16.53	41.5 Qp	0.3 / 0.3 / 0.0	42.1	Line 1	-5.9	N/A
0.485	39.1 Qp	0.0 / 0.1 / 0.0	39.2	Neutral	-8.8	N/A

Tested by: JCS



Printed

Signature

Reviewed by: TKS



Printed

Signature

Radiated Electromagnetic Emissions

Test Report #:	5390 Run 02a	Test Area:	LTS 10m
Test Method:	EN55022	Test Date:	22-Oct-2002
EUT Model #:	SP35	EUT Power:	60 Hz / 110 VAC
EUT Serial #:	44	Temperature:	15 °C
Manufacturer:	DataCard	Relative Humidity:	55 %
EUT Description:	Table top printer	Air Pressure:	100.4 kPa
Notes:	with mag stripe. smart card installed.		
Page: 1 of 1			

FREQ (MHz)	LEVEL (dBuV)	CABLE / ANT / PREAMP (dB) (dB/m) (dB)	FINAL (dBuV/m)	POL / HGT / AZ (m) (DEG)	DELTA1 FCC B	DELTA2 N/A
<hr/>						
<hr/>						
No significant EUT emissions detected from transmitter 30 MHz to 1000 MHz, vert and hor ant.						

Tested by: J. C. Sausen



Printed

Signature

Reviewed by: TKS



Printed

Signature

Appendix B

Constructional Data Form

and/or

Product Information Form(s)



Form**EMC Test Plan and Constructional Data Form**

PLEASE COMPLETE THIS DOCUMENT IN FULL, ENTERING N/A IF THE FIELD IS NOT APPLICABLE.

Applicant -- NOTE: *This information will be input into your test report as shown below.*
Press the F1 key at any time to get HELP for the current field selected.

Company: Datacard Group

Address: 11111 Bren Road West
Minnetonka, MN 55343

Contact: Bill Myntti Position: Electrical Engineer

Phone: 952 988 2937 Fax: 2658

E-mail Address: bill_myntti@datacard.com

General Equipment Description -- NOTE: This information will be input into your test report as shown below.

EUT Description 13.56 MHz RF ID

EUT Name SP35

Model No.: SP35CIATUSBSC4/6 Serial No.: D000044

Product Options: Magstripe, Smartcard, Supplies RFID, Graphics

Configurations to be tested: Printing full color card, encoding magentic stripe, operating Gemplus 680 contatless copler.

Test Objective

- | | | | | | |
|-------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|---------------------------------------|----------------------------|------|------|
| <input checked="" type="checkbox"/> EMC Directive 89/336/EEC (EMC) | <input checked="" type="checkbox"/> FCC: Class | <input checked="" type="checkbox"/> A | <input type="checkbox"/> B | Part | b, c |
| Std: EN55022:1998 | <input type="checkbox"/> VCCI: Class | <input type="checkbox"/> A | <input type="checkbox"/> B | | |
| <input type="checkbox"/> Machinery Directive 89/392/EEC (EMC) | <input checked="" type="checkbox"/> BCIQ: Class | <input type="checkbox"/> A | <input type="checkbox"/> B | | |
| Std: | <input checked="" type="checkbox"/> Canada: Class | <input type="checkbox"/> A | <input type="checkbox"/> B | | |
| <input type="checkbox"/> Medical Device Directive 93/42/EEC (EMC) | <input checked="" type="checkbox"/> Australia: Class | <input type="checkbox"/> A | <input type="checkbox"/> B | | |
| Std: | <input checked="" type="checkbox"/> Other: RTTE Directive, EN 300 330 and
EN301 489-3: 2000 | | | | |
| <input type="checkbox"/> Vehicle Directive 72/245/EEC (EMC) | | | | | |
| Std: | | | | | |
| <input type="checkbox"/> FDA Reviewers Guidance for Premarket
Notification Submissions (EMC) | | | | | |

Form



EMC Test Plan and Constructional Data Form

TÜV Product Service Certification Requested

- Attestation of Conformity (AoC) International EMC Mark (IEM)
 Certificate of Conformity (CoC) Compliance Document
Protection Class (N/A for vehicles) Class I Class II Class III

(Press F1 when field is selected to show additional information on Protection Class.)

Attendance

Test will be: Attended by the customer Unattended by the customer

Failure - Complete this section if testing will not be attended by the customer.

If a failure occurs, TÜV Product Service should:

- Call contact listed above, if not available then stop testing. (After hrs phone): _____
 Continue testing to complete test series.
 Continue testing to define corrective action.
 Stop testing.

EUT Specifications and Requirements

Length: 16" Width: 8" Height: 10" Weight: 8 lbs.

Power Requirements

Regulations require testing to be performed at typical power ratings in the countries of intended use. (i.e., European power is typically 230 VAC 50 Hz or 400 VAC 50 Hz, single and three phase, respectively)

Voltage: 100-230 (If battery powered, make sure battery life is sufficient to complete testing.)

of Phases: 1

Current (Amps/phase(max)): 2A Current (Amps/phase(nominal)): 1A

Other _____

Other Special Requirements

Typical Installation and/or Operating Environment

(ie. Hospital, Small Business, Industrial/Factory, etc.)
Office Environment

EUT Power Cable

- Permanent OR Removable Length (in meters): 3
 Shielded OR Unshielded
 Not Applicable

EMC Test Plan and Constructional Data Form

EUT Interface Ports and Cables												
Interface			Shielding									
Type	Analog	Digital	Qty	Yes	No	Type	Termination	Connector Type	Port Termination	Length (in meters)	Removable Permanent	
EXAMPLE:												
RS232	<input type="checkbox"/>	<input checked="" type="checkbox"/>	2	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Foil over braid	Coaxial	Metallized 9-pin D-Sub	Characteristic Impedance	6	<input checked="" type="checkbox"/>	<input type="checkbox"/>
USB	<input type="checkbox"/>	<input checked="" type="checkbox"/>	2	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Foil;	None	USB A-B	USB spec 1.1	2	<input checked="" type="checkbox"/>	<input type="checkbox"/>
RS232	<input type="checkbox"/>	<input checked="" type="checkbox"/>	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Foil	None	Dsub9	None	2	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>						<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>						<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>						<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>						<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>						<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>						<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>						<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>						<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>						<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>						<input type="checkbox"/>	<input type="checkbox"/>

EMC Test Plan and Constructional Data Form**EUT Software.**

Revision Level: 4.17.1

Description: Pre production firmware, fully capable of running all sub systems.

EUT Operating Modes to be Tested -- list the operating modes to be used during test. It is recommended the equipment be tested while operating in a typical operation mode. FCC testing of personal computers and/or peripherals requires that a simple program generate a complete line of upper case H's. Provide a general description of all software, firmware, and PLD algorithms used in the equipment. List all code modules as described above, with the revision level used during testing. Consult with your TÜV Product Service Representative if additional assistance is required.

1. FCC/ RTTE testing was done using a diagnostic program that ensure constant RF communications under the worst case circumstances, Highest power level, highest data duty cycle, high data transmission rate.
2. SP35 testing all options except contacted smartcard option, this includes SP35 printing full color images, encoding data on the magnetic stripe and reading a contactless smartcard
3. SP35 testing contacted smartcard option. The printer repeatedly issued smartcard transaction using the contacted smartcard option.

EUT System Components -- List and describe all components which are part of the EUT. For FCC testing a minimum configuration is required. (ie. Mouse, Printer, Monitor, External Disk Drive, Motherboard, etc.)

Description	Model #	Serial #	FCC ID #

EMC Test Plan and Constructional Data Form

Support Equipment -- List and describe all support equipment which is not part of the EUT. (i.e. peripherals, simulators, etc)			
<i>Description</i>	<i>Model #</i>	<i>Serial #</i>	<i>FCC ID #</i>
Computer Gateway2000	Solo2300	BC497510552	
Power Supply Gateway2000	ADP-50FB	AC298046351	

Oscillator Frequencies			
<i>Frequency</i>	<i>Derived Frequency</i>	<i>Component # / Location</i>	<i>Description of Use</i>
4MHz	Fund.	Y4	Oscillator for system clock generation
13.56MHz	Fund.	Y3	RFID communication clock
12MHz	48MHz	U10	TPH logic control
48MHz	4MHz	U6, U7, U10	system clock

Power Supply			
<i>Manufacturer</i>	<i>Model #</i>	<i>Serial #</i>	<i>Type</i>
Analog Vision	PEC0240	02000125	<input checked="" type="checkbox"/> Switched-mode: (Frequency) _____ <input type="checkbox"/> Linear <input type="checkbox"/> Other: _____
			<input type="checkbox"/> Switched-mode: (Frequency) _____ <input type="checkbox"/> Linear <input type="checkbox"/> Other: _____

Power Line Filters		
<i>Manufacturer</i>	<i>Model #</i>	<i>Location in EUT</i>

EMC Test Plan and Constructional Data Form

Critical EMI Components (Capacitors, ferrites, etc.)

Description	Manufacturer	Part # or Value	Qty	Component # / Location
Ferrite bead	Steward	28A2025-0A0	1	TPH data cable
Ferrite bead	Ferrite	0431164951	1	RFID cable
Inductor	Steward	60ohm	1	Smartcard ground
Capacitor, 330uF, 35V	Panasonic		2	TPH power

EMC Critical Detail -- Describe other EMC Design details used to reduce high frequency noise.

(PLEASE INSERT "ELECTRONIC SIGNATURE" BELOW IF POSSIBLE)

Authorization Signatures

Customer authorization to perform tests
according to this test plan.

Date

Bill Myntti

Test Plan/CDF Prepared By (please print)

Date

Appendix C

MEASUREMENT PROTOCOL FOR FCC

GENERAL INFORMATION

Measurement Uncertainty

The test system for conducted emissions is defined as the LISN, tuned receiver or spectrum analyzer, and coaxial cable. The test system for radiated emissions is defined as the antenna, the pre-amplifier, the spectrum analyzer and the coaxial cable. These test systems have a measurement uncertainty of ± 4.5 dB. The equipment comprising the test systems are calibrated on an annual basis.

Justification

The Equipment Under Test (EUT) is configured in a typical user arrangement in accordance with the manufacturer's instructions. A cable is connected to each available port and either terminated with a peripheral into its characteristic impedance or left unterminated. When appropriate, the cables are manually manipulated with respect to each other to obtain maximum emissions from the unit.

CONDUCTED EMISSIONS

The final level, expressed in dB μ V, is arrived at by taking the reading directly from the EMI receiver. This level is compared directly to the FCC limit.

To convert between dB μ V and μ V, the following conversions apply:

$$\text{dB}\mu\text{V} = 20(\log \mu\text{V})$$

$$\mu\text{V} = \text{Inverse log}(\text{dB}\mu\text{V}/20)$$

RADIATED EMISSIONS

The final level, expressed in dB μ V/m, is arrived at by taking the reading from the spectrum analyzer (Level dB μ V), adding the antenna correction factor and cable loss factor (Factor dB) to it, then subtracting the preamp gain. This result then has the FCC limit subtracted from it to provide the Delta which gives the tabular data as shown in the data sheets in Attachment A.

Example:

FREQ (MHz)	LEVEL (dB μ V)	CABLE/ANT/PREAMP (dB)	FINAL (dB μ V/m)	POL/HGT/AZ (m)	DELTA1 FCC B
60.80	42.5Qp	+ 1.2 + 10.9 - 25.5 =	29.1	V 1.0 0.0 -	-10.9

DETAILS OF TEST PROCEDURES

General Standard Information

The test methods used comply with ANSI C63.4-1992 - "Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz."

Conducted Emissions

Conducted emissions on the 60 Hz power interface of the EUT are measured in the frequency range of 450 kHz to 30 MHz. The measurements are performed using a receiver, which has CISPR characteristic bandwidth and quasi-peak detection, and a Line Impedance Stabilization Network (LISN), with $50\ \Omega/50\ \mu\text{H}$ (CISPR 16) characteristics. Table top equipment is placed on a non-conducting table 80 centimeters above the floor and is positioned 40 centimeters from the vertical ground plane (wall) of the screen room. In some cases, a pre-scan using a spectrum analyzer is initially performed on the units comprising the system under test to locate the highest emissions. If the minimum passing margin appears to be less than 20 dB with a peak mode measurement, the emissions are re-measured using a tuned receiver or spectrum analyzer with quasi-peak and average detection and recorded on the data sheets.

Radiated Emissions

Radiated emissions from the EUT are measured in the frequency range of 30 to 1000 MHz using a spectrum analyzer and appropriate broadband linearly polarized antennas. Measurements between 30 MHz and 1000 MHz are made with 120 kHz/6 dB bandwidth and quasi-peak detection and measurements above 1000 MHz are made with a 1 MHz/6 dB bandwidth and peak detection. Table top equipment is placed on a 1.0 X 1.5 meter non-conducting table 80 centimeters above the ground plane. Floor standing equipment is placed directly on the turntable/ground plane. Interface cables that are closer than 40 centimeters to the ground plane are bundled in the center in a serpentine fashion so they are at least 40 centimeters from the ground plane. Cables to simulators/testers (if used in this test) are routed through the center of the table and to a screen room located outside the test area. The antenna is positioned 3 meters horizontally from the EUT. To locate maximum emissions from the test sample the antenna is varied in height from 1 to 4 meters, measurement scans are made with both horizontal and vertical antenna polarizations and the EUT are rotated 360 degrees. Intentional radiators are rotated through three orthogonal axes to determine the attitude that maximizes the emissions.

In the frequency range of 9 kHz to 30 MHz, measurements are made with quasi-peak or average detection with a loop antenna. The antenna is positioned 1 meter above the ground plane and rotated about its vertical axis for maximum response at each azimuth about the EUT. The antenna is also positioned horizontally at the specified distances.