

## TABLE OF CONTENTS

APPLICANT: GREAT POWER ELECTRONIC PRODUCTS CO.

FCC ID: GEGGP895T

### TEST REPORT CONTAINING:

PAGE 1.....TEST PROCEDURE  
PAGE 2.....TEST PROCEDURE AND CIRCUIT DESCRIPTION  
PAGE 3.....RADIATION INTERFERENCE TEST DATA  
PAGE 4.....OCCUPIED BANDWIDTH TEST DATA

### EXHIBITS CONTAINING:

EXHIBIT 1.....POWER OF ATTORNEY LETTER  
EXHIBIT 2.....BLOCK DIAGRAM  
EXHIBIT 3.....SCHEMATIC  
EXHIBIT 4.....INSTRUCTION MANUAL  
EXHIBIT 5.....SAMPLE OF FCC ID LABEL & SKETCH OF LOCATION  
EXHIBIT 6.....EXTERNAL PHOTO - FRONT SIDE  
EXHIBIT 7.....EXTERNAL PHOTO - BACK SIDE  
EXHIBIT 8.....INTERNAL PHOTO - COMPONENT SIDE  
EXHIBIT 9.....INTERNAL PHOTO - COPPER SIDE  
EXHIBIT 10.....OCCUPIED BANDWIDTH PLOT  
EXHIBIT 11.....OCCUPIED BANDWIDTH PLOT

APPLICANT: GREAT POWER ELECTRONIC PRODUCTS CO.

FCC ID: GEGGP895T

REPORT #: F:\CUS\G\GRT\GRT118H9.RPT

PAGE: TABLE OF CONTENTS LIST

APPLICANT: GREAT POWER ELECTRONIC PRODUCTS CO.  
FCC ID: GEGGP895T

TEST EQUIPMENT LIST

1. Spectrum Analyzer: Hewlett Packard 8566B - Opt 462, w/ preselector 85685A, & Quasi-Peak Adapter HP 85650A, & HP 8449B - OPT H02 Cal. 6/26/98
2. Signal Generator, Hewlett Packard 8640B, cal. 10/1/98
3. Eaton Biconical Antenna Model 94455-1  
20-200 MHz Serial No. 0997 Cal. 5/15/98
4. Electro-Metric Dipole Kit, 20-1000 MHz, Model TDA-30 10/15/98
5. Electro-Metric Horn 1-18 GHz, Model RGA-180, Cal. 8/15/98
6. Electro-Metric Antennas Model TDA-30/1-4, Cal. 10/15/98
7. Electro-Metric Line Impedance Stabilization Network Model No. EM-7821, Serial No. 101; 100KHz-30MHz 50uH. Cal. 11/19/98
8. Electro-Metric Line Impedance Stabilization Network Model No. EM-7820, Serial No. 2682; 10KHz-30MHz 50uH. Cal. 11/19/98
9. Special low loss cable was used above 1 GHz
10. Tenney Temperature Chamber

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz. The ambient temperature of the UUT was &temp& with a humidity of 70%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz)	METER READING + ACF = FS
33	20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

APPLICANT: GREAT POWER ELECTRONIC PRODUCTS CO.  
FCC ID: GEGGP895T  
REPORT #: F:\CUS\G\GRT\GRT118H9.RPT  
PAGE #: 1

## TEST PROCEDURES CONTINUED

APPLICANT: GREAT POWER ELECTRONIC PRODUCTS CO.  
FCC ID: GEGGP895T

ANSI STANDARD C63.4-1992 10.1.7 MEASUREMENT PROCEDURES: The unit under test was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

The situation was similar for the conducted measurement except that the table did not rotate. The EUT was setup as described in ANSIC63.4-1992 with the EUT 40 cm from the vertical ground wall.

### CIRCUIT\_DESCRIPTION:

In the transmit mode the momentary switches SW1, & SW3 provide input to the encoder intergrated circuit IC1. IC1 internally modulates the RF portion of IC1. The modulated output of IC1 is connected to the tuned circuit L1/C6, which connected to low pass filter L3, C7, C8, and L3. From the Low Pass filter the signal goes to the antenna. The RF frequency is determined by the crystal XTAL1.

### ANTENNA\_AND\_GROUND\_CIRCUITRY

This unit makes use of a short, antenna. The antenna is inductively coupled. The antenna is self contained, no provision is made for an external antenna. This unit is powered from a 9.0V battery.

No ground connection is provided. The unit relies on the ground tract of the printed circuit board.

APPLICANT: GREAT POWER ELECTRONIC PRODUCTS CO.  
FCC ID: GEGGP895T  
REPORT #: F:\CUS\G\GRT\GRT118H9.RPT  
PAGE #: 2

APPLICANT: GREAT POWER ELECTRONIC PRODUCTS CO.

FCC ID: GEGGP895T

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NO.: 15.227

REQUIREMENTS: CARRIER FREQUENCY WILL NOT EXCEED 80 dBuV/m AT 3M.  
OUT-OF-BAND EMISSIONS SHALL NOT EXCEED:

30 - 88 MHz	40.0 dBuV/M	MEASURED AT 3 METERS
88 - 216 MHz	43.5 dBuV/M	
216 - 960 MHz	46.0 dBuV/M	
ABOVE 960 MHz	54.0 dBuV/M	

TEST DATA:

EMISSION FREQUENCY MHz	METER READING AT 3 METERS dBuV	COAX LOSS dB	ANTENNA CORRECTION FACTOR	FIELD STRENGTH dBuV/m@3m	PEAK MARGIN dB	ANT. POL.
27.15	50.80	0.20	11.75	62.75	17.25	H
54.29	10.00	0.80	9.61	20.41	19.59	H
108.58	4.20	0.80	8.38	13.38	30.12	V
135.73	8.10	0.80	15.32	24.22	19.28	V
190.02	16.20	0.90	13.67	30.77	12.73	V
217.16	14.60	1.20	12.42	28.22	51.78	V
244.31	12.90	1.20	13.21	27.31	18.69	V
271.45	11.70	1.40	14.00	27.10	18.90	V
298.60	5.50	1.40	15.61	22.51	23.49	V
325.74	6.00	1.40	14.85	22.25	23.75	V

SAMPLE CALCULATION:  $FSdBuV/m = MR(dBuV) + ACFdB$ .

TEST PROCEDURE: The procedure used was ANSI STANDARD C63.4-1992. The spectrum was scanned from 30 MHz to 1000 MHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The UUT was tested in 3 orthogonal planes.

TEST RESULTS: THE UNIT DOES MEET THE FCC REQUIREMENTS.

PERFORMED BY:\_\_S. S. SANDERS\_\_\_\_\_ DATE: MARCH 24, 1999

APPLICANT: GREAT POWER ELECTRONIC PRODUCTS CO.

FCC ID: GEGGP895T

NAME OF TEST: Occupied Bandwidth

RULES PART NO.: 15.227

REQUIREMENTS: The field strength of any emissions appearing outside the 26.96-27.28 MHz band shall not exceed 100 uV/m (15.209).

THE GRAPH IN EXHIBIT 10 & 11 REPRESENTS THE WORSE CASE OCCUPIED BANDWIDTH EMISSIONS FOR THIS DEVICE.

METHOD OF MEASUREMENT: A small sample of the transmitter output was fed into the spectrum analyzer and the attached plot was taken. The vertical scale is set to -10 dBm per division. The horizontal scale is set to 5 kHz per division.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: S. S. SANDERS MARCH 24, 1999

APPLICANT: GREAT POWER ELECTRONIC PRODUCTS CO.  
FCC ID: GEGGP895T  
REPORT #: F:\CUS\G\GRT\GRT118H9.RPT  
PAGE #: 4