

MONICOR

ELECTRONIC CORP.

Crystal Specification
3rd Overtone Crystal
September 20, 1995
Rev A

Frequency Range: 53.575 MHz to 58.75 MHz or as specified by PO

Temperature Range: -10 to +60 degrees C

Mode: 3rd overtone

Frequency Tolerance (at 25 +/- 3 degrees C): +/- 10 ppm

Frequency Stability (over temperature range): +/- 8ppm -30 to +60 degrees C

Package: HC-45/U or UM-1

Resistance: 45 ohms

Load Capacitance: Series mode

Case Capacitance: 7 pf maximum

Drive Level: 1 mW nominal

Modulation: +/- 12 ppm (Modulation Range)

Aging: +/- 2 ppm/year maximum

Monicor Part Numbers:

10000-378-XXX Crystal, 3rd OT, series UM-1 Tx


10001-378-XXX Crystal, 3rd OT, series UM-1 Rx

Modulation Characteristics:

For transmit crystals in the frequency range of 57.18 MHz through 58.74 MHz, per Monicor part number 10000-398-XXX, the modulation specs are as follows:

Modulation: +/- 12ppm, Ls = 750 nH, Cx = 6.5-30pf. C_{montional} >= 1.2pf.

Schematic:



MONICOR ELECTRONIC CORP.
FCC ID: GES4BAM2000S
EXHIBIT #: 8

2964 N.W. 60th STREET FORT LAUDERDALE, FLORIDA 33309 (305) 979-1907