



FCC Test Report

Report No.: AGC00014130502FE03

FCC ID : GFOBX-5
APPLICATION PURPOSE : Class II Permissive Change
PRODUCT DESIGNATION : Bluetooth speaker
BRAND NAME : Cowin
MODEL NAME : X-9S
CLIENT : Cowin Electronics Corp., Limited
DATE OF ISSUE : May 28,2013
STANDARD(S) : FCC Part 15 Rules
REPORT VERSION : V 1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	May 28,2013	Valid	Extension Report

Product Change Record

This is a variant report based on model X-9Bluetooth. The new product model is X-9S. Two Models all the same except for PCB Components and product appearance. But Bluetooth Module no any change. The original report can be referred to AGC05X1130302F2. Only Radiated Emission and Band Edges were verified for the differences based on the original product.


VERIFICATION OF COMPLIANCE

Applicant	Cowin Electronics Corp., Limited
	Cell B, 3th Floor, Tower B, Hongzhuyongqi Technology Park, Lezhujiao, Xixiang, Baoan, Shenzhen, Guangdong, China
Manufacturer	Cowin Electronics Corp., Limited
	Cell B, 3th Floor, Tower B, Hongzhuyongqi Technology Park, Lezhujiao, Xixiang, Baoan, Shenzhen, Guangdong, China
Product Designation	Bluetooth speaker
Brand Name	Cowin
Test Model	X-9S
FCC ID	GFOBX-5
Date of Test	May 20,2013~May 27,2013

WE HEREBY CERTIFY THAT:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2003) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Rules Part 15.247.

Prepared By



Wall Huang

May 28, 2013

Checked By



Forrest Lei

May 28, 2013

Authorized By



Solger Zhang

May 28, 2013

TABLE OF CONTENTS

1. GENERAL INFORMATION	6
1.1 PRODUCT DESCRIPTION	6
1.2 TABLE OF CARRIER FREQUENCIES	6
1.3 RECEIVER INPUT BANDWIDTH	7
1.4 EXAMPLE OF A HOPPING SEQUENCY IN DATA MODE	8
1.5 EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR.....	8
1.6 RELATED SUBMITTAL(S) / GRANT (S).....	8
1.7 TEST METHODOLOGY	8
1.8 MEASUREMENT UNCERTAINTY	8
1.9 TEST FACILITY	9
1.10 SPECIAL ACCESSORIES.....	9
1.11 EQUIPMENT MODIFICATIONS	9
2. SYSTEM TEST CONFIGURATION.....	10
2.1 CONFIGURATION OF TESTED SYSTEM	10
2.2 EQUIPMENT USED IN EUT SYSTEM	10
3. SUMMARY OF TEST RESULTS.....	11
4. DESCRIPTION OF TEST MODES.....	11
5. RADIATED EMISSION	12
5.1 MEASUREMENT PROCEDURE	12
5.2 TEST SETUP.....	13
5.3 TEST EQUIPMENT LIST	14
5.4 TEST RESULT	15
6. BAND EDGES EMISSION	19
6.1 MEASUREMENT PROCEDURE	19
6.2 TEST SET-UP.....	19
6.3 TEST RESULT	19
APPENDIX I	23
PHOTOGRAPHS OF THE EUT	23
APPENDIX II	29
PHOTOGRAPHS OF THE TEST SETUP	29

1. GENERAL INFORMATION

1.1 PRODUCT DESCRIPTION

The EUT is a **Bluetooth speaker** designed as a “Communication Device”. It is designed by way of utilizing the FHSS technology to achieve the system operation.

A major technical description of EUT is described as following:

Operation Frequency	2.402 GHz to 2.480GHz
Bluetooth Version	V2.1 with EDR
Modulation	GFSK, $\pi/4$ -DQPSK, 8DPSK
Number of channels	79
Antenna Designation	Integrated Antenna
Antenna Gain	0.8dBi
Hardware Version	N/A
Software Version	N/A
Power Supply	DC 3.7V by Built-in Li-ion Battery

Note: The USB port is only used to charging.

1.2 TABLE OF CARRIER FREQUENCIES

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	0	2402MHZ
	1	2403MHZ
	:	:
	38	2440 MHZ
	39	2441 MHZ
	40	2442 MHZ
	:	:
	77	2479 MHZ
	78	2480 MHZ

1.3 RECEIVER INPUT BANDWIDTH

The input bandwidth of the receiver is 1.3 MHz. In every connection one Bluetooth device is the master and the other one is slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally the type of connection (e.g. single or multisport (packet)) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also the slave of the connection will use these settings.

Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be sent on the same frequency, it is sent on the next frequency of the hopping sequence.

1.4 EXAMPLE OF A HOPPING SEQUENCY IN DATA MODE

Example of a 79 hopping sequence in data mode:

40,21,44,23,42,53,46,55,48,33,52,35,50,65,54,67
56,37,60,39,58,69,62,71,64,25,68,27,66,57,70,59
72,29,76,31,74,61,78,63,01,41,05,43,03,73,07,75
09,45,13,47,11,77,15,00,64,49,66,53,68,02,70,06
01,51,03,55,05,04

1.5 EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR

The generation of the hopping sequence in connection mode depends essentially on two input values:

1 LAP/UAP of the master of the connection

2 Internal master clock

The LAP(lower address part) are the 24 LSB's of the 48 BD_ADDRESS. The BD_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP(upper address part) are the 24MSB's of the 48BD_ADDRESS

The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and is never turned off. For synchronization with other units only offset are used. It has no relation to the time of the day. Its resolution is at least half the RX/TX slot length of 312.5us. The clock has a cycle of about One day(23h30). In most case it is implemented as 28 bit counter. For the deriving of the hopping sequence the entire.

LAP(24 bits), 4LSB's(4bits)(Input 1) and the 27MSB's of the clock(Input 2) are used. With this input values different mathematical procedures(permutations, additions, XOR-operations)are performed to generate the Sequence. This will be done at the beginning of every new transmission.

Regarding short transmissions the Bluetooth system has the following behavior:

The first connection between the two devices is established, a hopping sequence was generated. For Transmitting the wanted data the complete hopping sequence was not used. The connection ended.

The second connection will be established. A new hopping sequence is generated. Due to the fact the Bluetooth clock has a different value, because the period between the two transmission is longer(and it Cannot be shorter)than the minimum resolution of the clock(312.5us). The hopping sequence will always Differ from the first one.

1.6 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: GFOBX-5**, filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

1.7 TEST METHODOLOGY

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4 (2003). Radiated testing was performed at an antenna to EUT distance 3 meters.

1.8 MEASUREMENT UNCERTAINTY

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

- Uncertainty of Conducted Emission, $U_c = \pm 2.75\text{dB}$
- Uncertainty of Radiated Emission, $U_c = \pm 3.2\text{dB}$

1.9 TEST FACILITY

All measurement facilities used to collect the measurement data are located at
Attestation of Global Compliance(Shenzhen) Co., Ltd.

2/F., Building 2, No.1-No.4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Bao'an District, Shenzhen,
Guangdong, China

The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2003.
FCC register No.: 259865

1.10 SPECIAL ACCESSORIES

Refer to section 2.2.


1.11 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.


2. SYSTEM TEST CONFIGURATION

2.1 CONFIGURATION OF TESTED SYSTEM

Configure 1 (Normal Hopping mode)



Configure 2 (Control continuous TX through PC)



****Note:** All the accessories have been used during the test.

2.2 EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Mfr/Brand	Model/Type No.	Remark
1	Bluetooth speaker	N/A	X-9S	EUT
2	PC	DELL	INSPIRON	A.E

3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.209	Radiated Emission	Compliant
§15.247	Band Edges	Compliant

****Note:** The EUT can work normally when charging. The adapter was supplied by lab during test.

4. DESCRIPTION OF TEST MODES

The EUT has been operated in three modulations: GFSK, $\pi/4$ -DQPSK, 8-DPSK independently. The following operating modes were applied for the related test items. All 3axis have been tested.

No.	TEST MODES
1	Low Channel(TX)
2	Middle Channel(TX)
3	High Channel(TX)
4	Normal Hopping

****Note:** All the test modes were tested, and the battery is full filled, only the result of the worst case was recorded in the report.

5. RADIATED EMISSION

5.1 MEASUREMENT PROCEDURE

1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.


The following table is the setting of spectrum analyzer and receiver.'

Spectrum Parameter	Setting
Start Frequency	1GHz
Stop Frequency	26.5GHz
RB/VB(Emission in restricted band)	1MHz/1MHz for Peak, 1MHz/10Hz for Average
RB/VB(Emission in non-restricted band)	1MHz/1MHz for Peak


Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

5.2 TEST SETUP


RADIATED EMISSION TEST SETUP BELOW 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



5.3 TEST EQUIPMENT LIST

Description	Manufacturer	Model	SERIAL NUMBER	Cal. Date	Cal. Due
Spectrum Analyzer	Agilent	E4440A	N/A	07/18/2013	07/17/2013
Amplifier	EM	EM30180	0607030	07/18/2013	07/17/2013
Horn Antenna	EM	EM-AH-10180	N/A	04/21/2012	04/20/2014
EMI Test Receiver	Rohde & Schwarz	ESCI	N/A	07/18/2013	07/17/2013
Biological Antenna	A.H. Systems Inc.	SAS-521-4	N/A	06/08/2011	06/07/2013
Horn Antenna	A.H. Systems Inc.	SAS-574	N/A	07/18/2012	07/17/2013


5.4 TEST RESULT

THE WORST CASE IS NORMAL HOPPING MODE.

RADIATED EMISSION BELOW 30MHZ


No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHZ



Site: site #1	Polarization: Horizontal	Temperature: 26
Limit: FCC Class B 3M Radiation	Power:	Humidity: 60 %
EUT: Bluetooth speaker	Distance: 3m	
M/N: X-9S		
Mode: Normal Hopping		
Note:		


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		41.3167	17.98	7.34	25.32	40.00	-14.68	peak			
2		125.3833	14.03	12.72	26.75	43.50	-16.75	peak			
3		224.0000	22.34	12.48	34.82	46.00	-11.18	peak			
4	*	337.1667	19.79	18.89	38.68	46.00	-7.32	peak			
5		442.2500	16.05	21.48	37.53	46.00	-8.47	peak			
6		490.7500	13.51	22.36	35.87	46.00	-10.13	peak			



Site: site #1 Polarization: **Vertical** Temperature: 26
Limit: FCC Class B 3M Radiation Power: Humidity: 60 %
EUT: Bluetooth speaker Distance: 3m
M/N: X-9S
Mode: Normal Hopping
Note:


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		41.3167	26.95	6.79	33.74	40.00	-6.26	peak			
2		144.7833	20.39	12.85	33.24	43.50	-10.26	peak			
3		343.6333	16.35	19.00	35.35	46.00	-10.65	peak			
4	*	442.2500	19.51	21.48	40.99	46.00	-5.01	peak			
5		490.7500	17.32	22.36	39.68	46.00	-6.32	peak			
6		540.8667	15.90	23.46	39.36	46.00	-6.64	peak			

RADIATED EMISSION ABOVE 1GHZ (1-10th Harmonics)



Site: site #1 Polarization: *Horizontal* Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %
EUT: Bluetooth speaker Distance: 3m
M/N: X-9S
Mode: Normal Hopping
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	X	2402.000	64.29	10.32	74.61	74.00	0.61	peak			
2	*	2480.000	64.26	10.41	74.67	74.00	0.67	peak			
3		3686.667	28.64	13.26	41.90	74.00	-32.10	peak			
4		4793.333	34.59	7.66	42.25	74.00	-31.75	peak			



Site: site #1 Polarization: **Vertical** Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %
EUT: Bluetooth speaker Distance: 3m
M/N: X-9S
Mode: Normal Hopping
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	62.07	10.32	72.39	74.00	-1.61	peak			
2	*	2480.000	62.67	10.41	73.08	74.00	-0.92	peak			
3		3960.000	29.24	14.94	44.18	74.00	-29.82	peak			
4		4460.000	37.24	7.55	44.79	74.00	-29.21	peak			

****Note:** 5~25GHz at least have 20dB margin. No recording in the test report.
Factor=Antenna Factor+ Cable loss-Amplifier gain, Over=Measurement-Limit.

6. BAND EDGES EMISSION

6.1 MEASUREMENT PROCEDURE


- 1, Set the EUT Work on the top, the bottom operation frequency individually.
2. Set SPA Start or Stop Frequency = Operation Frequency, RBW $\geq$ 1%span, VBW $\geq$ RBW
3. The band edges was measured and recorded.

6.2 TEST SET-UP

The same as described in section 8.2


6.3 TEST RESULT

TEST PLOT OF BAND EDGE FOR LOW CHANNEL (3Mbps)



Site: site #1 Polarization: **Horizontal** Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %
EUT: Bluetooth speaker Distance: 3m
M/N: X-9S
Mode: Low Channel TX
Note:


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2388.292	18.38	10.31	28.69	74.00	-45.31	peak			
2		2390.000	17.31	10.31	27.62	74.00	-46.38	peak			
3		2395.042	19.19	10.31	29.50	74.00	-44.50	peak			
4	*	2402.088	63.70	10.32	74.02	74.00	0.02	peak			



Site: site #1 Polarization: **Vertical** Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %
EUT: Bluetooth speaker Distance: 3m
M/N: X-9S
Mode: Low Channel TX
Note:


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2390.000	17.77	10.31	28.08	74.00	-45.92	peak			
2		2394.917	19.51	10.31	29.82	74.00	-44.18	peak			
3		2397.958	20.60	10.32	30.92	74.00	-43.08	peak			
4	*	2402.075	62.90	10.32	73.22	74.00	-0.78	peak			

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL (3Mbps)



Site: site #1 Polarization: *Horizontal* Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %
EUT: Bluetooth speaker Distance: 3m
M/N: X-9S
Mode: High Channel TX
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.102	63.39	10.41	73.80	74.00	-0.20	peak			
2		2483.500	14.57	10.41	24.98	74.00	-49.02	peak			
3		2487.717	17.23	10.42	27.65	74.00	-46.35	peak			
4		2494.537	17.23	10.42	27.65	74.00	-46.35	peak			



Site: site #1 Polarization: **Vertical** Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %
EUT: Bluetooth speaker Distance: 3m
M/N: X-9S
Mode: High Channel TX
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.097	62.51	10.41	72.92	74.00	-1.08	peak			
2		2483.500	12.15	10.41	22.56	74.00	-51.44	peak			
3		2488.670	14.95	10.42	25.37	74.00	-48.63	peak			
4		2490.247	15.47	10.42	25.89	74.00	-48.11	peak			

APPENDIX I
PHOTOGRAPHS OF THE EUT
TOP VIEW OF EUT




BOTTOM VIEW OF EUT



FRONT VIEW OF EUT



BACK VIEW OF EUT




LEFT VIEW OF EUT




RIGHT VIEW OF EUT




OPEN VIEW OF EUT




INTERNAL VIEW OF EUT-1




INTERNAL VIEW OF EUT-2





INTERNAL VIEW OF EUT-3



INTERNAL VIEW OF EUT-4



APPENDIX II
PHOTOGRAPHS OF THE TEST SETUP
RADIATED EMISSION



----END OF REPORT----