

Compal Electronics Inc

No.581 & 581-1, Ruiguang Rd., Neihu District, Taipei city 11492, Taiwan

Tel:886-2-8797-8599; FAX:886-2-2658-6080

Date: June 30, 2025

Module Approval Checklist

FCC ID: **GKRCXCN3**

Item	Requirements	EUT
1.	The radio elements must have the radio frequency circuitry shielded. Physical components and tuning capacitor(s) may be located external to the shield, but must be on the module assembly	Yes. The module is equipped with its own shielding case.
2.	The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal	Yes. The module has buffer modulation / data inputs.
3.	The module must contain power supply regulation on the module	Yes. The module has its own power supply regulation.
4.	The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per §§ 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b)	Not applicable to licensed modules.
5.	The module must demonstrate compliance in a stand-alone configuration	Yes. The module was tested on evaluation board, and it's not inside of another device during testing
6.	The module must be labeled with its permanently affixed FCC ID label, or use an electronic display	Yes. The module transmitter will be labeled with its own FCC ID, and for OEM integration the integration manual contains labeling instructions for the host device per Part 15.212 (vi)
7.	The module must comply with all specific rules applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee	Yes. The module approved transmitter complies with all applicable rules and the integration manual contains any specific requirements addressed to the integrator and/or to the end-user of the final end-product.
8.	The module must comply with RF exposure requirements	Yes. The modular transmitter complies with RF exposure requirement.



Miranda Wu

Miranda_wu@compal.com