

RT041-08-101420-4A - DM / CHB

TECHNICAL REPORT

Equipment under test:

WORKABOUT PRO (7527C)
+ WA9005 + BT + RA2041 + RA3030
+ RFID Module HF-AM1-G2
FCC ID: GM3HFAM1G2

Company:

PSION TEKLOGIX

Diffusion: Mr PORTE

(Company: PSION TEKLOGIX)

Number of pages: 7 without annex

Ed.	Date	Modified page(s)	Written by		Technical verification Quality approval	
			Name	Visa	Name	Visa
0	14-Apr-08	Creation	Régis GONZALEZ		Olivier HEYER	

Duplication of this report is only permitted for an integral photographic facsimile. It includes the number of pages referenced above. This document is the result of testing a specimen or a sample of the product submitted. It does not imply an assessment of the conformity of the whole production of the item tested.



NAME OF THE EQUIPMENT UNDER TEST (E.U.T.) : WORKABOUT PRO (7527C) + WA9005 +
BT + RA2041 + RA3030 +
RFID Module HF-AM1-G2

Serial number : None

Part number : None

Software Version : None

MANUFACTURER'S NAME : PSION TEKLOGIX

APPLICANT'S ADDRESS:

Company : PSION TEKLOGIX

Address : 135 rue de la Duranne
BP 421000
13591 AIX EN PROVENCE CEDEX 3
FRANCE

Person(s) present during the tests : Mr PORTE

Responsible : Mr PORTE

DATE(S) OF STUDY : April, the 15th of 2008

EXPERT'S NAME : Olivier HEYER

CONTENTS

1.	INTRODUCTION.....	4
2.	REFERENCE DOCUMENT(S).....	4
3.	EQUIPMENT UNDER TEST CONFIGURATION.....	4
4.	RADIATED MEASUREMENTS	5
5.	MAXIMUM PERMISSIBLE EXPOSURE CALCULATIONS.....	6
6.	MAXIMUM PERMISSIBLE EXPOSURE LIMITS.....	6
7.	MAXIMUM PERMISSIBLE EXPOSURE ESTIMATION.....	7

1. INTRODUCTION

This document submits the results of Maximum Permissible Exposure (MPE) calculations performed on the equipment WORKABOUT PRO (7527C) + WA9005 + BT + RA2041 + RA3030 + RFID Module HF-AM1-G2

2. REFERENCE DOCUMENT(S)

Radio test report	R041-08-101420-4A Ed.1 from EMITECH Grand Sud Laboratory
OET Bulletin 65 (Aug 1997)	Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields
FCC Part 1	Practice and procedure
RSS 210 Issue 7	Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment

3. EQUIPMENT UNDER TEST CONFIGURATION

<u>Product description:</u>	FCC ID: GM3HFAM1G2 Utilization: RFID TAG reader Antenna type: Incorporated antenna Antenna gain: Unknown Operating frequency range: 13.56 MHz (Rfid); 2402MHz (Bluetooth); 2462MHz (Wifi); 836.4MHz (GSM); 1960MHz (GSM) Power source: 5 Vdc (stand alone) or mains voltage (with docking) Power level and frequency range are not user adjustable
-----------------------------	---

4. RADIATED MEASUREMENTS

These results come from EMITECH Grand Sud radio test report R041-08-101420-4A Ed.1.
Please find below carrier radiated field strength (detail in test report):

Measuring distance: 3 m on Open Area Test Site

Wifi radiated field strength:

Frequency (MHz)	Polarization	Measure (dB μ V/m)
2462.00	Vertical	112.70
2462.00	Horizontal	117.70

Bluetooth radiated field strength:

Frequency (MHz)	Polarization	Measure (dB μ V/m)
2402.00	Vertical	91.74
2402.00	Horizontal	88.48

GSM850 radiated field strength (ERP):

Frequency (MHz)	Polarization	Field strength (dBm)
836.40	Vertical	28.84
836.40	Horizontal	22.70

GSM1900 radiated field strength (EIRP):

Frequency (MHz)	Polarization	Field strength (dBm)
1960.00	Vertical	-27.40
1960.00	Horizontal	-33.96

5. MAXIMUM PERMISSIBLE EXPOSURE CALCULATIONS

Equipment Under Test is always held farer than 20 cm from the body. Then we have estimate the power density at this distance using OET Bulletin 65 (Aug 1997).

For Wifi and Bluetooth: $S = \frac{E^2}{3770}$ (1) of OET65

For GSM850: $S = \frac{1.64ERP}{1000\pi R^2}$ (5) and (6) of OET65

For GSM 1900: $S = \frac{EIRP}{1000\pi R^2}$ (6) of OET65

With S = power density (mW/cm²)
 E = electric field strength (V/m)
 ERP = effective radiated power (W)
 EIRP = equivalent isotropically radiated power (W)

When E is measured at 3m, level in dBμV/m must be increased by 23.52 dB when it is considered as far electric field ("plane wave" conditions) to be estimated at 20cm.

For information 1/d² propagation law results are specified (47.04 dB is then added)

6. MAXIMUM PERMISSIBLE EXPOSURE LIMITS

The limit for MPE estimation is (general population / uncontrolled exposure):

Frequency (MHz)	Limit for MPE (Power density in mW/cm ²)
836.40	0.5576
1960.00	1
2402.00	1
2462.00	1

7. MAXIMUM PERMISSIBLE EXPOSURE ESTIMATION

Using equations in §5, we can find following results:

Wifi:

Frequency (MHz)	Polarization	MPE Calculation (mW/cm ²)	Limit (mW/cm ²)
2462.00	Vertical	0.01	1
2462.00	Horizontal	0.04	1

For information using 1/d² propagation

Frequency (MHz)	Polarization	MPE Calculation (mW/cm ²)	Limit (mW/cm ²)
2462.00	Vertical	2.50	1
2462.00	Horizontal	7.90	1

Bluetooth:

Frequency (MHz)	Polarization	MPE Calculation (mW/cm ²)	Limit (mW/cm ²)
2402.00	Vertical	8.90 10 ⁻⁵	1
2402.00	Horizontal	4.20 10 ⁻⁵	1

For information using 1/d² propagation

Frequency (MHz)	Polarization	MPE Calculation (mW/cm ²)	Limit (mW/cm ²)
2402.00	Vertical	0.02	1
2402.00	Horizontal	0.01	1

GSM850:

Frequency (MHz)	Polarization	MPE Calculation (mW/cm ²)	Limit (mW/cm ²)
836.40	Vertical	10.00 10 ³	0.5576
836.40	Horizontal	2.43 10 ³	0.5576

GSM1900:

Frequency (MHz)	Polarization	MPE Calculation (mW/cm ²)	Limit (mW/cm ²)
1960.00	Vertical	1.45 10 ⁻⁸	1
1960.00	Horizontal	3.20 10 ⁻⁹	1

□□□ End of report □□□