

Report on the FCC and ISED Testing of the Scully Signal Company TP-100

In accordance with FCC 47 CFR Part 15.247 &
ISED Canada's Radio Standards Specifications
RSS-247

Prepared for: Scully Signal Company
70 Industrial Way
Wilmington, MA 01887

FCC ID: GMHTP-100 | IC: 956A-TP100



America

Add value.
Inspire trust.

COMMERCIAL-IN-CONFIDENCE

Document Number: BO72146375.100 | Issue: 01

SIGNATURE

Beth J. Walsh

Name	Job Title	Responsible For	Issue Date
Pete Walsh	Service Line Manager	Authorized Signatory	2019-Feb-28

Signatures in this approval box have checked this document in line with the requirements of TÜV SÜD America, Inc. document control rules.

FCC Accreditation
Designation Number US1063 Tampa, FL Test Laboratory

Innovation, Science, and Economic Development Canada
Accreditation
Main Site Number 2087A-2 Tampa, FL Test Laboratory
Satellite Site Number: 4175C Boca Raton, FL Test Laboratory

EXECUTIVE SUMMARY

A sample of this product was tested and found to be compliant with FCC Part 15.247, ISED Canada's RSS-247.



DISCLAIMER AND COPYRIGHT

This non-binding report has been prepared by TÜV SÜD America with all reasonable skill and care. The document is confidential to the potential Client and TÜV SÜD America. No part of this document may be reproduced without the prior written approval of TÜV SÜD America.
© TÜV SÜD

© 1995 SCD: ACCREDITATION

ACCREDITATION
Our A2LA Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our A2LA Accreditation.

TÜV SÜD America
5610 West Sligh Ave., Suite 100
Tampa, FL 33634

Phone: 813-284-2715
www.tuv-sud-america.com

TÜV SÜD



Signatures of the individuals responsible for testing the product**ENGINEERING STATEMENT**

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported testing was carried out on a sample equipment to demonstrate limited compliance with FCC 47 CFR Part 15.247 and ISED Canadas's RSS-247. The sample tested was found to comply with the requirements defined in the applied rules.

NAME	RESPONSIBLE FOR	SIGNATURE
Thierry Jean-Charles	Testing	

TABLE OF CONTENTS

1	GENERAL	4
1.1	Purpose	4
1.2	Applicant Information.....	4
1.3	Product Description	4
1.4	Test Methodology and Considerations	4
2	TEST FACILITIES	5
2.1	Location	5
2.2	Laboratory Accreditations/Recognitions/Certifications.....	5
2.3	Radiated & Conducted Emissions Test Site Description	6
2.3.1	Semi-Anechoic Chamber Test Site	6
2.3.2	Conducted Emissions Test Site Description.....	7
3	APPLICABLE STANDARD REFERENCES	8
4	LIST OF TEST EQUIPMENT	9
5	SUPPORT EQUIPMENT	10
6	EQUIPMENT UNDER TEST SETUP BLOCK DIAGRAM.....	10
7	SUMMARY OF TESTS.....	11
7.1	Antenna Requirement – FCC: Section 15.203.....	11
7.2	6 dB Bandwidth - FCC: Section 15.247(a)(2); ISED Canada: RSS-247 5.2(a); 99% Bandwidth ISED Canada: RSS-GEN 6.6.....	11
7.2.1	Measurement Procedure.....	11
7.2.2	Measurement Results	12
7.3	Peak Output Power – FCC: Section 15.247(b)(3); ISED Canada: RSS-247 5.4(d)	16
7.3.1	Measurement Procedure (Conducted Method)	16
7.3.2	Measurement Results	16
7.4	Band-Edge Compliance and Spurious Emissions	18
7.4.1	Band-Edge Compliance of RF Conducted Emissions – FCC: Section 15.247(d); ISED Canada: RSS-247 5.5.....	18
7.4.2	RF Conducted Spurious Emissions – FCC: Section 15.247(d); ISED Canada: RSS-247 5.5 ...	20
7.4.3	Radiated Spurious Emissions into Restricted Frequency Bands – FCC: Sections 15.205, 15.209; ISED Canada: RSS-Gen 8.9, 8.10	24
7.4.4	Sample Calculation:	25
7.5	Power Spectral Density – FCC: Section 15.247(e); ISED Canada: RSS-247 5.2(b)	26
7.5.1	PSD Measurement Procedure (Conducted Method).....	26
7.5.2	Measurement Results	26
8	MEASUREMENT UNCERTAINTIES	28
9	CONCLUSION.....	29

1 GENERAL

1.1 Purpose

The purpose of this report is to demonstrate compliance with Part 15 Subpart C of the FCC's Code of Federal Regulations Section 15.247 and Innovation Science and Economic Development Canada's Radio Standards Specification RSS-247 for the tests documented herein.

1.2 Applicant Information

Scully Signal Company
70 Industrial Way
Wilmington, MA 01887

1.3 Product Description

The EUT is a Truck Identification Module (TIM) Reader Programmer. The EUT incorporate an 802.11b Wi-Fi Transceiver.

Technical Details

Mode of Operation: IEEE 802.11b
Frequency Range: 2412 MHz - 2462 MHz
Number of Channels: 11
Channel Separation: 5 MHz
Data Rate: 1, 2, 5.5, 11 Mbps
Modulations: CCK, DSSS
Antenna Type/Gain: Balance Flex Dipole Antenna, 2.8 dBi
Input Power: 4 AA Batteries, 6 VDC

Model Number: TP-100

Test Sample Serial Number(s): XE-1239 Radiated Emissions, N/A RF Conducted Emissions

Test Sample Condition: The test samples were in good operating condition without any physical damages.

1.4 Test Methodology and Considerations

The EUT was evaluated for radiated and RF Conducted emissions using a test software attenuation setting of 48. The EUT is battery operated only without any provision for connection to the AC mains. Therefore, the EUT is exempted from the power line conducted emissions requirements.

Preliminary measurements were performed to determine the worst-case data rate. Final measurements were performed using the data rates leading to the worst-case results.

For the radiated emissions evaluation, preliminary measurements were performed on the EUT in three orthogonal orientations. The EUT on a side led to the highest radiated emissions.

The EUT was also evaluated for unintentional emissions. The results are documented separately in a supplier's declaration of conformity test report.

2 TEST FACILITIES

2.1 Location

The radiated and conducted emissions test sites are located at the following address:

TÜV SÜD America, Inc.
3998 FAU Blvd, Suite 310
Boca Raton, Florida 33431
Phone: (561) 961-5585
Fax: (561) 961-5587
<http://www.tuv-sud-america.com>

Innovation, Science and Economic Development Canada Lab Code: 4175C

2.2 Laboratory Accreditations/Recognitions/Certifications

TÜV SÜD America, Inc. is accredited to ISO/IEC 17025 by American Association for Laboratory Accreditation (A2LA) and has been issued certificate number 2955.15 in recognition of this accreditation. Unless otherwise specified, all test methods described within this report are covered under the ISO/IEC 17025 scope of accreditation.

Main Site Information:

TÜV SÜD America, Inc.
5610 West Sligh Ave., Suite 100
Tampa, FL 33634
Phone: 813-284-2715
www.tuv-sud-america.com

FCC Designation Number US1063
FCC Test Firm Registration #: 160606
Innovation, Science, and Economic Development Canada Lab Code: 2087A-2

2.3 Radiated & Conducted Emissions Test Site Description

2.3.1 Semi-Anechoic Chamber Test Site

The EMC radiated test facility consists of an RF-shielded enclosure. The interior dimensions of the indoor semi-anechoic chamber are approximately 48 feet (14.6 m) long by 36 feet (10.8 m) wide by 24 feet (7.3 m) high and consist of rigid, 1/8 inch (0.32 cm) steel-clad, wood core modular panels with steel framing. In the shielded enclosure, the faces of the panels are galvanized, and the chamber is self-supporting. 8-foot RF absorbing cones are installed on 4 walls and the ceiling. The steel-clad ground plane is covered with vinyl flooring.

The turntable is driven by pneumatic motor, which can support a 2000 lb. load. The turntable is flush with the chamber floor which it is connected to, around its circumference, with a continuous metallic loaded spring. An EMCO Model 1060 Multi-device controller controls the turntable position.

A pneumatic motor is used to control antenna polarizations and height relative to the ground. The height information is displayed on the control unit EMCO Model 1050.

The control room is an RF shielded enclosure attached to the semi-anechoic chamber with two bulkhead panels for connecting RF, and control cables. The dimension of the room is 7.3 m x 4.9 m x 3 m high and the entrance doors of both control and conducted rooms are 3 feet (0.91 m) by 7 feet (2.13 m).

A diagram of the Semi-Anechoic Chamber Test Site is shown in Figure 2.3.1-1 below:




Figure 2.3.1-1: Semi-Anechoic Chamber Test Site

2.3.2 Conducted Emissions Test Site Description

The dimensions of the shielded conducted room are $7.3 \times 4.9 \times 3 \text{ m}^3$. The power line conducted emission site includes two LISNs: a Solar Model 8028-50 $50 \Omega/50 \mu\text{H}$ and an EMCO Model 3825/2R, which are installed as shown in the figure below. For evaluations requiring 230 V, 50 Hz AC input, a Polarad LISN (S/N 879341/048) is used in conjunction with a California Instruments signal generator Model 2001RP-OP1.

A diagram of the room is shown below in figure 2.3.2-1:




Figure 2.3.2-1: AC Mains Conducted EMI Site

3 APPLICABLE STANDARD REFERENCES

The following standards were used:

- ❖ ANSI C63.10-2013: American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
- ❖ US Code of Federal Regulations (CFR): Title 47, Part 2, Subpart J: Equipment Authorization Procedures, 2018.
- ❖ US Code of Federal Regulations (CFR): Title 47, Part 15, Subpart C: Radio Frequency Devices, Intentional Radiators, 2018
- ❖ FCC KDB 558074 D01 DTS Meas Guidance v05 - Guidance for Performing Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating Under Section 15.257 of the FCC Rules, August 24, 2018.
- ❖ Innovation, Science and Economic Development Canada Radio Standards Specification: RSS-247 — Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices, Issue 2, February 2017.
- ❖ Innovation, Science and Economic Development Canada Radio Standards Specification: RSS-GEN — General Requirements for Compliance of Radio Apparatus, Issue 4, Amendment 1, March 2018.

4 LIST OF TEST EQUIPMENT

The calibration interval of test equipment is annually or the manufacturer's recommendations. Where the calibration interval deviates from the annual cycle based on the instrument manufacturer's recommendations, it shall be stated below.

Table 4-1: Test Equipment List

AssetID	Manufacturer	Model #	Equipment Type	Serial #	Calibration Performed Date	Calibration Due Date
BEMC00078	EMCO	6502	Active Loop Antenna	9104-2608	5/9/2018	5/9/2020
BEMC00282	Microwave Circuits	H3G020G4	2-20GHz Band Pass Filter	74541	5/17/2018	5/17/2019
BEMC00283	Rohde & Schwarz	FSP40	Spectrum Analyzer	1000033	11/28/2017	11/28/2019
BEMC00523	Agilent	E7405A	9kHz-26.5GHz EMC analyzer/HYZ	MY45103293	11/27/2018	11/27/2020
BEMC00653	Suhner	SF-102A	Cable (40GHz)	0944/2A	10/9/2018	10/9/2019
BEMC02002	EMCO	3108	30 MHz to 200 MHz Biconical Antenna	2147	11/28/2017	11/30/2019
BEMC02004	EMCO	3146	200 MHz to 1 GHz Log Periodic Antenna	1385	12/27/2017	12/27/2019
BEMC02006	EMCO	3115	Linear Polarized Horn antenna, 1-18 GHz	2573	4/7/2017	4/7/2019
BEMC02008	COM-power	AH-826	Horn Antenna (18 GHz to 26.5 GHz)	81009	NCR	NCR
BEMC02011	Hewlett-Packard	HP 8447D	100 kHz to 1.3 GHz low-noise, high gain amplifier	2443A03952	10/18/2018	10/18/2019
BEMC02086	Merrimac	FAN-6-10K	10dB Attenuator	23148-83-1	10/17/2018	10/17/2019
BEMC02095	ETS Lindgren	TILE4! - Version 4.2.A	Tile Automation Software	85242	NCR	NCR
BEMC02111	Aeroflex Inmet	40AH2W-20	Attenuator 20dB, 2.9 mm-M/F, DC-40GHz 2 W	2111	8/5/2018	8/5/2019
BEMC02121	Teledyne Storm Products	A81-0303	Radiated Cable Set	2121	7/26/2018	7/26/2019
BEMC02138	Hewlett Packard	8449B	Pre-Amplifier	3008A00320	11/26/2018	11/26/2019
TEMCO0171	MegaPhase, LLC	1GVT4	4A & 4B Test Cables	NC12-K1K1-59, 394	5/30/2018	5/30/2020

Notes:

- **NCR=No Calibration Required**
- **The assets were only used during the active period of the calibration cycle.**

5 SUPPORT EQUIPMENT

Table 5-1: EUT and Support Equipment Description – Radiated Emissions

Item #	Type Device	Manufacturer	Model/Part #	Serial #
1	EUT	Scully Signal Company	TP-100	XE-1239
2	Truck Identification Module (T.I.M.)	Scully Signal Company	08836	N/A

Table 5-2: Cable Description – Radiated Emissions

Cable #	Cable Type	Length	Shield	Termination
A	T.I.M.	10.83 m	No	EUT to TIM

6 EQUIPMENT UNDER TEST SETUP BLOCK DIAGRAM




Figure 6-1: EUT and Support Equipment Block Diagram

7 SUMMARY OF TESTS

Along with the tabular data shown below, plots were taken of all signals deemed important enough to document.

Test Begin Date: February 19, 2019
 Test End Date: February 21, 2019

Table 7-1: Summary of Tests

Requirements	FCC Rule Part	ISED Canada	Test Results
Antenna Requirement	FCC: Section 15.203		Pass
6 dB Bandwidth	FCC: Section 15.247(a)(2)	ISED Canada: RSS-247 5.2(a)	Pass
99% Bandwidth		ISED Canada: RSS-GEN 6.6	Pass
Peak Output Power	FCC: Section 15.247(b)(3)	ISED Canada: RSS-247 5.4(d)	Pass
Band-Edge Compliance of RF Conducted Emissions	FCC: Section 15.247(d)	ISED Canada: RSS-247 5.5	Pass
RF Conducted Spurious Emissions	FCC: Section 15.247(d)	ISED Canada: RSS-247 5.5	Pass
Radiated Spurious Emissions into Restricted Frequency Bands	FCC: Sections 15.205, 15.209	ISED Canada: RSS-Gen 8.9, 8.10	Pass
Power Spectral Density	FCC: Section 15.247(e)	ISED Canada: RSS-247 5.2(b)	Pass
Power Line Conducted Emissions	FCC: Section 15.207	ISED Canada: RSS-Gen 8.8	N/A

7.1 Antenna Requirement – FCC: Section 15.203

The EUT uses an internal 2.8 dBi balance flex dipole antenna which connects to the PCB via an IPEX MHF (U.FL compatible) connector. The antenna type is considered unique and therefore meets the requirements of FCC Section 15.203.

7.2 6 dB Bandwidth - FCC: Section 15.247(a)(2); ISED Canada: RSS-247 5.2(a); 99% Bandwidth ISED Canada: RSS-GEN 6.6

7.2.1 Measurement Procedure

The 6dB bandwidth was measured in accordance with ANSI C63.10 Subclause 11.8.1 Option 1. The RBW of the spectrum analyzer was set to 100 kHz and VBW 300 kHz. Span was set large enough to capture the emissions and >> RBW. A peak detector was used for the measurements.


The 99% occupied bandwidth was measured with the spectrum analyzer span set to fully display the emission. The RBW was set to 1% to 5% of the approximated bandwidth. The occupied 99% bandwidth was measured by using 99% bandwidth equipment function of the spectrum analyzer using a peak detector.

7.2.2 Measurement Results

Performed by: Thierry Jean-Charles


Table 7.2.2-1: 6dB / 99% Bandwidth

Frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)
2412	7.7750	11.2200
2437	7.7475	11.1425
2462	7.7700	11.1750




Date: 20.FEB.2019 15:19:35

Figure 7.2.2-1: 6dB BW - Low Channel – 11 Mbps




Date: 19.FEB.2019 16:45:54

Figure 7.2.2-2: 6dB BW - Middle Channel- 11 Mbps


Date: 20.FEB.2019 15:24:30

Figure 7.2.2-3: 6dB BW - High Channel – 11 Mbps




Date: 20.FEB.2019 14:47:46

Figure 7.2.2-4: 99% OBW - Low Channel – 2 Mbps



Date: 19.FEB.2019 16:23:36

Figure 7.2.2-5: 99% OBW - Middle Channel – 2 Mbps



Date: 20.FEB.2019 14:54:57

Figure 7.2.2-6 99% OBW - High Channel – 2 Mbps

7.3 Peak Output Power – FCC: Section 15.247(b)(3); ISED Canada: RSS-247 5.4(d)

7.3.1 Measurement Procedure (Conducted Method)

The fundamental emission output power was measured in accordance with ANSI C63.10 Subclause 11.9.2.2.2 Method AVGSA-1. The RF output of the equipment under test was directly connected to the input of the spectrum analyzer through suitable attenuation.


The Maximum Output Power allowed is 1 Watt (30 dBm)

7.3.2 Measurement Results

Performed by: Thierry Jean-Charles


Table 7.3.2-1: RF Output Power

Frequency (MHz)	Power (dBm)
2412	3.84
2437	4.07
2462	3.96




Date: 20.FEB.2019 14:59:53

Figure 7.3.2-1: RF Output Power - Low Channel -- 2 Mbps



Date: 20.FEB.2019 14:36:32

Figure 7.3.2-2: RF Output Power - Middle Channel – 2 Mbps

Date: 20.FEB.2019 14:56:59

Figure 7.3.2-3: RF Output Power - High Channel – 2 Mbps

7.4 Band-Edge Compliance and Spurious Emissions


7.4.1 Band-Edge Compliance of RF Conducted Emissions – FCC: Section 15.247(d); ISED Canada: RSS-247 5.5

7.4.1.1 Measurement Procedure

The RF Conducted Emissions at the Band-Edges were measured in accordance with Subclause 11.11 of ANSI C63.10. The RF output port of the EUT was connected to the input of the spectrum analyzer through suitable attenuation. The EUT was investigated at the lowest and highest channel available to determine band-edge compliance. For each measurement the spectrum analyzer's RBW was set to 100 kHz, and the VBW was set to \geq 300 kHz.


7.4.1.2 Measurement Results

Performed by: Thierry Jean-Charles



Date: 20.FEB.2019 15:56:58

Figure 7.4.1.2-1: Lower Band-Edge – 1 Mbps



Date: 20.FEB.2019 16:22:47

Figure 7.4.1.2-2: Upper Band-Edge – 1 Mbps


7.4.2 RF Conducted Spurious Emissions – FCC: Section 15.247(d); ISED Canada: RSS-247 5.5

7.4.2.1 Measurement Procedure

The RF Conducted Spurious Emissions were measured in accordance with Subclause 11.11 of ANSI C63.10. The RF output port of the equipment under test was directly connected to the input of the spectrum analyzer. The EUT was investigated for conducted spurious emissions from 30 MHz to 26 GHz, 10 times the highest fundamental frequency. Measurements were made at the low, center and high channels of the EUT. For each measurement, the spectrum analyzer's RBW was set to 100 kHz and the VBW was set to 300 kHz. The peak Max Hold function of the analyzer was utilized.


7.4.2.2 Measurement Results

Performed by: Thierry Jean-Charles




Date: 20.FEB.2019 16:01:49

Figure 7.4.2.2-1: 30 MHz – 13.5 GHz – Low Channel – 1 Mbps





Date: 20.FEB.2019 16:06:22

Figure 7.4.2.2-2: 13.5 GHz – 26 GHz – Low Channel – 1 Mbps

Date: 20.FEB.2019 12:29:16

Figure 7.4.2.2-3: 30 MHz – 13.5 GHz – Middle Channel – 1 Mbps





Date: 20.FEB.2019 16:10:32

Figure 7.4.2.2-6: 13.5 GHz – 26 GHz – High Channel – 1 Mbps

7.4.3 Radiated Spurious Emissions into Restricted Frequency Bands – FCC: Sections 15.205, 15.209; ISED Canada: RSS-Gen 8.9, 8.10**7.4.3.1 Measurement Procedure**

Radiated emissions tests were made over the frequency range of 9 kHz to 26 GHz, 10 times the highest fundamental frequency. Each emission found to be in a restricted band as defined by section 15.205, including any emission at the operational band-edge, was compared to the radiated emission limits as defined in Section 15.209.

For measurements below 30 MHz, the receive antenna height was set to 1 m and the EUT was rotated through 360 degrees. The resolution bandwidth was set to 200 Hz below 150 kHz and to 9 kHz above 150 kHz.

The EUT was rotated through 360° and the receive antenna height was varied from 1m to 4m so that the maximum radiated emissions level would be detected. For frequencies below 1000 MHz, quasi-peak measurements were made using a resolution bandwidth RBW of 120 kHz and a video bandwidth VBW of 300 kHz. For frequencies above 1000 MHz, peak measurements are made with RBW of 1 MHz and VBW of 3 MHz. Average measurements are performed in the linear scale using VBW of 30 Hz.

7.4.3.2 Duty Cycle Correction

The EUT was configured to transmit at 100% duty cycle during the evaluation. No duty cycle correction factors were used during the evaluation.

7.4.3.3 Measurement Results

Performed by: Jean Rene

Radiated band-edge and spurious emissions found in the restricted frequency bands of 9 kHz to 26 GHz are reported in the tables below.

Table 7.4.3.3-1: Radiated Spurious Emissions Tabulated Data – 1 Mbps

Frequency (MHz)	Level (dBuV)		Antenna Polarity (H/V)	Correction Factors (dB)	Corrected Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
	pk	Qpk/Avg			pk	Qpk/Avg	pk	Qpk/Avg	pk	Qpk/Avg
Low Channel 2412 MHz										
2390	50.82	37.49	H	1.56	52.38	39.05	74.0	54.0	21.6	14.9
2390	54.73	40.59	V	1.56	56.29	42.15	74.0	54.0	17.7	11.8
4824	41.56	35.58	H	9.20	50.76	44.78	74.0	54.0	23.2	9.2
4824	44.16	39.80	V	9.20	53.36	49.00	74.0	54.0	20.6	5.0
Middle Channel 2437 MHz										
4874	40.63	33.01	H	9.45	50.08	42.46	74.0	54.0	23.9	11.5
4874	44.74	40.37	V	9.45	54.19	49.82	74.0	54.0	19.8	4.2
7311	37.96	24.78	H	14.40	52.36	39.18	74.0	54.0	21.6	14.8
7311	39.80	28.29	V	14.40	54.20	42.69	74.0	54.0	19.8	11.3
High Channel 2462 MHz										
2483.5	51.09	37.80	H	1.84	52.93	39.64	74.0	54.0	21.1	14.4
2483.5	53.97	42.28	V	1.84	55.81	44.12	74.0	54.0	18.2	9.9
2488.87	56.30	43.91	V	1.85	58.15	45.76	74.0	54.0	15.8	8.2
4924	40.68	34.81	H	9.71	50.39	44.52	74.0	54.0	23.6	9.5
4924	46.21	42.81	V	9.71	55.92	52.52	74.0	54.0	18.1	1.5
7386	38.37	25.01	H	14.62	52.99	39.63	74.0	54.0	21.0	14.4
7386	39.99	29.30	V	14.62	54.61	43.92	74.0	54.0	19.4	10.1

Notes:

- All emissions above 7.386 GHz were attenuated below the limits and the noise floor of the measurement equipment.**

7.4.4 Sample Calculation:

$$R_C = R_U + CF_T$$

Where:

CF _T	=	Total Correction Factor (AF+CA+AG)-DC (Average Measurements Only)
R _U	=	Uncorrected Reading
R _C	=	Corrected Level
AF	=	Antenna Factor
CA	=	Cable Attenuation
AG	=	Amplifier Gain
DC	=	Duty Cycle Correction Factor

Example Calculation: PeakCorrected Level: $50.82 + 1.56 = 52.38 \text{ dB}\mu\text{V/m}$ Margin: $74 \text{ dB}\mu\text{V/m} - 52.38 \text{ dB}\mu\text{V/m} = 21.62 \text{ dB}$ **Example Calculation: Average**Corrected Level: $37.49 + 1.56 = 39.05 \text{ dB}\mu\text{V/m}$ Margin: $54 \text{ dB}\mu\text{V/m} - 39.05 \text{ dB}\mu\text{V/m} = 14.95 \text{ dB}$

7.5 Power Spectral Density – FCC: Section 15.247(e); ISED Canada: RSS-247 5.2(b)

7.5.1 PSD Measurement Procedure (Conducted Method)

The power spectral density was measured in accordance with ANSI C63.10 Subclause 11.10.2 Method PKPSD (peak PSD). The RF output port of the EUT was directly connected to the input of the spectrum analyzer. Offset values were input for cable and external attenuation. The spectrum analyzer RBW was set to 3 kHz and VBW to 10 kHz. The Span was adjusted to 1.5 times the DTS bandwidth and the sweep time was set to auto. The measurements were performed using a Peak detector.


7.5.2 Measurement Results

Performed by: Thierry Jean-Charles

Results are shown below.


Table 7.5.2-1: Power Spectral Density – 11 Mbps

Frequency (MHz)	PSD (dBm)	Limit (dBm)	Margin (dB)
2412	-19.26	8.0	27.26
2437	-15.41	8.0	23.41
2462	-18.46	8.0	26.46




Date: 20.FEB.2019 15:38:55

Figure 7.5.2-1: Power Spectral Density - Low Channel



Date: 19.FEB.2019 16:50:44

Figure 7.5.2-2: Power Spectral Density - Middle Channel



Date: 20.FEB.2019 15:42:22

Figure 7.5.2-3: Power Spectral Density – High Channel

8 MEASUREMENT UNCERTAINTIES

The expanded laboratory measurement uncertainty figures (U_{Lab}) provided below correspond to an expansion factor (coverage factor) $k = 1.96$ which provide confidence levels of 95%.

Table 8-1: Measurement Uncertainties

Parameter	U_{Lab}
Occupied Channel Bandwidth	$\pm 0.009 \%$
RF Conducted Output Power	$\pm 1.15 \text{ dB}$
Power Spectral Density	$\pm 1.15 \text{ dB}$
Antenna Port Conducted Emissions	$\pm 1.15 \text{ dB}$
Radiated Emissions $\leq 1\text{GHz}$	$\pm 5.86 \text{ dB}$
Radiated Emissions $> 1\text{GHz}$	$\pm 4.65 \text{ dB}$
Temperature	$\pm 0.860 \text{ }^{\circ}\text{C}$
Radio Frequency	$\pm 2.832 \times 10^{-8}$
AC Power Line Conducted Emissions	$\pm 3.72 \text{ dB}$

9 CONCLUSION

In the opinion of TÜV SÜD America, Inc. the models TP-100, manufactured by Scully Signal Company, meets the requirements of FCC Part 15.247 and Industry Canada's Radio Standards Specification RSS-247 for the tests documented herein.

END REPORT