



47 CFR PART 15 C - BLUETOOTH

TEST REPORT

of

ViewBook 730

Brand Name: ViewSonic
Model Name: VS14145
Report No.: SH11030006B01
FCC ID: GSS-VS14145
IC: 4280A-VS14145

prepared for

ViewSonic Corporation

381 Brea Canyon Road Walnut, CA 91789, USA



Shenzhen Electronic Product Quality Testing Center Morlab Laboratory

3/F, Electronic Testing Building, Shahe Road, Xili,
Nanshan District, Shenzhen, 518055 P. R. China

Tel: +86 755 86130398

Fax: +86 755 86130218



NOTE: This test report can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen Electronic Product Quality Testing Center Morlab Laboratory. Any objections should be raised to us within thirty workdays since the date of issue.

TABLE OF CONTENTS

| | |
|--|-----------|
| 1. TEST CERTIFICATION..... | 4 |
| 2. GENERAL INFORMATION | 5 |
| 2.1 EUT Description | 5 |
| 2.2 Test Standards and Results | 7 |
| 2.3 Facilities and Accreditations..... | 7 |
| 2.3.1 Facilities | 7 |
| 2.3.2 Test Environment Conditions..... | 8 |
| 2.4 EUT Setup and Operating Conditions..... | 8 |
| 3. 47 CFR PART 15C&RSS 210 REQUIREMENTS | 9 |
| 3.1 Number of Hopping Frequency..... | 9 |
| 3.1.1 Requirement | 9 |
| 3.1.2 Test Description | 9 |
| 3.1.3 Test Result..... | 9 |
| 3.2 Peak Output Power | 11 |
| 3.2.1 Requirement | 11 |
| 3.2.2 Test Description | 11 |
| 3.2.3 Test Result..... | 11 |
| 3.3 20dB Bandwidth | 17 |
| 3.3.1 Definition | 17 |
| 3.3.2 Test Description | 17 |
| 3.3.3 Test Result..... | 17 |
| 3.4 Carried Frequency Separation..... | 23 |
| 3.4.1 Definition | 23 |
| 3.4.2 Test Description | 23 |
| 3.4.3 Test Result..... | 23 |
| 3.5 Time of Occupancy (Dwell time) | 24 |
| 3.5.1 Requirement | 24 |
| 3.5.2 Test Description | 24 |
| 3.5.3 Test Result..... | 24 |
| 3.6 Conducted Spurious Emissions | 27 |
| 3.6.1 Requirement | 27 |

| | | |
|-------------|--|-----------|
| 3.6.2 | Test Description | 27 |
| 3.6.3 | Test Result..... | 27 |
| 3.7 | Band Edge | 31 |
| 3.7.1 | Requirement..... | 31 |
| 3.7.2 | Test Description | 31 |
| 3.7.3 | Test Result..... | 32 |
| 3.8 | Conducted Emission..... | 34 |
| 3.8.1 | Requirement..... | 34 |
| 3.8.2 | Test Description | 34 |
| 3.8.3 | Test Result..... | 35 |
| 3.9 | Radiated Emission | 37 |
| 3.9.1 | Requirement..... | 37 |
| 3.9.2 | Test Description | 37 |
| 3.9.3 | Test Result..... | 39 |
| 3.10 | RECEIVER SPURIOUS EMISSIONS | 42 |
| 3.10.1 | Requirement of the standard | 42 |
| 3.10.2 | Test Procedure | 43 |
| 3.10.3 | Test Setup | 43 |
| 3.10.4 | Test Results | 44 |

1. TEST CERTIFICATION

Equipment under Test: ViewBook 730

Brand Name: ViewSonic

Model Name: VS14145

FCC ID: GSS-VS14145

IC : 4280A-VS14145

Applicant: ViewSonic Corporation

381 Brea Canyon Road Walnut, CA 91789, USA

Manufacturer: Technology (China)CO.,LTD.

4-12Building, No1388, ZhangdongRoad, Pudong New District, Shanghai
, P.R.China.

Test Standards: 47 CFR Part 15 Subpart C

RSS 210; RSS-GEN

Test Date(s): Mar 11, 2011 –Mar 11, 2011

Test Result: PASS

* We Hereby Certify That:

The equipment under test was tested by Shenzhen Electronic Product Quality Testing Center Morlab Laboratory. The test data, data evaluation, test procedures and equipment configurations shown in this report were made in accordance with the requirement of related FCC rules.

The test results of this report only apply for the tested sample equipment identified above. The test report shall be invalid without all the signatures of the test engineer, the reviewer and the approver.

Tested by:

Shi Feng

Dated:

2011.3.21

Reviewed by:

Zhang Jun

Dated:


2011.3.21

Approved by:

Wei Bei

Dated:

2011.3.21



2. GENERAL INFORMATION

2.1 EUT Description

| | |
|------------------------------------|--|
| EUT Type..... | ViewBook 730 |
| Model Name | VS14145 |
| Serial No. | (n.a, marked #1 by test site) |
| IMEI..... | (n.a, marked #1 by test site) |
| Modulation Type..... | Frequency Hopping Spread Spectrum (FHSS) |
| Frequency | The frequency range used is 2402MHz - 2480MHz (79 channels, at intervals of 1MHz); The frequency block is 2400MHz to 2483.5MHz. |
| Power Supply | Battery Brand name: TCL Mode Name.: 43100113N Capacitance: 5000mAh Rated voltage: 3.7V Charge limited: 4.8V Manufacturer: TCL HYPERPOWER BATTERIES INC No.3,Hechang Dongliu Rd.,Huitai Industrial Zone,Huicheng District, Huizhou City, Guangdong Province ,China |
| Ancillary Equipments | AC Adapter (Charger for Battery) Brand name: GPE Mode Name.: GPE125-050200-Z Rated Input: AC100~240V, 0.4A, 50/60Hz Rated Output: DC5V, 2000mA Manufacturer: Golden Profit Electronics Ltd. Sha Yao Administrative District, Shijie Town, Dongguan City, Guangdong Province, P.R. China. |
| Antenna Specification | Brand Name.: AzureWave Model Name: AW-GH381 Manufacturer: AzureWave Technologies, Inc. Gain: -0.3dBd gain (Max) |

Note 1: The EUT is a Mobile Phone, it contains Bluetooth Module operating at 2.4GHz ISM band; the frequencies allocated for the Bluetooth Module is $F(\text{MHz})=2402+1*n$ ($0 \leq n \leq 78$). The lowest, middle, highest channel numbers of the Bluetooth Module used and tested in this report are separately 0 (2402MHz), 39 (2441MHz) and 78 (2480MHz).



Note 2: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

2.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C (Bluetooth, 2.4GHz ISM band radiators) and RSS 210 for the EUT FCC ID Certification and IC ID Certification:

| No. | Identity | | Document Title |
|-----|-------------------------------------|---------|-------------------------|
| 1 | 47 CFR Part 15 (10-1-05 Edition) | RSS 210 | Radio Frequency Devices |

Test detailed items/section required by FCC rules and results are as below:

| No. | Section | | Description | Result |
|-----|---------------------|---------|--------------------------------|--------|
| 1 | 15.247(a) | A8.1(4) | Number of Hopping Frequency | PASS |
| 2 | 15.247(b) | A8.2(a) | Peak Output Power | PASS |
| 3 | 15.247(a) | A8.1(1) | 20dB Bandwidth | PASS |
| 4 | 15.247(a) | A8.1(2) | Carrier Frequency Separation | PASS |
| 5 | 15.247(a) | A8.1(4) | Time of Occupancy (Dwell time) | PASS |
| 6 | 15.247(c) | A7.2.2 | Conducted Spurious Emission | PASS |
| 7 | 15.247(c) | A8.5 | Band Edge | PASS |
| 8 | 15.207 | A8.5 | Conducted Emission | PASS |
| 9 | 15.209 15.247(c) | A8.5 | Radiated Emission | PASS |

2.3 Facilities and Accreditations

2.3.1 Facilities

Shenzhen Electronic Product Quality Testing Center Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L1659.

All measurement facilities used to collect the measurement data are located at Electronic Testing Building, Shahe Road, Xili, Nanshan District, Shenzhen 518055 CHINA. The test site is constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22; the FCC registration number is 741109.

2.3.2 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

| | |
|-----------------------------|---------|
| Temperature (°C): | 20 - 25 |
| Relative Humidity (%): | 40 - 60 |
| Atmospheric Pressure (kPa): | 96 |

2.4 EUT Setup and Operating Conditions

The EUT has been tested under Operating and standby condition. CMU200 was used to control the EUT for staying in continuous transmitting mode. Channel 0, 39 and 78 with highest data rate (DH1) (DH3) (DH5) are chosen for tested.

Mode 1: AC charge+EUT Mode;

Mode 2: Battery+EUT Mode;

Worst Case:GFSK(1 Mbps) Mode 1 Channel Low (2402MHz)、Mid (2441MHz) and High (2480MHz) were chosen for full testing.

After the preliminary scan GFSK, $\pi/4$ -DQPSK,8-DPSK. we found the modulation at GFSK producing the highest emission level, so evaluated we chosen the above modes (worst case) as a representative.

3. 47 CFR PART 15C&RSS 210 REQUIREMENTS


3.1 Number of Hopping Frequency

3.1.1 Requirement

According to FCC section 15.247(a)(1)(ii), frequency hopping systems operating in the 2400MHz to 2483.5MHz bands shall use at least 75 hopping frequencies.

3.1.2 Test Description

A. Test Setup:



The Bluetooth Module of the EUT, which is powered by the Battery, is coupled to the Spectrum Analyzer (SA) and the Bluetooth Service Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. During the measurement, the Bluetooth Module of the EUT is activated and controlled by the SS, and is set to operate under test mode transmitting 339 bytes DH5 packages at maximum power.

B. Equipments List:

| Description | Manufacturer | Model | Serial No. | Cal. Date | Cal. Due |
|-------------------|--------------|---------|------------|-----------|----------|
| Service Simulator | Anritsu | MT8852A | 6K00002788 | 2010.9 | 1year |
| Spectrum Analyzer | R&S | FSP30 | 101020 | 2010.9 | 1year |
| Spectrum Analyzer | Agilent | E4440A | MY46187763 | 2010.9 | 1year |
| Power Splitter | Weinschel | 1506A | NW521 | (n.a.) | (n.a.) |
| Attenuator 1 | Resnet | 10dB | (n.a.) | (n.a.) | (n.a.) |
| Attenuator 2 | Resnet | 3dB | (n.a.) | (n.a.) | (n.a.) |

3.1.3 Test Result


The Bluetooth Module operates at hopping-on test mode; the frequencies number employed is

counted to verify the Module's using the number of hopping frequency, compliance to Hopping Sequence and Equal Usage of the channels

A. Test Verdict:

| Frequency Block (MHz) | Measured Channel Numbers | Min. Limit | Refer to Plot | Verdict |
|-----------------------|--------------------------|------------|---------------|---------|
| 2400 - 2483.5 | 79 | 75 | Plot A | PASS |

B. Test Plot:



(Plot A: 2402MHz to 2480MHz)

3.2 Peak Output Power

3.2.1 Requirement

According to FCC section 15.247(b)(1), for frequency hopping systems that operates in the 2400MHz to 2483.5MHz band employing at least 75 hopping channels, the maximum peak output power of the intentional radiator shall not exceed 1Watt. For all other frequency hopping systems in the 2400MHz to 2483.5MHz band, it is 0.125Watts.

3.2.2 Test Description

See section 3.1.2 of this report.

3.2.3 Test Result

The Bluetooth Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

A. Test Verdict:

GFSK (1Mbps)

| Channel | Frequency (MHz) | Measured Output Peak Power | | | Limit | | Verdict |
|---------|-----------------|----------------------------|---------|---------------|-------|---|---------|
| | | dBm | W | Refer to Plot | dBm | W | |
| 0 | 2402 | -0.31 | 0.00093 | Plot A | 30 | 1 | PASS |
| 39 | 2441 | 0.21 | 0.00105 | Plot B | | | PASS |
| 78 | 2480 | 0.46 | 0.00111 | Plot C | | | PASS |


$\pi/4$ -DQPSK (2Mbps)

| Channel | Frequency (MHz) | Measured Output Peak Power | | | Limit | | Verdict |
|---------|-----------------|----------------------------|---------|---------------|-------|---|---------|
| | | dBm | W | Refer to Plot | dBm | W | |
| 0 | 2402 | -0.48 | 0.00090 | Plot D | 30 | 1 | PASS |
| 39 | 2441 | 0.04 | 0.00101 | Plot E | | | PASS |
| 78 | 2480 | 0.29 | 0.00107 | Plot F | | | PASS |

8-DPSK (3Mbps)


| Channel | Frequency (MHz) | Measured Output Peak Power | | | Limit | | Verdict |
|---------|-----------------|----------------------------|---------|---------------|-------|---|---------|
| | | dBm | W | Refer to Plot | dBm | W | |
| 0 | 2402 | -0.66 | 0.00086 | Plot G | 30 | 1 | PASS |
| 39 | 2441 | -0.01 | 0.00100 | Plot H | | | PASS |
| 78 | 2480 | 0.06 | 0.00101 | Plot I | | | PASS |

B. Test Plot:




Date: 23.NOV.2010 15:15:34

(Plot A:Channel = 2402)




Date: 23.NOV.2010 15:30:18

(Plot B:Channel = 2441)




Date: 23.NOV.2010 15:42:23

(Plot C: Channel = 2480)




Date: 23.NOV.2010 15:16:49

(Plot D: Channel = 2402)




Date: 23.NOV.2010 15:32:16

(Plot E: Channel = 2441)




Date: 23.NOV.2010 15:35:54

(Plot F: Channel = 2480)




Date: 23.NOV.2010 15:23:25

(Plot G:Channel = 2402)



Date: 23.NOV.2010 15:32:35

(Plot H:Channel = 2441



Date: 23.NOV.2010 15:36:35

(Plot I: Channel = 2480)

3.3 20dB Bandwidth

3.3.1 Definition

The 20dB bandwidth is known as the 99% emission bandwidth, or 20dB bandwidth ($10 \times \log 1\% = 20\text{dB}$) taking the total RF output power.

3.3.2 Test Description

See section 3.1.2 of this report.

3.3.3 Test Result

The Bluetooth Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to record the 20dB bandwidth of the Module.

A. Test Verdict:

The maximum 20dB bandwidth measured is 1.361MHz according to the table below.

GFSK (1Mbps)

| Channel | Frequency (MHz) | 20dB Bandwidth (MHz) | Refer to Plot |
|---------|-----------------|----------------------|---------------|
| 0 | 2402 | 1.017 | Plot A |
| 39 | 2441 | 1.017 | Plot B |
| 78 | 2480 | 1.017 | Plot C |


$\pi/4$ -DQPSK (2Mbps)

| Channel | Frequency (MHz) | 20dB Bandwidth (MHz) | Refer to Plot |
|---------|-----------------|----------------------|---------------|
| 0 | 2402 | 1.344 | Plot D |
| 39 | 2441 | 1.341 | Plot E |
| 78 | 2480 | 1.337 | Plot F |

8-DPSK (3Mbps)


| Channel | Frequency (MHz) | 20dB Bandwidth (MHz) | Refer to Plot |
|---------|-----------------|----------------------|---------------|
| 0 | 2402 | 1.356 | Plot G |
| 39 | 2441 | 1.361 | Plot H |
| 78 | 2480 | 1.361 | Plot I |

B. Test Plot:




Date: 23.NOV.2010 15:49:13

(Plot A: Channel = 2402)




Date: 23.NOV.2010 15:58:47

(Plot B: Channel = 2441)




Date: 23.NOV.2010 16:10:06

(Plot C: Channel = 2480)




Date: 23.NOV.2010 15:52:50

(Plot D: Channel = 2402)




Date: 23.NOV.2010 16:04:29

(Plot E: Channel = 2441)




Date: 23.NOV.2010 16:19:50

(Plot F: Channel = 2480)




Date: 23.NOV.2010 15:55:28

(Plot G: Channel = 2402)



Date: 23.NOV.2010 16:06:29

(Plot H: Channel = 2441)



Date: 23.NOV.2010 16:18:57

(Plot I: Channel = 2480)

3.4 Carried Frequency Separation

3.4.1 Definition

According to FCC section 15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.


3.4.2 Test Description

See section 3.1.2 of this report.

3.4.3 Test Result

The Bluetooth Module operates at hopping-on test mode.

For any adjacent channels (e.g. the channel 39 and 40 as showed in the Plot A), the Module does have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel (refer to section 3.3.3), whichever is greater. So, the verdict is PASS.



Date: 12.NOV.2010 08:26:17

(Plot A: Carried Frequency Separation)

3.5 Time of Occupancy (Dwell time)

3.5.1 Requirement

According to FCC section 15.247(a)(1)(iii), frequency hopping systems in the 2400 - 2483.5MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

3.5.2 Test Description

See section 3.1.2 of this report.

3.5.3 Test Result

The average time of occupancy on any channel within the Period can be calculated with formulas (for DH1 and DH5 package type):

$$\begin{aligned}\{\text{Total of Dwell}\} &= \{\text{Pulse Time}\} * (1600 / 6) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\} \\ \{\text{Period}\} &= 0.4s * \{\text{Number of Hopping Frequency}\}\end{aligned}$$

The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.


A. Test Verdict:

DH5

| Channel | Frequency (MHz) | Pulse Time | | Total of Dwell (ms) | Limit (ms) | Verdict |
|---------|-----------------|------------|---------------|---------------------|------------|---------|
| | | Ms | Refer to Plot | | | |
| 0 | 2402 | 2.853 | Plot A | 304.32 | 400 | PASS |
| 39 | 2441 | 2.869 | Plot B | 306.03 | | PASS |
| 78 | 2480 | 2.853 | Plot C | 304.32 | | PASS |


B. Test Plot:

Note: the following plots record the Pulse Time of the Module carrier.




Date: 14.NOV.2010 18:19:50

(Plot A: Channel = 2402)



Date: 14.NOV.2010 18:15:45

(Plot B: Channel = 2441)



Date: 14.NOV.2010 18:24:40

(Plot C: Channel = 2480)

3.6 Conducted Spurious Emissions

3.6.1 Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

3.6.2 Test Description

See section 3.1.2 of this report.

3.6.3 Test Result


The Bluetooth Module operates at hopping-off test mode. The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions.

A. Test Verdict:

| Channel | Frequency (MHz) | Measured Max. Out of Band Emission (dBm) | Refer to Plot | Limit (dBm) | | Verdict |
|---------|-----------------|--|---------------|---------------|-------------------------|---------|
| | | | | Carrier Level | Calculated -20dBc Limit | |
| 0 | 2402 | -27.56 | Plot A.1/A.2 | 1.05 | -18.95 | PASS |
| 39 | 2441 | -28.74 | Plot B.1/B.2 | 0.11 | -19.89 | PASS |
| 78 | 2480 | -28.85 | Plot C.1/C.2 | 1.33 | -18.67 | PASS |


B. Test Plot:

Note: the power of the Module transmitting frequency should be ignored.




Date: 14.NOV.2010 18:40:35

(Plot A.1: Channel = 0, 30MHz to 3GHz)




Date: 14.NOV.2010 18:41:32

(Plot A.2: Channel = 0, 3GHz to 25GHz)




Date: 14.NOV.2010 18:35:39

(Plot B.1: Channel = 39, 30MHz to 3GHz)




Date: 14.NOV.2010 18:37:29

(Plot B.2: Channel = 39, 3GHz to 25GHz)



Date: 14.NOV.2010 18:42:27

(Plot C.1: Channel = 78, 30MHz to 3GHz)



Date: 14.NOV.2010 18:43:51

(Plot C.2: Channel = 78, 3GHz to 25GHz)

3.7 Band Edge


3.7.1 Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.


3.7.2 Test Description

Test Setup:

Conducted Band Edge




Radiated Band Edge



3.7.3 Test Result


The Bluetooth Module operates at hopping-off test mode. The lowest and highest channels are tested to verify the band edge emissions.

Conducted Band Edge:



Date: 25.MAR.2011 14:25:55

(Plot A1: Channel = 0)



(Plot B1: Channel = 78)

Radiated Band Edge:

| Frequency (MHz) | Measure Level (dBuV/m) | Correct Factor (dB) | Reading Level (dBuV) | Limit (dBuV/m) | Detector Type | Antenna Polarity |
|-----------------|------------------------|---------------------|----------------------|----------------|---------------|------------------|
| 2400 | 49.06 | 0.35 | 48.71 | 74 | Peak | H |
| 2400 | 34.40 | 0.35 | 34.05 | 54 | Average | |
| 2400 | 47.59 | 0.35 | 47.24 | 74 | Peak | V |
| 2400 | 32.62 | 0.35 | 32.27 | 54 | Average | |
| 2483.5 | 56.97 | 0.64 | 56.33 | 74 | Peak | H |
| 2483.5 | 44.72 | 0.64 | 44.08 | 54 | Average | |
| 2483.5 | 55.06 | 0.64 | 54.42 | 74 | Peak | V |
| 2483.5 | 42.80 | 0.64 | 42.16 | 54 | Average | |

NOTE:

Measurement Level = Reading Level + Correct Factor

3.8 Conducted Emission

3.8.1 Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).


| Frequency range (MHz) | Conducted Limit (dB μ V) | |
|-----------------------|------------------------------|----------|
| | Quai-peak | Average |
| 0.15 - 0.50 | 66 to 56 | 56 to 46 |
| 0.50 - 5 | 56 | 46 |
| 0.50 - 30 | 60 | 50 |

NOTE:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.8.2 Test Description

A. Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.4:2003


The Bluetooth Module of the EUT is powered by the Battery charged with the AC Adapter which is powered by 120V, 60Hz AC mains supply. The factors of the site are calibrated to correct the reading. During the measurement, the Bluetooth Module is activated and controlled by the Bluetooth Service Supplier (SS) via a Common Antenna, and is set to operate under hopping-on test mode transmitting 339 bytes DH5 packages at maximum power.

B. Equipments List:

| Description | Manufacturer | Model | Serial No. | Cal. Date | Cal. Due |
|----------------------|--------------|-------------|------------|-----------|----------|
| Receiver | Agilent | E7405A | US44210471 | 2010.9 | 1year |
| LISN | Schwarzbeck | NSLK 8127 | 812744 | 2010.9 | 1year |
| Service Supplier | R&S | CMU200 | 100448 | 2010.9 | 1year |
| Pulse Limiter (20dB) | Schwarzbeck | VTSD 9561-D | 9391 | (n.a.) | (n.a.) |


3.8.3 Test Result

The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.



(Plot A: L Phase)

EMI_E NV216 Auto Test-N CISPR 22



(Plot B: N Phase)

3.9 Radiated Emission

3.9.1 Requirement

According to FCC section 15.247(c), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).


According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field Strength (μ V/m) | Measurement Distance (m) |
|-----------------|--------------------------------|-----------------------------|
| 0.009-0.490 | 2400/F(kHz) | 300 |
| 0.490-1.705 | 24000/F(kHz) | 30 |
| 1.705-30 | 30 | 30 |
| 30 - 88 | 100 | 3 |
| 88 - 216 | 150 | 3 |
| 216 - 960 | 200 | 3 |
| 960 - 1000 | 500 | 3 |
| Above 1000 | 500 | 3 |


In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table)

3.9.2 Test Description

A. Test Setup:



radiated emissions below 30MHz



radiated emissions above 30MHz

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4 (2003). The EUT was set-up on insulator 80cm above the Ground Plane. The set-up and test methods were according to ANSI C63.4.

The Bluetooth Module of the EUT is powered by the Battery charged with the AC Adapter which is powered by 120V, 60Hz AC mains supply. The Module is located in a 3m Semi-Anechoic Chamber;

the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading. During the measurement, the Bluetooth Module is activated and controlled by the Bluetooth Service Supplier (SS) via a Common Antenna, and is set to operate under hopping-on test mode transmitting 339 bytes DH5 packages at maximum power.

For the Test Antenna: In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength, the azimuth range of turntable was 0° to 360°, the receive antenna has two polarizations horizontal and vertical. When doing measurements above 1GHz, the EUT was placed within the 3dB beam width range of the horn antenna, and the EUT was tested in 3 orthogonal positions as recommended in ANSI C63.4 for Radiated Emissions and the worst-case data was presented.

B. Equipments List:

| Description | Manufacturer | Model | Serial No. | Cal. Date | Cal. Due |
|-----------------------|--------------|------------|------------|-----------|----------|
| System Simulator | Anritsu | MT8852A | 6K00002788 | 2010.9 | 1year |
| Spectrum Analyzer | R&S | FSP30 | 101020 | 2010.9 | 1year |
| Receiver | Agilent | E7405A | US44210471 | 2010.9 | 1year |
| Full-Anechoic Chamber | Albatross | 9m*6m*6m | (n.a.) | 2009.10 | 2year |
| Test Antenna - Bi-Log | Schwarzbeck | VULB 9163 | 9163-274 | 2010.9 | 1year |
| Test Antenna - Horn | Schwarzbeck | BBHA 9120C | 9120C-384 | 2010.9 | 1year |
| Test Antenna - Loop | R&S | HFH2-Z2 | 860004/001 | 2010.9 | 1year |

3.9.3 Test Result

A. Test Mode:

1. Channel 0: Frequency 2402MHz
2. Channel 39: Frequency 2441MHz
3. Channel 78: Frequency 2480Mhz

NOTE:

All test modes are performed, only the worst cases are recorded in this report.

B. Test Result for 9 kHz ~ 30 MHz:

| Frequency (MHz) | Level (dBuV) | Over Limit (dB) | Limit Line (dBuV) | Remark |
|-----------------|--------------|-----------------|-------------------|----------|
| -- | -- | -- | -- | See Note |


Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

C. Test Plots for 30 MHz ~ 10th Harmonic:



(Plot A.1: Antenna Horizontal)



(Plot A.2: Antenna Vertical)

3.10 RECEIVER SPURIOUS EMISSIONS

3.10.1 Requirement of the standard

According to RSS-GEN 4.10, the receiver shall be operated in the normal receive mode near the mid-point of the band over which the receiver is designed to operate. The search for spurious emissions shall be from the lowest frequency internally generated or used in the receiver (e.g. local oscillator, intermediate or carrier frequency), or 30 MHz, whichever is the higher, to at least 3 times the highest tuneable or local oscillator frequency, whichever is the higher, without exceeding 40 GHz. According to RSS-GEN 7.2.3.1, If the device has a detachable antenna of known antenna impedance, then the antenna conducted method is permitted in lieu of a radiated measurement. Receiver spurious emissions at any discrete frequency shall not exceed 2 nanowatts in the band 30-1000 MHz, or 5 nanowatts above 1 GHz.

| Limits for Conducted Receiver Spurious Emissions | |
|---|--------------|
| Frequency(MHz) | Limit |
| 30 – 1000 | 2nW |
| Above 1000 | 5nW |

According to RSS-GEN 7.2.3.2, for Radiated Measurement, all spurious emissions shall comply with the limits of Table below:


| Limits for Radiated Receiver Spurious Emissions | |
|--|--|
| Frequency(MHz) | Field Strength(μ V/m at 3metres) |
| 30 - 88 | 100 |
| 88 - 216 | 150 |
| 216 - 960 | 200 |
| Above 960 | 500 |

3.10.2 Test Procedure


Please refer to RSS-GEN section 4.10 and section 7.2.3 for the measurement methods.

3.10.3 Test Setup

Below 1GHz



Above 1GHz



3.10.4 Test Results

Conducted Receiver Spurious Emissions

1. TEST MODE: GFSK Transmitter Rx Mode

| Frequency(MHz) | Measure Result(nW) | Limit (nW) |
|----------------|--------------------|------------|
| 30 – 1000 | -- | 2 |
| Above 1000 | -- | 5 |

Radiated Receiver Spurious Emissions

2. TEST MODE: GFSK Transmitter Rx Mode

| No. | Frequency (MHz) | Antenna Polarization | Detector mode | Level ERP(dB μ V) | Limit (dB μ V) | Margin (dB) |
|-----|-----------------|----------------------|---------------|-----------------------|--------------------|-------------|
| 1 | 30 - 88 | Vertical | Peak | -- | 40 | >10 |
| 2 | 88 – 216 | Vertical | Peak | -- | 43.5 | >10 |
| 3 | 216 – 960 | Vertical | Peak | -- | 46 | >10 |
| 4 | 960 - 1000 | Vertical | Peak | -- | 54 | >10 |
| 5 | 1000 – 10000 | Vertical | Average | -- | 54 | >10 |
| 6 | 30 - 88 | Horizontal | Peak | -- | 40 | >10 |
| 7 | 88 – 216 | Horizontal | Peak | -- | 43.5 | >10 |
| 8 | 216 – 960 | Horizontal | Peak | -- | 46 | >10 |
| 9 | 960 - 1000 | Horizontal | Peak | -- | 54 | >10 |
| 10 | 1000 - 10000 | Horizontal | Average | -- | 54 | >10 |

Notes:

- 1) Both radiated measurement method and conducted measurement method were used. For the radiated method, the antenna polarization was set to vertical and horizontal respectively.
- 2) The measurement was performed at the mid operating frequencies.
- 3) “--” in the table above means that the emissions are too small to be measured and are at least 10 dB below the limit.

** END OF REPORT **