

FCC TEST REPORT

FCC ID : GTC01-9437

Applicant : INNCOM International, Inc

Address of Applicant : 277 West Main Street Niantic, CT 06357 United States of America.

Equipment Under Test (EUT) :

Product description : B574 Network Controller

Model No. : 01-9437

Frequency Range : 2405~2480MHz

Standards : FCC 15 Paragraph 15.247

Date of Test : March.24,2010

Test Engineer : Olic huang

Reviewed By : 

PERPARED BY:

Waltek Services (Shenzhen) Co., Ltd.

1/F, Fukangtai Building, West Baima Rd., Songgang Street, Baoan District, Shenzhen
518105, China

Tel :+86-755-27553488

Fax:+86-755-27553868

2 Contents

	Page
1 COVER PAGE.....	1
2 CONTENTS.....	2
3 TEST SUMMARY.....	4
4 GENERAL INFORMATION.....	5
4.1 CLIENT INFORMATION	5
4.2 GENERAL DESCRIPTION OF E.U.T.....	5
4.3 DETAILS OF E.U.T.	5
4.4 DESCRIPTION OF SUPPORT UNITS	5
4.5 STANDARDS APPLICABLE FOR TESTING.....	5
4.6 TEST FACILITY.....	6
4.7 TEST LOCATION.....	6
4.8 EQUIPMENT USED DURING TEST	7
5 CONDUCTED EMISSION TEST	10
5.1 TEST EQUIPMENT.....	10
5.2 TEST PROCEDURE	10
5.3 CONDUCTED TEST SETUP	11
5.4 EUT OPERATING CONDITION	11
5.5 CONDUCTED EMISSION LIMITS	12
5.6 CONDUCTED EMISSION TEST DATA	12
5.7 CONDUCTED EMISSION TEST SETUP VIEW.....	14
6 RADIATION EMISSION TEST.....	15
6.1 TEST EQUIPMENT.....	15
6.2 MEASUREMENT UNCERTAINTY.....	15
6.3 TEST PROCEDURE	15
6.4 RADIATED TEST SETUP	16
6.5 SPECTRUM ANALYZER SETUP.....	16
6.6 CORRECTED AMPLITUDE & MARGIN CALCULATION	17
6.7 SUMMARY OF TEST RESULTS.....	17
6.8 EUT OPERATING CONDITION	18
6.9 RADIATED EMISSIONS LIMIT ON PARAGRAPH 15.209	18
6.10 RADIATED EMISSIONS TEST RESULT.....	19
6.11 RADIATED EMISSION DATA	19
7 MAXIMUM PEAK OUTPUT POWER.....	24
8 HOPPING CHANNEL NUMBER.....	25
9 FREQUENCY SEPARATED.....	26
10 DWELL TIME.....	29

11 20-DB BANDWIDTH.....33

12 RADIATED SPURIOUS EMISSIONS INTO ADJACENT RESTRICTED BAND35

13 RF EXPOSURE TEST.....38

14 PHOTOGRAPHS OF TESTING.....40

15 PHOTOGRAPHS - CONSTRUCTIONAL DETAILS41

15.1 EUT – APPEARANCE VIEW41

15.2 EUT - FRONT VIEW41

15.3 EUT - BACK VIEW42

15.4 PCB1 - FRONT VIEW42

15.5 PCB1 - BACK VIEW43

15.6 PCB - COMPAGES VIEW43

15.7 PCB2 - FRONT VIEW44

15.8 PCB2 - BACK VIEW44

16 FCC ID LABEL.....45

3 Test Summary

Test Items	Test Requirement	Test Method	Limit / Severity	Result
Maximum peak output power	FCC Part 15:2008	ANSI C63.4: 2009	20dBm	PASS
Restricted Band	FCC Part 15:2008	ANSI C63.4: 2009	Note	PASS
Dwell time	FCC Part 15:2008	ANSI C63.4: 2009	Maximum:0.4 s	PASS
Channel separation	FCC Part 15:2008	ANSI C63.4: 2009	Channel separation at least 1MHz	PASS
Hopping channel No.	FCC Part 15:2008	ANSI C63.4: 2009	Total 16 channels	PASS
20-dB Bandwidth	FCC Part 15:2008	ANSI C63.4: 2009	Note	PASS
RF Exposure Test	FCC Part 15:2008	ANSI C63.4: 2009	Note	PASS
Mains Terminal Disturbance Voltage, 150kHz to 30MHz	FCC Part 15:2008	ANSI C63.4: 2009	N/A	PASS
Radiation Emission, 30MHz to 25GHz	FCC Part 15:2008	ANSI C63.4: 2009	N/A	PASS

Note : denote that for more details of the EUT , please refer to the relating test items as below .

Remark : the methods of measurement in all the test items were according to the FCC Public Notice DA 00-705 .

4 General Information

4.1 Client Information

Applicant: INNCOM International, Inc
Address of Applicant: 277 West Main Street Niantic, CT 06357 United States of America.

Manufacturer: Display Electronics (Songgang) Mfg. Co
Address of Manufacturer: No.1, Fifth Road, Yangyong Industrial Park, ShaPu community, Songgang, Bao An district, Shenzhen, China

4.2 General Description of E.U.T.

Product description: B574 Network Controller
Model No.: 01-9437

4.3 Details of E.U.T.

Power Supply: Adapter I/P : AC 100-120V~50-60Hz, 300mA
O/P: DC 12.0V, 1A

4.4 Description of Support Units

The EUT has been tested as an independent unit.

4.5 Standards Applicable for Testing

The customer requested FCC tests for a B574 Network Controller. The standards used were FCC 15 Paragraph 15.247, Paragraph 15.205, Paragraph 15.207, Paragraph 15.209, Paragraph 15.31, Paragraph 15.33, Paragraph 15.35.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC – Registration No.: 880581**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 880581, June 24, 2008.

- **IC – Registration No.: IC 7760A**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files. Registration IC7760A, July 24, 2008.

4.7 Test Location

All Emissions tests were performed at:-

1/F, Fukangtai Building, West Baima Rd., Songgang Street, Baoan District, Shenzhen 518105, Guangdong, China.

Remark : All the test results of the peripherals were conformed to the Fcc Verification requirements.

4.8 Equipment Used during Test

Equipment Name	Manufacturer Model	Equipment No	Internal No	Specification	Cal. Date	Due Date	Cert. No	Uncertainty
EMC Analyzer	Agilent/ E7405A	MY45114943	W2008001	9k-26.5GHz	Aug-09	Aug-10	Wws20081596	±1dB
Trilog Broadband Antenne	SCHWARZB ECK MESS-ELEKTROM / VULB9163	336	W2008002	30-3000 MHz	Aug-09	Aug-10		±1dB
Broad-band Horn Antenna	SCHWARZB ECK MESS-ELEKTROM / VULB9163	667	W2008003	1-18GHz	Aug-09	Aug-10		f<10 GHz: ±1dB 10GHz<f<18 GHz: ±1.5dB
Broadband Preamplifier	SCHWARZB ECK MESS-ELEKTROM / BBV 9718	9718-148	W2008004	0.5-18GHz	Aug-09	Aug-10		±1.2dB
10m Coaxial Cable with N-male Connectors usable up to 25GHz,	SCHWARZB ECK MESS-ELEKTROM / AK 9515 H	-	-	-	Aug-09	Aug-10		-
10m 50 Ohm Coaxial Cable with N-plug, individual length, usable up to 3(5)GHz, Connector	SCHWARZB ECK MESS-ELEKTROM / AK 9513				Aug-09	Aug-10		
Positioning Controller	C&C LAB/ CC-C-IF				N/A	N/A		
Color Monitor	SUNSP0/ SP-14C				N/A	N/A		
Test Receiver	ROHDE&SC HWARZ/ ESPI	101155	W2005001	9k-3GHz	Aug-09	Aug-10	Wws20080942	±1dB
EMI Receiver	Beijingkehuan	KH3931		9k-1GHz	Aug-09	Aug-10		
Two-Line V-Network	ROHDE&SC HWARZ/ ENV216	100115	W2005002	50Ω/50μH	Aug-09	Aug-10	Wws20080941	±10%

Equipment Name	Manufacturer Model	Equipment No	Internal No	Specification	Cal. Date	Due Date	Cert. No	Uncertainty
Absorbing Clamp	ROHDE&SC HWAZ/ MDS-21	100205	W2005003	impedance 50 Ω loss : 17 dB	Aug-09	Aug-10	Wws200 80943	± 1 dB
10m 50 Ohm Coaxial Cable with N-plug, individual length, usable up to 3(5)GHz, Connectors	SCHWARZB ECK MESS- ELEKTROM / AK 9514				Aug-09	Aug-10		
Digital Power Analyzer	Em Test AG/Switzerland/ DPA 500	V07451 03095	W2008012	Power: 2000VA Vol-range: 0-300V Freq_range: 10-80Hz	Aug-09	Aug-10	Wwd200 81185	Voltage distinguish:0.025% Power_freq distinguish:0.02Hz
Power Source	Em Test AG/Switzerland/ ACS 500	V07451 03096	W2008013	Vol-range: 0-300V Power_freq: 10-80Hz				
Electrostatic Discharge Simulator	Em Test AG/Switzerland/DITO	V07451 03094	W2008005	Contact discharge: 500V-10KV Air discharge: 500V-16.5KV	Aug-09	Aug-10	Wwc200 82400	7.5A current will be changed in $V_m=1.5V$
RF Generator	TESEQ GmbH/ NSG4070	25781	W2008008	Freq-range: 9K-1GHz RF voltage: -60 dBm- +10dBm	Aug-09	Aug-10	Wws200 81890	Power_freq distinguish:0.1Hz RF electricity distinguish 0.1 B
CDN M-Type	TESEQ GmbH/ CDN M016	25112	W2008009	Voltage correct factor 9.5 dB	Aug-09	Aug-10	Wwc200 82396	150K-80MHz: ± 1 dB 80-230MHz:-2- +3dB
EM-Clamp	TESEQ GmbH/ KEMZ 801	25453	W2008010	Freq_range: 0.15-1000 MHz	Aug-09	Aug-10	Wwc200 82397	0.3-400 MHz: ± 4 dB Other freq: ± 5 dB
Attenuator 6dB	TESEQ GmbH/ ATN6050	25365			Aug-09	Aug-10	Wws200 81597	

Equipment Name	Manufacturer Model	Equipment No	Internal No	Specification	Cal. Date	Due Date	Cert. No	Uncertainty
All Modules Generator	SCHAFFNER/6150	34579	W2008006	voltage:200V-4.4KV Pulse current: 100A-2.2KA	Aug-09	Aug-10	Wwc20082401	voltage: $\pm 10\%$ Pulse current: $\pm 10\%$
Capacitive Coupling Clamp	SCHAFFNER/CDN 8014	25311			Aug-09	Aug-10	Wwc20082398	-
Signal and Data Line Coupling Network	SCHAFFNER/CDN 117	25627	W2008011	1.2/50 μ S	Aug-09	Aug-10	Wwc20082399	-
AC Power Supply	TONGYUN/DTDGC-4				Aug-09	Aug-10	Wws20080944	-
Exposure Level Tester ELT-400	Narda Safety TEST Solutions/2304/03	M-0155	w2008022	Test freq range: 1—400kHz	Aug-09	Aug-10	Wwd20081191	Test uncertainty : 1—120kHz: $\pm 1.83\%$, 120 kHz-400 kHz: $\pm 4.06\%$
Magnetic Field Probe 100cm ²	Narda Safety TEST Solutions/2300/90.10	M-1070	w2008021	Test freq range: 1—400kHz				Test uncertainty : 1Hz-10Hz: $\pm 16.2\%$, 10Hz - 120kHz: $\pm 2.2\%$, 120 kHz-400 kHz: $\pm 4.7\%$
Active Loop Antenna Charger 10kHz-30MHz	Beijing Dazhi / ZN30900A	-	-	10kHz-30MHz	Aug-09	Aug-10		$\pm 1\text{dB}$

5 Conducted Emission Test

Test Requirement:	FCC Part15 Paragraph 15.207
Test Method:	Based on FCC Part15 Paragraph 15.207
Test Date:	March.23,2010
Frequency Range:	150kHz to 30MHz
Class:	Class B
Detector:	Peak for pre-scan (9kHz Resolution Bandwidth) Quasi-Peak & Average if maximised peak within 6dB of Average Limit

5.1 Test Equipment


Please refer to Section 5 this report.

5.2 Test Procedure

1. The EUT was connected to LISN and placed on a table.
2. The EUT was tested according to ANSI C63.4:2009. The frequency spectrum from 150kHz to 30MHz was investigated.
3. The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

5.3 Conducted Test Setup


The conducted emission tests were performed using the setup accordance with the ANSI C63.4: 2009, The specification used in this report was the FCC Part15 Paragraph 15.207 limits.



5.4EUT Operating Condition

Operating condition is according to ANSI C63.4: 2009.

- A. Setup the EUT and simulators as shown on follow.
- B. Enable RF signal and confirm EUT active.
- C. Modulate output capacity of EUT up to specification.




5.5Conducted Emission Limits

66-56 dBμV between 0.15MHz & 0.5MHz
56 dBμV between 0.5MHz & 5MHz
60 dBμV between 5MHz & 30MHz


Note: In the above limits, the tighter limit applies at the band edges.

5.6 Conducted Emission Test Data

Remark: the EUT was working at normal operated mode.
Live Line



Neutral Line



5.7 Conducted Emission Test Setup View



6 Radiation Emission Test

Test Requirement:	FCC Part15 Paragraph 15.247
Test Method:	Based on ANSI 63.4:2009
Test Date:	March.23,2010
Frequency Range:	30MHz to 25GHz
Measurement Distance:	3m
Detector:	Peak for pre-scan (120kHz resolution bandwidth) Quasi-Peak if maximised peak within 6dB of limit

6.1 Test Equipment

Please refer to Section 5 this report.

6.2 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in the field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.


Based on ANSI C63.4: 2009, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at WALTEK SERVICES EMC Lab is +/-5.03 dB.

6.3 Test Procedure

1. The adapter uses in the equipment under test for radiated emissions test.
2. The radiation emission should be tested under 3-axes(X,Y,Z) position(X denotes lying on the table,Y denotes side stand and Z denotes vertical stand),After pre-test,It was found that the worse radiation emission was get at the X position.
So the data shown was the X position only.
3. Maximizing procedure was performed on the six (6) highest emissions to ensure EUT is compliant with all installation combinations.
4. All data was recorded in the peak and average detection mode.
5. The EUT was under working mode during the final qualification test and the configuration was used to represent the worst case results.

6.4Radiated Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.4: 2009, The specification used in this report was the FCC Part15 Paragraph 15.209 limits and Paragraph 15.247 limits.



6.5 Spectrum Analyzer Setup

According to FCC Part15 Paragraph 15.247 Rules, the system was tested to 25000 MHz. Below 1GHz

Start Frequency	30 MHz
Stop Frequency	1000 MHz
Sweep Speed	Auto
IF Bandwidth.....	120 kHz
Video Bandwidth	100KHz
Quasi-Peak Adapter Bandwidth	120 kHz
Quasi-Peak Adapter Mode.....	Normal
Resolution Bandwidth	100KHz

Above 1GHz

Start Frequency	1000 MHz
Stop Frequency	25000MHz
Sweep Speed	Auto
IF Bandwidth.....	120 kHz
Video Bandwidth	1MHz
Quasi-Peak Adapter Bandwidth	120 kHz
Quasi-Peak Adapter Mode.....	Normal
Resolution Bandwidth	1MHz

6.6Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

Corr. Ampl. = Indicated Reading + Antenna Factor + Cable Factor – Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dBμV means the emission is 7dBμV below the maximum limit for Class B. The equation for margin calculation is as follows:

Margin = Corr. Ampl. – Class B Limit

6.7 Summary of Test Results

According to the data in section 7.11, the EUT complied with the FCC Part15 Paragraph 15.247 standards.

6.8 EUT Operating Condition

The same as section 6.4 of this report.

Let the EUT work in test mode and test it.

6.9 Radiated Emissions Limit on Paragraph 15.209

Frequency(MHZ)	Distance(m)	Field strength(dBuV/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

- Note:**
- (1) $RF\ Voltage(dBuV) = 20 \log RF\ Voltage(uV)$
 - (2) In the Above Table, the tighter limit applies at the band edges.
 - (3) Distance refers to the distance in meters between the measuring instrument antenna.
 - (4) The emission limit in this paragraph is based on measurement instrumentation employing an average detector. Measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
 - (5) Above 1GHz, make a Peak and average measurements for all emissions, Limit for peak is 74dBuV/m, According to Part 15.35(b) and average is 54BuV/m.

6.10 Radiated Emissions Test Result

Formula of conversion factors: the field strength at 3m was established by adding
The meter reading of the spectrum analyzer (which is set to read in units of dBuV/m)
To the antenna correction factor supplied by the antenna manufacturer. The antenna
Correction factors are stated in terms of dB. The gain of the pressetor was accounted
For in the spectrum analyser meter reading.

Example:

Freq(MHz) Meter Reading +ACF=FS

33 20dBuV+10.36dB=30.36dBuV/m @3m

6.11 Radiated Emission Data

A. Test Item: Radiated Emission Data
Test Voltage: AC 120V
Test Mode: TX On
Temperature: 25.5°C
Humidity: 51%RH
Test Result: PASS

Remarks: 30-1000MHz radiation test no significant emissions above the equipment noise floor
were detected.

And the below is the Fundamental and Harmonic .

Frequency (MHz)	Detect or	Antenna Polarization	Emission Level (dBuV/m)	FCC Part15 Subpart C Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Turntable Angle (°)
Low frequency							
2405	AV	Vertical	84.36		(Fund.)	1.1	0
4810	AV	Vertical	48.63	54.00	5.37	1.2	10
7215	AV	Vertical	42.36	54.00	11.64	1.1	20
9620	AV	Vertical	41.36	54.00	12.64	1.1	60
12025	AV	Vertical	40.25	54.00	13.75	1.2	90
14430	AV	Vertical	39.26	54.00	14.74	1.4	20
16835	AV	Vertical	37.56	54.00	16.44	1.7	120
19240	AV	Vertical	32.63	54.00	21.37	1.5	100
21645	AV	Vertical	31.03	54.00	22.97	1.6	120
24050	AV	Vertical	31.25	54.00	22.75	1.2	45

2405	AV	Horizontal	82.36		(Fund.)	1.1	10
4810	AV	Horizontal	47.62	54.00	6.38	1.2	120
7215	AV	Horizontal	38.96	54.00	15.04	1.1	10
9620	AV	Horizontal	36.97	54.00	17.03	1.2	1130
12025	AV	Horizontal	38.59	54.00	15.41	1.1	45
14430	AV	Horizontal	38.63	54.00	15.37	1.2	110
16835	AV	Horizontal	36.62	54.00	17.38	1.5	10
19240	AV	Horizontal	35.26	54.00	18.74	1.1	30
21645	AV	Horizontal	33.23	54.00	20.77	1.2	120
24050	AV	Horizontal	32.31	54.00	21.69	1.0	10
2405	PK	Vertical	92.11		(Fund.)	1.0	230
4810	PK	Vertical	65.36	74.00	8.64	1.0	130
7215	PK	Vertical	52.36	74.00	21.64	1.1	10
9620	PK	Vertical	51.26	74.00	22.74	1.1	100
12025	PK	Vertical	46.96	74.00	27.04	1.1	160
14430	PK	Vertical	48.59	74.00	25.41	1.1	120
16835	PK	Vertical	46.96	74.00	27.04	1.2	30
19240	PK	Vertical	46.36	74.00	27.64	1.3	130
21645	PK	Vertical	43.63	74.00	30.37	1.2	45
24050	PK	Vertical	43.01	74.00	30.99	1.2	135
2405	PK	Horizontal	91.52		(Fund.)	1.3	10
4810	PK	Horizontal	62.36	74.00	11.64	1.1	90
7215	PK	Horizontal	48.36	74.00	25.64	1.3	120
9620	PK	Horizontal	46.35	74.00	27.65	1.2	10
12025	PK	Horizontal	45.63	74.00	28.37	1.1	110
14430	PK	Horizontal	42.36	74.00	31.64	1.5	150
16835	PK	Horizontal	43.62	74.00	30.38	1.1	30
19240	PK	Horizontal	43.25	74.00	30.75	1.2	120
21645	PK	Horizontal	43.11	74.00	30.89	1.2	150
24050	PK	Horizontal	42.32	74.00	31.68	1.2	20
Middle frequency							
2440	AV	Vertical	83.36		(Fund.)	1.0	0
4880	AV	Vertical	49.36	54.00	4.64	1.0	20
7320	AV	Vertical	43.65	54.00	10.35	1.1	10

9760	AV	Vertical	42.65	54.00	11.35	1.0	20
12200	AV	Vertical	43.63	54.00	10.37	1.2	10
14640	AV	Vertical	41.36	54.00	12.64	1.1	120
17080	AV	Vertical	36.96	54.00	17.04	1.1	10
19520	AV	Vertical	35.36	54.00	18.64	1.5	30
21960	AV	Vertical	35.03	54.00	18.97	1.1	50
24400	AV	Vertical	36.36	54.00	17.64	1.2	50
2440	AV	Horizontal	81.52		(Fund.)	1.0	120
4880	AV	Horizontal	45.36	54.00	8.64	1.0	90
7320	AV	Horizontal	42.36	54.00	11.64	1.0	20
9760	AV	Horizontal	40.21	54.00	13.79	1.0	110
12200	AV	Horizontal	38.58	54.00	15.42	1.0	120
14640	AV	Horizontal	38.74	54.00	15.26	1.2	0
17080	AV	Horizontal	35.63	54.00	18.37	1.0	45
19520	AV	Horizontal	36.36	54.00	17.64	1.1	90
21960	AV	Horizontal	36.53	54.00	17.47	1.2	20
24400	AV	Horizontal	34.65	54.00	19.35	1.1	120
2440	PK	Vertical	91.44		(Fund.)	1.1	10
4880	PK	Vertical	63.36	74.00	10.64	1.1	20
7320	PK	Vertical	51.36	74.00	22.64	1.6	130
9760	PK	Vertical	51.24	74.00	22.76	1.0	140
12200	PK	Vertical	45.63	74.00	28.37	1.2	180
14640	PK	Vertical	46.36	74.00	27.64	1.2	30
17080	PK	Vertical	45.61	74.00	28.39	1.0	10
19520	PK	Vertical	43.36	74.00	30.64	1.2	120
21960	PK	Vertical	42.35	74.00	31.65	1.1	120
24400	PK	Vertical	41.02	74.00	32.98	1.1	110
2440	PK	Horizontal	89.36		(Fund.)	1.1	10
4880	PK	Horizontal	61.35	74.00	12.65	1.0	135
7320	PK	Horizontal	46.98	74.00	27.02	1.2	190
9760	PK	Horizontal	45.36	74.00	28.64	1.2	20
12200	PK	Horizontal	42.35	74.00	31.65	1.2	110
14640	PK	Horizontal	41.02	74.00	32.98	1.1	120
17080	PK	Horizontal	41.01	74.00	32.99	1.2	210

19520	PK	Horizontal	39.89	74.00	34.11	1.1	200
21960	PK	Horizontal	38.65	74.00	35.35	1.1	30
24400	PK	Horizontal	37.88	74.00	36.12	1.0	120
High frequency							
2480	AV	Vertical	81.63		(Fund.)	1.1	10
4960	AV	Vertical	50.11	54.00	3.89	1.2	110
7440	AV	Vertical	42.69	54.00	11.31	1.1	20
9920	AV	Vertical	41.22	54.00	12.78	1.1	135
12400	AV	Vertical	41.35	54.00	12.65	1.2	50
14880	AV	Vertical	42.31	54.00	11.69	1.4	60
17360	AV	Vertical	38.74	54.00	15.26	1.7	10
19840	AV	Vertical	35.62	54.00	18.38	1.5	150
22320	AV	Vertical	36.87	54.00	17.13	1.6	10
24800	AV	Vertical	38.77	54.00	15.23	1.2	50
2480	AV	Horizontal	83.11		(Fund.)	1.0	10
4960	AV	Horizontal	46.35	54.00	7.65	1.2	110
7440	AV	Horizontal	43.26	54.00	10.74	1.1	10
9920	AV	Horizontal	40.21	54.00	13.79	1.2	120
12400	AV	Horizontal	39.32	54.00	14.68	1.5	70
14880	AV	Horizontal	37.54	54.00	16.46	1.2	140
17360	AV	Horizontal	35.63	54.00	18.37	1.5	120
19840	AV	Horizontal	36.36	54.00	17.64	1.1	10
22320	AV	Horizontal	34.52	54.00	19.48	1.2	15
24800	AV	Horizontal	33.21	54.00	20.79	1.5	10
2480	PK	Vertical	89.69		(Fund.)	1.5	10
4960	PK	Vertical	62.58	74.00	11.42	1.1	10
7440	PK	Vertical	51.36	74.00	22.64	1.1	120
9920	PK	Vertical	52.32	74.00	21.68	1.4	110
12400	PK	Vertical	46.35	74.00	27.65	1.2	45
14880	PK	Vertical	46.36	74.00	27.64	1.1	190
17360	PK	Vertical	44.44	74.00	29.56	1.2	160
19840	PK	Vertical	42.21	74.00	31.79	1.2	110
22320	PK	Vertical	41.02	74.00	32.98	1.1	160
24800	PK	Vertical	41.02	74.00	32.98	1.4	90

2480	PK	Horizontal	92.65		(Fund.)	1.1	120
4960	PK	Horizontal	61.35	74.00	12. 65	1.1	110
7440	PK	Horizontal	50.36	74.00	23. 64	1.1	15
9920	PK	Horizontal	45.63	74.00	28. 37	1.2	110
12400	PK	Horizontal	45.36	74.00	28. 64	1.2	60
14880	PK	Horizontal	45.61	74.00	28. 39	1.5	70
17360	PK	Horizontal	43.36	74.00	30. 64	1.1	10
19840	PK	Horizontal	42.35	74.00	31. 65	1.5	110
22320	PK	Horizontal	40.36	74.00	33. 64	1.2	135
24800	PK	Horizontal	36.98	74.00	37. 02	1.1	45

7 Maximum Peak Output Power

Test Requirement:	FCC Part15 Paragraph 15.247
Test Method:	Based on ANSI 63.4:2009
Test Date:	March.23,2010
Test mode:	Compliance test in the worse case: Tx Lower/Tx Middle/Tx Upper
Requirements:	Regulation 15.247(b) The limit of Maximum Peak Output Power Measurement is 0.125W

Test procedure:

The following test procedure as below:

The transmitter output (antenna port) was connected to the spectrum analyzer.EUT and its simulators are placed on a table, let EUT working in test mode,then test it.

The bandwidth of the fundamental frequency was measured with the spectrum analyser using 100kHz RBW and 100kHz VBW.

Test Result: The unit does meet the FCC requirements.

Test Channel	Fundamental Frequency(MHz)	Output Power (mW)	Limit (W)	Power output level
Lower	2405	8.11	0.125	conducted
Middle	2440	8.11	0.125	conducted
Upper	2480	7.58	0.125	conducted

Note: The EUT uses 16 channels ,and according to 47 CFR Part 15 Subpart C Section 15.247 (b),the the maximum allowable power for this device is 0.125W.

8 Hopping Channel Number

Test Requirement: FCC Part15 C

Test Method: Based on FCC Part15 Paragraph 15.247

Test Date: March.23,2010


Test mode: The EUT work in test mode(Tx) and test it

Requirements: Regulation 15.247(b) For frequency hopping systems operating In the 2400-2483.5MHz band employing at least 15 hopping channels.

Test result: The total number of channels would be 16 channels.

The unit does meet the FCC requirements.

Please refer the graph as below:



9 Frequency Separated

The requirements in this clause are only applicable to equipment using frequency hopping spread spectrum (FHSS) modulation.

Channel Separated

Definition: A hopping channel is any of the centre frequencies defined within the hopping sequence of a FHSS system.

Limit: Non-adaptive frequency hopping system shall make use of non-overlapping channels separated by the channel bandwidth as measured at 20dB below peak power.

The hopping channels defined within a hopping sequence shall be at least 1MHz apart(channel separation)

Operating Environment:

Temperature: 25.50 °C

Humidity: 51 % RH

Barometric Pressure: 1012 mbar

EUT Operation Condition:


The EUT was programmed to be in continuously transmitting mode.

Test Result: PASS


Test Channel	Channel Separation	PASS/FAIL
Lower Channels	5MHz	Pass
Middle Channels	5MHz	Pass
Upper Channels	5MHz	Pass

Please refer to the below photos for more details


Lower Channel



Middle Channel



Upper Channel



10 Dwell time

The dwell time is the time spent at a particular frequency during any single hop.

Limit: the maximum dwell time shall be less than 0.4s.

Operating Environment:

Temperature: 25.5 °C

Humidity: 51 % RH

Barometric Pressure: 1012 mbar

EUT Operation Condition:

The EUT was programmed to be in continuously transmitting mode.

11.2 Test Procedure

The EUT output antenna port was connected to the spectrum analyzer. Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz, and the frequency span to zero span, measure the maximum time duration of one single pulse. So, the Dwell Time can be calculated as follows:

$$T = T_{\text{on-time}} * N_{\text{times}} / 1S * 0.4 * 16 \leq 0.4S.$$

11.3 Test Result: PASS


Please refer to the below photos for more details.

Low Channel

Dwell time of each occupation in this channel as follows:
 $0.0000198 \times 800 / 1\text{S} \times 0.4 \times 16 = 0.1014 < 0.4\text{S}$

Test Result: PASS

The Results are not be greater than 0.4 seconds.




Middle Channel

Dwell time of each occupation in this channel as follows:

$0.0000199 \times 800 / 1S \times 0.4 \times 16 = 0.1014 < 0.4S$

Test Result: PASS

The Results are not be greater than 0.4 seconds.




Upper Channel

Dwell time of each occupation in this channel as follows:
 $0.0000198 \times 800 / 1 \times 0.4 \times 16 = 0.1014 < 0.4 \text{S}$

Test Result: PASS

The Results are not be greater than 0.4 seconds.



11 20-dB Bandwidth

Test Requirement: FCC Part15 C
Test Method: Based on FCC Part15 Paragraph 15.247
Test Date: March.23,2010
Test mode: The EUT work in test mode(Tx) and test it


Test Procedure

- 1. The transmitter output (antenna port) was connected to the spectrum analyzer.
- 2. The bandwidth of the fundamental frequency was measure by spectrum analyser with 100KHz RBW and 100KHz VBW.The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power 20dB.


Test Result

Please refer the graph as below:


Lower Channel



Middle Channel



Upper Channel



12 Radiated spurious emissions into adjacent restricted band

Test Requirement:	FCC Part15 Paragraph 15.205
Test Method:	Based on FCC Part 15 Paragraph 15.247
Test Date:	March.23,2010
Requirements:	The EUT work in test mode(Tx) and test it


Requiments:

emissions that fall in the restricted bands(15.205).Above 1000MHz, compliance with the emissions limits in section 15.209 shall be demonstrated based on the average value of the measured emissions,The provisions in section 15.35 apply to these measurements.

Test procedure:

An in band field strength measurement of the fundamental emission using the RBW and detector function required by C63.4-2009 and FCC Rules.The procedure was repeated with an average detector and a plot made.The calculated field strength in the adjacent restricted band is presented below.

Lower bandedge/ restricted band (Peak Value)




For 2400MHz bandedge checked with 2405MHz frequency operated,the delta shown at the plot is $93.46-58.97=34.49\text{dB}$ for peak detector mode.

The fundamental emission at the frequency of 2405MHz is 92.11dBuV/m for peak detector mode,so the bandedge emission is $92.11-34.49=57.62\text{dBuV/m}$ for peak detector mode.Here the limit for the emission is 74 dBuV/m for the peak detector,so the result passed.

And the same as the average detector, the bandedge emission is $84.36-34.49=49.87\text{dBuV/m}$. Here the limit for the emission is 54.0dBuV/m for the average detector. the bandedge emission is lower than the average limit, so the result passed.

Remark: the radation test data,please refer to the section 6.11 .

Upper Bandedge/ Restricted Band (Peak Value)



For 2483.5MHz bandedge checked with 2480MHz frequency operated,the delta shown at the plot is 91.88-59.08=32.70dB for peak detector mode.

The fundamental emission at the frequency of 2480MHz is 92.65dBuV/m for peak detector mode,so the bandedge emission is 92.65-32.70=59.95dBuV/m for peak detector mode.Here the limit for the emission is 74 dBuV/m for the peak detector,so the result passed.

And the same as the average detector, the bandedge emission is 83.11-32.70=50.41dBuV/m. Here the limit for the emission is 54.0dBuV/m for the average detector. the bandedge emission is lower than the average limit, so the result passed.

Remark: the radation test data,please refer to the section 6.11

13 RF Exposure Test

Test Requirement: FCC Part 2 Subpart J
 Test Method: Based on FCC Part 15 Paragraph 15.247
 Test Date: March.23,2010
 Requirements: The EUT work in test mode(Tx) and test it

Requiments:

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

The procedures / limit

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to


$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
-4.65	0.343	18.18	8.11	0.000554	1	Complies
-4.65	0.343	18.18	8.11	0.000554	1	Complies
-4.36	0.366	17.59	7.58	0.000552	1	Complies

14 Photographs of Testing

Radiation Emission Test View For 30MHz-1000MHz




Radiation Emission Test View For 1GHz-25GHz

15 Photographs - Constructional Details


15.1 EUT – Appearance View




15.2 EUT - Front View




15.3 EUT - Back View




15.4 PCB1 - Front View




15.5 PCB1 - Back View




15.6 PCB - Compages View



15.7 PCB2 - Front View



15.8 PCB2 - Back View



16 FCC ID Label

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:(1)this device may not cause harmful interference,and (2) this device must accept any interference received, including interference that may cause undesired operation.

The Label must not be a stick-on paper. The Label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Proposed Label Location on EUT
EUT Bottom View/proposed FCC Mark Location

