

FCC 15.249 2.4GHz Report

for

ACCO Brands, Inc.

**1500 Fashion Island Blvd., 3rd Floor, San Mateo,
CA 94404, USA**

**Product Name : Advanced Fit Slim
Wireless Keyboard**

Model Name : M01438-K

Brand : Kensington

FCC ID : GV3M01438-K

**Prepared by: : AUDIX Technology Corporation,
EMC Department**



The test report is based on a single evaluation of one sample of the above-mentioned products. It does not imply an assessment of the whole production and does not permit the use of the test lab logo.
The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST or any agency of the U.S. Government.

TABLE OF CONTENTS

Description	Page
TEST REPORT CERTIFICATION	3
1. REVISION RECORD OF TEST REPORT	4
2. SUMMARY OF TEST RESULTS	5
3. GENERAL INFORMATION	6
3.1. Description of Application.....	6
3.2. Description of EUT.....	6
3.3. Antenna Information.....	7
3.4. EUT Specifications Assessed in Current Report	7
3.5. Description of Key Components.....	7
3.6. Test Configuration	8
3.7. Tested Supporting System List.....	8
3.8. Setup Configuration.....	8
3.9. Operating Condition of EUT	8
3.10. Description of Test Facility	9
3.11. Measurement Uncertainty.....	9
4. MEASUREMENT EQUIPMENT LIST	10
4.1. Radiated Emission Measurement.....	10
4.2. RF Conducted Measurement	10
5. CONDUCTED EMISSION MEASUREMENT	11
6. RADIATED EMISSION	12
6.1. Block Diagram of Test Setup.....	12
6.2. Radiated Emission Limits.....	13
6.3. Test Procedure	14
6.4. Measurement Result Explanation	15
6.5. Test Results.....	15
7. EMISSION BANDWIDTH MEASUREMENT	16
7.1. Block Diagram of Test Setup.....	16
7.2. Test Procedure	16
7.3. Test Results.....	16
8. DEVIATION TO TEST SPECIFICATIONS.....	17
APPENDIX A TEST PHOTOGRAPHS	
APPENDIX B EUT PHOTOGRAPHS	

TEST REPORT CERTIFICATION

Applicant : ACCO Brands, Inc.
Manufacturer : ACCO Brands, Inc.
EUT Description
(1) Product : Advanced Fit Slim Wireless Keyboard
(2) Model : M01438-K
(3) Brand : Kensington
(4) Power Rating : DC 3V

Applicable Standards:

47CFRFCC Part 15 Subpart C
ANSI C63.10:2013

Audix Technology Corp. tested the equipment mentioned in accordance with the requirements set forth in the above standards. Test results indicate that the equipment tested is capable of demonstrating compliance with the requirements as documented within this report.

Audix Technology Corp. does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens and samples.

Date of Report: 2019. 04. 12

Reviewed by:

Annie Yu (Annie Yu/Administrator)

Approved by:

Ben Cheng (Ben Cheng/Manager)

1. REVISION RECORD OF TEST REPORT

Edition No	Issued Data	Revision Summary	Report Number
0	2019. 04. 12	Original Report	EM-F190128

2. SUMMARY OF TEST RESULTS

Rule	Description	Results
15.207	Conducted Emission	N/A, Note
15.205/ 15.209/ 15.249(a)	Radiated Band Edge and Radiated Spurious Emission Fundamental Frequency	PASS
15.215	Emission Bandwidth	PASS
15.203	Antenna Requirement	PASS
Note: The EUT only employs battery power for operation, so it is unnecessary to test.		

3. GENERAL INFORMATION

3.1. Description of Application

Applicant	ACCO Brands, Inc. 1500 Fashion Island Blvd., 3rd Floor, San Mateo, CA 94404, USA
Manufacturer	ACCO Brands, Inc. 1500 Fashion Island Blvd., 3rd Floor, San Mateo, CA 94404, USA
Product	Advanced Fit Slim Wireless Keyboard
Model	M01438-K
Brand	Kensington

3.2. Description of EUT

Test Model	M01438-K
Serial Number	N/A
Power Rating	DC 3V
RF Features	2.4GHz
Transmit Type	1T1R
Sample Status	Production
Date of Receipt	2019. 03. 29
Date of Test	2019. 04. 08 ~ 11
Interface Ports of EUT	None
Accessories Supplied	None

3.3. Antenna Information

No.	Antenna Part Number	Manufacture	Antenna Type	Frequency (MHz)	Max Gain (dBi)
1	---	---	PCB Antenna	2408-2474	1.8

3.4. EUT Specifications Assessed in Current Report

Mode	Fundamental Range (MHz)	Channel Number	Modulation	Data Rate
2.4GHz	2408-2474	34	FSK	1Mbps

Channel List			
Channel Number	Frequency (MHz)	Channel Number	Frequency (MHz)
1	2408	18	2442
2	2410	19	2444
3	2412	20	2446
4	2414	21	2448
5	2416	22	2450
6	2418	23	2452
7	2420	24	2454
8	2422	25	2456
9	2424	26	2458
10	2426	27	2460
11	2428	28	2462
12	2430	29	2464
13	2432	30	2466
14	2434	31	2468
15	2436	32	2470
16	2438	33	2472
17	2440	34	2474


3.5. Description of Key Components

None

3.6. Test Configuration

Mode	Duty Cycle (x)	T (ms)	Duty Cycle Factor (dB)
2.4GHz	0.494	7.9	N/A

Note: When duty cycle is less than 98% (0.98) that duty cycle factor $10\log(1/x)$ is needed to add in conducted test items measured in average detector.



Item	Mode	Test Channel
Radiated Test Case	Radiated Band Edge ^{Note1}	2.4GHz / 1/34
	Radiated Spurious Emission (30MHz-1GHz) ^{Note1}	2.4GHz / 34
	Radiated Spurious Emission (Above 1GHz) ^{Note1}	2.4GHz / 1/17/34
	Fundamental Frequency	2.4GHz / 1/17/34
	Occupied Bandwidth 99% Power	2.4GHz / 1/17/34

Note 1: Mobile Device

Portable Device, and 3 axis were assessed. The worst scenario for Radiated Spurious Emission as follow: Lie Side Stand

3.7. Tested Supporting System List

None

3.8. Setup Configuration



3.9. Operating Condition of EUT

To set EUT RF function on continues transmitting and choosing channel.

3.10. Description of Test Facility

Name of Test Firm	Audix Technology Corporation / EMC Department No. 53-11, Dingfu, Linkou Dist., New Taipei City 244, Taiwan Tel: +886-2-26092133 Fax: +886-2-26099303 Website : www.audixtech.com Contact e-mail: attemc_report@audixtech.com
Accreditations	The laboratory is accredited by following organizations under ISO/IEC 17025:2005 (1) NVLAP(USA) NVLAP Lab Code 200077-0 (2) TAF(Taiwan) No. 1724
Test Facilities	FCC OET Designation Number under APEC MRA by NCC is : TW1724 (1) Semi-Anechoic Chamber (IC Test Site Registration No.:5183B-1)

3.11. Measurement Uncertainty

Test Item	Frequency Range	Uncertainty
Radiation Test (Distance: 3m)	30MHz~1000MHz	± 3.68dB
	Above 1GHz	±5.82dB

Remark : Uncertainty = $ku_c(y)$

Test Item	Uncertainty
Occupied Bandwidth 99% Power	±1kHz

4. MEASUREMENT EQUIPMENTLIST

4.1. Radiated Emission Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
1.	Spectrum Analyzer	Agilent	N9010A-526	MY53400071	2018. 09. 12	1 Year
2.	Test Receiver	R & S	ESCS30	100338	2018. 06. 20	1 Year
3.	Amplifier	HP	8447D	2944A06305	2019. 01. 30	1 Year
4.	Amplifier	HP	8449B	3008A00529	2019. 01. 23	1 Year
5.	Bilog Antenna	CHASE	CBL6112D	33821	2019. 01. 19	1 Year
6.	Loop Antenna	R&S	HFH2-Z2	891847/27	2017. 12. 18	2 Years
7.	Double-Ridged Waveguide Horn	EMCO	3115	9609-4927	2018. 06. 22	1 Year
8.	Horn Antenna	COM-POWER	AH-840	101092	2018. 05. 07	1 Year
9.	2.4GHz Notch Filter	K&L	7NSL10-2441.5E130.5-00	1	2018. 07. 24	1 Year
10.	3GHz Notch Filter	Microwave Circuits	H3G018G1	484796	2018. 08. 22	1 Year
11.	Digital Thermo-Hygro Meter	IMax	HTC-1	No.1 3m A/C	2018. 04. 20	1 Year
12.	Test Software	Audix	e3	V6.120619c	N.C.R.	N.C.R.

4.2. RF Conducted Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Keysight	N9010B-544	MY55460198	2018. 04. 26	1 Year
2.	Digital Thermo-Hygro Meter	Shenzhen Datronn Electronics	KT-905	RF	2018. 04. 19	1 Year

5. CONDUCTED EMISSION MEASUREMENT

【The EUT only employs Batteries power for operation, no conductive emission limits are required according to FCC Part 15 Section §15.207】


6. RADIATED EMISSION

6.1. Block Diagram of Test Setup


6.1.1. Block Diagram of EUT

Indicated as section 3.8


6.1.2. Setup Diagram for 9kHz-30MHz



6.1.3. Setup Diagram for 30-1000MHz



6.1.4. Setup Diagram for above 1GHz



6.2. Radiated Emission Limits

6.2.1. General Limit

In any 100kHz bandwidth outside the frequency band, the radio frequency power produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level. In addition, radiated emissions which fall in restricted bands, as defined in FCC Section 15.205, must also comply with the radiated emission limits specified as below.

Frequency (MHz)	Distance(m)	Limits	
		dB μ V/m	μ V/m
0.009 - 0.490	300	67.6-20 log f(kHz)	2400/f kHz
0.490 - 1.705	30	87.6-20 log f(kHz)	24000/f kHz
1.705 - 30	30	29.5	30
30 - 88	3	40.0	100
88- 216	3	43.5	150
216- 960	3	46.0	200
Above 960	3	54.0	500
Above 1000	3	74.0 dB μ V/m (Peak) 54.0 dB μ V/m (Average)	

Remark : (1) dB μ V/m = 20 log (μ V/m)

- (2) The tighter limit applies to the edge between two frequency bands.
- (3) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
- (4) Fundamental and emission fall within operation band are exempted from this section.
- (5) Pursuant to ANSI C63.10: 6.6.4.3, if the maximized peak measured value complies with the average limit, then it is unnecessary to perform an average measurement.

6.2.2. Limite for Fundamental & Harmonics Frequency

Fundamental Frequency	Field strength of fundamental		Field strength of harmonics	
	mV/m	dB μ V/m	μ V/m	dB μ V/m
902-928MHz	50	94(Quasi-Peak)	500	74 (Peak)
				54(Average)
2400-2483.5MHz	50	114 (Peak)	500	74 (Peak)
		94(Average)		54(Average)
5725-5875MHz	50	114 (Peak)	500	74 (Peak)
		94(Average)		54(Average)
24.0-24.25GHz	250	128 (Peak)	2500	88 (Peak)
		108(Average)		68(Average)

Remark: mV/m=1000 μ V/m; dB μ V/m = 20 log (μ V/m)

6.3. Test Procedure

Frequency Range 9kHz~30MHz:

The EUT setup on the turntable which has 80cm height to the ground. The turn table rotated 360 degrees and antenna fixed to 1 m to find the maximum emission level. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10-2013regulation.

- (1) RBW = 9kHz with peak and average detector.
- (2) Detector: average and peak (9kHz-490kHz)
 Q.P. (490kHz-30MHz)

Frequency Range 30MHz ~ 25GHz:

The EUT setup on the turntable which has 80 cm (for 30-1000MHz) and 1.5m (for above 1GHz) height to the ground. The turn table rotated 360 degrees and antenna varied from 1 m to 4 m to find the maximum emission level. Both horizontal and vertical polarization are required. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10-2013regulation.

Frequency below 1GHz:

Spectrum Analyzer is used for pre-testing with following setting:

- (1)RBW = 120kHz
- (2)VBW \geq 3 x RBW.
- (3)Detector = Peak.
- (4)Sweep time = auto.
- (5)Trace mode = max hold.
- (6)Allow sweeps to continue until the trace stabilizes.
- (7)When peak-detected value is lower than limit that the measurement using the Q.P. detector is not required, otherwise using Q.P. for final measurement.

Frequency above 1GHz to 10th harmonic (up to 25 GHz):**Peak Detector:**

- (1) RBW = 1MHz
- (2) VBW $\geq 3 \times$ RBW.
- (3) Detector = Peak.
- (4) Sweep time = auto.
- (5) Trace mode = max hold.
- (6) Allow sweeps to continue until the trace stabilizes.
- (7) When peak-detected value is lower than limit that the measurement using the average detector is not required, otherwise using average detector for final measurement.

Average Detector:**■ Option 1:**

- (1) RBW = 1MHz
- (2) VBW $\geq 1/ T$.

Modulation Type	T (ms)	1/ T (kHz)	VBW Setting (kHz)
2.4GHz	---	---	0.13

N/A: 1/ T is not implemented when duty cycle presented in section 3.7 is $\geq 98\%$.

- (1) Detector = Peak.
- (2) Sweep time = auto.
- (3) Trace mode = max hold.
- (4) Allow sweeps to continue until the trace stabilizes.

□ Option 2:

Average Emission Level = Peak Emission Level + D.C.C.F.

6.4. Measurement Result Explanation

■ Peak Emission Level = Antenna Factor + Cable Loss + Meter Reading

■ Average Emission Level = Antenna Factor + Cable Loss + Meter Reading

□ Average Emission Level = Peak Emission Level + DCCF

Duty Cycle Correction Factor (DCCF) = $20\log(TX_{on}/TX_{on+off})$ presented in section 3.7


□ ERP = Peak Emission Level - 95.2dB - 2.14dB

6.5. Test Results

Please refer to Appendix A.

7. EMISSION BANDWIDTH MEASUREMENT

7.1. Block Diagram of Test Setup



7.2. Test Procedure

- (1) Set RBW close to 1-5 % of 20dB BW.
- (2) Set $VBW \geq RBW$.
- (3) Detector = Peak.
- (4) Trace mode = max hold.
- (5) Sweep = auto couple.
- (6) Allow the trace to stabilize.
- (7) Setting channel bandwidth function x dB to -20dB to record the final bandwidth.

7.3. Test Results

Please refer to Appendix A

8. DEVIATION TO TEST SPECIFICATIONS

【NONE】



Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

APPENDIX A

Tel: +886 2 26099301
Fax: +886 2 26099303

APPDNDIX A

TEST DATA AND PLOTS

(Model: M01438-K)

TABLE OF CONTENTS

A.1 RADIATED EMISSION	2
A.1.1 Emissions Applied to General Requirement.....	2
A.1.2 Fundamental Frequency.....	9
A.2 EMISSION BANDWIDTH MEASUREMENT	12
A.2.1 Emission Bandwidth.....	12
A.2.2 Measurement Plots	12

A.1 RADIATED EMISSION

Test Date	2019/04/11	Temp./Hum.	23°C/49%
Test Voltage	DC 3V (Via Battery)		

A.1.1 Emissions Applied to General Requirement

A.2.1.1 Frequency 9kHz~30MHz

The emissions (9kHz~30MHz) not reported for there is no emission be found.

A.2.1.2 Frequency Below 1GHz

Mode	2.4GHz	Frequency	TX 2474MHz
------	--------	-----------	------------

Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
93.05	16.05	2.20	5.63	23.88	43.50	19.62	Peak
216.24	17.15	3.60	6.37	27.12	46.00	18.88	Peak
240.49	18.38	3.85	6.81	29.04	46.00	16.96	Peak
299.66	19.69	4.43	12.84	36.96	46.00	9.04	Peak
335.55	20.76	4.99	6.83	32.58	46.00	13.42	Peak
671.17	25.25	7.23	6.29	38.77	46.00	7.23	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
116.33	18.43	2.49	4.68	25.60	43.50	17.90	Peak
144.46	17.32	2.83	3.25	23.40	43.50	20.10	Peak
161.92	16.37	3.03	3.58	22.98	43.50	20.52	Peak
227.88	17.74	3.72	2.07	23.53	46.00	22.47	Peak
299.66	19.69	4.43	3.96	28.08	46.00	17.92	Peak
334.58	20.73	4.98	4.90	30.61	46.00	15.39	Peak


A.2.1.3 Frequency Above 1 GHz to 10th harmonics

Band Edge:



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.68	28.28	6.02	17.89	52.19	74.00	21.81	Peak
2390.04	28.28	6.03	17.23	51.54	74.00	22.46	Peak
2407.44	28.30	6.05	55.21	89.56	---	---	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2382.96	28.27	6.02	8.19	42.48	54.00	11.52	Average
2390.04	28.28	6.03	0.14	34.45	54.00	19.55	Average
2408.16	28.30	6.05	52.88	87.23	---	---	Average

Mode	2.4GHz	Frequency	TX 2408MHz
------	--------	-----------	------------



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2385.36	28.28	6.02	14.74	49.04	74.00	24.96	Peak
2390.04	28.28	6.03	10.24	44.55	74.00	29.45	Peak
2407.44	28.30	6.05	50.85	85.20	---	---	Peak



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2382.72	28.27	6.02	3.63	37.92	54.00	16.08	Average
2390.04	28.28	6.03	-1.55	32.76	54.00	21.24	Average
2408.16	28.30	6.05	48.63	82.98	---	---	Average

Mode	2.4GHz	Frequency	TX 2474MHz
------	--------	-----------	------------



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2473.76	28.37	6.12	57.52	92.01	---	---	Peak
2483.52	28.38	6.13	26.46	60.97	74.00	13.03	Peak
2483.60	28.38	6.13	25.91	60.42	74.00	13.58	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2474.08	28.37	6.12	55.29	89.78	---	---	Average
2483.52	28.38	6.13	3.13	37.64	54.00	16.36	Average
2486.00	28.38	6.13	8.14	42.65	54.00	11.35	Average

Mode	2.4GHz	Frequency	TX 2474MHz
------	--------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2474.56	28.37	6.12	51.51	86.00	---	---	Peak
2483.52	28.38	6.13	19.46	53.97	74.00	20.03	Peak
2483.60	28.38	6.13	20.57	55.08	74.00	18.92	Peak



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2474.08	28.37	6.12	49.33	83.82	---	---	Average
2483.52	28.38	6.13	0.08	34.59	54.00	19.41	Average
2486.16	28.38	6.13	3.02	37.53	54.00	16.47	Average

A.2.1.3 Frequency Above 1GHz

Mode	2.4GHz	Frequency	TX 2408MHz
------	--------	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4818.00	32.85	8.45	5.73	47.03	54.00	6.97	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4818.00	32.85	8.45	7.19	48.49	54.00	5.51	Average
4818.00	32.85	8.45	15.06	56.36	74.00	17.64	Peak

Mode	2.4GHz	Frequency	TX 2440MHz
------	--------	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4880.00	32.96	8.52	5.57	47.05	54.00	6.95	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4880.00	32.96	8.52	6.93	48.41	54.00	5.59	Average
4880.00	32.96	8.52	14.78	56.26	74.00	17.74	Peak

Mode	2.4GHz	Frequency	TX 2474MHz
------	--------	-----------	------------

Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dB μ V)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector
4950.00	33.09	8.59	5.16	46.84	54.00	7.16	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dB μ V)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector
4950.00	33.09	8.59	6.68	48.36	54.00	5.64	Average
4950.00	33.09	8.59	14.72	56.40	74.00	17.60	Peak

A.1.2 Fundamental Frequency

Mode	2.4GHz	Frequency	TX 2408MHz
------	--------	-----------	------------




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2408.69	28.30	6.05	55.65	90.00	94.00	4.00	Peak

Remark: Horizontal is the strongest polarization and peak value has complied with average limit, so vertical won't be listed in test report.

Mode	2.4GHz	Frequency	TX 2440MHz
------	--------	-----------	------------




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2440.55	28.34	6.08	55.55	89.97	94.00	4.03	Peak

Remark: Horizontal is the strongest polarization and peak value has complied with average limit, so vertical won't be listed in test report.

Mode	2.4GHz	Frequency	TX 2474MHz
------	--------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2474.13	28.37	6.12	57.77	92.26	94.00	1.74	Peak

Remark: Horizontal is the strongest polarization and peak value has complied with average limit, so vertical won't be listed in test report.

A.2 EMISSION BANDWIDTH MEASUREMENT

Test Date	2019/04/08	Temp./Hum.	24°C/54%
Test Voltage	DC 3V (Via Battery)		

A.2.1 Emission Bandwidth

Mode	Centre Frequency (MHz)	20dB Occupied Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
2.4GHz	2408	2.438	2.6403
	2440	2.596	2.6557
	2474	2.676	2.8253

A.2.2 Measurement Plots





Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

APPENDIX B

Tel: +886 2 26099301
Fax: +886 2 26099303

APPDNDIX B

TEST PHOTOGRAPHS

(Model: M01438-K)