

FCC TEST REPORT

Client Name : ACCO Brands, Inc.

Address : 1500 Fashion Island Blvd., 3rd Floor, San Mateo, CA
94404, USA

Product Name : wireless dongle

Date : Oct. 29, 2020



Shenzhen Anbotech Compliance Laboratory Limited



Contents

1. General Information.....	4
1.1. Client Information.....	4
1.2. Description of Device (EUT).....	4
1.3. Auxiliary Equipment Used During Test.....	5
1.4. Description of Test Modes.....	5
1.5. List of Channels.....	6
1.6. Description of Test Setup.....	7
1.7. Test Equipment List.....	8
1.8. Measurement Uncertainty.....	9
1.9. Description of Test Facility.....	9
2. Summary of Test Results.....	10
3. Conducted Emission Test.....	11
3.1. Test Standard and Limit.....	11
3.2. Test Setup.....	11
3.3. Test Procedure.....	11
3.4. Test Data.....	12
4. Radiated Emission and Band Edge.....	15
4.1. Test Standard and Limit.....	15
4.2. Test Setup.....	16
4.3. Test Procedure.....	17
4.4. Test Data.....	18
5. 20dB Bandwidth Test.....	28
5.1. Test Standard and Limit.....	28
5.2. Test Setup.....	28
5.3. Test Procedure.....	28
5.4. Test Data.....	28
6. Antenna Requirement.....	31
6.1. Test Standard and Requirement.....	31
6.2. Antenna Connected Construction.....	31



TEST REPORT

Applicant : ACCO Brands, Inc.
Manufacturer : ACCO Brands, Inc.
Product Name : wireless dongle
Model No. : M01517-D
Trade Mark : Kensington
Rating(s) : Input: DC5V, 25mA via USB Port

Test Standard(s) : FCC Part15 Subpart C, Paragraph 15.249

Test Method(s) : ANSI C63.10: 2013

The device described above is tested by Shenzhen Anbotech Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotech Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotech Compliance Laboratory Limited.

Date of Receipt

Sept. 21, 2020

Date of Test

Sept. 21~Oct. 26, 2020

Prepared by

Yilia Zhong

(Engineer / Yilia Zhong)

Reviewer

Bibo Zhang

(Supervisor / Bibo Zhang)

Approved & Authorized Signer

Kingkong Jin

(Manager / Kingkong Jin)



1. General Information

1.1. Client Information

Applicant	:	ACCO Brands, Inc.
Address	:	1500 Fashion Island Blvd., 3rd Floor, San Mateo, CA 94404, USA
Manufacturer	:	ACCO Brands, Inc.
Address	:	1500 Fashion Island Blvd., 3rd Floor, San Mateo, CA 94404, USA

1.2. Description of Device (EUT)

Product Name	:	wireless dongle
Model No.	:	M01517-D
Trade Mark	:	Kensington
Test Power Supply	:	AC 120V, 60Hz for MacBook Air / DC 5V by USB Port
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Product Description	Operation Frequency:	2408~2474MHz
	Number of Channel:	34 Channels
	Modulation Type:	FSK
	Antenna Type:	PCB Antenna
	Antenna Gain(Peak):	-5.35 dBi
Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.		

1.3. Auxiliary Equipment Used During Test

MacBook Air	:	Model: A1466 Input: 14.85V/3.05A CMIIT ID: C02HXB48DRVC
	:	Adapter:
	:	Input: AC 100-240V, 1A, 50-60Hz Output: 14.85V/3.05A

1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH01
Mode 2	CH17
Mode 3	CH34

For Conducted Emission	
Final Test Mode	Description
Mode 1	CH01
Mode 2	CH17
Mode 3	CH34

For Radiated Emission	
Final Test Mode	Description
Mode 1	CH01
Mode 2	CH17
Mode 3	CH34

Note:


1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.



1.5. List of Channels

Channel	Freq.	Channel	Freq.	Channel	Freq.	Channel	Freq.
	(MHz)		(MHz)		(MHz)		(MHz)
1	2408	10	2426	19	2444	28	2462
2	2410	11	2428	20	2446	29	2464
3	2412	12	2430	21	2448	30	2466
4	2414	13	2432	22	2450	31	2468
5	2416	14	2434	23	2452	32	2470
6	2418	15	2436	24	2454	33	2472
7	2420	16	2438	25	2456	34	2474
8	2422	17	2440	26	2458		
9	2424	18	2442	27	2460		

1.6. Description of Test Setup



1.7. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Nov. 04, 2019	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESPI3	101604	Nov. 04, 2019	1 Year
3.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Nov. 04, 2019	1 Year
4.	MAX Spectrum Analysis	Agilent	N9020A	MY51170037	Nov. 04, 2019	1 Year
5.	Preamplifier	SKET Electronic	BK1G18G30 D	KD17503	Nov. 04, 2019	1 Year
6.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Nov. 01, 2019	1 Year
7.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Nov. 01, 2019	1 Year
8.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Nov. 01, 2019	1 Year
9.	Horn Antenna	A-INFO	LB-180400-K F	J211060628	Nov. 01, 2019	1 Year
10.	Pre-amplifier	SONOMA	310N	186860	Nov. 04, 2019	1 Year
11.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
12.	RF Test Control System	YIHENG	YH3000	2017430	Nov. 04, 2019	1 Year
13.	Power Sensor	DAER	RPR3006W	15I00041SN045	Nov. 04, 2019	1 Year
14.	Power Sensor	DAER	RPR3006W	15I00041SN046	Nov. 04, 2019	1 Year
15.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Nov. 04, 2019	1 Year
16.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Nov. 04, 2019	1 Year
17.	Signal Generator	Agilent	E4421B	MY41000743	Nov. 04, 2019	1 Year
18.	DC Power Supply	LW	TPR-6420D	374470	Nov. 04, 2019	1 Year
19.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80 B	N/A	Nov. 04, 2019	1 Year



1.8. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 3.9 dB (Horizontal)
		Ur = 3.8 dB (Vertical)
Conduction Uncertainty	:	Uc = 3.4 dB

1.9. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotech Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111, September 30, 2020.

ISED-Registration No.: 8058A

Shenzhen Anbotech Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A, September 30, 2020.

Test Location

Shenzhen Anbotech Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102



2. Summary of Test Results

Standard Section	Test Item	Result
15.203	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.249	Radiated Emission	PASS
15.215(c)	20dB Bandwidth	PASS
15.249(c)	Band Edge	PASS
Remark: "N/A" is an abbreviation for Not Applicable.		




3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50

Remark: (1) *Decreasing linearly with logarithm of the frequency.
 (2) The lower limit shall apply at the transition frequency.

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data


PASS

During the test, pre-scan all the modes, and found the Low channel which is the worst case, only the worst case is recorded in the report.



Conducted Emission Test Data


Test Site: 1# Shielded Room
Operating Condition: CH 01
Test Specification: AC 120V, 60Hz for MacBook Air
Comment: Live Line
Tem.: 21.3°C Hum.: 63%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1499	34.00	19.90	53.90	66.00	-12.10	QP	
2	0.1547	29.97	19.90	49.87	65.74	-15.87	QP	
3	0.1859	16.34	19.90	36.24	54.21	-17.97	AVG	
4	0.2660	25.95	19.89	45.84	61.24	-15.40	QP	
5	0.4020	24.11	19.94	44.05	57.81	-13.76	QP	
6	0.5181	5.39	19.99	25.38	46.00	-20.62	AVG	
7	0.5380	21.63	19.99	41.62	56.00	-14.38	QP	
8	1.2740	6.06	20.13	26.19	46.00	-19.81	AVG	
9	1.6935	6.50	20.13	26.63	46.00	-19.37	AVG	
10	2.2019	6.36	20.14	26.50	46.00	-19.50	AVG	
11	4.5979	17.25	20.20	37.45	56.00	-18.55	QP	
12	4.6977	7.87	20.20	28.07	46.00	-17.93	AVG	

Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: CH 01
Test Specification: AC 120V, 60Hz for MacBook Air
Comment: Neutral Line
Tem.: 21.3°C Hum.: 63%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1940	16.63	19.90	36.53	53.86	-17.33	AVG	
2	0.1965	30.34	19.90	50.24	63.75	-13.51	QP	
3	0.3379	21.83	19.91	41.74	59.25	-17.51	QP	
4	0.5100	19.39	19.98	39.37	56.00	-16.63	QP	
5	0.5140	6.40	19.98	26.38	46.00	-19.62	AVG	
6	0.8175	2.91	20.07	22.98	46.00	-23.02	AVG	
7	1.0140	16.23	20.12	36.35	56.00	-19.65	QP	
8	1.8140	0.40	20.14	20.54	46.00	-25.46	AVG	
9	2.4780	1.04	20.15	21.19	46.00	-24.81	AVG	
10	3.0859	20.30	20.16	40.46	56.00	-15.54	QP	
11	4.2738	19.17	20.19	39.36	56.00	-16.64	QP	
12	4.3738	3.41	20.19	23.60	46.00	-22.40	AVG	



4. Radiated Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

Test Standard	FCC Part15 C Section 15.249					
Test Limit	Frequency (MHz)	Field Strength of fundamental ((millivolts /meter)	Field Strength of Harmonics (microvolts/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	2400~2483.5	50	-	114.0	Peak	3
	2400~2483.5	50	-	94.0	Average	3
	2400~2483.5	-	500	74.0	Peak	3
	2400~2483.5	-	500	54.0	Average	3

Remark:

(1) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup

Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz





Figure 3. Above 1 GHz



4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW = 1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW = 30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW = 300kHz, Detector = Quasi-Peak, Trace mode = Max hold, Sweep = auto couple.

For above 1GHz, Set the spectrum analyzer as:

RBW = 1MHz, VBW = 1MHz, Detector = Peak, Trace mode = Max hold, Sweep = auto couple.

RBW = 1MHz, VBW = 10Hz, Detector = Average, Trace mode = Max hold, Sweep = auto couple.

4.4. Test Data

PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

During the test, pre-scan all the modes, and found the Middle channel which is the worst case, only the worst case is recorded in the report



Report No.: 18220WC00136901

FCC ID: GV3M01517-D

Page 19 of 31

Test Results (30~1000MHz)

Test Mode: Mode 2
Power Source: DC 5V by USB Port
Polarization: Vertical
Temp.(°C)/Hum.(%RH): 24.9°C/59%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (°)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	33.0370	41.15	-16.83	24.32	40.00	-15.68	QP	100	0	
2	53.9763	32.20	-16.07	16.13	40.00	-23.87	QP	100	360	
3	99.7028	38.58	-15.71	22.87	43.50	-20.63	QP	100	0	
4	161.4742	44.68	-19.85	24.83	43.50	-18.67	QP	100	360	
5	398.3312	42.66	-14.98	27.68	46.00	-18.32	QP	100	0	
6	803.1933	39.33	-8.90	30.43	46.00	-15.57	QP	100	360	



Report No.: 18220WC00136901

FCC ID: GV3M01517-D

Page20 of 31

Test Results (30~1000MHz)

Test Mode: Mode 2
Power Source: DC 5V by USB Port
Polarization: Horizontal
Temp.(°C)/Hum.(%RH): 24.9°C/59%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor ()	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	72.0843	33.59	-20.74	12.85	40.00	-27.15	QP	100	360	
2	99.7028	39.74	-15.71	24.03	43.50	-19.47	QP	100	0	
3	160.0648	40.59	-19.90	20.69	43.50	-22.81	QP	100	360	
4	206.3976	43.21	-17.59	25.62	43.50	-17.88	QP	100	0	
5	398.3312	47.46	-14.98	32.48	46.00	-13.52	QP	100	360	
6	803.1933	39.34	-8.90	30.44	46.00	-15.56	QP	100	0	



Test Results (1GHz-25GHz)

Test Mode: CH01 (Low channel)									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.	Detector
2408.0000	95.65	31.12	2.18	35.33	93.62	114.00	-20.38	V	Peak
2408.0000	85.18	31.12	2.18	35.33	83.15	94.00	-10.85	V	AVG
4816.0000	47.18	34.01	2.58	34.65	49.12	74.00	-24.88	V	Peak
4816.0000	38.56	34.01	2.58	34.65	40.50	54.00	-13.50	V	AVG
7224.0000	47.13	36.16	2.97	35.07	51.19	74.00	-22.81	V	Peak
7224.0000	38.57	36.16	2.97	35.07	42.63	54.00	-11.37	V	AVG
9632.0000	*								
12040.0000	*								
14448.0000	*								
16856.0000	*								
2408.0000	94.43	31.12	2.18	35.33	92.40	114.00	-21.60	H	Peak
2408.0000	82.52	31.12	2.18	35.33	80.49	94.00	-13.51	H	AVG
4816.0000	48.98	34.01	2.58	34.65	50.92	74.00	-23.08	H	Peak
4816.0000	38.22	34.01	2.58	34.65	40.16	54.00	-13.84	H	AVG
7224.0000	45.67	36.16	2.97	35.07	49.73	74.00	-24.27	H	Peak
7224.0000	35.50	36.16	2.97	35.07	39.56	54.00	-14.44	H	AVG
9632.0000	*								
12040.0000	*								
14448.0000	*								
16856.0000	*								

Note:

1. Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Test Mode: CH17 (Middle channel)									
Frequency (MHz)	Read Level (dBUV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBUV/m)	Limit (dBUV/m)	Over Limit (dB)	Pol.	Detector
2440.0000	94.21	31.12	2.20	34.51	93.02	114.00	-20.98	V	Peak
2440.0000	85.02	31.22	2.20	34.51	83.93	94.00	-10.07	V	AVG
4880.0000	47.28	34.98	2.49	34.14	50.61	74.00	-23.39	V	Peak
4880.0000	38.04	34.98	2.49	34.14	41.37	54.00	-12.63	V	AVG
7320.0000	48.35	36.01	3.01	34.56	52.81	74.00	-21.19	V	Peak
7320.0000	35.16	36.01	3.01	34.56	39.62	54.00	-14.38	V	AVG
9760.0000	*								
12200.0000	*								
14640.0000	*								
17080.0000	*								
2440.0000	96.11	31.12	2.20	34.51	94.92	114.00	-19.08	H	Peak
2440.0000	83.66	31.12	2.20	34.51	82.47	94.00	-11.53	H	AVG
4880.0000	48.01	34.98	2.49	34.14	51.34	74.00	-22.66	H	Peak
4880.0000	40.80	34.98	2.49	34.14	44.13	54.00	-9.87	H	AVG
7320.0000	47.32	36.01	3.01	34.56	51.78	74.00	-22.22	H	Peak
7320.0000	36.50	36.01	3.01	34.56	40.96	54.00	-13.04	H	AVG
9760.0000	*								
12200.0000	*								
14640.0000	*								
17080.0000	*								

Note:

1. Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.



Test Mode: CH34(High channel)									
Frequency (MHz)	Read Level (dBUV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBUV/m)	Limit (dBUV/m)	Over Limit (dB)	Pol.	Detector
2474.0000	93.13	31.65	2.23	36.07	90.94	114.00	-23.06	V	Peak
2474.0000	85.59	31.65	2.23	36.07	83.40	94.00	-10.60	V	AVG
4948.0000	50.70	35.06	2.60	34.93	53.43	74.00	-20.57	V	Peak
4948.0000	41.43	35.06	2.60	34.93	44.16	54.00	-9.84	V	AVG
7422.0000	46.39	36.19	3.12	35.11	50.59	74.00	-23.41	V	Peak
7422.0000	37.31	36.19	3.12	35.11	41.51	54.00	-12.49	V	AVG
9896.0000	*								
12370.0000	*								
14844.0000	*								
17318.0000	*								
2474.0000	93.13	31.65	2.23	36.07	90.94	114.00	-23.06	H	Peak
2474.0000	85.09	31.65	2.23	36.07	82.90	94.00	-11.10	H	AVG
4948.0000	47.11	35.06	2.60	34.93	49.84	74.00	-24.16	H	Peak
4948.0000	38.39	35.06	2.60	34.93	41.12	54.00	-12.88	H	AVG
7422.0000	45.29	36.19	3.12	35.11	49.49	74.00	-24.51	H	Peak
7422.0000	38.67	36.19	3.12	35.11	42.87	54.00	-11.13	H	AVG
9896.0000	*								
12370.0000	*								
14844.0000	*								
17318.0000	*								

Note:

1. Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.



Radiated Band Edge:







Remark:

1. Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor






CH: Low



CH: Middle




CH: High

5. 20dB Bandwidth Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.249
---------------	-----------------------------

5.2. Test Setup



5.3. Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as:
RBW = 30kHz, VBW $\geq$ 3*RBW =100kHz,
Detector= Average
Trace mode= Max hold.
Sweep- auto couple.
4. Mark the peak frequency and -20dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

5.4. Test Data

Test Item : 20dB Bandwidth

Test Voltage : AC 120V, 60Hz for MacBook Air

Test Result : PASS


Test Mode : Mode 1

Temperature : 22.4℃


Humidity : 55%RH

Frequency (MHz)	Bandwidth (kHz)	Result
2408MHZ	2080	PASS
2440MHZ	2075	PASS
2474MHZ	2071	PASS






Test Mode: Low



Test Mode: Middle



Test Mode: High

6. Antenna Requirement

6.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

6.2. Antenna Connected Construction

The antenna is a PCB Antenna which permanently attached, and the best case gain of the antenna is -5.35 dBi. It complies with the standard requirement.

----- End of Report -----