

# Worldwide Testing Services(Taiwan) Co., Ltd.

Report Number: W6M22103-20740-P-247-R

FCC ID: GX9CHMG

## 10 Maximum Permissible Exposure

### 10.1 Exemption Limits for Routine Evaluation according to 47 CFR FCC Part 2 Subpart J, section 2.1091

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a “worst case” or conservative prediction.

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 20 cm normally can be maintained between the user and the device.

#### MPE Calculation Method

##### (A) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6

##### (B) Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

f = frequency in MHz

\*Plane-wave equivalent power density


E = Electric field (V/m) P = output power (W) G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

The formula can be changed to

mW/cm<sup>2</sup>.



# Worldwide Testing Services(Taiwan) Co., Ltd.

Report Number: W6M22103-20740-P-247-R

FCC ID: GX9CHMG

Frequency	Max output power		Antenna Gain	Power Density(S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
	(dBm)	(W)				
WCDMA Band II	22.57	0.18	3.15	0.0742	1	Complies
WCDMA Band IV	22.74	0.19	3.49	0.0835	1	Complies
WCDMA Band V	23.64	0.23	1.15	0.0599	0.5644	Complies
LTE Band II	23.35	0.22	3.15	0.0889	1	Complies
LTE Band IV	23.15	0.21	3.49	0.0918	1	Complies
LTE Band V	23.81	0.24	1.15	0.0623	0.5577	Complies
LTE Band XII	23.46	0.22	-0.04	0.0437	0.4740	Complies
LTE Band XIII	23.66	0.23	0.9	0.0569	0.5213	Complies

From the peak EUT RF output power, the minimum mobile separation distance,  $d=0.2$  m, as well as the gain of the used antenna, the RF power density can be obtained.