

FCC Part 15D – Compliance Information

EUT AND PRODUCT INFORMATION

Type of Equipment	UPCS (DECT 6.0)
Applicant Name	CLIMAX TECHNOLOGY CO., LTD.
Address	No.258, Sinhu 2nd Rd., Neihu District, Taipei City 114, Taiwan (R.O.C.)
Contact	George Lin
Telephone	+886-2-27940001
Email	George@climax.com.tw
Grantee Code	GX9
IC Company Number	2304B
Brand Name	CLIMAX

	FP	PP	Repeater		
EUT Type/System	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>		
FCC ID	GX91041RV	GX9CP GX9WTRVS			
Industry Canada ID	2304B-1041RV	2304B-CP 2304B-WTRVS			
Model name	CTC-1041RV	CP-23 WTRVS3			
HW Version	V8.0	CP-23 : V1.1 WTRVS3 : V1.1			
SW Version	OCA41RVB13_7070A Vffa_d3	CP-23 : Vfpa_a5 WTRVS3 : HS100914D00			
Maximum Antenna Gain					
Can the EUT be Initiating Device	<input type="checkbox"/> YES	<input checked="" type="checkbox"/> YES	<input type="checkbox"/> YES		
Does the EUT transmit signaling channels	<input checked="" type="checkbox"/> YES	<input type="checkbox"/> YES	<input type="checkbox"/> YES		
Max number of slots in use simultaneously					
Test standard:	<input checked="" type="checkbox"/> FCC part 15D	<input checked="" type="checkbox"/> RSS-213, Issue 3 / RSS-GEN, Issue 4			
Frequency Band	1921.536 – 1928.448 MHz				
Number of RF Channels	5				
Frame Period	10 ms				
Max. Burst length					
Min. Burst Length					
Minimum Number of System Channels					
Supported DECT Slot Types	<input checked="" type="checkbox"/> Full Slot	<input type="checkbox"/> Long Slot			
Operating Mode	<input type="checkbox"/> Simplex	<input checked="" type="checkbox"/> Duplex			

FCC Part 15D – Compliance Information

ANTENNAS				
Base (FP)	Antenna	Type	Internal	External
	1	PIFA ANTENNA (on PCB)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	2	DIPOLE ANTENNA	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	3		<input type="checkbox"/>	<input type="checkbox"/>
	4		<input type="checkbox"/>	<input type="checkbox"/>
Does RX and TX use the same antenna(s)?			<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
Handset (PP)	Antenna	Type	Internal	External
	1	PIFA ANTENNA (on PCB)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	2		<input type="checkbox"/>	<input type="checkbox"/>
	Does RX and TX use the same antenna(s)?			<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No

ANTENNA DIVERSITY			
	Antenna	Diversity Supported	
		TX	RX
Base (FP)	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	2	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	3	<input type="checkbox"/>	<input type="checkbox"/>
	4	<input type="checkbox"/>	<input type="checkbox"/>
Handset (PP)	1	<input type="checkbox"/>	<input type="checkbox"/>
	2	<input type="checkbox"/>	<input type="checkbox"/>

VOLTAGE AND TEMPERATURE RANGES			
VOLTAGES	FP	PP	Repeater
Nominal Voltage	12V	CP-23 : 3Vdc WTRVS3 : 3Vdc	
Cut-Off Voltage (if applicable)			
POWER SOURCE	Type		Manufacturer
Base or Repeater	Switching Power Supply Ni-MH 7.2V		Elementech International Co., Ltd. SHENZHEN HIGHPOWER TECHNOLOGY CO., LTD
Handset (PP) (charger)	CP-23 : Cylindrical Lithium 1.5V*2 WTRVS3 : Lithium 3V*1		Energizer Energizer
Data Connections	<input checked="" type="checkbox"/> PSTN <input type="checkbox"/> Others (please specify)		

FCC Part 15D – Compliance Information

ANCILLARY EQUIPMENT	
Description	Medical Emergency Alarm System
Type	CTC-1041RV
Manufacturer	CLIMAX TECHNOLOGY CO., LTD.

HOST DEVICE	
Description	Emergency Communicator (Call Point) Voice Reach Talking Pendant
Type	CP-23 WTRVS
Manufacturer	CLIMAX TECHNOLOGY CO., LTD.

ADDITIONAL INFORMATION	

FCC Part 15D – Compliance Information

MANUFACTURERS DECLARATIONS

FCC part 15.323 (c)(5)

The applicant declares that the system in this application has more than 40 duplex system access channels defined, and that the system is operating in Least Interfered Channel (LIC) mode in accordance with this section.

Applicant Agrees	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
------------------	---	-----------------------------

FCC part 15.323 (c)(5)

No device or group of co-operating devices located within 1m of each other shall during any frame period occupy more than 6 MHz of aggregate bandwidth, or alternatively, more than one third of the time and spectrum windows defined by the system.

Applicant Agrees	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
------------------	---	-----------------------------

FCC part 15.323 (c)(10)

The applicant hereby declares that the system in this application **does** use the criteria of (c)(10) of this section.

Applicant Agrees	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
------------------	---	-----------------------------

FCC part 15.323 (c)(11)

The applicant hereby declares that system in this application **does not** use the criteria of (c)(11) of this section.

Applicant Agrees	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
------------------	---	-----------------------------

FCC part 15.323 (c)(12)

The provisions of (c)(10) or (c)(11) of this section **shall not** be used to extend the range of spectrum occupied over space or time for the purpose of denying fair access to spectrum to other devices.

Applicant Agrees	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
------------------	---	-----------------------------

ADDITIONAL REMARKS:

>

DECLARED BY:

>2013.09.04

>George Lin

Date

Name (print)

Signature



FCC Part 15D – Compliance Information

About this document

This document specifies the information that is needed to select the correct testcases and test procedures for testing to FCC Part 15D. The form must be completed by the applicant and submitted by Nemko before testing is started.

Preparation of Equipment for Testing

Note (a): Number of samples for testing

The following samples are needed for FCC 15D testing:

RF Conducted Tests:

One sample with a 50 ohm antenna connector (preferably SMA Female). Only one antenna connector is needed for these tests even if the equipment has more than one antenna.

Monitoring Tests:

One sample with 50 ohm antenna connectors fitted to all antennas (preferably SMA female). Additionally we need a companion device that will work together with the EUT, the companion device must also have antenna connectors on all antennas.

Radiated Tests:

One sample with integral antennas. This sample will be used to measure Antenna Gain, Part 15B and Power-Line Conducted tests.

Note (b): Monitoring Tests

Monitoring tests are performed by establishing a connection from the handset (or the initiating device) to the base station (or the responding device). Most tests are performed by establishing connections from the initiating device to the responding device and observing which channel and/or timeslot is used.

For monitoring tests we need a EUT and a Companion device that both have antenna connectors on all antennas (preferably SMA female, again). Additionally, we need access to the CLK100 signal on the Base Station, this is necessary because some of the tests require that the interferers are synced to the DECT frame.

Note (c): Connection to an external power supply

Means of connecting the equipment to an external power supply shall be supplied by the applicant together with the equipment to be tested.

Battery operated equipment shall be supplied with the necessary batteries and chargers. All tests on battery operated equipment will be performed with batteries.

Note (d): Burst Mode

Most RF tests are performed with the EUT in force transmit mode. Software and necessary programming tools must be submitted to Nemko together with the test samples before start of testing.

Note (e): Test-Mode (Loopback Mode)

Some FCC test may also be performed in Loopback Mode with a CMD60 or similar DECT tester. If loopback mode is implemented in the EUT, the method for setting the equipment in Loopback should be submitted to Nemko together with the test samples before start of testing.