

FCC PART 15 SUBPART C TEST REPORT

for

Smart Home Alarm System

Model No.: Z1

FCC ID: GX9Z1

of

Applicant: **CLIMAX TECHNOLOGY CO., LTD.**

Address: **No. 258, Sinhu 2nd Rd., Neihu District 114
Taipei City Taiwan (R.O.C.)**

Tested and Prepared

by

Worldwide Testing Services (Taiwan) Co., Ltd.

FCC Registration No.: 930600


Industry Canada filed test laboratory Reg. No. IC 5679A-1, IC 5107A-1

A2LA Accredited No.: 2732.01



Report No.: W6M21705-16865-C-2

6F, NO. 58, LANE 188, RUEY-KUANG RD., NEIHU TAIPEI 114, TAIWAN, R.O.C.
TEL: 886-2-66068877 FAX: 886-2-66068879 E-mail: wts@wts-lab.com



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2
FCC ID: GX9Z1

TABLE OF CONTENTS

1	General Information	2
1.1	Notes	2
1.2	Testing laboratory	3
1.2.1	<i>Location</i>	3
1.2.2	<i>Details of accreditation status</i>	3
1.3	Details of approval holder.....	3
1.4	Application details	4
1.5	Test item	4
1.6	Test standards	4
2	Technical test	5
2.1	Summary of test results.....	5
2.2	Test environment	5
2.3	Test Mode	5
2.4	Test equipment utilized.....	6
2.5	General Test Procedure.....	8
3	Test results (enclosure)	9
3.1	Transmission Requirements.....	10
3.1.1	<i>Limit of Transmission Time</i>	10
3.1.2	<i>Active Time</i>	10
3.2	Output Power (Field Strength).....	11
3.3	Out of Band Radiated Emissions	13
3.4	Transmitter Radiated Emissions in restricted Bands	14
3.5	Spurious Emission radiated, Transmitter	15
3.6	Channel Bandwidth.....	26
3.7	Antenna requirement.....	27
3.8	Duty Cycle	28
3.9	Conducted Measurement at (AC) Power Line	29



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2
FCC ID: GX9Z1

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems. The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

The test results of this test report relate exclusively to the item tested as specified in 1.5.

The test report may only be reproduced or published in full.

Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services(Taiwan) Co., Ltd.

Tester:

June 16, 2017

Kent Lin

Date

WTS-Lab.

Name

Signature

Technical responsibility for area of testing:

June 16, 2017

Kevin Wang

Date

WTS

Name

Signature



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2

FCC ID: GX9Z1

1.2 Testing laboratory

1.2.1 Location

OATS

No.5-1, Lishui, Shuang Sing Village,
Wanli Dist., New Taipei City 207,
Taiwan (R.O.C.)

3 meter semi-anechoic chamber

No.35, Aly. 21, Ln. 228, Ankang Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

TEL:886-2-6613-0228

FAX:886-2-2791-5046

Company

Worldwide Testing Services(Taiwan) Co., Ltd.

6F, NO. 58, LANE 188, RUEY-KUANG RD.

NEIHU, TAIPEI 114, TAIWAN R.O.C.

Tel : 886-2-66068877

Fax : 886-2-66068879

1.2.2 Details of accreditation status

Accredited testing laboratory

A2LA accredited number: 2732.01

FCC filed test laboratory Reg. No. 930600

Industry Canada filed test laboratory Reg. No. IC 5679A-1, IC 5107A-1

Test location, where different from Worldwide Testing Services (Taiwan) Co., Ltd. :

Name: /.

Accredited number: /.

Street: /.

Town: /.

Country: /.

Telephone: /.

Fax: /.

1.3 Details of approval holder

Name: CLIMAX TECHNOLOGY CO., LTD.


Street: No. 258, Sinhu 2nd Rd., Neihu District

City: 114 Taipei City

Country: Taiwan (R.O.C.)

Telephone: +886-2-2794-0001

Fax: +886-2-2792-6618



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2

FCC ID: GX9Z1

1.4 Application details

Date of receipt of test item: May 4, 2017
Date of test: from May 5, 2017 to June 16, 2017

1.5 Test item

Description of test item: Smart Home Alarm System
Type identification: Z1
Brand name: ./.
Multi-listing model number: without
Transmitting frequency: 433.82 MHz
Operation mode: simplex
Voltage supply: Battery: NI-MH 1100mAh*6 AA, 7.2 Vd.c.
Adaptor: I/P: 100-240 Va.c., 50/60Hz, 0.5A
O/P: 12 Vd.c., 1A

(The device is tested under fresh battery condition.)

Highest clock frequency: 433.82 MHz
Antenna type: PCB antenna
Photos: see Annex

Manufacturer (if applicable)

Name: ./.
Street: ./.
Town: ./.
Country: ./.

Additional information: ./.

1.6 Test standards

Technical standard : FCC RULES PART 15 SUBPART C § 15.231 (a) (2016-10)



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2
FCC ID: GX9Z1

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.

or

The deviations as specified in 3 were ascertained in the course of the tests performed.

2.2 Test environment

Temperature: 23 °C

Relative humidity content: 20 ... 75 %

Air pressure: 86 ... 103 kPa

Test item Name	Uncertainty
Estimation Result of Uncertainty of Conducted Emission	Expanded Uncertainty : 0.74 dB
Estimation Result of Uncertainty of Radiated Emission(3M)	Expanded Uncertainty : 0.009-30 MHz : 2.17 dB 30-1000 MHz : 3.30 dB 1-18 GHz : 2.28 dB 18-40 GHz : 2.19 dB
Estimation Result of Uncertainty of Bandwidth Measurement 20 dB Bandwidth, Occupied bandwidth, Channel bandwidth, Necessary Bandwidth	Expanded Uncertainty : 0.45 kHz
Estimation Result of Uncertainty of Frequency Drift Measurement Frequency stability	Expanded Uncertainty : 6.09 Hz
Estimation Result of Uncertainty of Band Edge Measurement	Expanded Uncertainty : 0.98 dBc

2.3 Test Mode

This EUT is the portable device. So the EUT was tested on three different axes. Please see assessment test results as section 3 of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2

FCC ID: GX9Z1

2.4 Test equipment utilized

No.	Test equipment	Type	Serial No.	Manufacturer	Cal. Date	Next Cal. Date
ETSTW-CE 001	EMI TEST RECEIVER	ESHS10	842121/013	R&S	2017/5/19	2018/5/19
ETSTW-CE 003	AC POWER SOURCE	APS-9102	D161137	GW	Function Test	
ETSTW-CE 008	HF-EICHLEITUNG RF STEP ATTENUATOR 139dB DPSP	334.6010.02	844581/024	R&S	Function Test	
ETSTW-CE 009	TEMP.&HUMIDITY CHAMBER	GTH-225-40-1P-U	MAA0305-009	GIANT FORCE	2016/7/15	2017/7/14
ETSTW-CE 016	TWO-LINE V-NETWORK	ENV216	100050	R&S	2016/9/12	2017/9/11
ETSTW-CE 028	MXE EMI Receiver	N9038A	MY53220110	Agilent	2016/8/26	2017/8/25
ETSTW-RE 003	EMI TEST RECEIVER	ESI 26	831438/001	R&S	2017/5/19	2018/5/18
ETSTW-RE 004	EMI TEST RECEIVER	ESI 40	832427/004	R&S	2017/5/19	2018/5/18
ETSTW-RE 005	EMI TEST RECEIVER	ESVS10	843207/020	R&S	2016/7/4	2017/7/3
ETSTW-RE 012	TUNABLE BANDREJECT FILTER	D.C 0309	146	K&L	Function Test	
ETSTW-RE 013	TUNABLE BANDREJECT FILTER	D.C 0336	397	K&L	Function Test	
ETSTW-RE 018	MICROWAVE HORN ANTENNA	AT4560	27212	AR	2016/6/24	2017/6/23
ETSTW-RE 027	Passive Loop Antenna	6512	00034563	ETS-Lindgren	2016/6/29	2017/6/28
ETSTW-RE 030	Double-Ridged Guide Horn Antenna	3117	00035224	ETS-Lindgren	2017/3/22	2018/3/21
ETSTW-RE 042	Biconical Antenna	HK116	100172	R&S	2017/2/7	2018/2/6
ETSTW-RE 043	Log-Periodic Dipole Antenna	HL223	100166	R&S	2017/4/10	2018/4/9
ETSTW-RE 044	Log-Periodic Antenna	HL050	100094	R&S	2017/4/27	2018/4/26
ETSTW-RE 045	ESA-E SERIES SPECTRUM ANALYZER	E4404B	MY45111242	Agilent	Pre-test Use	
ETSTW-RE 050	Attenuator 10dB	50HF-010-1	None	JFW	2017/3/1	2018/2/28
ETSTW-RE 051	Attenuator 6dB	50HF-006-1	None	JFW	2017/3/1	2018/2/28
ETSTW-RE 053	Attenuator 3dB	50HF-003-1	None	JFW	2017/3/1	2018/2/28
ETSTW-RE 055	SPECTRUM ANALYZER	FSU 26	200074	R&S	2017/3/1	2018/2/28
ETSTW-RE 060	Attenuator 30dB	5015-30	F651012z-01	ATM	2017/3/1	2018/2/28
ETSTW-RE 062	Amplifier Module	CHC 2	None	KMIC	2017/4/12	2018/4/11
ETSTW-RE 064	Bluetooth Test Set	MT8852B-042	6K00005709	Anritsu	Function Test	
ETSTW-RE 069	Double-Ridged Guide Horn Antenna	3117	00069377	ETS-Lindgren	Function Test	
ETSTW-RE 072	CELL SITE TEST SET	8921A	3339A00375	HP	2016/9/8	2017/9/7
ETSTW-RE 088	SOLID STATE AMPLIFIER	KMA180265A01	99057	KMIC	2016/9/20	2017/9/19
ETSTW-RE 091	Match Pad	MDCS1500	None	WOKEN	2017/4/6	2018/4/5
ETSTW-RE 099	DC Block	50DB-007-1	None	JFW	2017/3/1	2018/2/28
ETSTW-RE 112	AC POWER SOURCE	TFC-1005	T-0A023536	T-Power	Function test	
ETSTW-RE 115	2.4GHz Notch Filter	N0124411	473874	MICROWAVE CIRCUITS	2017/1/12	2018/1/11
ETSTW-RE 120	RF Player	MP9200	MP9210-111022	ADIVIC	Function test	
ETSTW-RE 122	SIGNAL GENERATOR	SMF100A	102149	R&S	2017/5/19	2018/5/18
ETSTW-RE 125	5GHz Notch filter	5NSL11-5200/E221.3-O/O	1	K&L Microwave	2016/8/10	2017/8/9
ETSTW-RE 126	5GHz Notch filter	5NSL12-5800/E221.3-O/O	1	K&L Microwave	2016/8/10	2017/8/9
ETSTW-RE 127	RF Switch Box	RFS-01	None	WTS	2017/3/1	2018/2/28
ETSTW-RE 128	5.3GHz Notch filter	N0153001	SN487233	Microwave Circuits	2016/8/10	2017/8/9




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2

FCC ID: GX9Z1

ETSTW-RE 129	5.5GHz Notch filter	N0555984	SN487234	Microwave Circuits	2016/8/10	2017/8/9
ETSTW-RE 130	Handheld RF Spectrum Analyzer	N9340A	CN0147000204	Agilent	Pre-test Use	
ETSTW-RE 142	Amplifier	8447D	2805A03378	Agilent	2017/4/12	2018/4/11
ETSTW-RE 143	Humidity Temperature Meter	TES-1260	110104623	TES	2016/8/19	2017/8/18
ETSTW-RE 147	Bi-log Hybrid Antenna	MCTD 2786B	BLB16M04005	ETC	2017/3/22	2018/3/21
ETSTW-EMI 011	USB Compact Modulator	SFC-U	101689	R&S	2017/5/10	2018/5/9
ETSTW-GSM 002	Universal Radio Communication Tester	CMU 200	109439	R&S	2017/2/24	2018/2/23
ETSTW-GSM 003	Radio Communication Analyzer	MT8820C	6201342073	Anritsu	2017/2/10	2018/2/9
ETSTW-GSM 004	Wideband Radio Communication Tester	CMW500	128092	R&S	2016/12/15	2017/12/14
ETSTW-GSM 019	Band Reject Filter	WRCTF824/849-822/851-40 /12+9SS	3	WI	2017/1/12	2018/1/11
ETSTW-GSM 020	Band Reject Filter	WRCD1747/1748-1743/1752-32/5SS	1	WI	2017/1/12	2018/1/11
ETSTW-GSM 021	Band Reject Filter	WRCD1879.5/1880.5-1875.5/1884.5-32/5SS	3	WI	2017/1/12	2018/1/11
ETSTW-GSM 022	Band Reject Filter	WRCT901.9/903.1-904.25-50/8SS	1	WI	2017/1/12	2018/1/11
ETSTW-GSM 023	Power Divider	4901.19.A	None	SUHNER	2016/9/14	2017/9/13
ETSTW-Cable 010	BNC Cable	RGS-142	None	THERMAX	2016/9/12	2017/9/11
ETSTW-Cable 011	SMA to N type Cable	RGU-400	None	THERMAX	Pre-test Use NCR	
ETSTW-Cable 012	BNC Cable	RGS-400	None	THERMAX	2016/9/12	2017/9/11
ETSTW-Cable 016	BNC Cable	Switch Box	B Cable 1	Schwarz beck	2017/2/23	2018/2/22
ETSTW-Cable 017	BNC Cable	X Cable	B Cable 2	Schwarz beck	2017/2/23	2018/2/22
ETSTW-Cable 018	BNC Cable	Y Cable	B Cable 3	Schwarz beck	2017/2/23	2018/2/22
ETSTW-Cable 019	BNC Cable	Z Cable	B Cable 4	Schwarz beck	2017/2/23	2018/2/22
ETSTW-Cable 020	N TYPE Cable	OATS Cable 1	N30N30-L335-15M	JYE BAO CO.,LTD.	2017/4/21	2018/4/20
ETSTW-Cable 022	N TYPE Cable	5006	0002	JYE BAO CO.,LTD.	2017/4/6	2018/4/5
ETSTW-Cable 026	Microwave Cable	SUCOFLEX 104	279075	HUBER+SUHNER	2017/3/1	2018/2/28
ETSTW-Cable 027	Microwave Cable	SUCOFLEX 104	279083	HUBER+SUHNER	2017/5/3	2018/5/2
ETSTW-Cable 028	Microwave Cable	FA147A0015M2020	30064-2	UTIFLEX	2016/9/20	2017/9/19
ETSTW-Cable 029	Microwave Cable	FA147A0015M2020	30064-3	UTIFLEX	2016/9/20	2017/9/19
ETSTW-Cable 030	Microwave Cable	SUCOFLEX 104 (S_Cable 9)	279067	HUBER+SUHNER	2017/3/1	2018/2/28
ETSTW-Cable 031	Microwave Cable	SUCOFLEX 104 (S_Cable 10)	238092	HUBER+SUHNER	2017/4/12	2018/4/11
ETSTW-Cable 043	Microwave Cable	SUCOFLEX 104	317576	HUBER+SUHNER	2017/4/12	2018/4/11
ETSTW-Cable 048	Microwave Cable	SUCOFLEX 104	325519	HUBER+SUHNER	2017/4/12	2018/4/11
ETSTW-Cable 058	Microwave Cable	SUCOFLEX 104	none	HUBER+SUHNER	2017/2/20	2018/2/19
ETSTW-Cable 064	Microwave Cable	SUCOFLEX 104	MY28891	HUBER+SUHNER	2017/4/12	2018/4/11
ETSTW-Cable 066	SMA type cable	32022	None	ASTROLAB	2016/9/12	2017/9/11
ETSTW-Cable 071	N TYPE CABLE	EMCCFD400-NM-NM-25000	170239	EMCI	2017/2/20	2018/2/19
WTSTW-SW 002	EMI TEST SOFTWARE	EZ_EMC	None	Farad	Version ETS-03A1	
WTSTW-SW 006	EMI TEST SOFTWARE	e3	None	AUDIX	Version 9.161014	
WTSTW-SW 008	Signal studio	Agilent	None	AUDIX	Version 2.0.0.1	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2
FCC ID: GX9Z1

2.5 General Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.10-2013 6.2 using a LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.10-2013 6.3 using a spectrum analyzer. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was the 100 kHz and the video bandwidth was 300 kHz.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of $\text{dB}\mu\text{V}$) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.

Example:

Freq (MHz)	METER READING + ACF + CABLE LOSS (to the receiver) = FS
33	$20 \text{ dB}\mu\text{V} + 10.36 \text{ dB/m} + 6 \text{ dB} = 36.36 \text{ dB}\mu\text{V/m} @3\text{m}$

ANSI STANDARD C63.10-2013 6.2.2 MEASUREMENT PROCEDURES: The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m (non metallic table). The EUT was placed in the center of the table. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to 10th harmonic of the fundamental.

Peak readings were taken in three (3) orthogonal planes and the highest readings.

Measurements were made by Worldwide Testing Services(Taiwan) Co., Ltd. at the registered open field test site located at. The Registration Number: **930600**

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

ANSI STANDARD C63.10-2013 B.2.7: Any measurements that utilize special test software shall be indicated and referenced in the test report. During testing, test software 'EZ EMC' was used for setting up different operation modes.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2

FCC ID: GX9Z1

3 Test results (enclosure)

1st test

test after modification

production test

TEST CASE	Para. Number	Required	Test passed	Test failed
Transmission Requirements	FCC 15.231(a)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Radiated Emission	FCC 15.231(b)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Bandwidth of Emission	FCC 15.231(c)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Frequency Tolerance	FCC 15.231(d)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Period Alternate Field Strength Requirements	FCC 15.231(e)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Antenna Requirement	FCC 15.203	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Conducted Measurement at (AC) Power Line	FCC 15.207	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

The following is intentionally left blank.

Registration number: W6M21705-16865-C-2
 FCC ID: GX9Z1

3.1 Transmission Requirements

FCC 15.231(a)

3.1.1 Limit of Transmission Time


According to 15.231(a)(1), a manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

According to 15.231(a)(2), a transmitter activated automatically shall cease transmission within 5 seconds after activation.


3.1.2 Active Time

This manually operated transmitter employs a switch that automatically deactivate the transmitter within 341.082164 ms of being released.

This transmitter is operated by automatic activation and active will cease transmission in _ ms after activation..



Test equipment used : ETSTW-RE 004




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2

FCC ID: GX9Z1

3.2 Output Power (Field Strength)



Site : Chamber

Condition : FCC 15.231(433MHz)Power(PK)

Polarization: *Horizontal*

EUT : W6M21705-16865

Power : 120 V.a.c.


M/N:

Distance: 3m

Test Mode : TX 433.82MHz


Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	433.7944	46.95	peak	24.82	71.77	100.80	230	160	-29.03	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2
FCC ID: GX9Z1



Site : Chamber

Condition : FCC 15.231(433MHz)Power(PK)

Polarization: **Vertical**

EUT : W6M21705-16865

Power : 120 V_{a.c.}

M/N:

Distance: 3m

Test Mode : TX 433.82MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	433.8165	50.94	peak	24.82	75.76	100.80	125	130	-25.04	

Limit 15.231(b)

Fundamental Frequency (MHz)	Field strength of fundamental, limit μ V/m
40.66 – 40.70	2,250
70 – 130	1,250
130 – 174	1,250 to 3,750
174 – 260	3,750
260 – 470	3,750 to 12,500** (433.82 MHz: 80.82 dB μ V/m = 10,992 μ V/m)
Above 470	12,500

** linear interpolation

Test equipment used: ETSTW-RE 004, ETSTW-RE 062, ETSTW-RE 142, ETSTW-RE 147



Registration number: W6M21705-16865-C-2

FCC ID: GX9Z1

3.3 Out of Band Radiated Emissions

FCC Rule: 15.231(b) , 15.35

For out of band emissions that are close to or that exceed the 20 dB attenuation requirement described in the specification, radiated measurements were performed at a 3 m separation distance to determine whether these emissions complied with the general radiated emission requirement.

Guidance on Measurement of pulsed emission: 15.35(c)

“the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.”

Duty Cycle correction = $20 \log (\text{dwell time}/100\text{ms or one period})$

Limits:

For frequencies (Average measurements)

Correction factor conform 15.35 (c) (Average measurements)

Duty cycle correction :

Max. Peak reading – duty cycle correction

Max permitted average Limits = Max permitted Fundamental limit – 20 dB

For example for 433.85 fundamental carrier:

Max permitted average Limit: $80.8 \text{ dB}\mu\text{V/m} - 20 \text{ dB} = 60.8 \text{ dB}\mu\text{V/m}$

For frequencies above 1GHz (Peak measurements).

Modified Limits for peak conform 15.35 (b) = Max Permitted average Limits + 20dB (because Peak detector is used)



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2

FCC ID: GX9Z1

3.4 Transmitter Radiated Emissions in restricted Bands

FCC Rules: 15.231 (b), 15.205, 15.209, 15.35

Radiated emission measurements were performed from 30 MHz to 8000 MHz.

For radiated emission tests, the analyzer setting was as followings:

RES BW VID BW

Frequency <1 GHz 100 kHz 100 kHz (Peak measurements)

Frequency >1 GHz 1 MHz 1 MHz (Peak measurements)

1 MHz 1 MHz (Average measurements)

Limits:

For frequencies below 1GHz :

Frequency of Emission (MHz)	Field strength (microvolts/meter)	Field Strength (dB microvolts/meter)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

For frequencies above 1GHz (Average measurements).

Guidance on Measurement of pulsed emission:

“If the emission is pulsed, modify the unit for continues operation , use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.

For frequencies above 1GHz (Average measurements).

The correction factor, based on the channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

Duty cycle correction = $20 \log (\text{dwell time}/100\text{ms})$

No duty cycle correction was added to the reading

Modified Limits for peak conform 15.35 (b) = Max Permitted average Limits + 20dB (because Peak detector is used)

Above 960 MHz

For mode DSSS CW: $54 \text{ dB}\mu\text{V/m} + 20 \text{ dB} = 74 \text{ dB}\mu\text{V/m}$



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2

FCC ID: GX9Z1

3.5 Spurious Emission radiated, Transmitter

Spurious emission was measured with modulation (declared by manufacturer).

The limits on the field strength of the spurious emission in the table § 15.231(b) are based on the fundamental frequency of the intentional radiator. Spurious emission shall be attenuated to the average (or alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in § 15.209, whichever limit permits a higher field strength.

In addition, radiated emission which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

SAMPLE CALCULATION OF LIMIT. All results will be updated by an automatic measuring system in accordance to point 2.3.

Calculation of test results:

Such factors like antenna correction, cable loss, external attenuation etc. are already included in the provided measurement results. This is done by using validated test software and calibrated test system according the accreditation requirements.

The peak and average spurious emission plots was measured with the average limits.

In the Table being listed the critical peak and average value an exhibit the compliance with the above calculated Limits.

Summary table with radiated data of the test plots




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2
FCC ID: GX9Z1

Radiated Emission Measurement
File :1 Data :#1 Date: 2017/6/7
90.0 dBuV/m Time: 下午 09:22:53

Operator: Leon
Temperature:24 °C
Humidity:60 %



Site : Chamber

Condition : FCC 15.231(433MHz) 30-300(PK)

Polarization: *Horizontal*

EUT : W6M21705-16865

Power : 120 V.a.c.

M/N:

Distance: 3m

Test Mode : TX 433.82MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	199.8997	39.13	peak	-10.75	28.38	80.80	100	155	-52.42	
	199.8997	38.93	AVG	-10.75	28.18	60.80	100	155	-32.62	
	239.9398	37.56	peak	-8.38	29.18	80.80	100	20	-51.62	
*	239.9398	37.36	AVG	-8.38	28.98	60.80	100	20	-31.82	




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2
FCC ID: GX9Z1

Radiated Emission Measurement
File :1 Data :#2 Date: 2017/6/7
90.0 dBuV/m Time: 下午 09:26:41

Operator: Leon
Temperature:24 °C
Humidity:60 %



Site : Chamber

Condition : FCC 15.231(433MHz) 30-300(PK)

Polarization: *Vertical*

EUT : W6M21705-16865

Power : 120 Va.c.


M/N:

Distance: 3m

Test Mode : TX 433.82MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	35.4107	42.64	peak	-8.83	33.81	80.80	100	65	-46.99	
	35.4107	42.44	AVG	-8.83	33.61	60.80	100	65	-27.19	
	47.3144	46.22	peak	-10.21	36.01	80.80	100	240	-44.79	
*	47.3144	46.02	AVG	-10.21	35.81	60.80	100	240	-24.99	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2
FCC ID: GX9Z1

Radiated Emission Measurement

Operator: Leon

File :2

Data :#1


Date: 2017/6/7

Temperature:24 °C

90.0 dBuV/m

Time: 下午 09:18:00

Humidity:60 %



Site : Chamber

Condition : FCC 15.231(433MHz) 300-1000(PK)

Polarization: *Horizontal*

EUT : W6M21705-16865

Power : 120 Va.c.


M/N:

Distance: 3m

Test Mode : TX 433.82MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	549.6992	37.02	peak	-1.90	35.12	80.80	100	155	-45.68	
*	549.6992	36.82	AVG	-1.90	34.92	60.80	100	155	-25.88	
	950.9017	29.59	peak	4.60	34.19	80.80	100	230	-46.61	
	950.9017	29.39	AVG	4.60	33.99	60.80	100	230	-26.81	




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2
FCC ID: GX9Z1

Radiated Emission Measurement
File :2 Data :#2 Date: 2017/6/7
90.0 dBuV/m Time: 下午 09:20:32

Operator: Leon
Temperature:24 °C
Humidity:60 %



Site : Chamber

Condition : FCC 15.231(433MHz) 300-1000(PK)

Polarization: Vertical

EUT : W6M21705-16865

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 433.82MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	549.6992	37.99	peak	-1.90	36.09	80.80	100	55	-44.71	
*	549.6992	37.79	AVG	-1.90	35.89	60.80	100	55	-24.91	
	750.3006	32.15	peak	0.53	32.68	80.80	100	240	-48.12	
	750.3006	31.95	AVG	0.53	32.48	60.80	100	240	-28.32	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2

FCC ID: GX9Z1

Radiated Emission Measurement

File :3

Data :#1

Date: 2017/6/7

Operator: Leon

90.0 dBuV/m

Time: 下午 10:58:36

Temperature:24 °C

80

Humidity:60 %

Limit1:

Limit2:

70

60

50

40

30

20

10

0

-10.0

1000.000 1100.00 1200.00 1300.00 1400.00 1500.00 1600.00 1700.00 1800.00 2000.00 MHz

Site : Chamber

Condition : FCC 15.231(433MHz) 1000-2000(PK)

Polarization: *Horizontal*

EUT : W6M21705-16865

Power : 120 Va.c.


M/N:

Distance: 3m

Test Mode : TX 433.82MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1301.460	41.80	peak	-9.18	32.62	74.00	150	230	-41.38	
*	1537.074	46.95	peak	-8.67	38.28	74.00	150	50	-35.72	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2
FCC ID: GX9Z1

Radiated Emission Measurement

Operator: Leon

File :3


Data :#4

Date: 2017/6/7

Temperature:24 °C

Time: 下午 11:00:19

Humidity:60 %



Site : Chamber

Condition : FCC 15.231(433MHz) 1000-2000(PK)

Polarization: **Vertical**

EUT : W6M21705-16865

Power : 120 Va.c.


M/N:

Distance: 3m

Test Mode : TX 433.82MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1301.460	42.92	peak	-9.18	33.74	74.00	150	260	-40.26	
*	1537.074	45.84	peak	-8.67	37.17	74.00	150	85	-36.83	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2

FCC ID: GX9Z1

Radiated Emission Measurement

Operator: Leon

File :3

Data :#2


Date: 2017/6/7

Temperature:24 °C

90.0 dBuV/m

Time: 下午 11:01:48

Humidity:60 %



Site : Chamber

Condition : FCC 15.231(433MHz) 2000-4000(PK)

Polarization: *Horizontal*

EUT : W6M21705-16865

Power : 120 Va.c.


M/N:

Distance: 3m

Test Mode : TX 433.82MHz


Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2602.920	41.48	peak	-3.78	37.70	80.80	150	175	-43.10	
*	3036.740	41.51	peak	-3.09	38.42	80.80	150	40	-42.38	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2
FCC ID: GX9Z1



Site : Chamber

Condition : FCC 15.231(433MHz) 2000-4000(PK)

Polarization: **Vertical**

EUT : W6M21705-16865

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 433.82MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2602.920	41.52	peak	-3.78	37.74	80.80	150	115	-43.06	
*	3036.740	41.15	peak	-3.09	38.06	80.80	150	200	-42.74	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2
FCC ID: GX9Z1

Radiated Emission Measurement

Operator: Leon

File :3

Data :#3

Date: 2017/6/7

Temperature:24 °C

90.0 dBuV/m

Time: 下午 11:0


Humidity:60 %

1

111

• • •

Limit1:



Site : Chamber

Condition : FCC 15.231(433MHz) 4000-8000(PK)

Polarization: *Horizontal*

EUT: W6M21705-16865

Power : 120 V.a.c.

M/N:

Distance: 3m

Test Mode : TX 433.82MHz

Note: i

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2

FCC ID: GX9Z1

Radiated Emission Measurement

Operator: Leon

File :3

Data :#6


Date: 2017/6/7

Temperature:24 °C

90.0 dBuV/m

Time: 下午 11:05:29

Humidity:60 %



Site : Chamber

Condition : FCC 15.231(433MHz) 4000-8000(PK)

Polarization: **Vertical**

EUT : W6M21705-16865

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 433.82MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

Note

1. Correction Factor = Antenna factor + Cable loss - Preamplifier
2. The formula of measured value as: Test Result = Reading + Correction Factor
3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
4. All not in the table noted test results are more than 20 dB below the relevant limits.
5. Measurement uncertainty for 3m measurement: 30-1000 MHz = ± 3.30 dB, 1-18 GHz = ± 2.28 dB, 18-40 GHz= ± 2.19 dB ; Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.
6. Up Line: PK Limit Line, Down Line: Ave Limit Line.

All other not noted test plots do not contain significant test results in relation to the limits
Test results: The unit meet the FCC requirements.


Test equipment used: ETSTW-RE 004, ETSTW-RE 030, ETSTW-RE 062, ETSTW-RE 142, ETSTW-RE 147

Registration number: W6M21705-16865-C-2

FCC ID: GX9Z1

3.6 Channel Bandwidth

Measurement of Necessary Bandwidth (BN)




Used frequency	Bandwidth	Limit
433.82 MHz	60.12024048 kHz	1.08455 MHz

Explanation: The bandwidth fulfills the requirements of FCC § 15.231,

Limits:

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

Test equipment used: ETSTW-RE 004



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2

FCC ID: GX9Z1

3.7 Antenna requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

Explanation: This PCB antenna is integral antenna which passes antenna requirement.

The equipment meets the requirements	yes <input checked="" type="checkbox"/>	no <input type="checkbox"/>
--------------------------------------	--	--------------------------------

Registration number: W6M21705-16865-C-2

FCC ID: GX9Z1


3.8 Duty Cycle

The correction factor, based on the channel dwell time in a 100ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the measured value.

Average Reading = Peak Reading (dBuV/m) + Duty Cycle Correction


Duty Cycle Correction = $20 \log (\text{Cycle})$

In order to determine the Duty Cycle, the EUT is measured as:



Testing Mode	T period (ms)	T on (ms)	Duty Cycle	Duty Cycle Correction $20 * \log(\text{Duty Cycle})$
Transmitting mode	100	97.7	0.977	-0.20

Test equipment used: ETSTW-RE 055, ETSTW-RE 004



Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M21705-16865-C-2


FCC ID: GX9Z1

3.9 Conducted Measurement at (AC) Power Line

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.


This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2
FCC ID: GX9Z1



Condition: FCC part15B ClassB ENV216 line

EUT : W6M21705-16865

Mode :

Power : 120 Va.c.

Operator : Syuan

Note :

Freq	Level	Read	Factor	Limit	Over	Pol/Phase	Remark
		MHz	dBuV	dB	dBuV	dB	
1	0.157	31.01	21.17	9.84	65.61	-34.60	line QP
2	0.157	24.48	14.64	9.84	65.61	-41.13	line Average
3	0.182	34.69	24.87	9.82	64.40	-29.71	line QP
4	0.182	25.23	15.41	9.82	64.40	-39.17	line Average
5	0.231	32.14	22.33	9.81	62.42	-30.28	line QP
6	0.231	23.31	13.50	9.81	62.42	-39.11	line Average
7 *	0.335	30.98	21.18	9.80	59.34	-28.36	line QP
8	0.335	24.16	14.36	9.80	59.34	-35.18	line Average
9	0.663	27.25	17.47	9.78	56.00	-28.75	line QP
10	0.663	19.49	9.71	9.78	56.00	-36.51	line Average
11	0.925	24.43	14.66	9.77	56.00	-31.57	line QP
12	0.925	16.96	7.19	9.77	56.00	-39.04	line Average

Note

1. The formula of measured value as: Test Result = Reading + Correction Factor
2. The Correction Factor = Cable Loss + LISN Insertion Loss + Pulse Limit Loss
3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
4. All not in the table noted test results are more than 20 dB below the relevant limits.
5. Measurement uncertainty = ± 0.74 dB; Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.
6. Up Line: QP Limit Line, Down Line: Ave Limit Line.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21705-16865-C-2

FCC ID: GX9Z1

Limits:

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi Peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Test equipment used: ETSTW-CE 001, ETSTW-CE 016, ETSTW-CE 028.