

TABLE OF CONTENTS

APPLICANT: BESCO ELECTRONIC MANUFACTURING CO., LTD.

FCC ID: GXKBS3100TX

TEST REPORT CONTAINING:

PAGE 1.....	TEST PROCEDURE
PAGE 2.....	TEST CONT. & CIRCUIT DESCRIPTION
PAGE 3.....	RADIATION INTERFERENCE TEST DATA
PAGE 4.....	CALCULATION OF DUTY CYCLE
PAGE 5.....	OCCUPIED BANDWIDTH

EXHIBIT ATTACHMENTS:

EXHIBIT 1.....	POWER OF ATTORNEY LETTER
EXHIBIT 2.....	LETTER CONFIRMING MODIFICATIONS
EXHIBIT 3.....	BLOCK DIAGRAM
EXHIBIT 4.....	SCHEMATIC
EXHIBIT 5.....	PARTS LIST
EXHIBIT 6A-6B.....	INSTRUCTION MANUAL
EXHIBIT 7.....	FCC ID LABEL SAMPLE
EXHIBIT 8.....	SKETCH OF FCC ID LABEL LOCATION
EXHIBIT 9.....	DUTY CYCLE PLOT - SMALL PULSES
EXHIBIT 10.....	DUTY CYCLE PLOT - LARGE PULSES
EXHIBIT 11.....	DUTY CYCLE PLOT
EXHIBIT 12.....	OCCUPIED BANDWIDTH PLOT
EXHIBIT 13.....	FRONT VIEW EXTERNAL PHOTO
EXHIBIT 14.....	REAR VIEW EXTERNAL PHOTO
EXHIBIT 15.....	COMPONENT SIDE INTERNAL PHOTO
EXHIBIT 16.....	COPPER SIDE INTERNAL PHOTO

APPLICANT: BESCO ELECTRONIC MANUFACTURING CO., LTD.

FCC ID: GXKBS3100TX

REPORT #: F:\CUS\B\BESCO\BES257H8.RPT

PAGE: TABLE OF CONTENTS LIST

APPLICANT: BESCO ELECTRONIC MANUFACTURING CO., LTD.
FCC ID: GXKBS3100TX

TEST EQUIPMENT LIST

1. Spectrum Analyzer: Hewlett Packard 8566B - Opt 462, w/ preselector 85685A, & Quasi-Peak Adapter HP 85650A, & HP 8449B - OPT H02 Cal. 6/26/98
 2. Signal Generator, Hewlett Packard 8640B, cal. 6/26/98
 3. Eaton Biconical Antenna Model 94455-1
20-200 MHz Serial No. 0997 Cal. 5/15/98
 4. Electro-Metric Dipole Kit, 20-1000 MHz, Model TDA 25 cal. 5/15/97
 5. Electro-Metric Horn 1-18 GHz, Model RGA-180, Cal. 8/15/98
 6. Electro-Metric Antennas Model TDS-25-1, TDS-25-2, 5/15/97
 7. Electro-Metric Line Impedance Stabilization Network Model No. EM-7821, Serial No. 101; 100KHz-30MHz 50uH. 12/3/97
 8. Electro-Metric Line Impedance Stabilization Network Model No. EM-7820, Serial No. 2682; 10KHz-30MHz 50uH. 12/3/97
8. Special low loss cable was used above 1 GHz.

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz. The ambient temperature of the UUT was 78.3oF with a humidity of 55%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) METER READING + ACF = FS
33 20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

APPLICANT: BESCO ELECTRONIC MANUFACTURING CO., LTD.
FCC ID: GXKBS3100TX
REPORT #: F:\CUS\B\BESCO\BES257H8.RPT
PAGE #: 1

TEST PROCEDURES CONTD.

ANSI STANDARD C63.4-1992 10.1.7 MEASUREMENT PROCEDURES: The UUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The UUT was placed in the center of the table. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to 10th harmonic of the fundamental.

Peak readings were taken in three (3) orthogonal planes and the highest readings were converted to average readings based on the duration of "ON" time.

Measurements were made by TIMCO ENGINEERING INC. at the registered open field test site located at 6051 N.W. 19th Lane, Gainesville, Fl 32605.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

RULES:2.1033(b)(4) CIRCUIT DESCRIPTION

This unit is a low power security device transmitter. The oscillator is a an LC oscillator formed by the transistor Q1 and the tuned circuit made up of antenna, L1, C2, C1, & C4. The inductor is printed on the PCB. The integrated circuit IC1 is a voltage sensor which will not allow the unit to transmit if the voltage is too low. The unit is completely self contained and is powered by a 12Volt battery. The calculations are shown in the report and they duty cycle is 3.80%.

ANTENNA & GROUND:

This unit uses the PCB inductor as the antenna. There is no provision for an external antenna.

APPLICANT: BESCO ELECTRONIC MANUFACTURING CO., LTD.

FCC ID: GXKBS3100TX

REPORT #: F:\CUS\B\BESCO\BES257H8.RPT

PAGE #: 2

APPLICANT: BESCO ELECTRONIC MANUFACTURING CO., LTD.

FCC ID: GXKBS3100TX

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NO.: 15.231

REQUIREMENTS:

Fundamental Frequency	Field Strength of Fundamental	Field Strength of Harmonics and Spurious Emissions (dBuV/m @ 3m)
MHz	dBuV	
40.66 to 40.70	67.04	47.04
70 to 130	61.94	41.94
130 to 174	61.94 to 71.48	41.94 to 51.48
174 to 260	71.48	51.48
260 to 470	71.48 to 81.94	51.48 to 61.94
470 and above	81.94	61.94

THE LIMIT FOR AVERAGE FIELD STRENGTH dBuV/m FOR THE FUNDAMENTAL FREQUENCY= 78.02 dBuV/m dBuV/m. NO FUNDAMENTAL EMISSION IS ALLOWED IN THE RESTRICTED BANDS OF 15.205.

THE LIMIT FOR AVERAGE FIELD STRENGTH dBuV/m FOR THE HARMONICS AND SPURIOUS FREQUENCIES = 58.02 dBuV/m dBuV/m. SPURIOUS IN THE RESTRICTED BANDS MUST BE LESS THAN 54dBuV/m OR MEET 15.209.

TEST DATA:

EMISSION FREQ.	METER READING MHz	COAX LOSS @ 3m dBuV	ACF dB	PEAK	AVERAGE		
				FIELD STRNGTH	FIELD STRNGTH	MARGIN	ANT.
361.22	66.60	1.40	15.88	83.88	55.65	22.37	H
722.40	35.60	2.00	21.94	59.54	31.32	26.70	H
1083.60R	34.40	1.00	24.33	59.73	31.51	22.49	H
1444.80R	34.10	1.00	25.78	60.88	32.66	21.34	V
1806.00	22.50	1.00	27.22	50.72	22.50	35.52	H
2167.20	13.40	1.06	28.42	42.87	14.65	43.37	V
2528.40	4.30	1.11	29.32	34.73	6.51	51.51	V
2889.60	2.30	1.16	30.22	33.69	5.46	48.54	V
3250.80	2.10	1.22	31.13	34.44	6.22	51.80	V
3612.10R	2.30	1.27	32.03	35.60	7.38	46.62	H

SAMPLE CALCULATION OF LIMIT @ 303 MHZ:

$$(470 - 260) \text{ MHz} = 210 \text{ MHz}$$

$$(12500 - 3750) \mu\text{V/m} = 8750 \mu\text{V/m}$$

$$8750 \mu\text{V/m} / 210 \text{ MHz} = 41.67 \mu\text{V/m/MHz}$$

$$(303 - 260) \text{ MHz} = 43 \text{ MHz}$$

$$43 \text{ MHz} * 41.67 \mu\text{V/m/MHz} = 1791.81 \mu\text{V/m}$$

$$(1791.81 + 3750) \mu\text{V/m} = 5541.81 \mu\text{V/m} \text{ limit @ 303 MHz}$$

The transmitter ceases transmitting when the button is released.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: S.S. SANDERS DATE TESTED: SEPTEMBER 11, 1998

APPLICANT: BESCO ELECTRONIC MANUFACTURING CO., LTD.

FCC ID: GXKBS3100TX

CALCULATION OF DUTY CYCLE:

The period of the pulse train is determined by observing it on an oscilloscope or a spectrum analyzer with zero(0) frequency span. A plot is then made of the pulse train with a sweep time of 100milliseconds. This sweep determines the duration of the pulse train, which in this case is 10.2 milliseconds. This sweep allows the determination of the number of and type of pulses, i.e. long & short. Plots are then made showing the duration of each type of pulse and its duration. From the 100millisecond Plot the number of a given type of pulse is then multiplied by the duration of that type pulse. This allows the calculation of the amount of time the UUT is on within 100milliseconds. If the pulse train is longer than 100milliseconds then this number is multiplied by 100 to determine the percentage ON TIME. If the pulse train is less than 100milliseconds the total on-time is divided by the length of the pulse train and then multiplied by 100 to determine the percentage ON TIME. In this case there were 1 pulses 0.52milliseconds long and 12pulses 0.28milliseconds long for a total of 3.88milliseconds on time within either the 100milliseconds or the pulse train. The average field strength is determined by multiplying the peak field strength by the percent on time. In this case the percentage ON time was 3.80%percent.

APPLICANT: BESCO ELECTRONIC MANUFACTURING CO., LTD.

FCC ID: GXKBS3100TX

REPORT #: F:\CUS\B\BESCO\BES257H8.RPT

PAGE #: 4

APPLICANT: BESCO ELECTRONIC MANUFACTURING CO., LTD.

FCC ID: GXKBS3100TX

NAME OF TEST: Occupied Bandwidth

RULES PART NO.: 15.231(C)

REQUIREMENTS: The bandwidth of the emission shall be no wider than .25% of the center frequency for devices operating between 70 and 900 MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier.

$$\begin{aligned} 361.22 \text{ MHz} * .0025 &= .90305 \text{ MHz} \\ .90305 \text{ MHz}/2 &= +/- 451.525 \end{aligned}$$

THE GRAPH ON THE FOLLOWING PAGE REPRESENTS THE EMISSIONS TAKEN FOR THE DEVICE.

METHOD OF MEASUREMENT: A small sample of the transmitter output was fed into the spectrum analyzer and the above photo was taken. The vertical scale is set to 10 dB per division: the horizontal scale is set to 100 kHz per division.

TEST RESULTS: The unit meets the FCC requirements.

PERFORMED BY: DATE: SEPTEMBER 11, 1998

APPLICANT: BESCO ELECTRONIC MANUFACTURING CO., LTD.
FCC ID: GXKBS3100TX
REPORT #: F:\CUS\B\BESCO\BES257H8.RPT
PAGE #: 5