

ELITE ELECTRONIC ENGINEERING INCORPORATED  
1516 CENTRE CIRCLE  
DOWNERS GROVE, ILLINOIS 60515-1082

ELITE PROJECT: 30250

DATE TESTED: September 21, 2001

TEST PERSONNEL: Daniel E. Crowder

TEST SPECIFICATION: FCC "Code of Federal Regulations" Title 47  
Part 15, Subpart C, Section 15.205


ENGINEERING TEST REPORT NO. 24091

MEASUREMENT OF RF INTERFERENCE FROM  
A MODEL TELEPILOT V1.0 TRANSMITTER


FOR: Telemotive Industrial Controls  
Glendale Heights, Illinois

PURCHASE ORDER NO.: 7994-000


Report By:

  
Daniel E. Crowder

Witnessed By:

  
Talmage Wesley  
Telemotive Industrial Controls

Approved By:

  
Raymond J. Klouda  
Registered Professional  
Engineer of Illinois - 44894

ENGINEERING TEST REPORT NO. 24091  
ADMINISTRATIVE DATA AND SUMMARY OF TESTS

**DESCRIPTION OF TEST ITEM:** Transmitter

**MODEL NO:** TELEPILOT V1.0 **SERIAL NO:** None Assigned

**MANUFACTURER:** Telemotive Industrial Controls

**APPLICABLE SPECIFICATIONS:** FCC "Code of Federal Regulations"  
Title 47, Part 15, Subpart C

**QUANTITY OF ITEMS TESTED:** One (1)

**TEST PERFORMED BY:** ELITE ELECTRONIC ENGINEERING INCORPORATED  
Radio Interference Consultants  
Downers Grove, Illinois 60515

**DATE RECEIVED:** September 21, 2001

**DATE TESTED:** September 21, 2001

**PERSONNEL (OPERATORS, OBSERVERS, AND CO-ORDINATORS):**

**CUSTOMER:** Talmage Wesley of Telemotive Industrial Controls was present.

**ELITE ELECTRONIC:** Daniel E. Crowder

**ELITE JOB NO.:** 30250

**ABSTRACT:** The model TELEPILOT V1.0 Transmitter, does meet the conducted and radiated emission requirements of the FCC "Code of Federal Regulations" Title 47, Part 15, Subpart C, Section 15.205 et seq. for Intentional Radiators, when tested per ANSI C63.4-1992.

The radiated emissions level closest to the limit (worst case) occurred at 1319.4MHz. The emissions level at this frequency was 1.7dB within the limit. See data pages 21 and 22 for more details.

THIS REPORT SHALL NOT BE REPRODUCED, EXCEPT IN FULL, WITHOUT THE WRITTEN APPROVAL OF ELITE ELECTRONIC ENGINEERING INCORPORATED.

## TABLE OF CONTENTS

<u>PARAGRAPH</u>	<u>DESCRIPTION OF CONTENTS</u>	<u>PAGE NO.</u>
1.0	INTRODUCTION	4
1.1	DESCRIPTION OF TEST ITEM	4
1.2	PURPOSE	4
1.3	DEVIATIONS, ADDITIONS AND EXCLUSIONS	4
1.4	APPLICABLE DOCUMENTS	4
1.5	SUBCONTRACTOR IDENTIFICATION	4
1.6	LABORATORY CONDITIONS	5
2.0	TEST ITEM SETUP AND OPERATION	5
2.1	POWER INPUT	5
2.2	GROUNDING	5
2.3	PERIPHERAL EQUIPMENT	5
2.4	INTERCONNECT CABLES	5
3.0	TEST EQUIPMENT	5
3.1	TEST EQUIPMENT LIST	5
3.2	CALIBRATION TRACEABILITY	6
3.3	MEASUREMENT UNCERTAINTY	6
4.0	REQUIREMENTS, PROCEDURES AND RESULTS	7
4.1	POWERLINE CONDUCTED EMISSIONS	7
4.1.1	REQUIREMENTS	7
4.2	DUTY CYCLE FACTOR MEASUREMENTS	7
4.2.2	PROCEDURES	7
4.2.3	RESULTS	7
4.3	RADIATED MEASUREMENTS	7
4.3.1	REQUIREMENTS	7
4.3.2	PROCEDURES	8
4.3.3	RESULTS	9
4.4	OCCUPIED BANDWIDTH MEASUREMENTS	10
4.4.1	REQUIREMENTS	10
4.4.2	PROCEDURES	10
4.4.3	RESULTS	10
5.0	CONCLUSION	10
6.0	CERTIFICATION	11
7.0	ENDORSEMENT DISCLAIMER	11
TABLE I - EQUIPMENT LIST		12

TOTAL NUMBER OF PAGES IN THIS DOCUMENT,  
(INCLUDING DATA SHEETS) : 24

THIS REPORT SHALL NOT BE REPRODUCED, EXCEPT IN FULL, WITHOUT THE  
WRITTEN APPROVAL OF ELITE ELECTRONIC ENGINEERING INCORPORATED.

ENGINEERING TEST REPORT NO. 24091  
MEASUREMENT OF RF INTERFERENCE FROM  
A MODEL TELEPILOT V1.0 TRANSMITTER

**1.0 INTRODUCTION:**

**1.1 DESCRIPTION OF TEST ITEM:** This document presents the results of a series of radio interference measurements performed on a model TELEPILOT V1.0 Transmitter, (hereinafter referred to as the test item). No serial number was assigned to the test item. The test item was designed to transmit in the range 433.1MHz to 439.8MHz using an internal antenna. The tests were performed for Telemotive Industrial Controls of Glendale Heights, Illinois.

**1.2 PURPOSE:** The test series was performed to determine if the test item meets the conducted and radiated RF emission requirements of the FCC "Code of Federal Regulations" Title 47, Part 15, Subpart C, Sections for Intentional Radiators. Testing was performed in accordance with ANSI C63.4-1992.

**1.3 DEVIATIONS, ADDITIONS AND EXCLUSIONS:** There were no deviations, additions to, or exclusions from the test specification during this test series.

**1.4 APPLICABLE DOCUMENTS:** The following documents of the exact issue designated form part of this document to the extent specified herein:

- Federal Communications Commission "Code of Federal Regulations", Title 47, Part 15, Subpart C, dated 1 October 2000
- ANSI C63.4-1992, "American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz"

**1.5 SUBCONTRACTOR IDENTIFICATION:** This series of tests was

Grove, Illinois. The laboratory is accredited by the National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP). NVLAP Lab Code: 100278-0.

**1.6 LABORATORY CONDITIONS:** The temperature at the time of the test was 23°C and the relative humidity was 45%.

**2.0 TEST ITEM SETUP AND OPERATION:**

A block diagram of the test item setup is included as Figure 1.

**2.1 POWER INPUT:** The test item received 3.0VDC power from 2 AA size batteries.

**2.2 GROUNDING:** Since the test item was powered with batteries, it was ungrounded during the tests.

**2.3 PERIPHERAL EQUIPMENT:** There was no peripheral equipment submitted with the test item.

**2.4 INTERCONNECT CABLES:** There was no interconnect cables submitted with the test item.

**2.5 OPERATIONAL MODE:** For all tests the test item was placed on a 80cm high non-conductive stand. The test item was energized. For all tests, the test item was programmed to transmit continuously. Transmission was verified by observation of an LED which was lit whenever the transmitter was enabled. The transmitting mechanism automatically deactivated when released. The battery voltage was periodically checked to ensure proper operation at maximum level. The tests were performed separately with the test item operating at 433MHz and 439.8MHz.

**3.0 TEST EQUIPMENT:**

**3.1 TEST EQUIPMENT LIST:** A list of the test equipment used can be found on Table I. All equipment was calibrated per the instruction

manuals supplied by the manufacturer.

The fundamental, harmonics and spurious emissions were measured with a spectrum analyzer. The spectrum analyzer peak detected readings were converted to average readings using a duty cycle factor. All measurements were taken with the resolution and video bandwidth of the measuring instrument adjusted to 100kHz below 1GHz and 1MHz above 1GHz.

The duty cycle factor was calculated from the pulse train for the test item. A data plot was obtained to determine the duty cycle factor. The duty cycle factor was computed as the Word ON time divided by the Word period (ON time + OFF time). The duty cycle factor in dB = 20 log (Word ON/Word period). If the word period is more than 100 milliseconds, then the duty cycle would be computed on the maximum Word ON time during a 100 millisecond period.

**3.2 CALIBRATION TRACEABILITY:** Test equipment is maintained and calibrated on a regular basis. All calibrations are traceable to the National Institute of Standards and Technology (NIST).

**3.3 MEASUREMENT UNCERTAINTY:** All measurements are an estimate of their true value. The measurement uncertainty characterizes, with a specified confidence level, the spread of values which may be possible for a given measurement system.

The measurement uncertainty budgets were based on guidelines in "ISO Guide to the Expression of Uncertainty in Measurements" and NAMAS NIS81 "The Treatment of Uncertainty in EMC Measurements".

The measurement uncertainty for these tests is presented below:

Conducted Emission Measurements:

Combined Standard Uncertainty	1.07	-1.07
Expanded Uncertainty (95% confidence)	2.1	-2.1

Radiated Emission Measurements:

Combined Standard Uncertainty	2.26	-2.18
-------------------------------	------	-------

Expanded Uncertainty (95% confidence) 4.5 -4.4

**4.0 REQUIREMENTS, PROCEDURES AND RESULTS:****4.1 POWERLINE CONDUCTED EMISSIONS:**

**4.1.1 REQUIREMENTS:** Since the test item was powered by internal batteries, no conducted emissions tests were performed.

**4.2 DUTY CYCLE FACTOR MEASUREMENTS:**

**4.2.2 PROCEDURES:** The duty cycle factor is used to convert peak detected readings to average readings. This factor is computed from the time domain trace of the pulse modulation signal.

With the transmitter set up to transmit for maximum pulse density, the time domain trace is displayed on the spectrum analyzer. This trace is obtained by tuning center frequency to the transmitter frequency and then setting a zero span width with 10msec/div. The amplitude setting are adjusted so that the on/off transitions clear the 4th division from the bottom of the display. The markers are set at beginning and end of a word period. If the word period exceeds 100 msec the word period is set to 100 msec. The on-time and off-time are then measured. The on-time is total time signal level exceeds the 4th division. Off-time is time under for the word period. The duty cycle is then computed as the (On-time/ word period) where the word period = (On-time + Off-time).

**4.2.3 RESULTS:** The plots of the duty cycles are shown on data pages 15 and 16. The duty cycle factor was computed to be -11.4 dB

**4.3 RADIATED MEASUREMENTS:**

**4.3.1 REQUIREMENTS:** The test item must comply with the requirements of FCC "Code of Federal Regulations Title 47", Part 15, Subpart C, Section 15.205 et seq.

Paragraph 15.231(b) has the following radiated emission limits:

Fundamental Frequency MHz	Field Intensity uV/m @ 3 meters	Field Strength Harmonics and Spurious @ 3 meters
260 to 470	3,750 to 12,500*	375 to 1,250*

\* - Linear Interpolation

For 433MHz, the limit at the fundamental is 10962.5uV/m @ 3m and the limit on the harmonics is 1096.3uV/m @ 3m.

For 439.8MHz, the limit at the fundamental is 11241.7uV/m @ 3m and the limit on the harmonics is 1124.2uV/m @ 3m.

In addition, emissions appearing in the Restricted Bands of Operation listed in paragraph 15.205(a) shall not exceed the general requirements shown in paragraph 15.209.

**4.3.2 PROCEDURES:** All tests were performed in a 32ft. x 20ft. x 18ft. hybrid ferrite-tile/anechoic absorber lined test chamber. The walls and ceiling of the shielded chamber are lined with ferrite tiles. Anechoic absorber material is installed over the ferrite tile. The floor of the chamber is used as the ground plane. The chamber complies with ANSI C63.4 1992 for site attenuation.

The shielded enclosure prevents emissions from other sources, such as radio and TV stations from interfering with the measurements. All powerlines and signal lines entering the enclosure pass through filters on the enclosure wall. The powerline filters prevent extraneous signals from entering the enclosure on these leads.

Preliminary radiated emissions measurements were first performed using a peak detector and automatically plotted. The frequencies where significant emission levels were noted were then remeasured.

With the broadband measuring antennas positioned at a 3 meter

distance from the test item, the frequency range from 30MHz to 1GHz was investigated using a peak detector function with the antennas set for vertical polarization.

Final radiated emissions were performed on all significant broadband and narrowband emissions found in the preliminary sweeps using the following methods:

- 1) Measurements were made using a peak detector and a broadband antenna.
- 2) To ensure that maximum, or worst case, emission levels were measured, the following steps were taken:
  - (a) The test item was rotated so that all of its sides were exposed to the receiving antenna.
  - (b) Since the measuring antenna is linearly polarized, both horizontal and vertical field components were measured.
  - (c) The measuring antenna was raised and lowered from 1 to 4 meters for each antenna polarization to maximize the readings.
  - (d) The fundamental through the 10th harmonic of the transmit frequency were measured.

Since the test item can transmit over the range 430MHz to 439.8MHz, it was tested at two frequencies, one near the bottom of the frequency range (433MHz) and one near the top of the frequency range (439.8MHz).

**4.3.3 RESULTS:** The preliminary plots, with the test item transmitting at 433MHz, are presented on data pages 17 and 18. The preliminary plots, with the test item transmitting at 439.8MHz, are presented on data pages 19 and 20. The plots are presented for a reference only, and are not used to determine compliance.

The final open area radiated levels, with the test item transmitting at 433MHz, is presented on data page 21. The final open area radiated levels, with the test item transmitting at 439.8MHz, is

presented on data page 22. As can be seen from the data, all emissions measured from the test item were within the specification limits. The emissions level closest to the limit (worst case) occurred at 1319.4MHz. The emissions level at this frequency was 1.7dB within the limit. See data pages 21 and 22 for details. Photographs of the test configuration which yielded the highest, or worst case, radiated emission levels are shown on Figure 2.

**4.4 OCCUPIED BANDWIDTH MEASUREMENTS:**

**4.4.1 REQUIREMENTS:** In accordance with paragraph 15.231(c), all emissions within 20dB of the peak amplitude level of the center frequency are required to be within a band less than 0.25% of the center frequency wide.

**4.4.2 PROCEDURES:** The test item was placed on an 80cm high non-conductive stand. The unit was set to transmit continuously. With an antenna positioned nearby, occupied bandwidth emissions were displayed on the spectrum analyzer. The resolution bandwidth was set to 30 kHz and span was set to 2 MHz. The frequency spectrum near the fundamental was plotted.

**4.4.3 RESULTS:** The plot of the emissions near the fundamental frequencies are presented on data pages 23 and 24. As can be seen from this data page, the transmitter met the occupied bandwidth requirements.

**5.0 CONCLUSION:**

It was found that the Telemotive Industrial Controls model TELEPILOT V1.0 Transmitter, does meet the radiated emission requirements of the FCC "Code of Federal Regulations" Title 47, Part 15, Subpart C, Section 15.205 et seq. for Intentional Radiators, when tested per ANSI C63.4-1992.

**6.0 CERTIFICATION:**

Elite Electronic Engineering Incorporated certifies that the information contained in this report was obtained under conditions which meet or exceed those specified in the test specification.

The data presented in this test report pertains only to the test item at the test date as operated by Telemotive Industrial Controls personnel. Any electrical or mechanical modification made to the test item subsequent to the specified test date will serve to invalidate the data and void this certification.

**7.0 ENDORSEMENT DISCLAIMER:**

This report must not be used to claim product endorsement by NVLAP or any agency of the US Government.

TABLE I: TEST EQUIPMENT LIST

ELITE ELECTRONIC ENG. INC.							Page: 1	
Eq ID	Equipment Description	Manufacturer	Model No.	Serial No.	Frequency Range	Cal Date	Cal Inv	Due Date
<b>Equipment Type: ACCESSORIES, MISCELLANEOUS</b>								
XZG0	ATTENUATOR/SWITCH DRIVER	HEWLETT PACKARD	11713A	3439A02724	---	01/31/00	N/A	
<b>Equipment Type: AMPLIFIERS</b>								
APKO	PRE-AMPLIFIER	HEWLETT PACKARD	8449B	3008A00662	1-26.5GHZ	02/15/01	12	02/15/02
<b>Equipment Type: ANTENNAS</b>								
NDQ0	TUNED DIPOLE ANTENNA	EMCO	3121C-DB4	311	400-1000MHZ	11/29/00	12	11/29/01
NTAO	BILOG ANTENNA	CHASE EMC LTD.	BILOG CBL611	2057	0.03-2GHZ	05/09/01	12	05/09/02
NWF1	RIDGED WAVE GUIDE	EMCO	3105	2041	1-12.4GHZ	08/03/01	12	08/03/02
<b>Equipment Type: CONTROLLERS</b>								
CDD2	COMPUTER	HEWLETT PACKARD	D4171A#ABA	US61654645	---		N/A	
CMA0	MULTI-DEVICE CONTROLLER	EMCO	2090	9701-1213	---		N/A	
<b>Equipment Type: PRINTERS AND PLOTTERS</b>								
HRE1	LASER JET 5P	HEWLETT PACKARD	C3150A	USHB061052	---		N/A	
<b>Equipment Type: RECEIVERS</b>								
RAC1	SPECTRUM ANALYZER	HEWLETT PACKARD	85660B	3407A08369	100HZ-22GHZ	01/16/01	12	01/16/02
RACB	RF PRESELECTOR	HEWLETT PACKARD	85685A	3506A01491	20HZ-2GHZ	05/09/01	12	05/09/02
RAF3	QUASipeak ADAPTER	HEWLETT PACKARD	85650A	3303A01775	0.01-1000MHZ	01/17/01	12	01/17/02
<b>Equipment Type: TEST CHAMBERS (EMI)</b>								
R21F	3M ANECHOIC CHAMBER MEETS	EMC TEST SYSTEM	3M ANECHOIC		30MHZ-18GHZ	05/18/01	12	05/18/02

Cal. Interval: Listed in Months I/O: Initial Only N/A: Not Applicable

Note 1: For the purpose of this test, the equipment was calibrated over the specified frequency range, pulse rate, or modulation prior to the test or monitored by a calibrated instrument.




FIGURE 1: BLOCK DIAGRAM OF TEST ITEM SETUP

ETR 24091





FIGURE 2A TEST SETUP FOR RADIATED EMISSIONS MEASUREMENTS  
MAXIMIZED FOR MEASUREMENT OF WORST CASE EMISSIONS  
VERTICAL POLARIZATION



FIGURE 2B TEST SETUP FOR RADIATED EMISSIONS MEASUREMENTS  
MAXIMIZED FOR MEASUREMENT OF WORST CASE EMISSIONS  
VERTICAL POLARIZATION


ELITE ELECTRONIC ENGINEERING Co.  
Downers Grove, IL 60515

STR 24091



ELITE ELECTRONIC ENGINEERING Co.  
Downers Grove, IL 60515

ETR 24091



MANUFACTURER	TELEMOTIVE
MODEL	TELEPILOT U1.0
S/N	NONE ASSIGNED
TEST DATE	21 Sep 2001
NOTES	

page 16 of 24


ETR 24091

ELITE ELECTRONIC ENGINEERING Co.

Owners Grove, Ill. 60515

UNIV\_EM RUN RUN 1

WKAQ 08/24/01



RADIATED NARROWBAND EMISSIONS - dB UV/m

17 of 24

START = 30

100

FREQUENCY - MHz

1000


STOP = 2000

STR 24091

EEC ELITE ELECTRONIC ENGINEERING Co.  
Owners Grove, III. 60515

WKAQ 08/24/01

UNIV\_EM RUN RUN 2



RADIATED NARROWBAND EMISSIONS - dBuV/m

18, f 24

START = 2000

FREQUENCY - MHz

STOP = 5000


ETR 24091

EEC ELITE ELECTRONIC ENGINEERING Co.  
Downers Grove, Ill. 60515

UNIV\_EM RUN RUN 1

WKAQ 08/24/01

110



RADIATED NARROWBAND EMISSIONS - dB<sub>UV/m</sub>

19 1/24

START = 30

100

FREQUENCY - MHz


1000

STOP = 2000

ETL 240911

EEC ELITE ELECTRONIC ENGINEERING Co.  
WKA# 0824/01

UNIV\_EM RUN RUN 2



ETR No. 24091  
DATA PAGE

SPECIFICATION : FCC PART 15C (REV OCT 1, 94) TRANSMITTER OPEN FIELD DATA  
 MANUFACTURER : TELEMOBILE  
 MODEL : TELEPILOT V1.0  
 S/N : NONE ASSIGNED  
 TEST DATE : 21 Sep 2001  
 NOTES :  
 TEST ANTENNA : CHASE BI-LOG & DRWG ANTENNAS

FREQUENCY MHz	ANT POL	MTR RDG dBuV	CBL FAC dB	ANT FAC dB	DUTY CYCLE dB	TOTAL dBuV/m @3m	TOTAL uV/m @3m	LIMIT uV/m	NOTES
433.10	H	67.1	2.3	17.1	-11.4	75.1	5675.7	10962.5	
433.10	V	50.0	2.3	17.1	-11.4	58.0	792.5	10962.5	
866.30	H	10.4	3.2	22.1	-11.4	24.3	16.4	1096.3	
866.30	V	9.0	3.2	22.1	-11.4	22.9	14.0	1096.3	
1299.40	H	39.1	4.2	24.9	-11.4	56.8	690.5	1096.3	
1299.40	V	27.4	4.2	24.9	-11.4	45.1	179.5	1096.3	
1732.60	H	11.8	5.1	26.5	-11.4	32.0	40.0	1096.3	
1732.60	V	3.8	5.1	26.5	-11.4	24.0	15.9	1096.3	
2165.70	H	22.6	6.0	28.1	-11.4	45.3	183.6	1096.3	
2165.70	V	19.1	6.0	28.1	-11.4	41.8	122.7	1096.3	
2598.90	H	7.8	6.8	29.2	-11.4	32.4	41.6	1096.3	
2598.90	V	7.1	6.8	29.2	-11.4	31.7	38.3	1096.3	
3032.00	H	9.6	7.6	30.4	-11.4	36.1	64.2	1096.3	
3032.00	V	11.3	7.6	30.4	-11.4	37.8	78.0	1096.3	
3465.20	H	7.5	8.5	31.6	-11.4	36.2	64.7	1096.3	
3465.20	V	7.2	8.5	31.6	-11.4	35.9	62.5	1096.3	
3898.30	H	8.4	9.5	32.7	-11.4	39.2	91.3	500.0	*
3898.30	V	7.0	9.5	32.7	-11.4	37.8	77.7	500.0	*
4331.50	H	7.1	10.4	32.9	-11.4	39.0	89.6	500.0	*
4331.50	V	7.1	10.4	32.9	-11.4	39.0	89.6	500.0	*

\* DENOTES A FREQUENCY CONFLICT WITH RESTRICTED BANDS

checked by: \_\_\_\_\_

D. CROWDER

SPECIFICATION : FCC PART 15C (REV OCT 1, 94) TRANSMITTER OPEN FIELD DATA  
 MANUFACTURER : TELEMOBILE  
 MODEL : TELEPILOT V1.0  
 S/N : NONE ASSIGNED  
 TEST DATE : 21 Sep 2001  
 NOTES :  
 TEST ANTENNA : CHASE BI-LOG & DRWG ANTENNAS

FREQUENCY MHz	ANT POL	MTR RDG dBuV	CBL FAC dB	ANT FAC dB	DUTY CYCLE dB	TOTAL dBuV/m @3m	TOTAL uV/m @3m	LIMIT uV/m	NOTES
439.80	H	66.1	2.3	17.2	-11.4	74.2	5135.9	11241.7	
439.80	V	58.9	2.3	17.2	-11.4	67.0	2241.9	11241.7	
879.60	H	17.4	3.3	22.1	-11.4	31.4	37.0	1124.2	
879.60	V	11.0	3.3	22.1	-11.4	25.0	17.7	1124.2	
1319.40	H	34.5	4.2	25.0	-11.4	52.3	411.1	500.0	*
1319.40	V	28.8	4.2	25.0	-11.4	46.6	213.3	500.0	*
1759.20	H	11.1	5.2	26.6	-11.4	31.5	37.6	1124.2	
1759.20	V	9.7	5.2	26.6	-11.4	30.1	32.0	1124.2	
2199.00	H	25.7	6.1	28.2	-11.4	48.5	266.8	1124.2	
2199.00	V	20.6	6.1	28.2	-11.4	43.4	148.3	1124.2	
2638.80	H	7.7	6.8	29.3	-11.4	32.5	42.0	1124.2	
2638.80	V	6.6	6.8	29.3	-11.4	31.4	37.0	1124.2	
3078.60	H	9.4	7.7	30.5	-11.4	36.2	64.5	1124.2	
3078.60	V	11.3	7.7	30.5	-11.4	38.1	80.2	1124.2	
3518.40	H	6.4	8.6	31.8	-11.4	35.4	58.7	1124.2	
3518.40	V	7.6	8.6	31.8	-11.4	36.6	67.4	1124.2	
3958.20	H	8.8	9.6	32.9	-11.4	39.9	98.7	500.0	*
3958.20	V	6.6	9.6	32.9	-11.4	37.7	76.6	500.0	*
4398.00	H	6.2	10.6	32.9	-11.4	38.3	82.0	500.0	*
4398.00	V	6.5	10.6	32.9	-11.4	38.6	84.9	500.0	*


\* DENOTES A FREQUENCY CONFLICT WITH RESTRICTED BANDS

checked by:

  
D. CROWDER

## ELITE ELECTRONIC ENGINEERING CO

ETR 240 91



page 23 of 24

## ELITE ELECTRONIC ENGINEERING CO

