



FCC RADIO TEST REPORT

FCC ID : GZ5NVG558
Equipment : Fixed Broadband Gateway
Brand Name : ARRIS
Model Name : NVG558H
Applicant : Arris
101 Tournament Drive, Horsham PA, 19044
Manufacturer : Arris
101 Tournament Drive, Horsham PA, 19044
Standard : FCC 47 CFR Part 2, and 90(S)

The product was received on Sep. 26, 2019 and testing was started from Oct. 03, 2019 and completed on Oct. 10, 2019. We, Sporton International (USA) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA-603-E and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any agency of government.

The test results in this partial report apply exclusively to the tested model / sample. Without written approval of Sporton International (USA) Inc, the test report shall not be reproduced except in full.

Ken Chen

Approved by: Ken Chen

Sporton International (USA) Inc.
1175 Montague Expressway, Milpitas, CA 95035



Table of Contents

History of this test report	3
Summary of Test Result	4
1 General Description.....	5
1.1 Feature of Equipment Under Test.....	5
1.2 Modification of EUT.....	5
1.3 Testing Site	5
1.4 Applied Standards.....	5
2 Test Configuration of Equipment Under Test.....	6
2.1 Test Mode	6
2.2 Connection Diagram of Test System	7
2.3 Support Unit used in test configuration and system	7
2.4 Frequency List of Low/Middle/High Channels	7
3 Conducted Test Items	8
3.1 Measuring Instruments	8
3.2 Conducted Output Power Measurement and ERP Measurement.....	9
3.3 Field Strength of Spurious Radiation Measurement.....	10
4 List of Measuring Equipment	12
5 Uncertainty of Evaluation.....	13
Appendix A. Test Results of Conducted Test	
Appendix B. Test Results of ERP and Radiated Test	
Appendix C. Test Setup Photographs	



History of this test report



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.2	§2.1046 §90.635	Conducted Output Power and Effective Radiated Power	Pass	-
3.3	§2.1053 §90.691	Field Strength of Spurious Radiation	Pass	Under limit 32.67 dB at 2442.450 MHz

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1 General Description

1.1 Feature of Equipment Under Test

LTE

Product Specification subjective to this standard	
Antenna Type	WWAN: Fixed External Antenna / Fixed Internal Antenna

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Site

Test Site	Sportun International (USA) Inc.	
Test Site Location	1175 Montague Expressway, Milpitas, CA 95035 TEL : 408 9043300	
Test Site No.	Sportun Site No.	
	03CH01-CA	SAR01-CA
Test Engineer	Eric Jeng	Steven
Temperature	20°C	22.4°C
Relative Humidity	38.5%	47%

Note: The test site complies with ANSI C63.4 2014 requirement.

1.4 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR Part 2, 90
- ANSI / TIA-603-E
- ANSI C63.26-2015
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01
- Interim Guidance for Equipment Authorization of Devices with Channel Bandwidths Combined Across Two Contiguous Service Rule Allocations OET/Lab/EACB, June 6, 2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Test Mode


During all testing, EUT is in link mode with base station emulator at maximum power level.

For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

Frequency range investigated for radiated emission is 30 MHz to 9000 MHz.

Conducted Test Cases	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Max. Output Power	26	V	V	V	V	V	-	V	V	-	V	V	V	V	V	V
E.R.P.	26					V	-	V	V		V			V	V	V
Radiated Spurious Emission	26	Worst Case											V	V	V	
Remark		1. The mark "v" means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. LTE Band26 transmit frequency for part22 rule is 824MHz-849MHz, for part90 rule is 814MHz-824MHz. ERP over 15MHz bandwidth complies the ERP limit line of part22 rule, therefore ERP of the partial frequency spectrum which falls within part 22 also complies.														

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m

2.4 Frequency List of Low/Middle/High Channels

LTE Band 26 Channel and Frequency List					
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest	
15	Channel	26765	-	-	
	Frequency	821.5	-	-	
10	Channel	-	26740	-	
	Frequency	-	819	-	
5	Channel	26715	26740	26765	
	Frequency	816.5	819	821.5	
3	Channel	26705	26740	26775	
	Frequency	815.5	819	822.5	
1.4	Channel	26697	26740	26783	
	Frequency	814.7	819	823.3	


3 Conducted Test Items

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.1.1 Test Setup

3.1.2 Conducted Output Power



3.1.3 Test Result of Conducted Test

Please refer to Appendix A.



3.2 Conducted Output Power Measurement and ERP Measurement

3.2.1 Description of the Conducted Output Power Measurement and ERP Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for LTE Band 26.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.2.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.



3.3 Field Strength of Spurious Radiation Measurement

3.3.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA-603-E.

The power of any emission FCC Part 90.691 on any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth at least $43 + 10 \log(P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.


The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log_{10}(P[\text{Watts}])$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.3.2 Test Procedures


1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. For testing below 1GHz, make the measurement with the spectrum analyzer's RBW = 100 kHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. For testing above 1GHz, make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
12. ERP (dBm) = EIRP - 2.15
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10 \log(P)$ dB below the transmitter power P(Watts)

3.3.3 Test Setup

For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



3.3.4 Test Result of Field Strength of Spurious Radiated

Please refer to Appendix B.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Horn Antenna	SCHWARZBECK	BBHA 9120D	02140	1GHz~18GHz	Aug. 19, 2019	Oct. 03, 2019	Aug. 18, 2020	Radiation (03CH01-CA)
Bilog Antenna	TESEQ	6111D	50391	30MHz~1GHz	Jun. 26, 2019	Oct. 03, 2019	Jun. 25, 2020	Radiation (03CH01-CA)
Preamplifier	Jet-Power	JPA0118-55-303	1710001800055007	1GHz~18GHz	Apr. 01, 2019	Oct. 03, 2019	Mar. 31, 2020	Radiation (03CH01-CA)
Preamplifier	Keysight	83017A	MY53270323	1GHz~26.5GHz	Jul. 26, 2019	Oct. 03, 2019	Jul. 25, 2020	Radiation (03CH01-CA)
Amplifier	SONOMA	310N	372241	N/A	Jul. 26, 2019	Oct. 03, 2019	Jul. 25, 2020	Radiation (03CH01-CA)
EMI Test Receiver	R&S	ESU26	100049	20Hz~26.5GHz	Jul. 31, 2019	Oct. 03, 2019	Jul. 30, 2020	Radiation (03CH01-CA)
Filter	Wainwright	WHKX12-2700-3000-18000-60ST	SN9	3G High pass	Aug. 02, 2019	Oct. 03, 2019	Aug. 01, 2020	Radiation (03CH01-CA)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Oct. 03, 2019	N/A	Radiation (03CH01-CA)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Oct. 03, 2019	N/A	Radiation (03CH01-CA)
Radio Communication Analyze	Anritsu	MT8820C	<u>6201300652</u>	30MHz-2.7GHz, 3.4GHz-3.8GHz	Apr. 09, 2019	Oct. 10, 2019	Apr. 08, 2020	Conducted (SAR01-CA)



5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.36
---	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.59
---	------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.20
---	------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	21.87	-	-
15	1	37		21.30	-	-
15	1	74		21.68	-	-
15	36	0		20.54	-	-
15	36	20		20.38	-	-
15	36	39		20.42	-	-
15	75	0		20.47	-	-
15	1	0	16-QAM	21.21	-	-
15	1	37		20.63	-	-
15	1	74		21.06	-	-
15	36	0		19.62	-	-
15	36	20		19.48	-	-
15	36	39		19.53	-	-
15	75	0		19.57	-	-
10	1	0	QPSK	-	21.86	-
10	1	25		-	21.19	-
10	1	49		-	21.57	-
10	25	0		-	20.51	-
10	25	12		-	20.24	-
10	25	25		-	20.33	-
10	50	0		-	20.46	-
10	1	0	16-QAM	-	21.10	-
10	1	25		-	20.56	-
10	1	49		-	21.05	-
10	25	0		-	19.52	-
10	25	12		-	19.34	-
10	25	25		-	19.33	-
10	50	0		-	19.41	-



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	21.71	21.70	21.73
	1	12		21.16	21.06	21.20
	1	24		21.57	21.80	21.64
	12	0		20.53	20.44	20.29
	12	7		20.33	20.12	20.30
	12	13		20.30	20.30	20.39
	25	0		20.41	20.37	20.29
5	1	0	16-QAM	21.07	21.12	21.14
	1	12		20.48	20.47	20.57
	1	24		20.86	21.12	21.00
	12	0		19.54	19.38	19.54
	12	7		19.34	19.32	19.41
	12	13		19.47	19.44	19.56
	25	0		19.52	19.49	19.49
3	1	0	QPSK	21.81	21.67	21.84
	1	8		21.30	21.22	21.30
	1	14		21.67	21.68	21.79
	8	0		20.47	20.26	20.36
	8	4		20.19	20.13	20.26
	8	7		20.37	20.35	20.36
	15	0		20.42	20.39	20.45
3	1	0	16-QAM	21.09	21.18	21.05
	1	8		20.44	20.35	20.62
	1	14		20.95	21.11	20.96
	8	0		19.53	19.55	19.42
	8	4		19.42	19.23	19.47
	8	7		19.41	19.33	19.47
	15	0		19.55	19.37	19.47



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	21.80	21.80	21.82
1.4	1	3		21.18	21.03	21.33
1.4	1	5		21.50	21.70	21.77
1.4	3	0		21.75	21.85	21.69
1.4	3	1		21.23	21.02	21.21
1.4	3	3		21.60	21.62	21.60
1.4	6	0		20.47	20.38	20.42
1.4	1	0		21.01	21.06	21.21
1.4	1	3	16-QAM	20.63	20.43	20.67
1.4	1	5		20.91	21.15	21.07
1.4	3	0		21.11	21.01	21.23
1.4	3	1		20.54	20.46	20.71
1.4	3	3		21.05	21.02	21.00
1.4	6	0		19.57	19.50	19.54



Appendix B. Test Results of ERP and Radiated Test

ERP

<Reporting Only>

LTE Band 26 / 15MHz (Channel 26765) (GT - LC = 2.1 dB)							
Channel	Mode	RB		Conducted		ERP	
		Size	Offset	Power (dBm)	Power (Watts)	ERP(dBm)	ERP(W)
Lowest	QPSK	1	0	21.87	0.15	21.82	0.15
Middle		-	-	-	-	-	-
Highest		-	-	-	-	-	-
Lowest	16QAM	1	0	21.21	0.13	21.16	0.13
Middle		-	-	-	-	-	-
Highest		-	-	-	-	-	-
Limit	ERP < 100W			Result		PASS	

**Radiated Spurious Emission****LTE Band 26**

LTE Band 26 / 3MHz / QPSK									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Low	1628.3	-62.67	-13	-49.67	-74.1	-67.94	1.09	8.51	H
	2442.45	-56.43	-13	-43.43	-72.65	-63.44	1.33	10.50	H
	3256.6	-56.13	-13	-43.13	-75.06	-64.25	1.54	11.81	H
	1628.3	-63.54	-13	-50.54	-74.3	-68.81	1.09	8.51	V
	2442.45	-45.67	-13	-32.67	-74.52	-52.68	1.33	10.50	V
	3256.6	-56.37	-13	-43.37	-75.02	-64.49	1.54	11.81	V
Middle	1635.3	-62.25	-13	-49.25	-73.7	-67.54	1.09	8.53	H
	2452.95	-57.06	-13	-44.06	-73.24	-64.09	1.34	10.51	H
	3270.6	-56.61	-13	-43.61	-75.48	-64.76	1.55	11.85	H
	1635.3	-63.41	-13	-50.41	-74.2	-68.70	1.09	8.53	V
	2452.95	-58.84	-13	-45.84	-74.63	-65.87	1.34	10.51	V
	3270.6	-56.81	-13	-43.81	-75.41	-64.96	1.55	11.85	V
High	1642.3	-60.70	-13	-47.70	-72.17	-68.16	1.09	8.55	H
	2436.45	-58.72	-13	-45.72	-74.96	-67.87	1.33	10.48	H
	3284.6	-56.65	-13	-43.65	-75.47	-66.98	1.55	11.88	H
	1642.3	-62.29	-13	-49.29	-73.11	-69.75	1.09	8.55	V
	2436.45	-59.07	-13	-46.07	-74.95	-68.22	1.33	10.48	V
	3284.6	-56.84	-13	-43.84	-75.39	-67.17	1.55	11.88	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



LTE Band 26 / 10MHz / QPSK									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1629	-62.18	-13	-49.18	-73.61	-67.45	1.09	8.51	H
	2443.5	-57.60	-13	-44.60	-73.82	-64.61	1.33	10.50	H
	3258	-56.18	-13	-43.18	-75.11	-64.31	1.54	11.82	H
	1629	-63.15	-13	-50.15	-73.91	-68.42	1.09	8.51	V
	2443.5	-58.97	-13	-45.97	-74.81	-65.98	1.33	10.50	V
	3258	-56.61	-13	-43.61	-75.26	-64.74	1.54	11.82	V

LTE Band 26 / 15MHz / QPSK									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Low	1629.5	-62.05	-13	-49.05	-73.48	-67.32	1.09	8.51	H
	2444.25	-56.50	-13	-43.50	-72.71	-63.52	1.33	10.50	H
	3259	-56.00	-13	-43.00	-74.92	-64.13	1.54	11.82	H
	1629.5	-62.79	-13	-49.79	-73.55	-68.06	1.09	8.51	V
	2444.25	-58.39	-13	-45.39	-74.23	-65.41	1.33	10.50	V
	3259	-56.59	-13	-43.59	-75.23	-64.72	1.54	11.82	V