

## FCC 47 CFR MPE REPORT

SEIKAKU TECHNICAL GROUP LIMITED

PORTABLE SOUND SYSTEM WITH BLUETOOTH

Model Number: WS-6MU2

Additional Model: WS-6, WS-6M, WS-6MU1, READY 6B,

READY 6B 1WR, READY 6B 2WR

FCC ID: H38WS-6

|                          |                                                                     |
|--------------------------|---------------------------------------------------------------------|
| Prepared for:            | SEIKAKU TECHNICAL GROUP LIMITED                                     |
|                          | Offshore Chambers, P.O.Box 217 Apia, Samoa                          |
|                          |                                                                     |
| Prepared By:             | EST Technology Co., Ltd.                                            |
|                          | Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China |
| Tel: 86-769-83081888-808 |                                                                     |

|                 |                       |
|-----------------|-----------------------|
| Report Number:  | ESTE-R2007082         |
| Date of Test:   | Jun. 14~Jul. 07, 2020 |
| Date of Report: | Jul. 09, 2020         |

## Maximum Permissible Exposure

### 1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

#### 1.1. Limits for Maximum Permissible Exposure (MPE)

##### (a) Limits for Occupational/Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|-----------------------------------------|------------------------------------------------------------------------|
| 0.3-3.0               | 614                               | 1.63                              | (100)*                                  | 6                                                                      |
| 3.0-30                | 1842/f                            | 4.89/f                            | (900/f)*                                | 6                                                                      |
| 30-300                | 61.4                              | 0.163                             | 1.0                                     | 6                                                                      |
| 300-1500              |                                   |                                   | F/300                                   | 6                                                                      |
| 1500-10000            |                                   |                                   | 5                                       | 6                                                                      |

##### (b) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|-----------------------------------------|------------------------------------------------------------------------|
| 0.3-1.34              | 614                               | 1.63                              | (100)*                                  | 30                                                                     |
| 1.34-30               | 824/f                             | 2.19/f                            | (180/f)*                                | 30                                                                     |
| 30-300                | 27.5                              | 0.073                             | 0.2                                     | 30                                                                     |
| 300-1500              |                                   |                                   | F/1500                                  | 30                                                                     |
| 1500-10000            |                                   |                                   | 1.0                                     | 30                                                                     |

Note: f=frequency in MHz; \*Plane-wave equivalent power density

## 1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

## 2. Conducted Power Result

| Mode           | Frequency (MHz) | Peak output power (dBm) | Peak output power (mW) | Target power (dBm) | Antenna gain |          |
|----------------|-----------------|-------------------------|------------------------|--------------------|--------------|----------|
|                |                 |                         |                        |                    | (dBi)        | (Linear) |
| GFSK           | 2402            | -3.41                   | 0.4560                 | -3±1               | -0.58        | 0.875    |
|                | 2441            | -3.90                   | 0.4074                 | -3±1               | -0.58        | 0.875    |
|                | 2480            | -4.29                   | 0.3724                 | -4±1               | -0.58        | 0.875    |
| $\pi/4$ -DQPSK | 2402            | -2.75                   | 0.5309                 | -2±1               | -0.58        | 0.875    |
|                | 2441            | -2.79                   | 0.5260                 | -2±1               | -0.58        | 0.875    |
|                | 2480            | -3.25                   | 0.4732                 | -3±1               | -0.58        | 0.875    |

## 3. Calculated Result and Limit

| Mode           | Target power (dBm) | Antenna gain |          | Power Density (S) (mW/cm <sup>2</sup> ) | Limited of Power Density (S) (mW/cm <sup>2</sup> ) | Test Result |
|----------------|--------------------|--------------|----------|-----------------------------------------|----------------------------------------------------|-------------|
|                |                    | (dBi)        | (Linear) |                                         |                                                    |             |
| 2.4G Band      |                    |              |          |                                         |                                                    |             |
| GFSK           | -2                 | -0.58        | 0.875    | 0.00011                                 | 1                                                  | Compiles    |
| $\pi$ /4-DQPSK | -1                 | -0.58        | 0.875    | 0.00014                                 | 1                                                  | Compiles    |

**End of Test Report**